Gateway Documentation - Retail Bills Service

Oracle FLEXCUBE Universal Banking

Release FCUBS_12.0.3.0.0

[April] [2014]

Table Of Contents

1. BACKGROUND **1**

2. FCUBSRBService **2**

2.1. QueryPDCContract **2**

2.1.1. RB-QueryPDCContract-Req-IO-MSG.xsd *2*

2.1.2. RB-QueryPDCContract-Res-Full-MSG.xsd *8*

2.2. QueryPDR **111**

2.2.1. RB-QueryPDR-Req-IO-MSG.xsd *111*

2.2.2. RB-QueryPDR-Res-Full-MSG.xsd *117*

2.3. QueryStatusChg **204**

2.3.1. RB-QueryStatusChg-Req-IO-MSG.xsd *204*

2.3.2. RB-QueryStatusChg-Res-Full-MSG.xsd *210*

2.4. Queryfcychecksinput **225**

2.4.1. RB-Queryfcychecksinput-Req-IO-MSG.xsd *225*

2.4.2. RB-Queryfcychecksinput-Res-Full-MSG.xsd *232*

2.5. ReverseInwardContract **329**

2.5.1. RB-ReverseInwardContract-Req-Full-MSG.xsd *329*

2.5.2. RB-ReverseInwardContract-Req-IO-MSG.xsd *421*

2.5.3. RB-ReverseInwardContract-Res-Full-MSG.xsd *427*

2.5.4. RB-ReverseInwardContract-Res-PK-MSG.xsd *521*

2.6. ReverseOutwardcollection **530**

2.6.1. RB-ReverseOutwardcollection-Req-Full-MSG.xsd *530*

2.6.2. RB-ReverseOutwardcollection-Req-IO-MSG.xsd *632*

2.6.3. RB-ReverseOutwardcollection-Res-Full-MSG.xsd *638*

2.6.4. RB-ReverseOutwardcollection-Res-PK-MSG.xsd *742*

2.7. ReverseOvscheckspay **751**

2.7.1. RB-ReverseOvscheckspay-Req-Full-MSG.xsd *751*

2.7.2. RB-ReverseOvscheckspay-Req-IO-MSG.xsd *850*

2.7.3. RB-ReverseOvscheckspay-Res-Full-MSG.xsd *856*

2.7.4. RB-ReverseOvscheckspay-Res-PK-MSG.xsd *956*

2.8. ReversePDCContract **965**

2.8.1. RB-ReversePDCContract-Req-Full-MSG.xsd *965*

2.8.2. RB-ReversePDCContract-Req-IO-MSG.xsd *1066*

2.8.3. RB-ReversePDCContract-Res-Full-MSG.xsd *1072*

2.8.4. RB-ReversePDCContract-Res-PK-MSG.xsd *1175*

2.9. Reversefcychecksinput **1184**

2.9.1. RB-Reversefcychecksinput-Req-Full-MSG.xsd *1184*

2.9.2. RB-Reversefcychecksinput-Req-IO-MSG.xsd *1278*

2.9.3. RB-Reversefcychecksinput-Res-Full-MSG.xsd *1285*

2.9.4. RB-Reversefcychecksinput-Res-PK-MSG.xsd *1381*

2.10. ModifyOutwardcollection **1391**

2.10.1. RB-ModifyOutwardcollection-Req-Full-MSG.xsd *1391*

2.10.2. RB-ModifyOutwardcollection-Req-IO-MSG.xsd *1493*

2.10.3. RB-ModifyOutwardcollection-Res-Full-MSG.xsd *1552*

2.10.4. RB-ModifyOutwardcollection-Res-PK-MSG.xsd *1656*

2.11. ModifyOvscheckspay **1717**

2.11.1. RB-ModifyOvscheckspay-Req-Full-MSG.xsd *1717*

2.11.2. RB-ModifyOvscheckspay-Req-IO-MSG.xsd *1816*

2.11.3. RB-ModifyOvscheckspay-Res-Full-MSG.xsd *1873*

2.11.4. RB-ModifyOvscheckspay-Res-PK-MSG.xsd *1973*

2.12. ModifyPDCContract **2033**

2.12.1. RB-ModifyPDCContract-Req-Full-MSG.xsd *2033*

2.12.2. RB-ModifyPDCContract-Req-IO-MSG.xsd *2134*

2.12.3. RB-ModifyPDCContract-Res-Full-MSG.xsd *2192*

2.12.4. RB-ModifyPDCContract-Res-PK-MSG.xsd *2295*

2.13. Modifyfcychecksinput **2355**
2.13.1. RB-Modifyfcychecksinput-Req-Full-MSG.xsd *2355*
2.13.2. RB-Modifyfcychecksinput-Req-IO-MSG.xsd *2449*
2.13.3. RB-Modifyfcychecksinput-Res-Full-MSG.xsd *2501*
2.13.4. RB-Modifyfcychecksinput-Res-PK-MSG.xsd *2597*
2.14. QueryBulkInwardInput **2651**
2.14.1. RB-QueryBulkInwardInput-Req-IO-MSG.xsd *2651*
2.14.2. RB-QueryBulkInwardInput-Res-Full-MSG.xsd *2657*
2.15. QueryBulkInwardPDR **2676**
2.15.1. RB-QueryBulkInwardPDR-Req-IO-MSG.xsd *2676*
2.15.2. RB-QueryBulkInwardPDR-Res-Full-MSG.xsd *2682*
2.16. QueryBulkInwardReal **2699**
2.16.1. RB-QueryBulkInwardReal-Req-IO-MSG.xsd *2699*
2.16.2. RB-QueryBulkInwardReal-Res-Full-MSG.xsd *2705*
2.17. QueryBulkOutClearing **2723**
2.17.1. RB-QueryBulkOutClearing-Req-IO-MSG.xsd *2723*
2.17.2. RB-QueryBulkOutClearing-Res-Full-MSG.xsd *2729*
2.18. QueryBulkPDRContract **2752**
2.18.1. RB-QueryBulkPDRContract-Req-IO-MSG.xsd *2752*
2.18.2. RB-QueryBulkPDRContract-Res-Full-MSG.xsd *2758*
2.19. QueryBulkRealization **2774**
2.19.1. RB-QueryBulkRealization-Req-IO-MSG.xsd *2774*
2.19.2. RB-QueryBulkRealization-Res-Full-MSG.xsd *2780*
2.20. QueryCashletterdishonour **2795**
2.20.1. RB-QueryCashletterdishonour-Req-IO-MSG.xsd *2795*
2.20.2. RB-QueryCashletterdishonour-Res-Full-MSG.xsd *2801*
2.21. QueryCashletterrealize **2886**
2.21.1. RB-QueryCashletterrealize-Req-IO-MSG.xsd *2886*
2.21.2. RB-QueryCashletterrealize-Res-Full-MSG.xsd *2892*
2.22. QueryCreatebulkfcycheck **2904**
2.22.1. RB-QueryCreatebulkfcycheck-Req-IO-MSG.xsd *2904*
2.22.2. RB-QueryCreatebulkfcycheck-Res-Full-MSG.xsd *2910*
2.23. QueryCreatebulkfcyreal **2933**
2.23.1. RB-QueryCreatebulkfcyreal-Req-IO-MSG.xsd *2933*
2.23.2. RB-QueryCreatebulkfcyreal-Res-Full-MSG.xsd *2940*
2.24. QueryFcychecksfinance **2957**
2.24.1. RB-QueryFcychecksfinance-Req-IO-MSG.xsd *2957*
2.24.2. RB-QueryFcychecksfinance-Res-Full-MSG.xsd *2963*
2.25. QueryFcychecksrealize **3054**
2.25.1. RB-QueryFcychecksrealize-Req-IO-MSG.xsd *3054*
2.25.2. RB-QueryFcychecksrealize-Res-Full-MSG.xsd *3060*
2.26. QueryInwardContract **3144**
2.26.1. RB-QueryInwardContract-Req-IO-MSG.xsd *3144*
2.26.2. RB-QueryInwardContract-Res-Full-MSG.xsd *3151*
2.27. QueryInwardRealize **3246**
2.27.1. RB-QueryInwardRealize-Req-IO-MSG.xsd *3246*
2.27.2. RB-QueryInwardRealize-Res-Full-MSG.xsd *3252*
2.28. QueryOutBulkCol **3341**
2.28.1. RB-QueryOutBulkCol-Req-IO-MSG.xsd *3341*
2.28.2. RB-QueryOutBulkCol-Res-Full-MSG.xsd *3347*
2.29. QueryOutFinDet **3367**
2.29.1. RB-QueryOutFinDet-Req-IO-MSG.xsd *3367*
2.29.2. RB-QueryOutFinDet-Res-Full-MSG.xsd *3373*
2.30. QueryOutRealization **3464**
2.30.1. RB-QueryOutRealization-Req-IO-MSG.xsd *3464*
2.30.2. RB-QueryOutRealization-Res-Full-MSG.xsd *3470*

2.31. QueryOutwardcollection **3556**
2.31.1. RB-QueryOutwardcollection-Req-IO-MSG.xsd *3556*
2.31.2. RB-QueryOutwardcollection-Res-Full-MSG.xsd *3562*
2.32. QueryOverseasfinance **3666**
2.32.1. RB-QueryOverseasfinance-Req-IO-MSG.xsd *3666*
2.32.2. RB-QueryOverseasfinance-Res-Full-MSG.xsd *3672*
2.33. QueryOverseaspdr **3763**
2.33.1. RB-QueryOverseaspdr-Req-IO-MSG.xsd *3763*
2.33.2. RB-QueryOverseaspdr-Res-Full-MSG.xsd *3769*
2.34. QueryOvsbulkcontract **3855**
2.34.1. RB-QueryOvsbulkcontract-Req-IO-MSG.xsd *3855*
2.34.2. RB-QueryOvsbulkcontract-Res-Full-MSG.xsd *3861*
2.35. QueryOvsbulkrealize **3881**
2.35.1. RB-QueryOvsbulkrealize-Req-IO-MSG.xsd *3881*
2.35.2. RB-QueryOvsbulkrealize-Res-Full-MSG.xsd *3887*
2.36. QueryOvscheckspay **3903**
2.36.1. RB-QueryOvscheckspay-Req-IO-MSG.xsd *3903*
2.36.2. RB-QueryOvscheckspay-Res-Full-MSG.xsd *3910*
2.37. QueryOvsrealizecontract **4011**
2.37.1. RB-QueryOvsrealizecontract-Req-IO-MSG.xsd *4011*
2.37.2. RB-QueryOvsrealizecontract-Res-Full-MSG.xsd *4017*
2.38. DeleteInwardRealize **4103**
2.38.1. RB-DeleteInwardRealize-Req-Full-MSG.xsd *4103*
2.38.2. RB-DeleteInwardRealize-Req-IO-MSG.xsd *4190*
2.38.3. RB-DeleteInwardRealize-Res-Full-MSG.xsd *4196*
2.38.4. RB-DeleteInwardRealize-Res-PK-MSG.xsd *4284*
2.39. DeleteOutBulkCol **4293**
2.39.1. RB-DeleteOutBulkCol-Req-Full-MSG.xsd *4293*
2.39.2. RB-DeleteOutBulkCol-Req-IO-MSG.xsd *4311*
2.39.3. RB-DeleteOutBulkCol-Res-Full-MSG.xsd *4317*
2.39.4. RB-DeleteOutBulkCol-Res-PK-MSG.xsd *4337*
2.40. DeleteOutFinDet **4346**
2.40.1. RB-DeleteOutFinDet-Req-Full-MSG.xsd *4346*
2.40.2. RB-DeleteOutFinDet-Req-IO-MSG.xsd *4435*
2.40.3. RB-DeleteOutFinDet-Res-Full-MSG.xsd *4441*
2.40.4. RB-DeleteOutFinDet-Res-PK-MSG.xsd *4532*
2.41. DeleteOutRealization **4541**
2.41.1. RB-DeleteOutRealization-Req-Full-MSG.xsd *4541*
2.41.2. RB-DeleteOutRealization-Req-IO-MSG.xsd *4625*
2.41.3. RB-DeleteOutRealization-Res-Full-MSG.xsd *4631*
2.41.4. RB-DeleteOutRealization-Res-PK-MSG.xsd *4717*
2.42. DeleteOutwardcollection **4726**
2.42.1. RB-DeleteOutwardcollection-Req-Full-MSG.xsd *4726*
2.42.2. RB-DeleteOutwardcollection-Req-IO-MSG.xsd *4828*
2.42.3. RB-DeleteOutwardcollection-Res-Full-MSG.xsd *4834*
2.42.4. RB-DeleteOutwardcollection-Res-PK-MSG.xsd *4938*
2.43. DeleteOverseasfinance **4947**
2.43.1. RB-DeleteOverseasfinance-Req-Full-MSG.xsd *4947*
2.43.2. RB-DeleteOverseasfinance-Req-IO-MSG.xsd *5036*
2.43.3. RB-DeleteOverseasfinance-Res-Full-MSG.xsd *5042*
2.43.4. RB-DeleteOverseasfinance-Res-PK-MSG.xsd *5133*
2.44. DeleteOverseaspdr **5142**
2.44.1. RB-DeleteOverseaspdr-Req-Full-MSG.xsd *5142*
2.44.2. RB-DeleteOverseaspdr-Req-IO-MSG.xsd *5226*
2.44.3. RB-DeleteOverseaspdr-Res-Full-MSG.xsd *5232*
2.44.4. RB-DeleteOverseaspdr-Res-PK-MSG.xsd *5318*
2.45. DeleteOvsbulkcontract **5327**

2.45.1. RB-DeleteOvsbulkcontract-Req-Full-MSG.xsd *5327*
2.45.2. RB-DeleteOvsbulkcontract-Req-IO-MSG.xsd *5345*
2.45.3. RB-DeleteOvsbulkcontract-Res-Full-MSG.xsd *5351*
2.45.4. RB-DeleteOvsbulkcontract-Res-PK-MSG.xsd *5370*
2.46. DeleteOvsbulkrealize **5379**
2.46.1. RB-DeleteOvsbulkrealize-Req-Full-MSG.xsd *5379*
2.46.2. RB-DeleteOvsbulkrealize-Req-IO-MSG.xsd *5393*
2.46.3. RB-DeleteOvsbulkrealize-Res-Full-MSG.xsd *5399*
2.46.4. RB-DeleteOvsbulkrealize-Res-PK-MSG.xsd *5414*
2.47. DeleteOvscheckspay **5423**
2.47.1. RB-DeleteOvscheckspay-Req-Full-MSG.xsd *5423*
2.47.2. RB-DeleteOvscheckspay-Req-IO-MSG.xsd *5522*
2.47.3. RB-DeleteOvscheckspay-Res-Full-MSG.xsd *5534*
2.47.4. RB-DeleteOvscheckspay-Res-PK-MSG.xsd *5634*
2.48. DeleteOvsrealizecontract **5648**
2.48.1. RB-DeleteOvsrealizecontract-Req-Full-MSG.xsd *5648*
2.48.2. RB-DeleteOvsrealizecontract-Req-IO-MSG.xsd *5732*
2.48.3. RB-DeleteOvsrealizecontract-Res-Full-MSG.xsd *5738*
2.48.4. RB-DeleteOvsrealizecontract-Res-PK-MSG.xsd *5823*
2.49. DeletePDCContract **5832**
2.49.1. RB-DeletePDCContract-Req-Full-MSG.xsd *5832*
2.49.2. RB-DeletePDCContract-Req-IO-MSG.xsd *5933*
2.49.3. RB-DeletePDCContract-Res-Full-MSG.xsd *5939*
2.49.4. RB-DeletePDCContract-Res-PK-MSG.xsd *6042*
2.50. DeletePDR **6051**
2.50.1. RB-DeletePDR-Req-Full-MSG.xsd *6051*
2.50.2. RB-DeletePDR-Req-IO-MSG.xsd *6136*
2.50.3. RB-DeletePDR-Res-Full-MSG.xsd *6142*
2.50.4. RB-DeletePDR-Res-PK-MSG.xsd *6229*
2.51. DeleteStatusChg **6238**
2.51.1. RB-DeleteStatusChg-Req-Full-MSG.xsd *6238*
2.51.2. RB-DeleteStatusChg-Req-IO-MSG.xsd *6251*
2.51.3. RB-DeleteStatusChg-Res-Full-MSG.xsd *6257*
2.51.4. RB-DeleteStatusChg-Res-PK-MSG.xsd *6271*
2.52. Deletefcychecksinput **6280**
2.52.1. RB-Deletefcychecksinput-Req-Full-MSG.xsd *6280*
2.52.2. RB-Deletefcychecksinput-Req-IO-MSG.xsd *6374*
2.52.3. RB-Deletefcychecksinput-Res-Full-MSG.xsd *6381*
2.52.4. RB-Deletefcychecksinput-Res-PK-MSG.xsd *6477*
2.53. ModifyInwardContract **6487**
2.53.1. RB-ModifyInwardContract-Req-Full-MSG.xsd *6487*
2.53.2. RB-ModifyInwardContract-Req-IO-MSG.xsd *6579*
2.53.3. RB-ModifyInwardContract-Res-Full-MSG.xsd *6639*
2.53.4. RB-ModifyInwardContract-Res-PK-MSG.xsd *6733*
2.54. CreatePDR **6795**
2.54.1. RB-CreatePDR-Req-Full-MSG.xsd *6795*
2.54.2. RB-CreatePDR-Req-IO-MSG.xsd *6880*
2.54.3. RB-CreatePDR-Res-Full-MSG.xsd *6944*
2.54.4. RB-CreatePDR-Res-PK-MSG.xsd *7031*
2.55. CreateStatusChg **7097**
2.55.1. RB-CreateStatusChg-Req-Full-MSG.xsd *7097*
2.55.2. RB-CreateStatusChg-Req-IO-MSG.xsd *7110*
2.55.3. RB-CreateStatusChg-Res-Full-MSG.xsd *7117*
2.55.4. RB-CreateStatusChg-Res-PK-MSG.xsd *7131*
2.56. Createfcychecksinput **7140**
2.56.1. RB-Createfcychecksinput-Req-Full-MSG.xsd *7140*
2.56.2. RB-Createfcychecksinput-Req-IO-MSG.xsd *7234*
2.56.3. RB-Createfcychecksinput-Res-Full-MSG.xsd *7304*

2.56.4. RB-Createfcychecksinput-Res-PK-MSG.xsd 7400
2.57. DeleteBulkInwardInput 7472
2.57.1. RB-DeleteBulkInwardInput-Req-Full-MSG.xsd 7472
2.57.2. RB-DeleteBulkInwardInput-Req-IO-MSG.xsd 7489
2.57.3. RB-DeleteBulkInwardInput-Res-Full-MSG.xsd 7495
2.57.4. RB-DeleteBulkInwardInput-Res-PK-MSG.xsd 7513
2.58. DeleteBulkInwardPDR 7522
2.58.1. RB-DeleteBulkInwardPDR-Req-Full-MSG.xsd 7522
2.58.2. RB-DeleteBulkInwardPDR-Req-IO-MSG.xsd 7537
2.58.3. RB-DeleteBulkInwardPDR-Res-Full-MSG.xsd 7543
2.58.4. RB-DeleteBulkInwardPDR-Res-PK-MSG.xsd 7560
2.59. DeleteBulkInwardReal 7569
2.59.1. RB-DeleteBulkInwardReal-Req-Full-MSG.xsd 7569
2.59.2. RB-DeleteBulkInwardReal-Req-IO-MSG.xsd 7585
2.59.3. RB-DeleteBulkInwardReal-Res-Full-MSG.xsd 7591
2.59.4. RB-DeleteBulkInwardReal-Res-PK-MSG.xsd 7609
2.60. DeleteBulkOutClearing 7618
2.60.1. RB-DeleteBulkOutClearing-Req-Full-MSG.xsd 7618
2.60.2. RB-DeleteBulkOutClearing-Req-IO-MSG.xsd 7638
2.60.3. RB-DeleteBulkOutClearing-Res-Full-MSG.xsd 7644
2.60.4. RB-DeleteBulkOutClearing-Res-PK-MSG.xsd 7666
2.61. DeleteBulkPDRContract 7675
2.61.1. RB-DeleteBulkPDRContract-Req-Full-MSG.xsd 7675
2.61.2. RB-DeleteBulkPDRContract-Req-IO-MSG.xsd 7689
2.61.3. RB-DeleteBulkPDRContract-Res-Full-MSG.xsd 7695
2.61.4. RB-DeleteBulkPDRContract-Res-PK-MSG.xsd 7711
2.62. DeleteBulkRealization 7720
2.62.1. RB-DeleteBulkRealization-Req-Full-MSG.xsd 7720
2.62.2. RB-DeleteBulkRealization-Req-IO-MSG.xsd 7733
2.62.3. RB-DeleteBulkRealization-Res-Full-MSG.xsd 7739
2.62.4. RB-DeleteBulkRealization-Res-PK-MSG.xsd 7753
2.63. DeleteCashletterdishonour 7762
2.63.1. RB-DeleteCashletterdishonour-Req-Full-MSG.xsd 7762
2.63.2. RB-DeleteCashletterdishonour-Req-IO-MSG.xsd 7845
2.63.3. RB-DeleteCashletterdishonour-Res-Full-MSG.xsd 7851
2.63.4. RB-DeleteCashletterdishonour-Res-PK-MSG.xsd 7936
2.64. DeleteCashletterrealize 7945
2.64.1. RB-DeleteCashletterrealize-Req-Full-MSG.xsd 7945
2.64.2. RB-DeleteCashletterrealize-Req-IO-MSG.xsd 7955
2.64.3. RB-DeleteCashletterrealize-Res-Full-MSG.xsd 7961
2.64.4. RB-DeleteCashletterrealize-Res-PK-MSG.xsd 7973
2.65. DeleteCreatebulkfcycheck 7982
2.65.1. RB-DeleteCreatebulkfcycheck-Req-Full-MSG.xsd 7982
2.65.2. RB-DeleteCreatebulkfcycheck-Req-IO-MSG.xsd 8003
2.65.3. RB-DeleteCreatebulkfcycheck-Res-Full-MSG.xsd 8009
2.65.4. RB-DeleteCreatebulkfcycheck-Res-PK-MSG.xsd 8031
2.66. DeleteCreatebulkfcyreal 8040
2.66.1. RB-DeleteCreatebulkfcyreal-Req-Full-MSG.xsd 8040
2.66.2. RB-DeleteCreatebulkfcyreal-Req-IO-MSG.xsd 8055
2.66.3. RB-DeleteCreatebulkfcyreal-Res-Full-MSG.xsd 8061
2.66.4. RB-DeleteCreatebulkfcyreal-Res-PK-MSG.xsd 8078
2.67. DeleteFcychecksfinance 8087
2.67.1. RB-DeleteFcychecksfinance-Req-Full-MSG.xsd 8087
2.67.2. RB-DeleteFcychecksfinance-Req-IO-MSG.xsd 8176
2.67.3. RB-DeleteFcychecksfinance-Res-Full-MSG.xsd 8182
2.67.4. RB-DeleteFcychecksfinance-Res-PK-MSG.xsd 8273
2.68. DeleteFcychecksrealize 8282
2.68.1. RB-DeleteFcychecksrealize-Req-Full-MSG.xsd 8282

2.68.2. RB-DeleteFcychecksrealize-Req-IO-MSG.xsd *8364*
2.68.3. RB-DeleteFcychecksrealize-Res-Full-MSG.xsd *8370*
2.68.4. RB-DeleteFcychecksrealize-Res-PK-MSG.xsd *8453*
2.69. DeleteInwardContract **8462**
2.69.1. RB-DeleteInwardContract-Req-Full-MSG.xsd *8462*
2.69.2. RB-DeleteInwardContract-Req-IO-MSG.xsd *8554*
2.69.3. RB-DeleteInwardContract-Res-Full-MSG.xsd *8560*
2.69.4. RB-DeleteInwardContract-Res-PK-MSG.xsd *8654*
2.70. CreateCreatebulkfcyreal **8663**
2.70.1. RB-CreateCreatebulkfcyreal-Req-Full-MSG.xsd *8663*
2.70.2. RB-CreateCreatebulkfcyreal-Req-IO-MSG.xsd *8678*
2.70.3. RB-CreateCreatebulkfcyreal-Res-Full-MSG.xsd *8688*
2.70.4. RB-CreateCreatebulkfcyreal-Res-PK-MSG.xsd *8705*
2.71. CreateFcychecksfinance **8717**
2.71.1. RB-CreateFcychecksfinance-Req-Full-MSG.xsd *8717*
2.71.2. RB-CreateFcychecksfinance-Req-IO-MSG.xsd *8806*
2.71.3. RB-CreateFcychecksfinance-Res-Full-MSG.xsd *8872*
2.71.4. RB-CreateFcychecksfinance-Res-PK-MSG.xsd *8963*
2.72. CreateFcychecksrealize **9032**
2.72.1. RB-CreateFcychecksrealize-Req-Full-MSG.xsd *9032*
2.72.2. RB-CreateFcychecksrealize-Req-IO-MSG.xsd *9114*
2.72.3. RB-CreateFcychecksrealize-Res-Full-MSG.xsd *9178*
2.72.4. RB-CreateFcychecksrealize-Res-PK-MSG.xsd *9261*
2.73. CreateInwardContract **9327**
2.73.1. RB-CreateInwardContract-Req-Full-MSG.xsd *9327*
2.73.2. RB-CreateInwardContract-Req-IO-MSG.xsd *9419*
2.73.3. RB-CreateInwardContract-Res-Full-MSG.xsd *9489*
2.73.4. RB-CreateInwardContract-Res-PK-MSG.xsd *9583*
2.74. CreateInwardRealize **9655**
2.74.1. RB-CreateInwardRealize-Req-Full-MSG.xsd *9655*
2.74.2. RB-CreateInwardRealize-Req-IO-MSG.xsd *9742*
2.74.3. RB-CreateInwardRealize-Res-Full-MSG.xsd *9806*
2.74.4. RB-CreateInwardRealize-Res-PK-MSG.xsd *9894*
2.75. CreateOutBulkCol **9961**
2.75.1. RB-CreateOutBulkCol-Req-Full-MSG.xsd *9961*
2.75.2. RB-CreateOutBulkCol-Req-IO-MSG.xsd *9979*
2.75.3. RB-CreateOutBulkCol-Res-Full-MSG.xsd *9991*
2.75.4. RB-CreateOutBulkCol-Res-PK-MSG.xsd *10011*
2.76. CreateOutFinDet **10025**
2.76.1. RB-CreateOutFinDet-Req-Full-MSG.xsd *10025*
2.76.2. RB-CreateOutFinDet-Req-IO-MSG.xsd *10114*
2.76.3. RB-CreateOutFinDet-Res-Full-MSG.xsd *10180*
2.76.4. RB-CreateOutFinDet-Res-PK-MSG.xsd *10271*
2.77. CreateOutRealization **10339**
2.77.1. RB-CreateOutRealization-Req-Full-MSG.xsd *10339*
2.77.2. RB-CreateOutRealization-Req-IO-MSG.xsd *10423*
2.77.3. RB-CreateOutRealization-Res-Full-MSG.xsd *10486*
2.77.4. RB-CreateOutRealization-Res-PK-MSG.xsd *10572*
2.78. CreateOutwardcollection **10637**
2.78.1. RB-CreateOutwardcollection-Req-Full-MSG.xsd *10637*
2.78.2. RB-CreateOutwardcollection-Req-IO-MSG.xsd *10739*
2.78.3. RB-CreateOutwardcollection-Res-Full-MSG.xsd *10816*
2.78.4. RB-CreateOutwardcollection-Res-PK-MSG.xsd *10920*
2.79. CreateOverseasfinance **10999**
2.79.1. RB-CreateOverseasfinance-Req-Full-MSG.xsd *10999*
2.79.2. RB-CreateOverseasfinance-Req-IO-MSG.xsd *11088*
2.79.3. RB-CreateOverseasfinance-Res-Full-MSG.xsd *11154*
2.79.4. RB-CreateOverseasfinance-Res-PK-MSG.xsd *11245*

2.80. CreateOverseaspdr **11313**
2.80.1. RB-CreateOverseaspdr-Req-Full-MSG.xsd *11313*
2.80.2. RB-CreateOverseaspdr-Req-IO-MSG.xsd *11397*
2.80.3. RB-CreateOverseaspdr-Res-Full-MSG.xsd *11460*
2.80.4. RB-CreateOverseaspdr-Res-PK-MSG.xsd *11546*
2.81. CreateOvsbulkcontract **11612**
2.81.1. RB-CreateOvsbulkcontract-Req-Full-MSG.xsd *11612*
2.81.2. RB-CreateOvsbulkcontract-Req-IO-MSG.xsd *11630*
2.81.3. RB-CreateOvsbulkcontract-Res-Full-MSG.xsd *11642*
2.81.4. RB-CreateOvsbulkcontract-Res-PK-MSG.xsd *11661*
2.82. CreateOvsbulkrealize **11675**
2.82.1. RB-CreateOvsbulkrealize-Req-Full-MSG.xsd *11675*
2.82.2. RB-CreateOvsbulkrealize-Req-IO-MSG.xsd *11689*
2.82.3. RB-CreateOvsbulkrealize-Res-Full-MSG.xsd *11697*
2.82.4. RB-CreateOvsbulkrealize-Res-PK-MSG.xsd *11712*
2.83. CreateOvscheckspay **11722**
2.83.1. RB-CreateOvscheckspay-Req-Full-MSG.xsd *11722*
2.83.2. RB-CreateOvscheckspay-Req-IO-MSG.xsd *11821*
2.83.3. RB-CreateOvscheckspay-Res-Full-MSG.xsd *11895*
2.83.4. RB-CreateOvscheckspay-Res-PK-MSG.xsd *11995*
2.84. CreateOvsrealizecontract **12072**
2.84.1. RB-CreateOvsrealizecontract-Req-Full-MSG.xsd *12072*
2.84.2. RB-CreateOvsrealizecontract-Req-IO-MSG.xsd *12156*
2.84.3. RB-CreateOvsrealizecontract-Res-Full-MSG.xsd *12219*
2.84.4. RB-CreateOvsrealizecontract-Res-PK-MSG.xsd *12304*
2.85. CreatePDCContract **12369**
2.85.1. RB-CreatePDCContract-Req-Full-MSG.xsd *12369*
2.85.2. RB-CreatePDCContract-Req-IO-MSG.xsd *12470*
2.85.3. RB-CreatePDCContract-Res-Full-MSG.xsd *12545*
2.85.4. RB-CreatePDCContract-Res-PK-MSG.xsd *12648*
2.86. CloseBulkPDRContract **12725**
2.86.1. RB-CloseBulkPDRContract-Req-Full-MSG.xsd *12725*
2.86.2. RB-CloseBulkPDRContract-Req-IO-MSG.xsd *12739*
2.86.3. RB-CloseBulkPDRContract-Res-Full-MSG.xsd *12745*
2.86.4. RB-CloseBulkPDRContract-Res-PK-MSG.xsd *12761*
2.87. CloseBulkRealization **12770**
2.87.1. RB-CloseBulkRealization-Req-Full-MSG.xsd *12770*
2.87.2. RB-CloseBulkRealization-Req-IO-MSG.xsd *12783*
2.87.3. RB-CloseBulkRealization-Res-Full-MSG.xsd *12789*
2.87.4. RB-CloseBulkRealization-Res-PK-MSG.xsd *12803*
2.88. CloseCreatebulkfcycheck **12812**
2.88.1. RB-CloseCreatebulkfcycheck-Req-Full-MSG.xsd *12812*
2.88.2. RB-CloseCreatebulkfcycheck-Req-IO-MSG.xsd *12833*
2.88.3. RB-CloseCreatebulkfcycheck-Res-Full-MSG.xsd *12839*
2.88.4. RB-CloseCreatebulkfcycheck-Res-PK-MSG.xsd *12861*
2.89. CloseCreatebulkfcyreal **12870**
2.89.1. RB-CloseCreatebulkfcyreal-Req-Full-MSG.xsd *12870*
2.89.2. RB-CloseCreatebulkfcyreal-Req-IO-MSG.xsd *12885*
2.89.3. RB-CloseCreatebulkfcyreal-Res-Full-MSG.xsd *12891*
2.89.4. RB-CloseCreatebulkfcyreal-Res-PK-MSG.xsd *12908*
2.90. CloseOutBulkCol **12917**
2.90.1. RB-CloseOutBulkCol-Req-Full-MSG.xsd *12917*
2.90.2. RB-CloseOutBulkCol-Req-IO-MSG.xsd *12935*
2.90.3. RB-CloseOutBulkCol-Res-Full-MSG.xsd *12941*
2.90.4. RB-CloseOutBulkCol-Res-PK-MSG.xsd *12961*
2.91. CloseOvsbulkcontract **12970**
2.91.1. RB-CloseOvsbulkcontract-Req-Full-MSG.xsd *12970*
2.91.2. RB-CloseOvsbulkcontract-Req-IO-MSG.xsd *12988*

2.91.3. RB-CloseOvsbulkcontract-Res-Full-MSG.xsd *12994*
2.91.4. RB-CloseOvsbulkcontract-Res-PK-MSG.xsd *13013*
2.92. CloseOvsbulkrealize **13022**
2.92.1. RB-CloseOvsbulkrealize-Req-Full-MSG.xsd *13022*
2.92.2. RB-CloseOvsbulkrealize-Req-IO-MSG.xsd *13036*
2.92.3. RB-CloseOvsbulkrealize-Res-Full-MSG.xsd *13042*
2.92.4. RB-CloseOvsbulkrealize-Res-PK-MSG.xsd *13057*
2.93. CreateBulkInwardInput **13066**
2.93.1. RB-CreateBulkInwardInput-Req-Full-MSG.xsd *13066*
2.93.2. RB-CreateBulkInwardInput-Req-IO-MSG.xsd *13083*
2.93.3. RB-CreateBulkInwardInput-Res-Full-MSG.xsd *13095*
2.93.4. RB-CreateBulkInwardInput-Res-PK-MSG.xsd *13113*
2.94. CreateBulkInwardPDR **13127**
2.94.1. RB-CreateBulkInwardPDR-Req-Full-MSG.xsd *13127*
2.94.2. RB-CreateBulkInwardPDR-Req-IO-MSG.xsd *13142*
2.94.3. RB-CreateBulkInwardPDR-Res-Full-MSG.xsd *13151*
2.94.4. RB-CreateBulkInwardPDR-Res-PK-MSG.xsd *13168*
2.95. CreateBulkInwardReal **13179**
2.95.1. RB-CreateBulkInwardReal-Req-Full-MSG.xsd *13179*
2.95.2. RB-CreateBulkInwardReal-Req-IO-MSG.xsd *13195*
2.95.3. RB-CreateBulkInwardReal-Res-Full-MSG.xsd *13204*
2.95.4. RB-CreateBulkInwardReal-Res-PK-MSG.xsd *13222*
2.96. CreateBulkOutClearing **13233**
2.96.1. RB-CreateBulkOutClearing-Req-Full-MSG.xsd *13233*
2.96.2. RB-CreateBulkOutClearing-Req-IO-MSG.xsd *13253*
2.96.3. RB-CreateBulkOutClearing-Res-Full-MSG.xsd *13266*
2.96.4. RB-CreateBulkOutClearing-Res-PK-MSG.xsd *13288*
2.97. CreateBulkPDRContract **13303**
2.97.1. RB-CreateBulkPDRContract-Req-Full-MSG.xsd *13303*
2.97.2. RB-CreateBulkPDRContract-Req-IO-MSG.xsd *13317*
2.97.3. RB-CreateBulkPDRContract-Res-Full-MSG.xsd *13327*
2.97.4. RB-CreateBulkPDRContract-Res-PK-MSG.xsd *13343*
2.98. CreateBulkRealization **13355**
2.98.1. RB-CreateBulkRealization-Req-Full-MSG.xsd *13355*
2.98.2. RB-CreateBulkRealization-Req-IO-MSG.xsd *13368*
2.98.3. RB-CreateBulkRealization-Res-Full-MSG.xsd *13377*
2.98.4. RB-CreateBulkRealization-Res-PK-MSG.xsd *13391*
2.99. CreateCashletterdishonour **13403**
2.99.1. RB-CreateCashletterdishonour-Req-Full-MSG.xsd *13403*
2.99.2. RB-CreateCashletterdishonour-Req-IO-MSG.xsd *13486*
2.99.3. RB-CreateCashletterdishonour-Res-Full-MSG.xsd *13550*
2.99.4. RB-CreateCashletterdishonour-Res-PK-MSG.xsd *13635*
2.100. CreateCashletterrealize **13701**
2.100.1. RB-CreateCashletterrealize-Req-Full-MSG.xsd *13701*
2.100.2. RB-CreateCashletterrealize-Req-IO-MSG.xsd *13711*
2.100.3. RB-CreateCashletterrealize-Res-Full-MSG.xsd *13718*
2.100.4. RB-CreateCashletterrealize-Res-PK-MSG.xsd *13730*
2.101. CreateCreatebulkfcycheck **13739**
2.101.1. RB-CreateCreatebulkfcycheck-Req-Full-MSG.xsd *13739*
2.101.2. RB-CreateCreatebulkfcycheck-Req-IO-MSG.xsd *13760*
2.101.3. RB-CreateCreatebulkfcycheck-Res-Full-MSG.xsd *13775*
2.101.4. RB-CreateCreatebulkfcycheck-Res-PK-MSG.xsd *13797*
2.102. AuthorizeOutRealization **13814**
2.102.1. RB-AuthorizeOutRealization-Req-Full-MSG.xsd *13814*
2.102.2. RB-AuthorizeOutRealization-Req-IO-MSG.xsd *13898*
2.102.3. RB-AuthorizeOutRealization-Res-Full-MSG.xsd *13904*
2.102.4. RB-AuthorizeOutRealization-Res-PK-MSG.xsd *13990*
2.103. AuthorizeOutwardcollection **13999**

2.103.1. RB-AuthorizeOutwardcollection-Req-Full-MSG.xsd *13999*
2.103.2. RB-AuthorizeOutwardcollection-Req-IO-MSG.xsd *14101*
2.103.3. RB-AuthorizeOutwardcollection-Res-Full-MSG.xsd *14107*
2.103.4. RB-AuthorizeOutwardcollection-Res-PK-MSG.xsd *14211*
2.104. AuthorizeOverseasfinance **14220**
2.104.1. RB-AuthorizeOverseasfinance-Req-Full-MSG.xsd *14220*
2.104.2. RB-AuthorizeOverseasfinance-Req-IO-MSG.xsd *14309*
2.104.3. RB-AuthorizeOverseasfinance-Res-Full-MSG.xsd *14315*
2.104.4. RB-AuthorizeOverseasfinance-Res-PK-MSG.xsd *14406*
2.105. AuthorizeOverseaspdr **14415**
2.105.1. RB-AuthorizeOverseaspdr-Req-Full-MSG.xsd *14415*
2.105.2. RB-AuthorizeOverseaspdr-Req-IO-MSG.xsd *14499*
2.105.3. RB-AuthorizeOverseaspdr-Res-Full-MSG.xsd *14505*
2.105.4. RB-AuthorizeOverseaspdr-Res-PK-MSG.xsd *14591*
2.106. AuthorizeOvsbulkcontract **14600**
2.106.1. RB-AuthorizeOvsbulkcontract-Req-Full-MSG.xsd *14600*
2.106.2. RB-AuthorizeOvsbulkcontract-Req-IO-MSG.xsd *14618*
2.106.3. RB-AuthorizeOvsbulkcontract-Res-Full-MSG.xsd *14624*
2.106.4. RB-AuthorizeOvsbulkcontract-Res-PK-MSG.xsd *14643*
2.107. AuthorizeOvsbulkrealize **14652**
2.107.1. RB-AuthorizeOvsbulkrealize-Req-Full-MSG.xsd *14652*
2.107.2. RB-AuthorizeOvsbulkrealize-Req-IO-MSG.xsd *14666*
2.107.3. RB-AuthorizeOvsbulkrealize-Res-Full-MSG.xsd *14672*
2.107.4. RB-AuthorizeOvsbulkrealize-Res-PK-MSG.xsd *14687*
2.108. AuthorizeOvscheckspay **14696**
2.108.1. RB-AuthorizeOvscheckspay-Req-Full-MSG.xsd *14696*
2.108.2. RB-AuthorizeOvscheckspay-Req-IO-MSG.xsd *14795*
2.108.3. RB-AuthorizeOvscheckspay-Res-Full-MSG.xsd *14807*
2.108.4. RB-AuthorizeOvscheckspay-Res-PK-MSG.xsd *14907*
2.109. AuthorizeOvsrealizecontract **14921**
2.109.1. RB-AuthorizeOvsrealizecontract-Req-Full-MSG.xsd *14921*
2.109.2. RB-AuthorizeOvsrealizecontract-Req-IO-MSG.xsd *15005*
2.109.3. RB-AuthorizeOvsrealizecontract-Res-Full-MSG.xsd *15011*
2.109.4. RB-AuthorizeOvsrealizecontract-Res-PK-MSG.xsd *15096*
2.110. AuthorizePDCContract **15105**
2.110.1. RB-AuthorizePDCContract-Req-Full-MSG.xsd *15105*
2.110.2. RB-AuthorizePDCContract-Req-IO-MSG.xsd *15206*
2.110.3. RB-AuthorizePDCContract-Res-Full-MSG.xsd *15212*
2.110.4. RB-AuthorizePDCContract-Res-PK-MSG.xsd *15315*
2.111. AuthorizePDR **15324**
2.111.1. RB-AuthorizePDR-Req-Full-MSG.xsd *15324*
2.111.2. RB-AuthorizePDR-Req-IO-MSG.xsd *15409*
2.111.3. RB-AuthorizePDR-Res-Full-MSG.xsd *15415*
2.111.4. RB-AuthorizePDR-Res-PK-MSG.xsd *15502*
2.112. AuthorizeStatusChg **15511**
2.112.1. RB-AuthorizeStatusChg-Req-Full-MSG.xsd *15511*
2.112.2. RB-AuthorizeStatusChg-Req-IO-MSG.xsd *15524*
2.112.3. RB-AuthorizeStatusChg-Res-Full-MSG.xsd *15530*
2.112.4. RB-AuthorizeStatusChg-Res-PK-MSG.xsd *15544*
2.113. Authorizefcychecksinput **15553**
2.113.1. RB-Authorizefcychecksinput-Req-Full-MSG.xsd *15553*
2.113.2. RB-Authorizefcychecksinput-Req-IO-MSG.xsd *15647*
2.113.3. RB-Authorizefcychecksinput-Res-Full-MSG.xsd *15654*
2.113.4. RB-Authorizefcychecksinput-Res-PK-MSG.xsd *15750*
2.114. CloseBulkInwardInput **15760**
2.114.1. RB-CloseBulkInwardInput-Req-Full-MSG.xsd *15760*
2.114.2. RB-CloseBulkInwardInput-Req-IO-MSG.xsd *15777*
2.114.3. RB-CloseBulkInwardInput-Res-Full-MSG.xsd *15783*

2.114.4. RB-CloseBulkInwardInput-Res-PK-MSG.xsd *15801*
2.115. CloseBulkInwardPDR **15810**
2.115.1. RB-CloseBulkInwardPDR-Req-Full-MSG.xsd *15810*
2.115.2. RB-CloseBulkInwardPDR-Req-IO-MSG.xsd *15825*
2.115.3. RB-CloseBulkInwardPDR-Res-Full-MSG.xsd *15831*
2.115.4. RB-CloseBulkInwardPDR-Res-PK-MSG.xsd *15848*
2.116. CloseBulkInwardReal **15857**
2.116.1. RB-CloseBulkInwardReal-Req-Full-MSG.xsd *15857*
2.116.2. RB-CloseBulkInwardReal-Req-IO-MSG.xsd *15873*
2.116.3. RB-CloseBulkInwardReal-Res-Full-MSG.xsd *15879*
2.116.4. RB-CloseBulkInwardReal-Res-PK-MSG.xsd *15897*
2.117. CloseBulkOutClearing **15906**
2.117.1. RB-CloseBulkOutClearing-Req-Full-MSG.xsd *15906*
2.117.2. RB-CloseBulkOutClearing-Req-IO-MSG.xsd *15926*
2.117.3. RB-CloseBulkOutClearing-Res-Full-MSG.xsd *15932*
2.117.4. RB-CloseBulkOutClearing-Res-PK-MSG.xsd *15954*
2.118. AuthorizeBulkInwardInput **15963**
2.118.1. RB-AuthorizeBulkInwardInput-Req-Full-MSG.xsd *15963*
2.118.2. RB-AuthorizeBulkInwardInput-Req-IO-MSG.xsd *15980*
2.118.3. RB-AuthorizeBulkInwardInput-Res-Full-MSG.xsd *15986*
2.118.4. RB-AuthorizeBulkInwardInput-Res-PK-MSG.xsd *16004*
2.119. AuthorizeBulkInwardPDR **16013**
2.119.1. RB-AuthorizeBulkInwardPDR-Req-Full-MSG.xsd *16013*
2.119.2. RB-AuthorizeBulkInwardPDR-Req-IO-MSG.xsd *16028*
2.119.3. RB-AuthorizeBulkInwardPDR-Res-Full-MSG.xsd *16034*
2.119.4. RB-AuthorizeBulkInwardPDR-Res-PK-MSG.xsd *16051*
2.120. AuthorizeBulkInwardReal **16060**
2.120.1. RB-AuthorizeBulkInwardReal-Req-Full-MSG.xsd *16060*
2.120.2. RB-AuthorizeBulkInwardReal-Req-IO-MSG.xsd *16076*
2.120.3. RB-AuthorizeBulkInwardReal-Res-Full-MSG.xsd *16082*
2.120.4. RB-AuthorizeBulkInwardReal-Res-PK-MSG.xsd *16100*
2.121. AuthorizeBulkOutClearing **16109**
2.121.1. RB-AuthorizeBulkOutClearing-Req-Full-MSG.xsd *16109*
2.121.2. RB-AuthorizeBulkOutClearing-Req-IO-MSG.xsd *16129*
2.121.3. RB-AuthorizeBulkOutClearing-Res-Full-MSG.xsd *16135*
2.121.4. RB-AuthorizeBulkOutClearing-Res-PK-MSG.xsd *16157*
2.122. AuthorizeBulkPDRContract **16166**
2.122.1. RB-AuthorizeBulkPDRContract-Req-Full-MSG.xsd *16166*
2.122.2. RB-AuthorizeBulkPDRContract-Req-IO-MSG.xsd *16180*
2.122.3. RB-AuthorizeBulkPDRContract-Res-Full-MSG.xsd *16186*
2.122.4. RB-AuthorizeBulkPDRContract-Res-PK-MSG.xsd *16202*
2.123. AuthorizeBulkRealization **16211**
2.123.1. RB-AuthorizeBulkRealization-Req-Full-MSG.xsd *16211*
2.123.2. RB-AuthorizeBulkRealization-Req-IO-MSG.xsd *16224*
2.123.3. RB-AuthorizeBulkRealization-Res-Full-MSG.xsd *16230*
2.123.4. RB-AuthorizeBulkRealization-Res-PK-MSG.xsd *16244*
2.124. AuthorizeCashletterdishonour **16253**
2.124.1. RB-AuthorizeCashletterdishonour-Req-Full-MSG.xsd *16253*
2.124.2. RB-AuthorizeCashletterdishonour-Req-IO-MSG.xsd *16336*
2.124.3. RB-AuthorizeCashletterdishonour-Res-Full-MSG.xsd *16342*
2.124.4. RB-AuthorizeCashletterdishonour-Res-PK-MSG.xsd *16427*
2.125. AuthorizeCashletterrealize **16436**
2.125.1. RB-AuthorizeCashletterrealize-Req-Full-MSG.xsd *16436*
2.125.2. RB-AuthorizeCashletterrealize-Req-IO-MSG.xsd *16446*
2.125.3. RB-AuthorizeCashletterrealize-Res-Full-MSG.xsd *16452*
2.125.4. RB-AuthorizeCashletterrealize-Res-PK-MSG.xsd *16464*
2.126. AuthorizeCreatebulkfcycheck **16473**
2.126.1. RB-AuthorizeCreatebulkfcycheck-Req-Full-MSG.xsd *16473*

2.126.2. RB-AuthorizeCreatebulkfcycheck-Req-IO-MSG.xsd *16494*
2.126.3. RB-AuthorizeCreatebulkfcycheck-Res-Full-MSG.xsd *16500*
2.126.4. RB-AuthorizeCreatebulkfcycheck-Res-PK-MSG.xsd *16522*
2.127. AuthorizeCreatebulkfcyreal **16531**
2.127.1. RB-AuthorizeCreatebulkfcyreal-Req-Full-MSG.xsd *16531*
2.127.2. RB-AuthorizeCreatebulkfcyreal-Req-IO-MSG.xsd *16546*
2.127.3. RB-AuthorizeCreatebulkfcyreal-Res-Full-MSG.xsd *16552*
2.127.4. RB-AuthorizeCreatebulkfcyreal-Res-PK-MSG.xsd *16569*
2.128. AuthorizeFcychecksfinance **16578**
2.128.1. RB-AuthorizeFcychecksfinance-Req-Full-MSG.xsd *16578*
2.128.2. RB-AuthorizeFcychecksfinance-Req-IO-MSG.xsd *16667*
2.128.3. RB-AuthorizeFcychecksfinance-Res-Full-MSG.xsd *16673*
2.128.4. RB-AuthorizeFcychecksfinance-Res-PK-MSG.xsd *16764*
2.129. AuthorizeFcychecksrealize **16773**
2.129.1. RB-AuthorizeFcychecksrealize-Req-Full-MSG.xsd *16773*
2.129.2. RB-AuthorizeFcychecksrealize-Req-IO-MSG.xsd *16855*
2.129.3. RB-AuthorizeFcychecksrealize-Res-Full-MSG.xsd *16861*
2.129.4. RB-AuthorizeFcychecksrealize-Res-PK-MSG.xsd *16944*
2.130. AuthorizeInwardContract **16953**
2.130.1. RB-AuthorizeInwardContract-Req-Full-MSG.xsd *16953*
2.130.2. RB-AuthorizeInwardContract-Req-IO-MSG.xsd *17045*
2.130.3. RB-AuthorizeInwardContract-Res-Full-MSG.xsd *17051*
2.130.4. RB-AuthorizeInwardContract-Res-PK-MSG.xsd *17145*
2.131. AuthorizeInwardRealize **17154**
2.131.1. RB-AuthorizeInwardRealize-Req-Full-MSG.xsd *17154*
2.131.2. RB-AuthorizeInwardRealize-Req-IO-MSG.xsd *17241*
2.131.3. RB-AuthorizeInwardRealize-Res-Full-MSG.xsd *17247*
2.131.4. RB-AuthorizeInwardRealize-Res-PK-MSG.xsd *17335*
2.132. AuthorizeOutBulkCol **17344**
2.132.1. RB-AuthorizeOutBulkCol-Req-Full-MSG.xsd *17344*
2.132.2. RB-AuthorizeOutBulkCol-Req-IO-MSG.xsd *17362*
2.132.3. RB-AuthorizeOutBulkCol-Res-Full-MSG.xsd *17368*
2.132.4. RB-AuthorizeOutBulkCol-Res-PK-MSG.xsd *17388*
2.133. AuthorizeOutFinDet **17397**
2.133.1. RB-AuthorizeOutFinDet-Req-Full-MSG.xsd *17397*
2.133.2. RB-AuthorizeOutFinDet-Req-IO-MSG.xsd *17486*
2.133.3. RB-AuthorizeOutFinDet-Res-Full-MSG.xsd *17492*
2.133.4. RB-AuthorizeOutFinDet-Res-PK-MSG.xsd *17583*

1.BACKGROUND

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data.The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs.
The integration needs supported by the Gateway can be broadly categorized from the perspective of the Gateway as follows:

1. Inbound application integration – used when any external system needs to add, modify or query information within FLEXCUBE UBS
2. Outbound application integration– used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS
The following sections provide detailed XSD documentation of all operations available in FCUBSRBService of RB-Module

2.FCUBSRBService

Retail Bills ServiceRetail Bills Service

2.1.QueryPDCContract

QueryPDCContract

2.1.1.RB-QueryPDCContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.1.2.RB-QueryPDCContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-IO*
      - *CONREFNUM*
    - *Contract-Details-Full*
      - *CONREFNUM*
      - *BOOKDT*
      - *USERREFNUM*
      - *XREF*
      - *PRDCD*
      - *MODCOD*
      - *UDSTAT*
      - *STOPDT*
      - *EVENTCD*
      - *INSTRUCODE*
      - *CPTYIDEN*
      - *CPTYACCNUM*
      - *INSTRNO*
      - *INSTRDATE*
      - *CONTCCY*

AMOUNT
LCYAMT
OTHRPTYIDEN
BOOKINGDT
ACTDATE
VALUEDT
TRACKLIMIT
CRDLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
DISCOUNTAMT
COLLATERAL
COLLATVAL
COLLPOOL
ISRBNK
ISSUERBRN
CLGBANK
CLGBRN
SECTORCD
ENDPNT
INTREMARKS
ACCBRN
ROUTNO
DRACCBRN
INSTR_DESC
PRDDESC
CPTYNAME
OTHERPARTYNAME
ISSBANKNAME
ISSBRNCNAME
CLEARBANKNAME
AUTOLIQD
CLEARBRNCNAME
MAKER
MAKDTTIME
CHKR
CHKDTTIME
CONST
AUTHSTAT
BATCHREFENUM
BATCHSEQNO
DRACCREAL
CLGPRD

Party-Details

- *PRTYTYP*
- *PARTYIDEN*
- *PARTYNAME*
- *PARTYREFNO*
- *COUNTRYCD*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ADDLN4*
- *PARTLANG*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*

SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC

COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*

SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Charges

CONREFNO

Charge-Association

COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC

Charge-Application

CREATESN
COMPNT
TGCCY
TGAMT

- *CHRGCCY*
- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*

Charge-Liquidation

- *ESN*
- *COMPNT*
- *CHRGCCY*
- *CHRGAMT*
- *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*
- *MISGRPTXN*
- *COMPMIS1*
- *COMPMIS10*

COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5

- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Con

- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Clpref

- *CONTREFNNO*
- *CONTRACT_CCY*
- *LATEVNSEQNO*
- *PRD*
- *PRDDESC*
- *COUNTERPARTY*
- *CURRENCY*
- *TENOR*
- *UNITS*
- *LOAN_CONREFNO*
- *RATECODE*
- *EXCHANGERATE*
- *RATE_TYPE*
- *MAXIMUM*
- *MINIMUM*
- *PAYMENT_MODE*
- *LOANVALDATE*
- *MATURITY_DATE*
- *Ude*
  - *USERDEID*

UDEDESC
RATEASOF
USAGE
USERDEVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

USERREFNUM

Attribute	Description
Name	USERREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MODCOD

Attribute	Description
Name	MODCOD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BOOKINGDT

Attribute	Description
Name	BOOKINGDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACTDATE

Attribute	Description
Name	ACTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MARGINPERC

Attribute	**Description**	
Name	MARGINPERC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,F,N

TOP

DISCOUNTAMT

Attribute	**Description**	
Name	DISCOUNTAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COLLATERAL

Attribute	**Description**	
Name	COLLATERAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,C,T,N

TOP

COLLATVAL

Attribute	Description
Name	COLLATVAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ISRBNK

Attribute	Description
Name	ISRBNK
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ISSUERBRN

Attribute	Description
Name	ISSUERBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CLGBANK

Attribute	Description
Name	CLGBANK
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CLGBRN

Attribute	**Description**	
Name	CLGBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SECTORCD

Attribute	**Description**	
Name	SECTORCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

ENDPNT

Attribute	**Description**	
Name	ENDPNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTREMARKS

Attribute	**Description**	
Name	INTREMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ISSBANKNAME

Attribute	Description
Name	ISSBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ISSBRNCNAME

Attribute	Description
Name	ISSBRNCNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

CLEARBANKNAME

Attribute	Description
Name	CLEARBANKNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CLEARBRNCNAME

Attribute	Description
Name	CLEARBRNCNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,H,R,L

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

BATCHREFENUM

Attribute	**Description**	
Name	BATCHREFENUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BATCHSEQNO

Attribute	**Description**	
Name	BATCHSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DRACCREAL

Attribute	**Description**	
Name	DRACCREAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CLGPRD

Attribute	Description
Name	CLGPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / DRAWER,PAYEE

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PARTYNAME

Attribute	Description

Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTYREFNO

Attribute	Description
Name	PARTYREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTLANG

Attribute	Description
Name	PARTLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String

Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO

Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String

Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4

Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1

Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5

Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	

Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description

Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	**Description**	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS2

Attribute	**Description**	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	
Restrictions	

Restrictions	Description
maxLength	15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	
Restrictions	

Restrictions	Description
enumeration	Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	
Restrictions	

Restrictions	Description
maxLength	15

TOP

PARTYIDEN

Attribute	Description	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PARTYNAME

Attribute	Description	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CHGREQ

Attribute	Description	
Name	CHGREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTTYP

Attribute	Description	
Name	PARTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,S</td></tr></table>

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.2.QueryPDR

QueryPDR

2.2.1.RB-QueryPDR-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Master-IO*
  - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.2.2.RB-QueryPDR-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Master-IO*
      - *CONREFNUM*
    - *Master-Full*
      - *CONREFNUM*
      - *CPTYIDEN*
      - *INSTRNO*
      - *INSTRDATE*
      - *CCY*
      - *AMNT*
      - *OTHRBNKCHARGS*
      - *OTHRPTYIDEN*
      - *BANKCODE*
      - *BOOKINGDATE*
      - *DISCOUNTAMT*
      - *CHARGESCLAIMED*
      - *COLLATVAL*
      - *REASONCODE*
      - *REASON*

DISHONORDATE
PROTESTDATE
RETURNDATE
REMARK
MAKER
MAKDTTIME
CHKR
CHKDTTIME
CONTSTAT
AUTHSTAT
CPTYNAME
OTHERPARTYNAME
BANKNAME
NOTARYDESCRIPTION
NOTARYCODE
Charges
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements
- *CONREFNO*
- *Contract-Settlement*

IBANACNO
CUSTSPREAD
SPREADDEFN
COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4

INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5

DRCRIND

Settlement-Detail

- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*
- *SUPPID*
- *PAYERID*

PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9

MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1

FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRDATE

Attribute	**Description**	
Name	INSTRDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNT

Attribute	**Description**	
Name	AMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHRBNKCHARGS

Attribute	**Description**	
Name	OTHRBNKCHARGS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHRPTYIDEN

Attribute	**Description**
Name	OTHRPTYIDEN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BANKCODE

Attribute	Description
Name	BANKCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHARGESCLAIMED

Attribute	Description
Name	CHARGESCLAIMED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLATVAL

Attribute	Description
Name	COLLATVAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REASONCODE

Attribute	Description
Name	REASONCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

REASON

Attribute	Description
Name	REASON
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

DISHONORDATE

Attribute	Description
Name	DISHONORDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RETURNDATE

Attribute	Description
Name	RETURNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARK

Attribute	Description
Name	REMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYNAME

Attribute	**Description**	
Name	OTHERPARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BANKNAME

Attribute	**Description**	
Name	BANKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

NOTARYDESCRIPTION

Attribute	**Description**	
Name	NOTARYDESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

NOTARYCODE

Attribute	**Description**	
Name	NOTARYCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description

Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String

Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String

Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	Description	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	Description	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	**Description**	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	**Description**
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	**Description**
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	**Description**
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	**Description**
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EVENTSEQ

Attribute	**Description**	
Name	EVENTSEQ	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Adv

Attribute	**Description**	
Name	Adv	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ADVNAME

Attribute	**Description**	
Name	ADVNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SUPRESS

Attribute	**Description**	
Name	SUPRESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr></table>

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC

Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.3.QueryStatusChg

QueryStatusChg

2.3.1.RB-QueryStatusChg-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Master-IO*
  - *CONTREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.3.2.RB-QueryStatusChg-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Master-IO*
      - *CONTREFNO*
    - *Master-Full*
      - *CONTREFNO*
      - *CPTYIDEN*
      - *CPTYACCNUM*
      - *INSTRUMENTNO*
      - *INSTRULOC*
      - *INSTRSTAT*
      - *INSTRDATE*
      - *CCY*
      - *CONTRACTAMT*
      - *OTHRPTYIDEN*
      - *BANKCD*
      - *BRNCODE*
      - *BOOKINGDATE*
      - *MATURITYDATE*
      - *MAKER*

MAKDTTIME
CHKR
CHKDTTIME
CONTSTAT
AUTHSTAT
INTREMRKS
DRACFORREALISATION
COUNTRPRYNAM
OTHERPARTYNAME
BNKNAME
BRNNAME
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENTNO

Attribute	Description
Name	INSTRUMENTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRULOC

Attribute	Description

Name	INSTRULOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRSTAT

Attribute	Description
Name	INSTRSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONTRACTAMT

Attribute	Description
Name	CONTRACTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BANKCD

Attribute	Description
Name	BANKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DRACFORREALISATION

Attribute	Description
Name	DRACFORREALISATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.4.Queryfcychecksinput

Queryfcychecksinput

2.4.1.RB-Queryfcychecksinput-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Main-IO*
  - *CONREFNUM*
  - *USERREF_NO1*
  - *XREF*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.4.2.RB-Queryfcychecksinput-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-IO*
      - *CONREFNUM*
      - *USERREF_NO1*
      - *XREF*
    - *Main-Full*
      - *INSTRUMENT_CODE*
      - *INSTR_DESC*
      - *PRODUCT_CODE*
      - *PRDDESC*
      - *CONREFNUM*
      - *USERREF_NO1*
      - *XREF*
      - *BATCHREFENUM*
      - *BATCH_SEQ_NO*
      - *CASHLETTER_REFNUM*
      - *CPTY_ID*
      - *CTR_PRTY_NAME*
      - *CPTY_AC_NO*

ACC_BRANCH
INSTRUMENTNORE
INSTRUMENT_DATE
CURRENCY
AMNT
LCY_AMOUNT
NOSTROACC
ACCBRN
COLLECTINGBANKCIF
COLL_BNK_NAME
BOOKINGDATE
VAL_DATE_BANK
VALUE_DATE_CUST
OTHR_PARTY_NAME
DRAWEE_BNK_NAME
AUTOLIQD
INTREMRKS
FINANCING
MARGIN_PERCENTAGE
TRACK_LIMIT
CRLINE
DISCOUNTAMT
MAKER
MAKDTTIME
CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
VERSION_NO
LATVERNO
Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*

ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3

ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*

INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1

- REPRES2
- REPRES3
- REPRES4
- RCVRACC

Charges

- CONREFNO
- Charge-Association
  - COMPNT
  - CREATESN
  - RULE
  - WAIVER
  - DISACCRAPPL
  - ACCRREQD
  - DESC
- Charge-Application
  - CREATESN
  - COMPNT
  - TGCCY
  - TGAMT
  - CHRGCCY
  - CHRGAMT
  - DISACCRAPPL
  - WAIVER
  - LIQDIND
- Charge-Liquidation
  - ESN
  - COMPNT
  - CHRGCCY
  - CHRGAMT
  - LIQDSTAT

Misdetails

- CONREFNO
- LATESN
- MISGRP
- RELACC
- RELETED_REFERENCE
- MISHEAD
- RATEFLG
- POOLCD
- REFINANCE_RATE
- REFRATETYP
- PROCALCMTH
- REFSPREAD
- REFRATECD

COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6

TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Clpref
CONTREFNNO
CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE

MAXIMUM
MINIMUM
PAYMENT_MODE
LOANVALDATE
MATURITY_DATE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRODUCT_CODE

Attribute	Description
Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BATCHREFENUM

Attribute	**Description**	
Name	BATCHREFENUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BATCH_SEQ_NO

Attribute	**Description**	
Name	BATCH_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CASHLETTER_REFNUM

Attribute	**Description**	
Name	CASHLETTER_REFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	Description	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CTR_PRTY_NAME

Attribute	Description	
Name	CTR_PRTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTY_AC_NO

Attribute	Description	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACC_BRANCH

Attribute	Description	
Name	ACC_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INSTRUMENTNORE

Attribute	Description
Name	INSTRUMENTNORE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLECTINGBANKCIF

Attribute	Description
Name	COLLECTINGBANKCIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRLINE

Attribute	Description
Name	CRLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,L,R,H,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	**Description**	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	Description	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	Description	
Name	CLEARNW	
Datatype	String	
Description	Indicates Network Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	Description	
Name	COVERBY	
Datatype	String	
Description	Indicates Cover By Clearing : C Message : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	**Description**	
Name	BANKPRIOR	
Datatype	String	
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	**Description**	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	**Description**	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	**Description**	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description

Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNITS

Attribute	**Description**	
Name	UNITS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LOAN_CONREFNO

Attribute	**Description**	
Name	LOAN_CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RATECODE

Attribute	**Description**	
Name	RATECODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,S

TOP

EXCHANGERATE

Attribute	**Description**	
Name	EXCHANGERATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CHGREQ

Attribute	**Description**	
Name	CHGREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.5.ReverseInwardContract

ReverseInwardContract

2.5.1.RB-ReverseInwardContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *INSTRUMENT_CODE*
    - *INSTRUMENT_DESCRIPTION*
    - *PRCD*
    - *CONREFNUM*
    - *USERREF_NO*
    - *XREF*
    - *BATCHREFENUM*
    - *BATCHSEQNO*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *ACCBRN*
    - *CPTY_AC_NO*
    - *INSTNO*
    - *INSTRDATE*
    - *CCY*

AMT
LCYAMT
BNKCD
BNKNAME
BRNCDE
BRNNAME
REFNO
DATE
CORRESPBNK
CORRESPACNO
OTHERPARTYIDE
OTHR_PARTYNAME
BOKNGDT
MATDT
GRACEDAYS
PAYDUEDATE
ACBRN1
ACFORREALISATION
PROTEST
AUTOLIQD
LIQWITHBUKNG
INTREMARKS
REASON_CODE
REASON
CONREFNOLOG
MAKER
MAKDTTIME
CHKR
CHKDTTIME
SE_TXNSTAT
AUTHSTAT
VERSIONNORB
LATVERNO
Contract-Parties
- *PARTYTYPE*
- *PARTYIDEN*
- *PARTYNAME*
- *COUNTRYCD*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ADDLN4*
- *LANG*

Settlements

CONREFNO

Contract-Settlement

- *IBANACNO*
- *CUSTSPREAD*
- *SPREADDEFN*
- *COMPNT*
- *TAGCCY*
- *ACCBRN*
- *ACC*
- *ACCCCY*
- *EXRATE*
- *NETIND*
- *ERICCY*
- *ERIAMT*
- *GENMSG*
- *RATECD*
- *CLEARNW*
- *COVERBY*
- *RTGSPMNT*
- *BANKPRIOR*
- *RTGSNW*
- *PAYBY*
- *TRANSTYP*
- *INSTYP*
- *INSNO*
- *CHGDET*
- *PAYMNTDET1*
- *PAYMNTDET2*
- *PAYMNTDET3*
- *PAYMNTDET4*
- *SNDTRRCVINFO1*
- *SNDTRRCVINFO2*
- *SNDTRRCVINFO3*
- *SNDTRRCVINFO4*
- *SNDTRRCVINFO5*
- *COVREQRD*
- *RECVCVR*
- *RECEIVER*
- *REIMINST1*
- *REIMINST2*
- *REIMINST3*
- *REIMINST4*
- *RCVRCORRS1*
- *RCVRCORRS2*

RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5

ORDINST5

ULTBEN5

DRCRIND

Settlement-Detail

- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*

SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Charges

CONREFNO

Charge-Association

COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC

Charge-Application

CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND

Charge-Liquidation

ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3

FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con

CONTREFNO

EVENTSEQ

Adv

- *ADVNAME*
- *SUPRESS*
- *PRIOR*
- *MEDM*
- *PARTYIDEN*
- *PARTYNAME*
- *CHGREQ*
- *PARTTYP*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description
Name	INSTRUMENT_DESCRIPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCHSEQNO

Attribute	Description

Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTNO

Attribute	Description
Name	INSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRNCDE

Attribute	Description
Name	BRNCDE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORRESPBNK

Attribute	Description
Name	CORRESPBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CORRESPACNO

Attribute	Description
Name	CORRESPACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

OTHERPARTYIDE

Attribute	Description
Name	OTHERPARTYIDE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACBRN1

Attribute	Description
Name	ACBRN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQWITHBUKNG

Attribute	Description
Name	LIQWITHBUKNG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REASON

Attribute	Description
Name	REASON
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CONREFNOLOG

Attribute	**Description**
Name	CONREFNOLOG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	**Description**
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	**Description**
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	Description	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SE_TXNSTAT

Attribute	Description	
Name	SE_TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,L,R,H

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

VERSIONNORB

Attribute	Description	
Name	VERSIONNORB	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>DRAWER,PAYEE,REMITTING_BANK,DRAWEE</td></tr></table>

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1

Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2

Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	**Description**
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	**Description**
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	**Description**
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	**Description**
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDINST5

Attribute	Description
Name	ORDINST5

Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1

Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	**Description**	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	**Description**	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application

Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	**Description**	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	Description	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	Description	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	Description	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	Description	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	Description	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	Description	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	Description	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs — unbounded minOccurs — 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs — unbounded minOccurs — 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs — unbounded minOccurs — 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs — unbounded minOccurs — 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength — 105 minLength — 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL

Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

2.5.2.RB-ReverseInwardContract-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Contract-Details-IO*
  - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.5.3.RB-ReverseInwardContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *INSTRUMENT_CODE*
    - *INSTRUMENT_DESCRIPTION*
    - *PRCD*
    - *CONREFNUM*
    - *USERREF_NO*
    - *XREF*
    - *BATCHREFENUM*
    - *BATCHSEQNO*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *ACCBRN*
    - *CPTY_AC_NO*
    - *INSTNO*
    - *INSTRDATE*
    - *CCY*
    - *AMT*
    - *LCYAMT*
    - *BNKCD*

BNKNAME
BRNCDE
BRNNAME
REFNO
DATE
CORRESPBNK
CORRESPACNO
OTHERPARTYIDE
OTHR_PARTYNAME
BOKNGDT
MATDT
GRACEDAYS
PAYDUEDATE
ACBRN1
ACFORREALISATION
PROTEST
AUTOLIQD
LIQWITHBUKNG
INTREMARKS
REASON_CODE
REASON
CONREFNOLOG
MAKER
MAKDTTIME
CHKR
CHKDTTIME
SE_TXNSTAT
AUTHSTAT
VERSIONNORB
LATVERNO
Contract-Parties
  PARTYTYPE
  PARTYIDEN
  PARTYNAME
  COUNTRYCD
  ADDLN1
  ADDLN2
  ADDLN3
  ADDLN4
  LANG
Settlements
  CONREFNO
  Contract-Settlement
    IBANACNO

CUSTSPREAD
SPREADDEFN
COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1

INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND

Settlement-Detail

- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*

- NOOFDEC
- ADDID
- SNDRRCVRINFO1
- SNDRRCVRINFO2
- SNDRRCVRINFO3
- SNDRRCVRINFO4
- SNDRRCVRINFO5
- SNDRRCVRINFO6
- DECLARTION
- REPRES1
- REPRES2
- REPRES3
- REPRES4
- RCVRACC

Charges

- CONREFNO
- Charge-Association
  - COMPNT
  - CREATESN
  - RULE
  - WAIVER
  - DISACCRAPPL
  - ACCRREQD
  - DESC
- Charge-Application
  - CREATESN
  - COMPNT
  - TGCCY
  - TGAMT
  - CHRGCCY
  - CHRGAMT
  - DISACCRAPPL
  - WAIVER
  - LIQDIND
- Charge-Liquidation
  - ESN
  - COMPNT
  - CHRGCCY
  - CHRGAMT
  - LIQDSTAT

Misdetails

- CONREFNO
- LATESN
- MISGRP

RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6

FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv

ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description
Name	INSTRUMENT_DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTNO

Attribute	**Description**	
Name	INSTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRDATE

Attribute	**Description**	
Name	INSTRDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BRNCDE

Attribute	Description
Name	BRNCDE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

REFNO

Attribute	**Description**	
Name	REFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DATE

Attribute	**Description**	
Name	DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CORRESPBNK

Attribute	**Description**	
Name	CORRESPBNK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CORRESPACNO

Attribute	**Description**	
Name	CORRESPACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

OTHERPARTYIDE

Attribute	Description
Name	OTHERPARTYIDE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACBRN1

Attribute	Description
Name	ACBRN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

LIQWITHBUKNG

Attribute	Description
Name	LIQWITHBUKNG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

REASON

Attribute	Description
Name	REASON

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CONREFNOLOG

Attribute	Description
Name	CONREFNOLOG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SE_TXNSTAT

Attribute	**Description**	
Name	SE_TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,L,R,H

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

VERSIONNORB

Attribute	**Description**	
Name	VERSIONNORB	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / DRAWER,PAYEE,REMITTING_BANK,DRAWEE

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	**Description**	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	**Description**	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1

Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2

Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5

Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1

Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	**Description**	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	**Description**	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application

Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	**Description**	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	Description	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	Description	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	Description	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	Description	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL

Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	**Description**	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.5.4.RB-ReverseInwardContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNUM*
    - *Contract-Details-IO*
      - *CONREFNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.6.ReverseOutwardcollection

ReverseOutwardcollection

2.6.1.RB-ReverseOutwardcollection-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNUM*
    - *BOOKDT*
    - *USERREFNUM*
    - *BRN*
    - *PRDCD*
    - *MODULE*
    - *UDS*
    - *STOPDT*
    - *VERSIONNO*
    - *EVENTSEQ*
    - *EVENTCODE*
    - *INSTRUCODE*
    - *PRODTYP*
    - *CPTYIDEN*
    - *CPTYACCNUM*

INSTRNO
INSTRU_DATE
INITCCY
OSAMT
LCYAMT
OTHRPTYIDEN
BNKCD
BRN_D
REFERENCENO
BOOKINGDT
MATDAYS
LEADDAYS
DISPATCHDT
GRACEDAYS
PROTEST
TRACKLIMIT
CREDITLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
DISCAMT
COLLATERAL
COLLVL
COLLPOOL
ACCBRN
PAYDUEDATE
DRACCBRN
INTREMARKS
INSTRUMENT_DESCRIPTION
TXTPDTDESC
CPTYNAME
OTHERPARTYNAME
BNKNAME
BRNNAME
XREF
BATCHREFENUM
BATCHSEQNO
DRACCREAL
AUTOLIQD
CONTREFLOG
MAKER
MAKDTTIME
CHKR
CHKDTTIME

EVENTLOG
CONST
AUTHSTAT
LATVERNO
DATE
Party-Details
  PARTTYP
  PARTYIDEN
  PARTYNAME
  ADDLN1
  ADDLN2
  ADDLN3
  ADDLN4
  CNTY
  PRTYLANG
Settlements
  CONREFNO
  Contract-Settlement
    IBANACNO
    CUSTSPREAD
    SPREADDEFN
    COMPNT
    TAGCCY
    ACCBRN
    ACC
    ACCCCY
    EXRATE
    NETIND
    ERICCY
    ERIAMT
    GENMSG
    RATECD
    CLEARNW
    COVERBY
    RTGSPMNT
    BANKPRIOR
    RTGSNW
    PAYBY
    TRANSTYP
    INSTYP
    INSNO
    CHGDET
    PAYMNTDET1
    PAYMNTDET2

PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2

BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*

ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP

PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3

- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*

- *CREATESN*
- *COMPNT*
- *TGCCY*
- *TGAMT*
- *CHRGCCY*
- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Con*
  - *CONTREFNO*
  - *EVENTSEQ*
  - *Adv*
    - *ADVNAME*
    - *SUPRESS*
    - *PRIOR*
    - *MEDM*
    - *PARTYIDEN*
    - *PARTYNAME*
    - *CHGREQ*
    - *PARTTYP*
- *Clpref*
  - *CONTREFNNO*
  - *CONTRACT_CCY*
  - *LATEVNSEQNO*
  - *PRD*
  - *PRDDESC*
  - *COUNTERPARTY*
  - *CURRENCY*
  - *TENOR*
  - *UNITS*
  - *LOAN_CONREFNO*
  - *RATECODE*
  - *EXCHANGERATE*
  - *RATE_TYPE*
  - *MAXIMUM*
  - *MINIMUM*
  - *PAYMENT_MODE*

LOANVALDATE

MATURITY_DATE

Ude

USERDEID

UDEDESC

RATEASOF

USAGE

USERDEVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

USERREFNUM

Attribute	Description
Name	USERREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDS

Attribute	Description
Name	UDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSIONNO

Attribute	Description
Name	VERSIONNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

PRODTYP

Attribute	Description
Name	PRODTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INITCCY

Attribute	Description
Name	INITCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

OSAMT

Attribute	Description
Name	OSAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BRN_D

Attribute	Description
Name	BRN_D
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKINGDT

Attribute	Description
Name	BOOKINGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LEADDAYS

Attribute	Description
Name	LEADDAYS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISPATCHDT

Attribute	Description
Name	DISPATCHDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,N,F</td></tr></table>

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COLLATERAL

Attribute	**Description**	
Name	COLLATERAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,C,T,N

TOP

COLLVL

Attribute	**Description**	
Name	COLLVL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COLLPOOL

Attribute	**Description**	
Name	COLLPOOL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description
Name	INSTRUMENT_DESCRIPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

TXTPDTDESC

Attribute	Description
Name	TXTPDTDESC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTYNAME

Attribute	**Description**	
Name	CPTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYNAME

Attribute	**Description**	
Name	OTHERPARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BNKNAME

Attribute	**Description**	
Name	BNKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CONTREFLOG

Attribute	Description
Name	CONTREFLOG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EVENTLOG

Attribute	Description
Name	EVENTLOG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,H,R,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / DRAWEE,DRAWER,PAYEE,COLLECTING_BANK,

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRTYLANG

Attribute	Description
Name	PRTYLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO

Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String

Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4

Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1

Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5

Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	

Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String

Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	Description	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	Description	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	Description	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description

Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / DRAWEE,DRAWER,PAYEE,COLLECTING_BANK,

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description

Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.6.2.RB-ReverseOutwardcollection-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.6.3.RB-ReverseOutwardcollection-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNUM*
    - *BOOKDT*
    - *USERREFNUM*
    - *BRN*
    - *PRDCD*
    - *MODULE*
    - *UDS*
    - *STOPDT*
    - *VERSIONNO*
    - *EVENTSEQ*
    - *EVENTCODE*
    - *INSTRUCODE*
    - *PRODTYP*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *INSTRNO*
    - *INSTRU_DATE*
    - *INITCCY*

OSAMT
LCYAMT
OTHRPTYIDEN
BNKCD
BRN_D
REFERENCENO
BOOKINGDT
MATDAYS
LEADDAYS
DISPATCHDT
GRACEDAYS
PROTEST
TRACKLIMIT
CREDITLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
DISCAMT
COLLATERAL
COLLVL
COLLPOOL
ACCBRN
PAYDUEDATE
DRACCBRN
INTREMARKS
INSTRUMENT_DESCRIPTION
TXTPDTDESC
CPTYNAME
OTHERPARTYNAME
BNKNAME
BRNNAME
XREF
BATCHREFENUM
BATCHSEQNO
DRACCREAL
AUTOLIQD
CONTREFLOG
MAKER
MAKDTTIME
CHKR
CHKDTTIME
EVENTLOG
CONST
AUTHSTAT

LATVERNO
DATE
Party-Details
- *PARTTYP*
- *PARTYIDEN*
- *PARTYNAME*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ADDLN4*
- *CNTY*
- *PRTYLANG*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*

SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5

COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*

SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD

COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6

- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*

TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
Clpref
CONTREFNNO
CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM
PAYMENT_MODE
LOANVALDATE
MATURITY_DATE
Ude

USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USERREFNUM

Attribute	Description
Name	USERREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

UDS

Attribute	Description
Name	UDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

STOPDT

Attribute	Description
Name	STOPDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VERSIONNO

Attribute	Description
Name	VERSIONNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRODTYP

Attribute	Description
Name	PRODTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INITCCY

Attribute	Description
Name	INITCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OSAMT

Attribute	Description
Name	OSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BRN_D

Attribute	Description
Name	BRN_D
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BOOKINGDT

Attribute	Description
Name	BOOKINGDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LEADDAYS

Attribute	Description
Name	LEADDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISPATCHDT

Attribute	Description
Name	DISPATCHDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CREDITLINE

Attribute	**Description**	
Name	CREDITLINE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

OTHPARTYLIMIT

Attribute	**Description**	
Name	OTHPARTYLIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MARGINPERC

Attribute	**Description**	
Name	MARGINPERC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,N,F

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLVL

Attribute	Description
Name	COLLVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PAYDUEDATE

Attribute	**Description**	
Name	PAYDUEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DRACCBRN

Attribute	**Description**	
Name	DRACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INTREMARKS

Attribute	**Description**	
Name	INTREMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INSTRUMENT_DESCRIPTION

Attribute	**Description**	
Name	INSTRUMENT_DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

TXTPDTDESC

Attribute	Description
Name	TXTPDTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONTREFLOG

Attribute	Description
Name	CONTREFLOG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVENTLOG

Attribute	Description
Name	EVENTLOG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,H,R,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / DRAWEE,DRAWER,PAYEE,COLLECTING_BANK,

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN3

Attribute	Description	
Name	ADDLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDLN4

Attribute	Description	
Name	ADDLN4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CNTY

Attribute	Description	
Name	CNTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRTYLANG

Attribute	Description	
Name	PRTYLANG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	Description	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	Description	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	**Description**
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	**Description**
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	**Description**
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	**Description**
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	**Description**	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	**Description**	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	**Description**
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	**Description**
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	**Description**
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	**Description**
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number

Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY

Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / DRAWEE,DRAWER,PAYEE,COLLECTING_BANK,

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description

Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.6.4.RB-ReverseOutwardcollection-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNUM*
    - *Contract-Details-IO*
      - *CONREFNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.7.ReverseOvscheckspay

ReverseOvscheckspay

2.7.1.RB-ReverseOvscheckspay-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONTREFNO*
    - *LATESTVERSIONNO*
    - *RECORD_STAT*
    - *AUTHSTATUS*
    - *CURR_EVENT_CODE*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHKR*
    - *CHKDTTIME*
    - *EVENT_SEQ_NO*
    - *CONT_STAT*
    - *AUTH_STAT*
    - *CPTY_ID*
    - *CPTY_AC_NO*
    - *INSTRNO*

INSTRUMENT_DATE
CURRENCY
AMNT
NET_AMT_REALISED
OTHER_BANK_CHARGES
COLL_BNK_CIF
BOOKINGDATE
MATURITY_DATE
VALUE_DATE
TRACK_LIMIT
CREDIT_LINE
FINANCING
INT_REM
INSTRUMENT_CODE
INSTR_DESC
PRCD
PRODDESC
USERREF_NO
XREF
COUNTRPRYNAM
LCY_AMT
COLLBANKNAME
PAYDUEDATE
CONREF
EVENTSEQ
PARTYTYP
ADDRESS
PARTYADDR2
PARTYADDR3
PARTYADDR4
WALKINCUSTFLG
COLLEC_BANK_CIF
COLLBNKNAME
DISCOUNT_AMOUNT
DB_ACC_REAL
BULK_INPUT_REF_NO
DRAWEE_BNK_NAME
AUTOLIQD
OTHER_PARTY_ID
VERSION_NO
TRANSITDAYS
MARGIN_PERCENTAGE
ACC_BRANCH
OTHR_PARTY_NAME

ACCBRN

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*

COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6

- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*

CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2

ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*

REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4

RCVRACC

Clpref

CONTREFNNO

CONTRACT_CCY

LATEVNSEQNO

PRD

PRDDESC

COUNTERPARTY

CURRENCY

TENOR

UNITS

LOAN_CONREFNO

RATECODE

EXCHANGERATE

RATE_TYPE

MAXIMUM

MINIMUM

PAYMENT_MODE

LOANVALDATE

MATURITY_DATE

Ude

USERDEID

UDEDESC

RATEASOF

USAGE

USERDEVAL

Con

CONTREFNO

EVENTSEQ

Adv

ADVNAME

SUPRESS

PRIOR

MEDM

PARTYIDEN

PARTYNAME

CHGREQ

PARTTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESTVERSIONNO

Attribute	**Description**	
Name	LATESTVERSIONNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTATUS

Attribute	**Description**	
Name	AUTHSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CURR_EVENT_CODE

Attribute	**Description**	
Name	CURR_EVENT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONT_STAT

Attribute	Description
Name	CONT_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,L,R,H,</td></tr></table>

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,U,</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRNO

Attribute	**Description**	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRUMENT_DATE

Attribute	**Description**	
Name	INSTRUMENT_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

CURRENCY

Attribute	**Description**	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNT

Attribute	**Description**	
Name	AMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

INT_REM

Attribute	Description
Name	INT_REM
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLBANKNAME

Attribute	Description
Name	COLLBANKNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREF

Attribute	Description
Name	CONREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ADDRESS

Attribute	Description
Name	ADDRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYADDR2

Attribute	Description
Name	PARTYADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYADDR3

Attribute	Description
Name	PARTYADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYADDR4

Attribute	Description
Name	PARTYADDR4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINCUSTFLG

Attribute	Description
Name	WALKINCUSTFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

COLLEC_BANK_CIF

Attribute	Description
Name	COLLEC_BANK_CIF
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BULK_INPUT_REF_NO

Attribute	Description
Name	BULK_INPUT_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OTHER_PARTY_ID

Attribute	Description
Name	OTHER_PARTY_ID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACC_BRANCH

Attribute	Description
Name	ACC_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD

Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	**Description**	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	**Description**
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	**Description**
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	**Description**
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	**Description**
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	**Description**
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	**Description**
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	**Description**
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	**Description**
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	**Description**
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	**Description**
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Con

Attribute	**Description**
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	**Description**
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CHGREQ

Attribute	**Description**	
Name	CHGREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.7.2.RB-ReverseOvscheckspay-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONTREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.7.3.RB-ReverseOvscheckspay-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONTREFNO*
    - *LATESTVERSIONNO*
    - *RECORD_STAT*
    - *AUTHSTATUS*
    - *CURR_EVENT_CODE*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHKR*
    - *CHKDTTIME*
    - *EVENT_SEQ_NO*
    - *CONT_STAT*
    - *AUTH_STAT*
    - *CPTY_ID*
    - *CPTY_AC_NO*
    - *INSTRNO*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*

NET_AMT_REALISED
OTHER_BANK_CHARGES
COLL_BNK_CIF
BOOKINGDATE
MATURITY_DATE
VALUE_DATE
TRACK_LIMIT
CREDIT_LINE
FINANCING
INT_REM
INSTRUMENT_CODE
INSTR_DESC
PRCD
PRODDESC
USERREF_NO
XREF
COUNTRPRYNAM
LCY_AMT
COLLBANKNAME
PAYDUEDATE
CONREF
EVENTSEQ
PARTYTYP
ADDRESS
PARTYADDR2
PARTYADDR3
PARTYADDR4
WALKINCUSTFLG
COLLEC_BANK_CIF
COLLBNKNAME
DISCOUNT_AMOUNT
DB_ACC_REAL
BULK_INPUT_REF_NO
DRAWEE_BNK_NAME
AUTOLIQD
OTHER_PARTY_ID
VERSION_NO
TRANSITDAYS
MARGIN_PERCENTAGE
ACC_BRANCH
OTHR_PARTY_NAME
ACCBRN
TXNUDFDETAILS
  FLDNAME

- *FLDVAL*
- *Charges*
  - *CONREFNO*
  - *Charge-Association*
    - *COMPNT*
    - *CREATESN*
    - *RULE*
    - *WAIVER*
    - *DISACCRAPPL*
    - *ACCRREQD*
    - *DESC*
  - *Charge-Application*
    - *CREATESN*
    - *COMPNT*
    - *TGCCY*
    - *TGAMT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *DISACCRAPPL*
    - *WAIVER*
    - *LIQDIND*
  - *Charge-Liquidation*
    - *ESN*
    - *COMPNT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *LIQDSTAT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*

COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9

- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*

BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1

BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*

ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Clpref
CONTREFNNO

CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM
PAYMENT_MODE
LOANVALDATE
MATURITY_DATE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESTVERSIONNO

Attribute	Description
Name	LATESTVERSIONNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTATUS

Attribute	Description
Name	AUTHSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CURR_EVENT_CODE

Attribute	Description
Name	CURR_EVENT_CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

EVENT_SEQ_NO

Attribute	Description	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONT_STAT

Attribute	Description	
Name	CONT_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,L,R,H,

TOP

AUTH_STAT

Attribute	Description	
Name	AUTH_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U,

TOP

CPTY_ID

Attribute	Description	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

INT_REM

Attribute	Description	
Name	INT_REM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INSTRUMENT_CODE

Attribute	Description	
Name	INSTRUMENT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTR_DESC

Attribute	Description	
Name	INSTR_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRCD

Attribute	Description	
Name	PRCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLBANKNAME

Attribute	Description
Name	COLLBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREF

Attribute	Description
Name	CONREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

ADDRESS

Attribute	Description
Name	ADDRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTYADDR2

Attribute	Description
Name	PARTYADDR2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTYADDR3

Attribute	Description
Name	PARTYADDR3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTYADDR4

Attribute	Description
Name	PARTYADDR4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINCUSTFLG

Attribute	Description
Name	WALKINCUSTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COLLEC_BANK_CIF

Attribute	Description
Name	COLLEC_BANK_CIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BULK_INPUT_REF_NO

Attribute	Description
Name	BULK_INPUT_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

OTHER_PARTY_ID

Attribute	Description
Name	OTHER_PARTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACC_BRANCH

Attribute	Description
Name	ACC_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Clpref

Attribute	**Description**	
Name	Clpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNNO

Attribute	**Description**	
Name	CONTREFNNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CONTRACT_CCY

Attribute	**Description**	
Name	CONTRACT_CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TENOR

Attribute	Description
Name	TENOR

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description

Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.7.4.RB-ReverseOvscheckspay-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONTREFNO*
    - *Main-IO*
      - *CONTREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.8.ReversePDCContract

ReversePDCContract

2.8.1.RB-ReversePDCContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNUM*
    - *BOOKDT*
    - *USERREFNUM*
    - *XREF*
    - *PRDCD*
    - *MODCOD*
    - *UDSTAT*
    - *STOPDT*
    - *EVENTCD*
    - *INSTRUCODE*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *INSTRNO*
    - *INSTRDATE*
    - *CONTCCY*

AMOUNT
LCYAMT
OTHRPTYIDEN
BOOKINGDT
ACTDATE
VALUEDT
TRACKLIMIT
CRDLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
DISCOUNTAMT
COLLATERAL
COLLATVAL
COLLPOOL
ISRBNK
ISSUERBRN
CLGBANK
CLGBRN
SECTORCD
ENDPNT
INTREMARKS
ACCBRN
ROUTNO
DRACCBRN
INSTR_DESC
PRDDESC
CPTYNAME
OTHERPARTYNAME
ISSBANKNAME
ISSBRNCNAME
CLEARBANKNAME
AUTOLIQD
CLEARBRNCNAME
MAKER
MAKDTTIME
CHKR
CHKDTTIME
CONST
AUTHSTAT
BATCHREFENUM
BATCHSEQNO
DRACCREAL
CLGPRD

- *Party-Details*
  - *PRTYTYP*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *PARTYREFNO*
  - *COUNTRYCD*
  - *ADDLN1*
  - *ADDLN2*
  - *ADDLN3*
  - *ADDLN4*
  - *PARTLANG*
- *Settlements*
  - *CONREFNO*
  - *Contract-Settlement*
    - *IBANACNO*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *COMPNT*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *ACCCCY*
    - *EXRATE*
    - *NETIND*
    - *ERICCY*
    - *ERIAMT*
    - *GENMSG*
    - *RATECD*
    - *CLEARNW*
    - *COVERBY*
    - *RTGSPMNT*
    - *BANKPRIOR*
    - *RTGSNW*
    - *PAYBY*
    - *TRANSTYP*
    - *INSTYP*
    - *INSNO*
    - *CHGDET*
    - *PAYMNTDET1*
    - *PAYMNTDET2*
    - *PAYMNTDET3*
    - *PAYMNTDET4*
    - *SNDTRRCVINFO1*
    - *SNDTRRCVINFO2*

SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC

COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*

SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT

CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10

COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5

- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Con

- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Clpref

- *CONTREFNNO*
- *CONTRACT_CCY*
- *LATEVNSEQNO*
- *PRD*
- *PRDDESC*
- *COUNTERPARTY*
- *CURRENCY*
- *TENOR*
- *UNITS*
- *LOAN_CONREFNO*
- *RATECODE*
- *EXCHANGERATE*
- *RATE_TYPE*
- *MAXIMUM*
- *MINIMUM*
- *PAYMENT_MODE*
- *LOANVALDATE*
- *MATURITY_DATE*
- *Ude*
  - *USERDEID*

UDEDESC
RATEASOF
USAGE
USERDEVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description

Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USERREFNUM

Attribute	Description
Name	USERREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MODCOD

Attribute	Description
Name	MODCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BOOKINGDT

Attribute	Description
Name	BOOKINGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACTDATE

Attribute	Description
Name	ACTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRDLINE

Attribute	Description
Name	CRDLINE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,F,N

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLATVAL

Attribute	Description
Name	COLLATVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ISRBNK

Attribute	Description
Name	ISRBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ISSUERBRN

Attribute	Description
Name	ISSUERBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBANK

Attribute	Description
Name	CLGBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBRN

Attribute	Description
Name	CLGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ENDPNT

Attribute	Description
Name	ENDPNT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTREMARKS

Attribute	**Description**	
Name	INTREMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ROUTNO

Attribute	**Description**	
Name	ROUTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	27

TOP

DRACCBRN

Attribute	**Description**	
Name	DRACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ISSBANKNAME

Attribute	Description
Name	ISSBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ISSBRNCNAME

Attribute	Description
Name	ISSBRNCNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CLEARBANKNAME

Attribute	Description
Name	CLEARBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLEARBRNCNAME

Attribute	Description
Name	CLEARBRNCNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,H,R,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DRACCREAL

Attribute	**Description**	
Name	DRACCREAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CLGPRD

Attribute	**Description**	
Name	CLGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Party-Details

Attribute	**Description**	
Name	Party-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRTYTYP

Attribute	**Description**	
Name	PRTYTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	DRAWER,PAYEE

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTYREFNO

Attribute	Description
Name	PARTYREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ADDLN1

Attribute	Description

Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTLANG

Attribute	Description
Name	PARTLANG
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	Description	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	Description	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	**Description**	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,S</td></tr></table>

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.8.2.RB-ReversePDCContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.8.3.RB-ReversePDCContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNUM*
    - *BOOKDT*
    - *USERREFNUM*
    - *XREF*
    - *PRDCD*
    - *MODCOD*
    - *UDSTAT*
    - *STOPDT*
    - *EVENTCD*
    - *INSTRUCODE*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *INSTRNO*
    - *INSTRDATE*
    - *CONTCCY*
    - *AMOUNT*
    - *LCYAMT*
    - *OTHRPTYIDEN*

BOOKINGDT
ACTDATE
VALUEDT
TRACKLIMIT
CRDLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
DISCOUNTAMT
COLLATERAL
COLLATVAL
COLLPOOL
ISRBNK
ISSUERBRN
CLGBANK
CLGBRN
SECTORCD
ENDPNT
INTREMARKS
ACCBRN
ROUTNO
DRACCBRN
INSTR_DESC
PRDDESC
CPTYNAME
OTHERPARTYNAME
ISSBANKNAME
ISSBRNCNAME
CLEARBANKNAME
AUTOLIQD
CLEARBRNCNAME
MAKER
MAKDTTIME
CHKR
CHKDTTIME
CONST
AUTHSTAT
BATCHREFENUM
BATCHSEQNO
DRACCREAL
CLGPRD
Party-Details
  PRTYTYP
  PARTYIDEN

- *PARTYNAME*
- *PARTYREFNO*
- *COUNTRYCD*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ADDLN4*
- *PARTLANG*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*

COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID

POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*

RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Charges

CONREFNO

Charge-Association

COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC

Charge-Application

CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL

- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*
  - *COSTCD4*
  - *COSTCD5*
  - *TXNMIS1*
  - *TXNMIS10*
  - *TXNMIS2*
  - *TXNMIS3*
  - *TXNMIS4*
  - *TXNMIS5*
  - *TXNMIS6*
  - *TXNMIS7*
  - *TXNMIS8*
  - *TXNMIS9*
  - *MISGRPCOMP*
  - *MISGRPTXN*
  - *COMPMIS1*
  - *COMPMIS10*
  - *COMPMIS2*
  - *COMPMIS3*
  - *COMPMIS4*

COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8

- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Con

- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Clpref

- *CONTREFNNO*
- *CONTRACT_CCY*
- *LATEVNSEQNO*
- *PRD*
- *PRDDESC*
- *COUNTERPARTY*
- *CURRENCY*
- *TENOR*
- *UNITS*
- *LOAN_CONREFNO*
- *RATECODE*
- *EXCHANGERATE*
- *RATE_TYPE*
- *MAXIMUM*
- *MINIMUM*
- *PAYMENT_MODE*
- *LOANVALDATE*
- *MATURITY_DATE*
- *Ude*
  - *USERDEID*
  - *UDEDESC*
  - *RATEASOF*
  - *USAGE*

USERDEVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USERREFNUM

Attribute	Description
Name	USERREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MODCOD

Attribute	Description
Name	MODCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BOOKINGDT

Attribute	Description
Name	BOOKINGDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACTDATE

Attribute	Description
Name	ACTDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,F,N

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLATVAL

Attribute	Description
Name	COLLATVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ISRBNK

Attribute	Description
Name	ISRBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ISSUERBRN

Attribute	Description
Name	ISSUERBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBANK

Attribute	Description
Name	CLGBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBRN

Attribute	Description
Name	CLGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ENDPNT

Attribute	Description
Name	ENDPNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>27</td></tr></table>

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ISSBANKNAME

Attribute	**Description**	
Name	ISSBANKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ISSBRNCNAME

Attribute	**Description**	
Name	ISSBRNCNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CLEARBANKNAME

Attribute	**Description**	
Name	CLEARBANKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

AUTOLIQD

Attribute	**Description**	
Name	AUTOLIQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CLEARBRNCNAME

Attribute	Description
Name	CLEARBRNCNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,H,R,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CLGPRD

Attribute	Description
Name	CLGPRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	DRAWER,PAYEE

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PARTYREFNO

Attribute	**Description**	
Name	PARTYREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COUNTRYCD

Attribute	**Description**	
Name	COUNTRYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTLANG

Attribute	Description
Name	PARTLANG
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String

Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	Description	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,S</td></tr></table>

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

UDEDESC

Attribute	**Description**	
Name	UDEDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

RATEASOF

Attribute	**Description**	
Name	RATEASOF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

USAGE

Attribute	**Description**	
Name	USAGE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

USERDEVAL

Attribute	**Description**	
Name	USERDEVAL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.8.4.RB-ReversePDCContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNUM*
    - *Contract-Details-IO*
      - *CONREFNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.9.Reversefcychecksinput

Reversefcychecksinput

2.9.1.RB-Reversefcychecksinput-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *INSTRUMENT_CODE*
    - *INSTR_DESC*
    - *PRODUCT_CODE*
    - *PRDDESC*
    - *CONREFNUM*
    - *USERREF_NO1*
    - *XREF*
    - *BATCHREFENUM*
    - *BATCH_SEQ_NO*
    - *CASHLETTER_REFNUM*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *CPTY_AC_NO*
    - *ACC_BRANCH*
    - *INSTRUMENTNORE*

INSTRUMENT_DATE
CURRENCY
AMNT
LCY_AMOUNT
NOSTROACC
ACCBRN
COLLECTINGBANKCIF
COLL_BNK_NAME
BOOKINGDATE
VAL_DATE_BANK
VALUE_DATE_CUST
OTHR_PARTY_NAME
DRAWEE_BNK_NAME
AUTOLIQD
INTREMRKS
FINANCING
MARGIN_PERCENTAGE
TRACK_LIMIT
CRLINE
DISCOUNTAMT
MAKER
MAKDTTIME
CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
VERSION_NO
LATVERNO
Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*

RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1

ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*

REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5

Lcl_Clearing

FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3

- *REPRES4*
- *RCVRACC*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*

COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8

TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Clpref
CONTREFNNO
CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM

PAYMENT_MODE
LOANVALDATE
MATURITY_DATE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRODUCT_CODE

Attribute	Description

Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BATCHREFENUM

Attribute	**Description**	
Name	BATCHREFENUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BATCH_SEQ_NO

Attribute	**Description**	
Name	BATCH_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CASHLETTER_REFNUM

Attribute	**Description**	
Name	CASHLETTER_REFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	**Description**	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CTR_PRTY_NAME

Attribute	Description	
Name	CTR_PRTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTY_AC_NO

Attribute	Description	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACC_BRANCH

Attribute	Description	
Name	ACC_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INSTRUMENTNORE

Attribute	Description	
Name	INSTRUMENTNORE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

COLLECTINGBANKCIF

Attribute	Description
Name	COLLECTINGBANKCIF
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 255

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRLINE

Attribute	Description
Name	CRLINE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	Description	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RECORD_STAT

Attribute	Description	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,L,R,H,

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U,

TOP

VERSION_NO

Attribute	Description	
Name	VERSION_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String

Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

2.9.2.RB-Reversefcychecksinput-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONREFNUM*
    - *USERREF_NO1*
    - *XREF*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

XREF

Attribute	**Description**
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

2.9.3.RB-Reversefcychecksinput-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *INSTRUMENT_CODE*
    - *INSTR_DESC*
    - *PRODUCT_CODE*
    - *PRDDESC*
    - *CONREFNUM*
    - *USERREF_NO1*
    - *XREF*
    - *BATCHREFENUM*
    - *BATCH_SEQ_NO*
    - *CASHLETTER_REFNUM*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *CPTY_AC_NO*
    - *ACC_BRANCH*
    - *INSTRUMENTNORE*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*

LCY_AMOUNT
NOSTROACC
ACCBRN
COLLECTINGBANKCIF
COLL_BNK_NAME
BOOKINGDATE
VAL_DATE_BANK
VALUE_DATE_CUST
OTHR_PARTY_NAME
DRAWEE_BNK_NAME
AUTOLIQD
INTREMRKS
FINANCING
MARGIN_PERCENTAGE
TRACK_LIMIT
CRLINE
DISCOUNTAMT
MAKER
MAKDTTIME
CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
VERSION_NO
LATVERNO
Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*

RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4

BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*

ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*

TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1

COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Clpref
CONTREFNNO
CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM
PAYMENT_MODE
LOANVALDATE
MATURITY_DATE

Ude

USERDEID

UDEDESC

RATEASOF

USAGE

USERDEVAL

Con

CONTREFNO

EVENTSEQ

Adv

ADVNAME

SUPRESS

PRIOR

MEDM

PARTYIDEN

PARTYNAME

CHGREQ

PARTTYP

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PRODUCT_CODE

Attribute	Description
Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCH_SEQ_NO

Attribute	Description
Name	BATCH_SEQ_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CASHLETTER_REFNUM

Attribute	Description
Name	CASHLETTER_REFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CTR_PRTY_NAME

Attribute	**Description**	
Name	CTR_PRTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTY_AC_NO

Attribute	**Description**	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACC_BRANCH

Attribute	**Description**	
Name	ACC_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INSTRUMENTNORE

Attribute	**Description**	
Name	INSTRUMENTNORE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

COLLECTINGBANKCIF

Attribute	**Description**	
Name	COLLECTINGBANKCIF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

COLL_BNK_NAME

Attribute	**Description**	
Name	COLL_BNK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BOOKINGDATE

Attribute	**Description**	
Name	BOOKINGDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTREMRKS

Attribute	**Description**	
Name	INTREMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,N,F

TOP

MARGIN_PERCENTAGE

Attribute	**Description**	
Name	MARGIN_PERCENTAGE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRACK_LIMIT

Attribute	**Description**	
Name	TRACK_LIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CRLINE

Attribute	Description
Name	CRLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,L,R,H,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String

Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ADVNAME

Attribute	**Description**	
Name	ADVNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SUPRESS

Attribute	**Description**	
Name	SUPRESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.9.4.RB-Reversefcychecksinput-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONREFNUM*
      - *USERREF_NO1*
      - *XREF*
    - *Main-IO*
      - *CONREFNUM*
      - *USERREF_NO1*
      - *XREF*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description

Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.10.ModifyOutwardcollection

ModifyOutwardcollection

2.10.1.RB-ModifyOutwardcollection-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNUM*
    - *BOOKDT*
    - *USERREFNUM*
    - *BRN*
    - *PRDCD*
    - *MODULE*
    - *UDS*
    - *STOPDT*
    - *VERSIONNO*
    - *EVENTSEQ*
    - *EVENTCODE*
    - *INSTRUCODE*
    - *PRODTYP*
    - *CPTYIDEN*
    - *CPTYACCNUM*

INSTRNO
INSTRU_DATE
INITCCY
OSAMT
LCYAMT
OTHRPTYIDEN
BNKCD
BRN_D
REFERENCENO
BOOKINGDT
MATDAYS
LEADDAYS
DISPATCHDT
GRACEDAYS
PROTEST
TRACKLIMIT
CREDITLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
DISCAMT
COLLATERAL
COLLVL
COLLPOOL
ACCBRN
PAYDUEDATE
DRACCBRN
INTREMARKS
INSTRUMENT_DESCRIPTION
TXTPDTDESC
CPTYNAME
OTHERPARTYNAME
BNKNAME
BRNNAME
XREF
BATCHREFENUM
BATCHSEQNO
DRACCREAL
AUTOLIQD
CONTREFLOG
MAKER
MAKDTTIME
CHKR
CHKDTTIME

EVENTLOG
CONST
AUTHSTAT
LATVERNO
DATE
Party-Details
  PARTTYP
  PARTYIDEN
  PARTYNAME
  ADDLN1
  ADDLN2
  ADDLN3
  ADDLN4
  CNTY
  PRTYLANG
Settlements
  CONREFNO
  Contract-Settlement
    IBANACNO
    CUSTSPREAD
    SPREADDEFN
    COMPNT
    TAGCCY
    ACCBRN
    ACC
    ACCCCY
    EXRATE
    NETIND
    ERICCY
    ERIAMT
    GENMSG
    RATECD
    CLEARNW
    COVERBY
    RTGSPMNT
    BANKPRIOR
    RTGSNW
    PAYBY
    TRANSTYP
    INSTYP
    INSNO
    CHGDET
    PAYMNTDET1
    PAYMNTDET2

PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2

BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*

ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP

PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3

- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*

- *CREATESN*
- *COMPNT*
- *TGCCY*
- *TGAMT*
- *CHRGCCY*
- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Con*
  - *CONTREFNO*
  - *EVENTSEQ*
  - *Adv*
    - *ADVNAME*
    - *SUPRESS*
    - *PRIOR*
    - *MEDM*
    - *PARTYIDEN*
    - *PARTYNAME*
    - *CHGREQ*
    - *PARTTYP*
- *Clpref*
  - *CONTREFNNO*
  - *CONTRACT_CCY*
  - *LATEVNSEQNO*
  - *PRD*
  - *PRDDESC*
  - *COUNTERPARTY*
  - *CURRENCY*
  - *TENOR*
  - *UNITS*
  - *LOAN_CONREFNO*
  - *RATECODE*
  - *EXCHANGERATE*
  - *RATE_TYPE*
  - *MAXIMUM*
  - *MINIMUM*
  - *PAYMENT_MODE*

LOANVALDATE

MATURITY_DATE

Ude

USERDEID

UDEDESC

RATEASOF

USAGE

USERDEVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USERREFNUM

Attribute	Description
Name	USERREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDS

Attribute	Description
Name	UDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSIONNO

Attribute	Description
Name	VERSIONNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

PRODTYP

Attribute	Description
Name	PRODTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INITCCY

Attribute	Description
Name	INITCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

OSAMT

Attribute	Description
Name	OSAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BRN_D

Attribute	Description
Name	BRN_D
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKINGDT

Attribute	Description
Name	BOOKINGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LEADDAYS

Attribute	Description
Name	LEADDAYS

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISPATCHDT

Attribute	Description
Name	DISPATCHDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,N,F</td></tr></table>

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COLLATERAL

Attribute	**Description**	
Name	COLLATERAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,C,T,N

TOP

COLLVL

Attribute	**Description**	
Name	COLLVL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COLLPOOL

Attribute	**Description**	
Name	COLLPOOL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description
Name	INSTRUMENT_DESCRIPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

TXTPDTDESC

Attribute	Description
Name	TXTPDTDESC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTYNAME

Attribute	**Description**	
Name	CPTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYNAME

Attribute	**Description**	
Name	OTHERPARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BNKNAME

Attribute	**Description**	
Name	BNKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CONTREFLOG

Attribute	Description
Name	CONTREFLOG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EVENTLOG

Attribute	Description
Name	EVENTLOG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,H,R,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / DRAWEE,DRAWER,PAYEE,COLLECTING_BANK,

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRTYLANG

Attribute	Description
Name	PRTYLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO

Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String

Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	Description	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO5

Attribute	Description	
Name	SNDTRRCVINFO5	
Datatype	String	
Description	Indicates Sender To Receiver Information 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	Description	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4

Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1

Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5

Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	

Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	**Description**
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	**Description**
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	**Description**
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	**Description**
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	**Description**	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS7

Attribute	**Description**	
Name	TRANMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS8

Attribute	**Description**	
Name	TRANMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String

Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description

Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / DRAWEE,DRAWER,PAYEE,COLLECTING_BANK,

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description

Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.10.2.RB-ModifyOutwardcollection-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNUM*
    - *VERSIONNO*
    - *EVENTSEQ*
    - *EVENTCODE*
    - *CPTYACCNUM*
    - *INSTRNO*
    - *INSTRU_DATE*
    - *OSAMT*
    - *LCYAMT*
    - *OTHRPTYIDEN*
    - *BNKCD*
    - *BRN_D*
    - *REFERENCENO*
    - *MATDAYS*
    - *LEADDAYS*
    - *DISPATCHDT*
    - *GRACEDAYS*
    - *PROTEST*

MARGINPERC
FINANCING
COLLATERAL
COLLVL
COLLPOOL
ACCBRN
SUBSYSSTAT
DRACCBRN
DRACCREAL
AUTOLIQD
MAKER
MAKDTTIME
CHKR
CHKDTTIME
EVENTLOG
CONST
AUTHSTAT
LATVERNO
DATE
Party-Details
  PARTYIDEN
  PARTYNAME
  ADDLN1
  ADDLN2
  ADDLN3
  ADDLN4
  CNTY
  WALKIN
  PRTYLANG
Settlements
  CONREFNO
  LATEVNSEQNO
  Contract-Settlement
    IBANACNO
    CUSTSPREAD
    SPREADDEFN
    COMPNT
    TAGCCY
    ACCBRN
    ACC
    ACCCCY
    EXRATE
    NETIND
    ERICCY

ERIAMT

GENMSG

RATECD

Settlement-Detail

- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *CONTREFNO*
- *ESN*
- *COMPNT*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *AMTTAG*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*
- *SUPPID*

PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFXRATE
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8

- *TXNMIS9*
- *MISGRPCOMP*
- *MISGRPTXN*
- *COMPMIS1*
- *COMPMIS10*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *FUNDMIS1*
- *FUNDMIS10*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*

CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
CHRGCCY
CHRGAMT
LIQDSTAT
Con
CONTREFNO
EVENTSEQ
Clpref
CONTREFNNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSIONNO

Attribute	Description
Name	VERSIONNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OSAMT

Attribute	Description
Name	OSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BRN_D

Attribute	Description
Name	BRN_D
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEADDAYS

Attribute	Description
Name	LEADDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISPATCHDT

Attribute	Description
Name	DISPATCHDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLVL

Attribute	Description
Name	COLLVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SUBSYSSTAT

Attribute	Description
Name	SUBSYSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EVENTLOG

Attribute	Description
Name	EVENTLOG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,H,R,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

WALKIN

Attribute	Description
Name	WALKIN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRTYLANG

Attribute	Description
Name	PRTYLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	Description	
Name	REGREP1	
Datatype	String	
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description	
Name	REGREP2	
Datatype	String	
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTTAG

Attribute	Description	
Name	AMTTAG	
Datatype	String	
Description	Indicates Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1

Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	**Description**	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	**Description**	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	**Description**	
Name	REFXRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	Description	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	Description	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	Description	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	Description	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**

Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String

Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.10.3.RB-ModifyOutwardcollection-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNUM*
    - *BOOKDT*
    - *USERREFNUM*
    - *BRN*
    - *PRDCD*
    - *MODULE*
    - *UDS*
    - *STOPDT*
    - *VERSIONNO*
    - *EVENTSEQ*
    - *EVENTCODE*
    - *INSTRUCODE*
    - *PRODTYP*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *INSTRNO*
    - *INSTRU_DATE*
    - *INITCCY*

OSAMT
LCYAMT
OTHRPTYIDEN
BNKCD
BRN_D
REFERENCENO
BOOKINGDT
MATDAYS
LEADDAYS
DISPATCHDT
GRACEDAYS
PROTEST
TRACKLIMIT
CREDITLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
DISCAMT
COLLATERAL
COLLVL
COLLPOOL
ACCBRN
PAYDUEDATE
DRACCBRN
INTREMARKS
INSTRUMENT_DESCRIPTION
TXTPDTDESC
CPTYNAME
OTHERPARTYNAME
BNKNAME
BRNNAME
XREF
BATCHREFENUM
BATCHSEQNO
DRACCREAL
AUTOLIQD
CONTREFLOG
MAKER
MAKDTTIME
CHKR
CHKDTTIME
EVENTLOG
CONST
AUTHSTAT

LATVERNO

DATE

Party-Details

- *PARTTYP*
- *PARTYIDEN*
- *PARTYNAME*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ADDLN4*
- *CNTY*
- *PRTYLANG*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*

SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5

COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*

SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD

COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6

- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*

TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
Clpref
CONTREFNNO
CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM
PAYMENT_MODE
LOANVALDATE
MATURITY_DATE
Ude

USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USERREFNUM

Attribute	Description
Name	USERREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

UDS

Attribute	Description
Name	UDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

STOPDT

Attribute	Description
Name	STOPDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSIONNO

Attribute	Description
Name	VERSIONNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRODTYP

Attribute	Description
Name	PRODTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INITCCY

Attribute	Description
Name	INITCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OSAMT

Attribute	Description
Name	OSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BRN_D

Attribute	Description
Name	BRN_D
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BOOKINGDT

Attribute	Description
Name	BOOKINGDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LEADDAYS

Attribute	Description
Name	LEADDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISPATCHDT

Attribute	Description
Name	DISPATCHDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CREDITLINE

Attribute	**Description**	
Name	CREDITLINE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

OTHPARTYLIMIT

Attribute	**Description**	
Name	OTHPARTYLIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MARGINPERC

Attribute	**Description**	
Name	MARGINPERC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,N,F

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLVL

Attribute	Description
Name	COLLVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PAYDUEDATE

Attribute	**Description**	
Name	PAYDUEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DRACCBRN

Attribute	**Description**	
Name	DRACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INTREMARKS

Attribute	**Description**	
Name	INTREMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INSTRUMENT_DESCRIPTION

Attribute	**Description**	
Name	INSTRUMENT_DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

TXTPDTDESC

Attribute	Description
Name	TXTPDTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONTREFLOG

Attribute	Description
Name	CONTREFLOG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVENTLOG

Attribute	Description
Name	EVENTLOG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,H,R,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / DRAWEE,DRAWER,PAYEE,COLLECTING_BANK,

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN3

Attribute	Description	
Name	ADDLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDLN4

Attribute	Description	
Name	ADDLN4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CNTY

Attribute	Description	
Name	CNTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRTYLANG

Attribute	Description	
Name	PRTYLANG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	Description	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	Description	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	Description	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	Description	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	Description	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS10

Attribute	Description	
Name	FUNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Txnmisdetails

Attribute	Description	
Name	Txnmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Compmisdetails

Attribute	Description	
Name	Compmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Fundmisdetails

Attribute	Description	
Name	Fundmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number

Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY

Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / DRAWEE,DRAWER,PAYEE,COLLECTING_BANK,

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description

Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

RATEASOF

Attribute	**Description**	
Name	RATEASOF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

USAGE

Attribute	**Description**	
Name	USAGE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

USERDEVAL

Attribute	**Description**	
Name	USERDEVAL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.10.4.RB-ModifyOutwardcollection-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNUM*
    - *Contract-Details-IO*
      - *CONREFNUM*
      - *VERSIONNO*
      - *EVENTSEQ*
      - *EVENTCODE*
      - *CPTYACCNUM*
      - *INSTRNO*
      - *INSTRU_DATE*
      - *OSAMT*
      - *LCYAMT*
      - *OTHRPTYIDEN*
      - *BNKCD*
      - *BRN_D*
      - *REFERENCENO*
      - *MATDAYS*
      - *LEADDAYS*

DISPATCHDT
GRACEDAYS
PROTEST
MARGINPERC
FINANCING
COLLATERAL
COLLVL
COLLPOOL
ACCBRN
SUBSYSSTAT
DRACCBRN
DRACCREAL
AUTOLIQD
MAKER
MAKDTTIME
CHKR
CHKDTTIME
EVENTLOG
CONST
AUTHSTAT
LATVERNO
DATE
Party-Details
  PARTYIDEN
  PARTYNAME
  ADDLN1
  ADDLN2
  ADDLN3
  ADDLN4
  CNTY
  WALKIN
  PRTYLANG
Settlements
  CONREFNO
  LATEVNSEQNO
  Contract-Settlement
    IBANACNO
    CUSTSPREAD
    SPREADDEFN
    COMPNT
    TAGCCY
    ACCBRN
    ACC
    ACCCCY

EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *CONTREFNO*
- *ESN*
- *COMPNT*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *AMTTAG*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*

ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFXRATE
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5

- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*
- *MISGRPTXN*
- *COMPMIS1*
- *COMPMIS10*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *FUNDMIS1*
- *FUNDMIS10*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*

COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
CHRGCCY
CHRGAMT
LIQDSTAT
Con
CONTREFNO
EVENTSEQ
Clpref
CONTREFNNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSIONNO

Attribute	Description
Name	VERSIONNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OSAMT

Attribute	Description
Name	OSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHRPTYIDEN

Attribute	**Description**	
Name	OTHRPTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BNKCD

Attribute	**Description**	
Name	BNKCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BRN_D

Attribute	**Description**	
Name	BRN_D	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFERENCENO

Attribute	**Description**	
Name	REFERENCENO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MATDAYS

Attribute	Description	
Name	MATDAYS	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEADDAYS

Attribute	Description	
Name	LEADDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISPATCHDT

Attribute	Description	
Name	DISPATCHDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PROTEST

Attribute	Description	
Name	PROTEST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLVL

Attribute	Description
Name	COLLVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SUBSYSSTAT

Attribute	**Description**	
Name	SUBSYSSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

DRACCBRN

Attribute	**Description**	
Name	DRACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DRACCREAL

Attribute	**Description**	
Name	DRACCREAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EVENTLOG

Attribute	Description
Name	EVENTLOG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,H,R,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

LATVERNO

Attribute	Description
Name	LATVERNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CNTY

Attribute	Description

Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

WALKIN

Attribute	Description
Name	WALKIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRTYLANG

Attribute	Description
Name	PRTYLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String

Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description

Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	**Description**	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CONTREFNO

Attribute	**Description**	
Name	CONTREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2

Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRPART

Attribute	**Description**	
Name	SNDRRCVRPART	
Datatype	Number	
Description	Indicates Sender Receiver Participant	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	**Description**	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3

Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	**Description**	
Name	REFXRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	**Description**
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	**Description**
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	**Description**
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	**Description**
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CONREFNO

Attribute	Description

Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description

Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String

Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Con

Attribute	Description	
Name	Con	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EVENTSEQ

Attribute	Description	
Name	EVENTSEQ	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Clpref

Attribute	Description	
Name	Clpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNNO

Attribute	Description	
Name	CONTREFNNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.11.ModifyOvscheckspay

ModifyOvscheckspay

2.11.1.RB-ModifyOvscheckspay-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONTREFNO*
    - *LATESTVERSIONNO*
    - *RECORD_STAT*
    - *AUTHSTATUS*
    - *CURR_EVENT_CODE*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHKR*
    - *CHKDTTIME*
    - *EVENT_SEQ_NO*
    - *CONT_STAT*
    - *AUTH_STAT*
    - *CPTY_ID*
    - *CPTY_AC_NO*
    - *INSTRNO*

INSTRUMENT_DATE
CURRENCY
AMNT
NET_AMT_REALISED
OTHER_BANK_CHARGES
COLL_BNK_CIF
BOOKINGDATE
MATURITY_DATE
VALUE_DATE
TRACK_LIMIT
CREDIT_LINE
FINANCING
INT_REM
INSTRUMENT_CODE
INSTR_DESC
PRCD
PRODDESC
USERREF_NO
XREF
COUNTRPRYNAM
LCY_AMT
COLLBANKNAME
PAYDUEDATE
CONREF
EVENTSEQ
PARTYTYP
ADDRESS
PARTYADDR2
PARTYADDR3
PARTYADDR4
WALKINCUSTFLG
COLLEC_BANK_CIF
COLLBNKNAME
DISCOUNT_AMOUNT
DB_ACC_REAL
BULK_INPUT_REF_NO
DRAWEE_BNK_NAME
AUTOLIQD
OTHER_PARTY_ID
VERSION_NO
TRANSITDAYS
MARGIN_PERCENTAGE
ACC_BRANCH
OTHR_PARTY_NAME

ACCBRN

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*

COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6

- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*

CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2

ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*

REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4

RCVRACC

Clpref

CONTREFNNO

CONTRACT_CCY

LATEVNSEQNO

PRD

PRDDESC

COUNTERPARTY

CURRENCY

TENOR

UNITS

LOAN_CONREFNO

RATECODE

EXCHANGERATE

RATE_TYPE

MAXIMUM

MINIMUM

PAYMENT_MODE

LOANVALDATE

MATURITY_DATE

Ude

USERDEID

UDEDESC

RATEASOF

USAGE

USERDEVAL

Con

CONTREFNO

EVENTSEQ

Adv

ADVNAME

SUPRESS

PRIOR

MEDM

PARTYIDEN

PARTYNAME

CHGREQ

PARTTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESTVERSIONNO

Attribute	**Description**	
Name	LATESTVERSIONNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTATUS

Attribute	**Description**	
Name	AUTHSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CURR_EVENT_CODE

Attribute	**Description**	
Name	CURR_EVENT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONT_STAT

Attribute	Description
Name	CONT_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,L,R,H,</td></tr></table>

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,U,</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRNO

Attribute	**Description**	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRUMENT_DATE

Attribute	**Description**	
Name	INSTRUMENT_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

CURRENCY

Attribute	**Description**	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNT

Attribute	**Description**	
Name	AMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

INT_REM

Attribute	Description
Name	INT_REM
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLBANKNAME

Attribute	Description
Name	COLLBANKNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREF

Attribute	Description
Name	CONREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ADDRESS

Attribute	Description
Name	ADDRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYADDR2

Attribute	Description
Name	PARTYADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYADDR3

Attribute	Description
Name	PARTYADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYADDR4

Attribute	Description
Name	PARTYADDR4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINCUSTFLG

Attribute	Description
Name	WALKINCUSTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COLLEC_BANK_CIF

Attribute	Description
Name	COLLEC_BANK_CIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BULK_INPUT_REF_NO

Attribute	Description
Name	BULK_INPUT_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OTHER_PARTY_ID

Attribute	Description
Name	OTHER_PARTY_ID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACC_BRANCH

Attribute	Description
Name	ACC_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD

Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	Description	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	Description	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	Description	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	Description	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS10

Attribute	Description	
Name	FUNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Txnmisdetails

Attribute	Description	
Name	Txnmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Compmisdetails

Attribute	Description	
Name	Compmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Fundmisdetails

Attribute	Description	
Name	Fundmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	Description	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	Description	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	Description	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	Description	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	**Description**
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	**Description**
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	**Description**
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	**Description**
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	Description	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	Description	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COUNTERPARTY

Attribute	**Description**	
Name	COUNTERPARTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CURRENCY

Attribute	**Description**	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TENOR

Attribute	**Description**	
Name	TENOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	**Description**
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	**Description**
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Con

Attribute	**Description**
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	**Description**
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CHGREQ

Attribute	**Description**	
Name	CHGREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.11.2.RB-ModifyOvscheckspay-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONTREFNO*
    - *LATESTEVENTSEQNO*
    - *LATESTVERSIONNO*
    - *RECORD_STAT*
    - *AUTHSTATUS*
    - *CURR_EVENT_CODE*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHKR*
    - *CHKDTTIME*
    - *EVENT_SEQ_NO*
    - *CONT_STAT*
    - *AUTH_STAT*
    - *INSTRNO*
    - *INSTRUMENT_DATE*
    - *AMNT*
    - *NET_AMT_REALISED*
    - *OTHER_BANK_CHARGES*

TRACK_LIMIT
CREDIT_LINE
FINANCING
INT_REM
USERREF_NO
XREF
COUNTRPRYNAM
LCY_AMT
COLLBANKNAME
EVENTSEQ
ADDRESS
PARTYADDR2
PARTYADDR3
PARTYADDR4
COLLEC_BANK_CIF
COLLBNKNAME
DISCOUNT_AMOUNT
DRAWEE_BNK_NAME
AUTOLIQD
VERSION_NO
SUBSYSSTAT
MARGIN_PERCENTAGE
OTHR_PARTY_NAME
TXNUDFDETAILS
- *FLDNAME*
- *FLDVAL*

Charges
- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*

WAIVER
LIQDIND
Charge-Liquidation
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFXRATE
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6

- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *FUNDMIS1*
- *FUNDMIS10*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *Settlement-Detail*
    - *INSTRCD1*
    - *INSTRCD2*
    - *INSTRCD3*
    - *INSTRCD4*
    - *ITIMEIND1*
    - *ITIMEIND2*
    - *ITIMEIND3*
    - *INSTRCD5*
    - *CONTREFNO*

ESN
COMPNT
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
AMTTAG
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2

REPRES3

REPRES4

RCVRACC

Clpref

CONTREFNNO

Con

CONTREFNO

EVENTSEQ

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATESTEVENTSEQNO

Attribute	Description
Name	LATESTEVENTSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATESTVERSIONNO

Attribute	Description
Name	LATESTVERSIONNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

AUTHSTATUS

Attribute	Description
Name	AUTHSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CURR_EVENT_CODE

Attribute	Description
Name	CURR_EVENT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONT_STAT

Attribute	Description
Name	CONT_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,L,R,H,</td></tr></table>

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

INT_REM

Attribute	Description
Name	INT_REM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLBANKNAME

Attribute	Description
Name	COLLBANKNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDRESS

Attribute	Description
Name	ADDRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTYADDR2

Attribute	Description
Name	PARTYADDR2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTYADDR3

Attribute	Description
Name	PARTYADDR3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PARTYADDR4

Attribute	**Description**	
Name	PARTYADDR4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COLLEC_BANK_CIF

Attribute	**Description**	
Name	COLLEC_BANK_CIF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COLLBNKNAME

Attribute	**Description**	
Name	COLLBNKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DISCOUNT_AMOUNT

Attribute	**Description**	
Name	DISCOUNT_AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUBSYSSTAT

Attribute	Description
Name	SUBSYSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TGCCY

Attribute	Description	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	Description	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	Description	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String

Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**	
Name	REGREP2	
Datatype	String	
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**
Name	ENVCONT2
Datatype	String

Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTTAG

Attribute	Description	
Name	AMTTAG	
Datatype	String	
Description	Indicates Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description	
Name	SNDRCUSTNAME2	
Datatype	String	
Description	Indicates Sender Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	Description	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4

Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	Description	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	Description	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	Description	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.11.3.RB-ModifyOvscheckspay-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONTREFNO*
    - *LATESTVERSIONNO*
    - *RECORD_STAT*
    - *AUTHSTATUS*
    - *CURR_EVENT_CODE*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHKR*
    - *CHKDTTIME*
    - *EVENT_SEQ_NO*
    - *CONT_STAT*
    - *AUTH_STAT*
    - *CPTY_ID*
    - *CPTY_AC_NO*
    - *INSTRNO*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*

NET_AMT_REALISED
OTHER_BANK_CHARGES
COLL_BNK_CIF
BOOKINGDATE
MATURITY_DATE
VALUE_DATE
TRACK_LIMIT
CREDIT_LINE
FINANCING
INT_REM
INSTRUMENT_CODE
INSTR_DESC
PRCD
PRODDESC
USERREF_NO
XREF
COUNTRPRYNAM
LCY_AMT
COLLBANKNAME
PAYDUEDATE
CONREF
EVENTSEQ
PARTYTYP
ADDRESS
PARTYADDR2
PARTYADDR3
PARTYADDR4
WALKINCUSTFLG
COLLEC_BANK_CIF
COLLBNKNAME
DISCOUNT_AMOUNT
DB_ACC_REAL
BULK_INPUT_REF_NO
DRAWEE_BNK_NAME
AUTOLIQD
OTHER_PARTY_ID
VERSION_NO
TRANSITDAYS
MARGIN_PERCENTAGE
ACC_BRANCH
OTHR_PARTY_NAME
ACCBRN
TXNUDFDETAILS
  FLDNAME

- *FLDVAL*
- *Charges*
  - *CONREFNO*
  - *Charge-Association*
    - *COMPNT*
    - *CREATESN*
    - *RULE*
    - *WAIVER*
    - *DISACCRAPPL*
    - *ACCRREQD*
    - *DESC*
  - *Charge-Application*
    - *CREATESN*
    - *COMPNT*
    - *TGCCY*
    - *TGAMT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *DISACCRAPPL*
    - *WAIVER*
    - *LIQDIND*
  - *Charge-Liquidation*
    - *ESN*
    - *COMPNT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *LIQDSTAT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*

COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9

- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*

BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1

BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*

ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Clpref
CONTREFNNO

CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM
PAYMENT_MODE
LOANVALDATE
MATURITY_DATE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESTVERSIONNO

Attribute	Description
Name	LATESTVERSIONNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTATUS

Attribute	Description
Name	AUTHSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CURR_EVENT_CODE

Attribute	Description
Name	CURR_EVENT_CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

EVENT_SEQ_NO

Attribute	Description	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONT_STAT

Attribute	Description	
Name	CONT_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,L,R,H,

TOP

AUTH_STAT

Attribute	Description	
Name	AUTH_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U,

TOP

CPTY_ID

Attribute	Description	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

INT_REM

Attribute	Description
Name	INT_REM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLBANKNAME

Attribute	Description
Name	COLLBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREF

Attribute	Description
Name	CONREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

ADDRESS

Attribute	Description
Name	ADDRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTYADDR2

Attribute	Description
Name	PARTYADDR2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTYADDR3

Attribute	Description
Name	PARTYADDR3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTYADDR4

Attribute	Description
Name	PARTYADDR4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINCUSTFLG

Attribute	Description
Name	WALKINCUSTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COLLEC_BANK_CIF

Attribute	Description
Name	COLLEC_BANK_CIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DB_ACC_REAL

Attribute	**Description**	
Name	DB_ACC_REAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BULK_INPUT_REF_NO

Attribute	**Description**	
Name	BULK_INPUT_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DRAWEE_BNK_NAME

Attribute	**Description**	
Name	DRAWEE_BNK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AUTOLIQD

Attribute	**Description**	
Name	AUTOLIQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

OTHER_PARTY_ID

Attribute	Description	
Name	OTHER_PARTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

VERSION_NO

Attribute	Description	
Name	VERSION_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRANSITDAYS

Attribute	Description	
Name	TRANSITDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MARGIN_PERCENTAGE

Attribute	Description	
Name	MARGIN_PERCENTAGE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACC_BRANCH

Attribute	Description	
Name	ACC_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Clpref

Attribute	**Description**	
Name	Clpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNNO

Attribute	**Description**	
Name	CONTREFNNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CONTRACT_CCY

Attribute	**Description**	
Name	CONTRACT_CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TENOR

Attribute	Description
Name	TENOR

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description

Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.11.4.RB-ModifyOvscheckspay-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONTREFNO*
    - *Main-IO*
      - *CONTREFNO*
      - *LATESTEVENTSEQNO*
      - *LATESTVERSIONNO*
      - *RECORD_STAT*
      - *AUTHSTATUS*
      - *CURR_EVENT_CODE*
      - *MAKER*
      - *MAKERDTSTAMP*
      - *CHKR*
      - *CHKDTTIME*
      - *EVENT_SEQ_NO*
      - *CONT_STAT*
      - *AUTH_STAT*
      - *INSTRNO*
      - *INSTRUMENT_DATE*

AMNT
NET_AMT_REALISED
OTHER_BANK_CHARGES
TRACK_LIMIT
CREDIT_LINE
FINANCING
INT_REM
USERREF_NO
XREF
COUNTRPRYNAM
LCY_AMT
COLLBANKNAME
EVENTSEQ
ADDRESS
PARTYADDR2
PARTYADDR3
PARTYADDR4
COLLEC_BANK_CIF
COLLBNKNAME
DISCOUNT_AMOUNT
DRAWEE_BNK_NAME
AUTOLIQD
VERSION_NO
SUBSYSSTAT
MARGIN_PERCENTAGE
OTHR_PARTY_NAME
TXNUDFDETAILS
  FLDNAME
  FLDVAL
Charges
  LATEVNSEQNO
  CONREFNO
  Charge-Association
    COMPNT
    CREATESN
    RULE
    WAIVER
    DISACCRAPPL
    ACCRREQD
    DESC
  Charge-Application
    COMPNT
    TGCCY
    TGAMT

CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFXRATE
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3

- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *FUNDMIS1*
- *FUNDMIS10*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *Settlement-Detail*
    - *INSTRCD1*
    - *INSTRCD2*
    - *INSTRCD3*
    - *INSTRCD4*
    - *ITIMEIND1*
    - *ITIMEIND2*

ITIMEIND3
INSTRCD5
CONTREFNO
ESN
COMPNT
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
AMTTAG
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6

DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Clpref
CONTREFNNO
Con
CONTREFNO
EVENTSEQ
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATESTEVENTSEQNO

Attribute	Description
Name	LATESTEVENTSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATESTVERSIONNO

Attribute	Description
Name	LATESTVERSIONNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

AUTHSTATUS

Attribute	Description
Name	AUTHSTATUS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CURR_EVENT_CODE

Attribute	**Description**	
Name	CURR_EVENT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	**Description**	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONT_STAT

Attribute	Description
Name	CONT_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,L,R,H,

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

INT_REM

Attribute	Description
Name	INT_REM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

USERREF_NO

Attribute	Description

Name	USERREF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLBANKNAME

Attribute	Description
Name	COLLBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDRESS

Attribute	Description
Name	ADDRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYADDR2

Attribute	Description
Name	PARTYADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYADDR3

Attribute	Description
Name	PARTYADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYADDR4

Attribute	Description
Name	PARTYADDR4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

COLLEC_BANK_CIF

Attribute	Description
Name	COLLEC_BANK_CIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AUTOLIQD

Attribute	**Description**	
Name	AUTOLIQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VERSION_NO

Attribute	**Description**	
Name	VERSION_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUBSYSSTAT

Attribute	**Description**	
Name	SUBSYSSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

MARGIN_PERCENTAGE

Attribute	**Description**	
Name	MARGIN_PERCENTAGE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	**Description**

Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String

Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	Description
Name	REFXRATE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Txnmisdetails

Attribute	**Description**	
Name	Txnmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

Compmisdetails

Attribute	**Description**	
Name	Compmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

Fundmisdetails

Attribute	**Description**	
Name	Fundmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String

Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD

Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG

Datatype	String
Description	Indicates Amount Tag
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.12.ModifyPDCContract

ModifyPDCContract

2.12.1.RB-ModifyPDCContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNUM*
    - *BOOKDT*
    - *USERREFNUM*
    - *XREF*
    - *PRDCD*
    - *MODCOD*
    - *UDSTAT*
    - *STOPDT*
    - *EVENTCD*
    - *INSTRUCODE*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *INSTRNO*
    - *INSTRDATE*
    - *CONTCCY*

AMOUNT
LCYAMT
OTHRPTYIDEN
BOOKINGDT
ACTDATE
VALUEDT
TRACKLIMIT
CRDLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
DISCOUNTAMT
COLLATERAL
COLLATVAL
COLLPOOL
ISRBNK
ISSUERBRN
CLGBANK
CLGBRN
SECTORCD
ENDPNT
INTREMARKS
ACCBRN
ROUTNO
DRACCBRN
INSTR_DESC
PRDDESC
CPTYNAME
OTHERPARTYNAME
ISSBANKNAME
ISSBRNCNAME
CLEARBANKNAME
AUTOLIQD
CLEARBRNCNAME
MAKER
MAKDTTIME
CHKR
CHKDTTIME
CONST
AUTHSTAT
BATCHREFENUM
BATCHSEQNO
DRACCREAL
CLGPRD

- *Party-Details*
  - *PRTYTYP*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *PARTYREFNO*
  - *COUNTRYCD*
  - *ADDLN1*
  - *ADDLN2*
  - *ADDLN3*
  - *ADDLN4*
  - *PARTLANG*
- *Settlements*
  - *CONREFNO*
  - *Contract-Settlement*
    - *IBANACNO*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *COMPNT*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *ACCCCY*
    - *EXRATE*
    - *NETIND*
    - *ERICCY*
    - *ERIAMT*
    - *GENMSG*
    - *RATECD*
    - *CLEARNW*
    - *COVERBY*
    - *RTGSPMNT*
    - *BANKPRIOR*
    - *RTGSNW*
    - *PAYBY*
    - *TRANSTYP*
    - *INSTYP*
    - *INSNO*
    - *CHGDET*
    - *PAYMNTDET1*
    - *PAYMNTDET2*
    - *PAYMNTDET3*
    - *PAYMNTDET4*
    - *SNDTRRCVINFO1*
    - *SNDTRRCVINFO2*

SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC

COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*

SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT

CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10

COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5

- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Con

- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Clpref

- *CONTREFNNO*
- *CONTRACT_CCY*
- *LATEVNSEQNO*
- *PRD*
- *PRDDESC*
- *COUNTERPARTY*
- *CURRENCY*
- *TENOR*
- *UNITS*
- *LOAN_CONREFNO*
- *RATECODE*
- *EXCHANGERATE*
- *RATE_TYPE*
- *MAXIMUM*
- *MINIMUM*
- *PAYMENT_MODE*
- *LOANVALDATE*
- *MATURITY_DATE*
- *Ude*
  - *USERDEID*

UDEDESC
RATEASOF
USAGE
USERDEVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description

Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USERREFNUM

Attribute	Description
Name	USERREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

MODCOD

Attribute	Description
Name	MODCOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BOOKINGDT

Attribute	**Description**	
Name	BOOKINGDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACTDATE

Attribute	**Description**	
Name	ACTDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALUEDT

Attribute	**Description**	
Name	VALUEDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRACKLIMIT

Attribute	**Description**	
Name	TRACKLIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CRDLINE

Attribute	**Description**
Name	CRDLINE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,F,N

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLATVAL

Attribute	Description
Name	COLLATVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ISRBNK

Attribute	Description
Name	ISRBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ISSUERBRN

Attribute	Description
Name	ISSUERBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBANK

Attribute	Description
Name	CLGBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBRN

Attribute	Description
Name	CLGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ENDPNT

Attribute	Description
Name	ENDPNT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTREMARKS

Attribute	**Description**	
Name	INTREMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ROUTNO

Attribute	**Description**	
Name	ROUTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	27

TOP

DRACCBRN

Attribute	**Description**	
Name	DRACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INSTR_DESC

Attribute	**Description**	
Name	INSTR_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTYNAME

Attribute	**Description**	
Name	CPTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYNAME

Attribute	**Description**	
Name	OTHERPARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ISSBANKNAME

Attribute	Description
Name	ISSBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ISSBRNCNAME

Attribute	Description
Name	ISSBRNCNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CLEARBANKNAME

Attribute	Description
Name	CLEARBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLEARBRNCNAME

Attribute	Description
Name	CLEARBRNCNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,H,R,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DRACCREAL

Attribute	**Description**	
Name	DRACCREAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CLGPRD

Attribute	**Description**	
Name	CLGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Party-Details

Attribute	**Description**	
Name	Party-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRTYTYP

Attribute	**Description**	
Name	PRTYTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	DRAWER,PAYEE

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTYREFNO

Attribute	Description
Name	PARTYREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ADDLN1

Attribute	Description

Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTLANG

Attribute	Description
Name	PARTLANG
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	**Description**	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	Description	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	Description	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	Description	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,S</td></tr></table>

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.12.2.RB-ModifyPDCContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNUM*
    - *EVENTSEQNO*
    - *EVENTCD*
    - *CPTYACCNUM*
    - *INSTRNO*
    - *INSTRDATE*
    - *AMOUNT*
    - *LCYAMT*
    - *OTHRPTYIDEN*
    - *ACTDATE*
    - *VALUEDT*
    - *MARGINPERC*
    - *FINANCING*
    - *COLLATERAL*
    - *COLLATVAL*
    - *COLLPOOL*
    - *ISRBNK*
    - *ISSUERBRN*

CLGBANK
CLGBRN
SECTORCD
ENDPNT
ACCBRN
ROUTNO
SUBSYSSTAT
AUTOLIQD
MAKER
MAKDTTIME
CHKR
CHKDTTIME
CONST
AUTHSTAT
Party-Details
  PARTYIDEN
  PARTYNAME
  COUNTRYCD
  ADDLN1
  ADDLN2
  ADDLN3
  ADDLN4
  WALKINCUST
  PARTLANG
Settlements
  CONREFNO
  LATEVNSEQNO
  Contract-Settlement
    IBANACNO
    CUSTSPREAD
    SPREADDEFN
    COMPNT
    TAGCCY
    ACCBRN
    ACC
    ACCCCY
    EXRATE
    NETIND
    ERICCY
    ERIAMT
    GENMSG
    RATECD
    Settlement-Detail
      INSTRCD1

INSTRCD2
INSTRCD3
INSTRCD4
ITIMEIND1
ITIMEIND2
ITIMEIND3
INSTRCD5
CONTREFNO
ESN
COMPNT
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5

Lcl_Clearing

AMTTAG
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1

- *SNDRRCVRINFO2*
- *SNDRRCVRINFO3*
- *SNDRRCVRINFO4*
- *SNDRRCVRINFO5*
- *SNDRRCVRINFO6*
- *DECLARTION*
- *REPRES1*
- *REPRES2*
- *REPRES3*
- *REPRES4*
- *RCVRACC*

Charges

- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*

REFRATETYP
PROCALCMTH
REFXRATE
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
Txnmisdetails
Compmisdetails

Fundmisdetails

TXNUDFDETAILS

FLDNAME

FLDVAL

Con

CONTREFNO

EVENTSEQ

Clpref

CONTREFNNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ACTDATE

Attribute	Description
Name	ACTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,F,N

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLATVAL

Attribute	Description
Name	COLLATVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ISRBNK

Attribute	Description
Name	ISRBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ISSUERBRN

Attribute	Description
Name	ISSUERBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CLGBANK

Attribute	Description
Name	CLGBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CLGBRN

Attribute	Description
Name	CLGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ENDPNT

Attribute	Description
Name	ENDPNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ROUTNO

Attribute	Description	
Name	ROUTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	27

TOP

SUBSYSSTAT

Attribute	Description	
Name	SUBSYSSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

AUTOLIQD

Attribute	Description	
Name	AUTOLIQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CONST

Attribute	Description
Name	CONST

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,H,R,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRYCD

Attribute	**Description**	
Name	COUNTRYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ADDLN1

Attribute	**Description**	
Name	ADDLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDLN2

Attribute	**Description**	
Name	ADDLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDLN3

Attribute	**Description**	
Name	ADDLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDLN4

Attribute	Description	
Name	ADDLN4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

WALKINCUST

Attribute	Description	
Name	WALKINCUST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PARTLANG

Attribute	Description	
Name	PARTLANG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Settlements

Attribute	Description	
Name	Settlements	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description

Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description

Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates Amount Tag
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	**Description**	
Name	SNDRCUSTNAME2	
Datatype	String	
Description	Indicates Sender Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4

Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description

Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	Description	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	Description	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	Description	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	Description	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

2.12.3.RB-ModifyPDCContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNUM*
    - *BOOKDT*
    - *USERREFNUM*
    - *XREF*
    - *PRDCD*
    - *MODCOD*
    - *UDSTAT*
    - *STOPDT*
    - *EVENTCD*
    - *INSTRUCODE*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *INSTRNO*
    - *INSTRDATE*
    - *CONTCCY*
    - *AMOUNT*
    - *LCYAMT*
    - *OTHRPTYIDEN*

BOOKINGDT
ACTDATE
VALUEDT
TRACKLIMIT
CRDLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
DISCOUNTAMT
COLLATERAL
COLLATVAL
COLLPOOL
ISRBNK
ISSUERBRN
CLGBANK
CLGBRN
SECTORCD
ENDPNT
INTREMARKS
ACCBRN
ROUTNO
DRACCBRN
INSTR_DESC
PRDDESC
CPTYNAME
OTHERPARTYNAME
ISSBANKNAME
ISSBRNCNAME
CLEARBANKNAME
AUTOLIQD
CLEARBRNCNAME
MAKER
MAKDTTIME
CHKR
CHKDTTIME
CONST
AUTHSTAT
BATCHREFENUM
BATCHSEQNO
DRACCREAL
CLGPRD
Party-Details
  PRTYTYP
  PARTYIDEN

- *PARTYNAME*
- *PARTYREFNO*
- *COUNTRYCD*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ADDLN4*
- *PARTLANG*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*

COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID

POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*

RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Charges

CONREFNO

Charge-Association

COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC

Charge-Application

CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL

- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*
  - *COSTCD4*
  - *COSTCD5*
  - *TXNMIS1*
  - *TXNMIS10*
  - *TXNMIS2*
  - *TXNMIS3*
  - *TXNMIS4*
  - *TXNMIS5*
  - *TXNMIS6*
  - *TXNMIS7*
  - *TXNMIS8*
  - *TXNMIS9*
  - *MISGRPCOMP*
  - *MISGRPTXN*
  - *COMPMIS1*
  - *COMPMIS10*
  - *COMPMIS2*
  - *COMPMIS3*
  - *COMPMIS4*

COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8

- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Con

- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Clpref

- *CONTREFNNO*
- *CONTRACT_CCY*
- *LATEVNSEQNO*
- *PRD*
- *PRDDESC*
- *COUNTERPARTY*
- *CURRENCY*
- *TENOR*
- *UNITS*
- *LOAN_CONREFNO*
- *RATECODE*
- *EXCHANGERATE*
- *RATE_TYPE*
- *MAXIMUM*
- *MINIMUM*
- *PAYMENT_MODE*
- *LOANVALDATE*
- *MATURITY_DATE*
- *Ude*
  - *USERDEID*
  - *UDEDESC*
  - *RATEASOF*
  - *USAGE*

USERDEVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USERREFNUM

Attribute	Description
Name	USERREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MODCOD

Attribute	Description
Name	MODCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BOOKINGDT

Attribute	Description
Name	BOOKINGDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACTDATE

Attribute	Description
Name	ACTDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,F,N

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLATVAL

Attribute	Description
Name	COLLATVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ISRBNK

Attribute	Description
Name	ISRBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ISSUERBRN

Attribute	Description	
Name	ISSUERBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CLGBANK

Attribute	Description	
Name	CLGBANK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CLGBRN

Attribute	Description	
Name	CLGBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SECTORCD

Attribute	Description	
Name	SECTORCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

ENDPNT

Attribute	Description
Name	ENDPNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>27</td></tr></table>

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ISSBANKNAME

Attribute	**Description**	
Name	ISSBANKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ISSBRNCNAME

Attribute	**Description**	
Name	ISSBRNCNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CLEARBANKNAME

Attribute	**Description**	
Name	CLEARBANKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

AUTOLIQD

Attribute	**Description**	
Name	AUTOLIQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CLEARBRNCNAME

Attribute	Description
Name	CLEARBRNCNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,H,R,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CLGPRD

Attribute	Description
Name	CLGPRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / DRAWER,PAYEE

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYREFNO

Attribute	Description
Name	PARTYREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTLANG

Attribute	Description
Name	PARTLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String

Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: enumeration Description: ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: enumeration Description: M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,S</td></tr></table>

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.12.4.RB-ModifyPDCContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNUM*
    - *Contract-Details-IO*
      - *CONREFNUM*
      - *EVENTSEQNO*
      - *EVENTCD*
      - *CPTYACCNUM*
      - *INSTRNO*
      - *INSTRDATE*
      - *AMOUNT*
      - *LCYAMT*
      - *OTHRPTYIDEN*
      - *ACTDATE*
      - *VALUEDT*
      - *MARGINPERC*
      - *FINANCING*
      - *COLLATERAL*
      - *COLLATVAL*

COLLPOOL
ISRBNK
ISSUERBRN
CLGBANK
CLGBRN
SECTORCD
ENDPNT
ACCBRN
ROUTNO
SUBSYSSTAT
AUTOLIQD
MAKER
MAKDTTIME
CHKR
CHKDTTIME
CONST
AUTHSTAT
Party-Details
  PARTYIDEN
  PARTYNAME
  COUNTRYCD
  ADDLN1
  ADDLN2
  ADDLN3
  ADDLN4
  WALKINCUST
  PARTLANG
Settlements
  CONREFNO
  LATEVNSEQNO
  Contract-Settlement
    IBANACNO
    CUSTSPREAD
    SPREADDEFN
    COMPNT
    TAGCCY
    ACCBRN
    ACC
    ACCCCY
    EXRATE
    NETIND
    ERICCY
    ERIAMT
    GENMSG

RATECD

Settlement-Detail

- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *CONTREFNO*
- *ESN*
- *COMPNT*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *AMTTAG*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*

- NOOFDEC
- ADDID
- SNDRRCVRINFO1
- SNDRRCVRINFO2
- SNDRRCVRINFO3
- SNDRRCVRINFO4
- SNDRRCVRINFO5
- SNDRRCVRINFO6
- DECLARTION
- REPRES1
- REPRES2
- REPRES3
- REPRES4
- RCVRACC

Charges

- LATEVNSEQNO
- CONREFNO
- Charge-Association
  - COMPNT
  - CREATESN
  - RULE
  - WAIVER
  - DISACCRAPPL
  - ACCRREQD
  - DESC
- Charge-Application
  - COMPNT
  - TGCCY
  - TGAMT
  - CHRGCCY
  - CHRGAMT
  - DISACCRAPPL
  - WAIVER
  - LIQDIND
- Charge-Liquidation
  - CHRGCCY
  - CHRGAMT
  - LIQDSTAT

Misdetails

- CONREFNO
- MISGRP
- RELACC
- RELETED_REFERENCE
- MISHEAD

RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFXRATE
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8

FUNDMIS9
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Clpref
CONTREFNNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACTDATE

Attribute	Description

Name	ACTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,F,N

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLATVAL

Attribute	Description
Name	COLLATVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ISRBNK

Attribute	Description
Name	ISRBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ISSUERBRN

Attribute	Description
Name	ISSUERBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBANK

Attribute	Description
Name	CLGBANK
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBRN

Attribute	Description
Name	CLGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ENDPNT

Attribute	Description
Name	ENDPNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

SUBSYSSTAT

Attribute	Description
Name	SUBSYSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,H,R,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINCUST

Attribute	Description
Name	WALKINCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PARTLANG

Attribute	Description
Name	PARTLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String

Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTTAG

Attribute	Description	
Name	AMTTAG	
Datatype	String	
Description	Indicates Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2

Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRPART

Attribute	**Description**	
Name	SNDRRCVRPART	
Datatype	Number	
Description	Indicates Sender Receiver Participant	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	**Description**	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3

Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number

Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description

Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	**Description**	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	1

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	1

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.13.Modifyfcychecksinput

Modifyfcychecksinput

2.13.1.RB-Modifyfcychecksinput-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *INSTRUMENT_CODE*
    - *INSTR_DESC*
    - *PRODUCT_CODE*
    - *PRDDESC*
    - *CONREFNUM*
    - *USERREF_NO1*
    - *XREF*
    - *BATCHREFENUM*
    - *BATCH_SEQ_NO*
    - *CASHLETTER_REFNUM*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *CPTY_AC_NO*
    - *ACC_BRANCH*
    - *INSTRUMENTNORE*

INSTRUMENT_DATE
CURRENCY
AMNT
LCY_AMOUNT
NOSTROACC
ACCBRN
COLLECTINGBANKCIF
COLL_BNK_NAME
BOOKINGDATE
VAL_DATE_BANK
VALUE_DATE_CUST
OTHR_PARTY_NAME
DRAWEE_BNK_NAME
AUTOLIQD
INTREMRKS
FINANCING
MARGIN_PERCENTAGE
TRACK_LIMIT
CRLINE
DISCOUNTAMT
MAKER
MAKDTTIME
CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
VERSION_NO
LATVERNO
Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*

RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1

ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*

REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3

- *REPRES4*
- *RCVRACC*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*

COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8

TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Clpref
CONTREFNNO
CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM

PAYMENT_MODE
LOANVALDATE
MATURITY_DATE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PRODUCT_CODE

Attribute	Description

Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BATCHREFENUM

Attribute	**Description**	
Name	BATCHREFENUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BATCH_SEQ_NO

Attribute	**Description**	
Name	BATCH_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CASHLETTER_REFNUM

Attribute	**Description**	
Name	CASHLETTER_REFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	**Description**	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CTR_PRTY_NAME

Attribute	Description	
Name	CTR_PRTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTY_AC_NO

Attribute	Description	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACC_BRANCH

Attribute	Description	
Name	ACC_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INSTRUMENTNORE

Attribute	Description	
Name	INSTRUMENTNORE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLECTINGBANKCIF

Attribute	Description
Name	COLLECTINGBANKCIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRLINE

Attribute	Description
Name	CRLINE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,L,R,H,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String

Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	Description	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

2.13.2.RB-Modifyfcychecksinput-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONREFNUM*
    - *USERREF_NO1*
    - *XREF*
    - *INSTRUMENTNORE*
    - *INSTRUMENT_DATE*
    - *AMNT*
    - *LCY_AMOUNT*
    - *OTHR_PARTY_NAME*
    - *DRAWEE_BNK_NAME*
    - *AUTOLIQD*
    - *INTREMRKS*
    - *MAKER*
    - *MAKDTTIME*
    - *CHKR*
    - *CHKDTTIME*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *SUBSYSSTAT*

- *Settlements*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Contract-Settlement*
    - *IBANACNO*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *COMPNT*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *ACCCCY*
    - *EXRATE*
    - *NETIND*
    - *ERICCY*
    - *ERIAMT*
    - *GENMSG*
    - *RATECD*
    - *Settlement-Detail*
      - *INSTRCD1*
      - *INSTRCD2*
      - *INSTRCD3*
      - *INSTRCD4*
      - *ITIMEIND1*
      - *ITIMEIND2*
      - *ITIMEIND3*
      - *INSTRCD5*
      - *CONTREFNO*
      - *ESN*
      - *COMPNT*
      - *BANKOPERCD*
      - *INSTRCD6*
      - *TRNSTYPCD*
      - *REGREP1*
      - *REGREP2*
      - *REGREP3*
      - *ENVCONT1*
      - *ENVCONT2*
      - *ENVCONT3*
      - *ENVCONT4*
      - *ENVCONT5*
    - *Lcl_Clearing*
      - *AMTTAG*
      - *SNDRCUSTNAME1*

SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
LATEVNSEQNO
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
COMPNT

- *TGCCY*
- *TGAMT*
- *CHRGCCY*
- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*

Charge-Liquidation

- *CHRGCCY*
- *CHRGAMT*
- *LIQDSTAT*

Misdetails

- *CONREFNO*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFXRATE*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*
- *MISGRPTXN*
- *COMPMIS1*
- *COMPMIS10*

COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Clpref
CONTREFNNO
Con
CONTREFNO
EVENTSEQ

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRUMENTNORE

Attribute	Description
Name	INSTRUMENTNORE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,L,R,H,

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U,

TOP

SUBSYSSTAT

Attribute	**Description**	
Name	SUBSYSSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

Settlements

Attribute	**Description**	
Name	Settlements	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number

Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	Description	
Name	REGREP1	
Datatype	String	
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description	
Name	REGREP2	
Datatype	String	
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1

Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	**Description**	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	**Description**	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String

Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String

Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String

Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.13.3.RB-Modifyfcychecksinput-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *INSTRUMENT_CODE*
    - *INSTR_DESC*
    - *PRODUCT_CODE*
    - *PRDDESC*
    - *CONREFNUM*
    - *USERREF_NO1*
    - *XREF*
    - *BATCHREFENUM*
    - *BATCH_SEQ_NO*
    - *CASHLETTER_REFNUM*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *CPTY_AC_NO*
    - *ACC_BRANCH*
    - *INSTRUMENTNORE*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*

LCY_AMOUNT
NOSTROACC
ACCBRN
COLLECTINGBANKCIF
COLL_BNK_NAME
BOOKINGDATE
VAL_DATE_BANK
VALUE_DATE_CUST
OTHR_PARTY_NAME
DRAWEE_BNK_NAME
AUTOLIQD
INTREMRKS
FINANCING
MARGIN_PERCENTAGE
TRACK_LIMIT
CRLINE
DISCOUNTAMT
MAKER
MAKDTTIME
CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
VERSION_NO
LATVERNO
Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*

RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4

BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*

ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*

TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1

COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Clpref
CONTREFNNO
CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM
PAYMENT_MODE
LOANVALDATE
MATURITY_DATE

Ude

USERDEID

UDEDESC

RATEASOF

USAGE

USERDEVAL

Con

CONTREFNO

EVENTSEQ

Adv

ADVNAME

SUPRESS

PRIOR

MEDM

PARTYIDEN

PARTYNAME

CHGREQ

PARTTYP

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PRODUCT_CODE

Attribute	Description
Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCH_SEQ_NO

Attribute	Description
Name	BATCH_SEQ_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CASHLETTER_REFNUM

Attribute	Description
Name	CASHLETTER_REFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CTR_PRTY_NAME

Attribute	**Description**	
Name	CTR_PRTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTY_AC_NO

Attribute	**Description**	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACC_BRANCH

Attribute	**Description**	
Name	ACC_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INSTRUMENTNORE

Attribute	**Description**	
Name	INSTRUMENTNORE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCBRN

Attribute	**Description**
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLECTINGBANKCIF

Attribute	**Description**
Name	COLLECTINGBANKCIF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COLL_BNK_NAME

Attribute	**Description**
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BOOKINGDATE

Attribute	**Description**
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTREMRKS

Attribute	**Description**	
Name	INTREMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,N,F

TOP

MARGIN_PERCENTAGE

Attribute	**Description**	
Name	MARGIN_PERCENTAGE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRACK_LIMIT

Attribute	**Description**	
Name	TRACK_LIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CRLINE

Attribute	Description
Name	CRLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,L,R,H,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATVERNO

Attribute	**Description**	
Name	LATVERNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Settlements

Attribute	**Description**	
Name	Settlements	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Settlement

Attribute	**Description**	
Name	Contract-Settlement	
Datatype		
Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	**Description**
Name	IBANACNO
Datatype	String

Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	Description	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	Description	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ADVNAME

Attribute	**Description**	
Name	ADVNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SUPRESS

Attribute	**Description**	
Name	SUPRESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.13.4.RB-Modifyfcychecksinput-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONREFNUM*
      - *USERREF_NO1*
      - *XREF*
    - *Main-IO*
      - *CONREFNUM*
      - *USERREF_NO1*
      - *XREF*
      - *INSTRUMENTNORE*
      - *INSTRUMENT_DATE*
      - *AMNT*
      - *LCY_AMOUNT*
      - *OTHR_PARTY_NAME*
      - *DRAWEE_BNK_NAME*
      - *AUTOLIQD*
      - *INTREMRKS*
      - *MAKER*
      - *MAKDTTIME*

CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
SUBSYSSTAT
Settlements
- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *Settlement-Detail*
    - *INSTRCD1*
    - *INSTRCD2*
    - *INSTRCD3*
    - *INSTRCD4*
    - *ITIMEIND1*
    - *ITIMEIND2*
    - *ITIMEIND3*
    - *INSTRCD5*
    - *CONTREFNO*
    - *ESN*
    - *COMPNT*
    - *BANKOPERCD*
    - *INSTRCD6*
    - *TRNSTYPCD*
    - *REGREP1*
    - *REGREP2*
    - *REGREP3*
    - *ENVCONT1*
    - *ENVCONT2*
    - *ENVCONT3*

ENVCONT4
ENVCONT5
Lcl_Clearing
AMTTAG
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
LATEVNSEQNO
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER

DISACCRAPPL
ACCRREQD
DESC
Charge-Application
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFXRATE
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8

TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Clpref
CONTREFNNO
Con
CONTREFNO
EVENTSEQ
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRUMENTNORE

Attribute	Description
Name	INSTRUMENTNORE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,L,R,H,</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,U,</td></tr></table>

TOP

SUBSYSSTAT

Attribute	Description
Name	SUBSYSSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String

Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**	
Name	REGREP2	
Datatype	String	
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**
Name	ENVCONT2
Datatype	String

Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description	
Name	AMTTAG	
Datatype	String	
Description	Indicates Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description	
Name	SNDRCUSTNAME2	
Datatype	String	
Description	Indicates Sender Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	Description	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4

Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	Description	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	Description	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	Description	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number

Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	**Description**	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

Clpref

Attribute	**Description**	
Name	Clpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNNO

Attribute	**Description**	
Name	CONTREFNNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.14.QueryBulkInwardInput

QueryBulkInwardInput

2.14.1.RB-QueryBulkInwardInput-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-IO*
    - *BATCHREFENUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.14.2.RB-QueryBulkInwardInput-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Input-IO*
      - *BATCHREFENUM*
    - *Bulk-Input-Full*
      - *INSTRUMENT_CODE*
      - *BATCHREFENUM*
      - *PRDCD*
      - *CPTY_ID*
      - *CPTY_NAME*
      - *ACCBRN*
      - *CPTY_AC_NO*
      - *OTHRPTY_ID*
      - *OTHRPTY_NM*
      - *BNKCD*
      - *BRNCODE*
      - *CORRESPBNK*
      - *CORRESPACNO*
      - *BOKNGDT*
      - *PROTEST*

AUTOLIQD
NOOFINSTRUMENTS
ACFORREALISATION
CRACCBRN
CCY
PROCESSSTAT
EVENTSEQNO
ESNLOG
RECORDSTAT
AUTHSTAT
CHKR
CHKDTTIME
BULKREF
MAKER
MAKDTTIME
Bulkinput-Detail
CONREFNUM
INSTRNO
INSTRU_DATE
CURRENCY
AMNT
REMITBANK_REF
REM_BNK_DT
LCY_AMOUNTT
MATURITYDATE
GRACEDAYS
REMARKS
PROCESSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Input-Full

Attribute	Description
Name	Bulk-Input-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CPTY_ID

Attribute	**Description**	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_NAME

Attribute	**Description**	
Name	CPTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CPTY_AC_NO

Attribute	**Description**	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

OTHRPTY_ID

Attribute	Description
Name	OTHRPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OTHRPTY_NM

Attribute	Description
Name	OTHRPTY_NM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CORRESPBNK

Attribute	Description	
Name	CORRESPBNK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CORRESPACNO

Attribute	Description	
Name	CORRESPACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BOKNGDT

Attribute	Description	
Name	BOKNGDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PROTEST

Attribute	Description	
Name	PROTEST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRACCBRN

Attribute	Description
Name	CRACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESNLOG

Attribute	Description
Name	ESNLOG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BULKREF

Attribute	Description
Name	BULKREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	**Description**	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Bulkinput-Detail

Attribute	**Description**	
Name	Bulkinput-Detail	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CONREFNUM

Attribute	**Description**	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INSTRNO

Attribute	**Description**	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REM_BNK_DT

Attribute	Description
Name	REM_BNK_DT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCY_AMOUNTT

Attribute	**Description**	
Name	LCY_AMOUNTT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MATURITYDATE

Attribute	**Description**	
Name	MATURITYDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GRACEDAYS

Attribute	**Description**	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PROCESSTAT

Attribute	**Description**
Name	PROCESSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,U,F,H

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.15.QueryBulkInwardPDR

QueryBulkInwardPDR

2.15.1.RB-QueryBulkInwardPDR-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Pdr-IO*
    - *BULKPDRREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Pdr-IO

Attribute	Description
Name	Bulk-Pdr-IO
Datatype	
Description	

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.15.2.RB-QueryBulkInwardPDR-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Pdr-IO*
      - *BULKPDRREFNO*
    - *Bulk-Pdr-Full*
      - *BATCHREFENUM*
      - *BULKPDRREFNO*
      - *ACTION*
      - *PRDTY*
      - *CPTY_ID*
      - *COUNTRPRYNAM*
      - *OTHRPTY_ID*
      - *OTHRPTY_NM*
      - *BANK_CODE*
      - *BANK_NAME*
      - *BRNCODE*
      - *BRANCH_NAME*
      - *VALUEDT*
      - *RETURN_DATE*
      - *PROCESSSTAT*

SEQNO
ESN
TXNSTAT
AUTHSTAT
CHKR
CHKDTTIME
MKRID
MKRDT
Bulk-Pdr-Detail
CONREFNUM
INSTRNO
INSTRUMENT_DATE
REMITBANK_REF
CCY
AMT
REASON_CODE
DISHONOUR_DATE
NOTARYCODE
PROTESTDATE
REMARKS
PROCESSSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Pdr-IO

Attribute	Description
Name	Bulk-Pdr-IO
Datatype	
Description	

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Bulk-Pdr-Full

Attribute	Description
Name	Bulk-Pdr-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

PRDTY

Attribute	Description
Name	PRDTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHRPTY_ID

Attribute	Description
Name	OTHRPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OTHRPTY_NM

Attribute	Description
Name	OTHRPTY_NM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BANK_CODE

Attribute	**Description**	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANK_NAME

Attribute	**Description**	
Name	BANK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNCODE

Attribute	**Description**	
Name	BRNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BRANCH_NAME

Attribute	**Description**	
Name	BRANCH_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,P

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,O,C

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MKRID

Attribute	Description	
Name	MKRID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MKRDT

Attribute	Description	
Name	MKRDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Bulk-Pdr-Detail

Attribute	Description	
Name	Bulk-Pdr-Detail	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CONREFNUM

Attribute	Description	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INSTRNO

Attribute	Description

Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REASON_CODE

Attribute	Description	
Name	REASON_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

DISHONOUR_DATE

Attribute	Description	
Name	DISHONOUR_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NOTARYCODE

Attribute	Description	
Name	NOTARYCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

PROTESTDATE

Attribute	Description	
Name	PROTESTDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,P

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.16.QueryBulkInwardReal

QueryBulkInwardReal

2.16.1.RB-QueryBulkInwardReal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liq-Master-IO*
    - *BULKREALNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liq-Master-IO

Attribute	Description
Name	Liq-Master-IO
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.16.2.RB-QueryBulkInwardReal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Liq-Master-IO*
      - *BULKREALNUM*
    - *Liq-Master-Full*
      - *BATCHREFENUM*
      - *BULKREALNUM*
      - *CPTY_ID*
      - *DUP_CPTY_NAME*
      - *CCY*
      - *OTHRPTY_ID*
      - *OTHRPTY_NM*
      - *BNKCD*
      - *BANK_NAME*
      - *BRNCODE*
      - *BRNNAME*
      - *CPTY_AC_NO*
      - *ACFORREALISATION*
      - *CRACCBRN*
      - *VALUEDATE*

ACCBRN
CORRESPBNK
CORRESPACNO
NETAMT_REAL
PROCESSSTAT
EVENTSEQNO
RECORDSTAT
AUTHSTAT
CKRID
CHKDTTIME
BULKREF
ESN
MAKER
MAKDTTIME
Liq-Detail
CONREFNUM
INSTRNO
INSTRUMENT_DATE
REMITBANK_REF
REM_BNK_DT
AMNT
REMRKS
PROCESSSTAT
OTHRBNKCHARGS
NETAMT_REAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Liq-Master-IO

Attribute	Description
Name	Liq-Master-IO
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Liq-Master-Full

Attribute	Description
Name	Liq-Master-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DUP_CPTY_NAME

Attribute	Description
Name	DUP_CPTY_NAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OTHRPTY_ID

Attribute	Description
Name	OTHRPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OTHRPTY_NM

Attribute	Description
Name	OTHRPTY_NM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANK_NAME

Attribute	**Description**	
Name	BANK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNCODE

Attribute	**Description**	
Name	BRNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTY_AC_NO

Attribute	**Description**	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	Description
Name	CRACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CORRESPBNK

Attribute	Description
Name	CORRESPBNK
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CORRESPACNO

Attribute	Description
Name	CORRESPACNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

NETAMT_REAL

Attribute	Description
Name	NETAMT_REAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,P</td></tr></table>

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RECORDSTAT

Attribute	**Description**	
Name	RECORDSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,O,C

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

CKRID

Attribute	**Description**	
Name	CKRID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BULKREF

Attribute	Description
Name	BULKREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Liq-Detail

Attribute	Description
Name	Liq-Detail

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

REM_BNK_DT

Attribute	Description
Name	REM_BNK_DT
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: U,P

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETAMT_REAL

Attribute	Description
Name	NETAMT_REAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.17.QueryBulkOutClearing

QueryBulkOutClearing

2.17.1.RB-QueryBulkOutClearing-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Bulk-Input-IO*
  - *BATCHREFENUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.17.2.RB-QueryBulkOutClearing-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Input-IO*
      - *BATCHREFENUM*
    - *Bulk-Input-Full*
      - *CRDLINE*
      - *OTHPARTYLIMIT*
      - *MARGINPERC*
      - *FINANCING*
      - *COLLATERAL*
      - *COLLPOOL*
      - *INSTRUCODE*
      - *PRDCODE*
      - *CPTYIDEN*
      - *CPTYACCNUM*
      - *CURRENCY*
      - *OTHRPTYIDEN*
      - *DRACCREAL*
      - *NOOFINSTRUMENTS*
      - *CLGPRD*

ISRBNK
ISSUERBRN
CLRBNK
CLGBRN
SECTORCR
ENDPOINT
ROUTNO
CHECKINSERIES
FIRSTINSTRNO
BOOKINGDATE
TRACKLIMIT
INSTRUMENT_DESCRIPTION
INSTRDESC
COUNTRPRYNAM
OTHERPARTYNAME
ISSBANKNAME
ISSBRNCNAME
CLEARBANKNAME
CLEARBRNCNAME
BATCHREFENUM
ACCBRN
PROCESSTAT
CONTSTATUS
AUTSTAT
CHECKER
CHECKERDT
VERSIONNUM
MKER
MAKERDT
DRACCBRN
VERNUMBER
Input-Detail
CONREFNUM
INSTRNO
INSTRDATE
LCYAMT
AMNT
VALUEDATE
DISCAMT
COLLTVAL
INTREMRKS
PROCESSSTAT
FCUBS_ERROR_RESP
ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Input-Full

Attribute	Description
Name	Bulk-Input-Full
Datatype	
Description	

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,F,N

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CLGPRD

Attribute	Description
Name	CLGPRD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ISRBNK

Attribute	Description
Name	ISRBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ISSUERBRN

Attribute	Description
Name	ISSUERBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLRBNK

Attribute	Description
Name	CLRBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBRN

Attribute	Description
Name	CLGBRN
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SECTORCR

Attribute	Description
Name	SECTORCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 27

TOP

CHECKINSERIES

Attribute	Description
Name	CHECKINSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FIRSTINSTRNO

Attribute	Description
Name	FIRSTINSTRNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description
Name	INSTRUMENT_DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSTRDESC

Attribute	Description
Name	INSTRDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSBANKNAME

Attribute	Description
Name	ISSBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSBRNCNAME

Attribute	Description
Name	ISSBRNCNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CLEARBANKNAME

Attribute	**Description**	
Name	CLEARBANKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CLEARBRNCNAME

Attribute	**Description**	
Name	CLEARBRNCNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATCHREFENUM

Attribute	**Description**	
Name	BATCHREFENUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,E

TOP

CONTSTATUS

Attribute	Description
Name	CONTSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,O,C

TOP

AUTSTAT

Attribute	Description
Name	AUTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDT

Attribute	Description
Name	CHECKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VERSIONNUM

Attribute	Description
Name	VERSIONNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MKER

Attribute	Description
Name	MKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

VERNUMBER

Attribute	Description
Name	VERNUMBER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Input-Detail

Attribute	Description
Name	Input-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLTVAL

Attribute	Description
Name	COLLTVAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,S,F,H</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.18.QueryBulkPDRContract

QueryBulkPDRContract

2.18.1.RB-QueryBulkPDRContract-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Bulkpdr-IO*
  - *BULKPDRREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulkpdr-IO

Attribute	Description
Name	Bulkpdr-IO
Datatype	
Description	

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	Bulk Dishonor / Protest / Return Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.18.2.RB-QueryBulkPDRContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulkpdr-IO*
      - *BULKPDRREFNO*
    - *Bulkpdr-Full*
      - *BANK_CODE*
      - *BRNCODE*
      - *BANKNAME*
      - *BRNNAME*
      - *ACTION*
      - *DISPATCHLOTREFNO*
      - *BULKPDRREFNO*
      - *PROCESSTAT*
      - *AUTHSTAT*
      - *CHKR*
      - *CHKDTTIME*
      - *EVSEQNO*
      - *MAKER*
      - *MAKDTTIME*
      - *RECORDSTAT*

ESNUI
Bulkpdrdetail
CONREFNUM
ACC_CCY
AMNT
DISHONOUR_DATE
NOTARYCODE
PROTESTDATE
INTREMRKS
DISHONOUR_REASON
RETURN_DATE
CPTYIDEN
OTHRPTYIDEN
CPTYNAME
OTHERPARTYNAME
INSTRNO
PROCESSSTAT
PRDTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulkpdr-IO

Attribute	Description
Name	Bulkpdr-IO
Datatype	
Description	

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	Bulk Dishonor / Protest / Return Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulkpdr-Full

Attribute	Description
Name	Bulkpdr-Full
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description	Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BRNCODE

Attribute	Description	
Name	BRNCODE	
Datatype	String	
Description	Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BANKNAME

Attribute	Description	
Name	BANKNAME	
Datatype	String	
Description	Bank Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description	Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

DISPATCHLOTREFNO

Attribute	Description	
Name	DISPATCHLOTREFNO	
Datatype	String	
Description	Dispatch Lot Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BULKPDRREFNO

Attribute	Description	
Name	BULKPDRREFNO	
Datatype	String	
Description	Bulk Dishonor / Protest / Return Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PROCESSTAT

Attribute	Description	
Name	PROCESSTAT	
Datatype	String	
Description	Process Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,U

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	Checker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	Date Time
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVSEQNO

Attribute	Description
Name	EVSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	Maker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	Date Time
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,O,C

TOP

ESNUI

Attribute	Description
Name	ESNUI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bulkpdrdetail

Attribute	Description
Name	Bulkpdrdetail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISHONOUR_DATE

Attribute	Description
Name	DISHONOUR_DATE
Datatype	Date
Description	Dishonour Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	Notary Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

PROTESTDATE

Attribute	**Description**	
Name	PROTESTDATE	
Datatype	Date	
Description	Protest Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTREMRKS

Attribute	**Description**	
Name	INTREMRKS	
Datatype	String	
Description	Internal Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DISHONOUR_REASON

Attribute	**Description**	
Name	DISHONOUR_REASON	
Datatype	String	
Description	Dishonor Reason	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RETURN_DATE

Attribute	**Description**	
Name	RETURN_DATE	
Datatype	Date	
Description	Return Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	CounterParty Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	Other Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	CounterParty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	Other Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO

Datatype	String
Description	Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,H,S,F

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Product Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.19.QueryBulkRealization

QueryBulkRealization

2.19.1.RB-QueryBulkRealization-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Master-IO*
  - *BULKREALNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	Bulk Realization Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.19.2.RB-QueryBulkRealization-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Master-IO*
      - *BULKREALNUM*
    - *Master-Full*
      - *BULKREALNUM*
      - *DISLOTREF*
      - *DRACFORREALISATION*
      - *COLBANKREFNUM*
      - *VDATE*
      - *CURRENCY*
      - *TOTNETREAL*
      - *DRACCBRN*
      - *TXNSTAT*
      - *AUTHSTAT*
      - *CHKR*
      - *CHKDTTIME*
      - *EVENSEQNO*
      - *MAKER*
      - *MAKDTTIME*

PROCESSTAT
MAXESN
Detail
CONREFNUM
AMUNT
INTREMRKS
NETREALAMT
CUSTNUMBER1
OTHRBNKCHARGS
INSTRNO
PROCESSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	Bulk Realization Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description	
Name	BULKREALNUM	
Datatype	String	
Description	Bulk Realization Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DISLOTREF

Attribute	Description	
Name	DISLOTREF	
Datatype	String	
Description	Dispatch Lot Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DRACFORREALISATION

Attribute	Description	
Name	DRACFORREALISATION	
Datatype	String	
Description	Debit Account for Realization	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COLBANKREFNUM

Attribute	Description	
Name	COLBANKREFNUM	
Datatype	String	
Description	Collecting Bank Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VDATE

Attribute	Description

Name	VDATE
Datatype	Date
Description	Value date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TOTNETREAL

Attribute	Description
Name	TOTNETREAL
Datatype	Number
Description	Total Net Realized
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Debit Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,O,C,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	Checker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	Date Time
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVENSEQNO

Attribute	Description
Name	EVENSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	Maker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	Date Time
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,U,F

TOP

MAXESN

Attribute	Description
Name	MAXESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Detail

Attribute	Description
Name	Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AMUNT

Attribute	Description
Name	AMUNT
Datatype	Number
Description	Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Internal Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

NETREALAMT

Attribute	Description
Name	NETREALAMT
Datatype	Number
Description	Net Realized Amount
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CUSTNUMBER1

Attribute	Description
Name	CUSTNUMBER1
Datatype	String
Description	Customer Identification

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OTHRBNKCHARGS

Attribute	**Description**	
Name	OTHRBNKCHARGS	
Datatype	Number	
Description	Other Bank Charges	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRNO

Attribute	**Description**	
Name	INSTRNO	
Datatype	String	
Description	Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

PROCESSTAT

Attribute	**Description**	
Name	PROCESSTAT	
Datatype	String	
Description	Process Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,U,F

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.20.QueryCashletterdishonour

QueryCashletterdishonour

2.20.1.RB-QueryCashletterdishonour-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Main-IO*
  - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.20.2.RB-QueryCashletterdishonour-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-IO*
      - *CONREFNUM*
    - *Main-Full*
      - *CONREFNUM*
      - *CASHREFNO*
      - *CPTY_ID*
      - *COUNTRPRYNAM*
      - *INSTRNO*
      - *INSTRU_DATE*
      - *CURRENCY*
      - *AMNT*
      - *COLLBNKNAME*
      - *BOKNGDT*
      - *OTHR_PARTYNAME*
      - *DRAWEE_BNK_NAME*
      - *REASON_CODE*
      - *REASON*
      - *DT_OF_DISHONOR*

OTHRBNKCHARGS
REMRKS
MAKER
MAKDTTIME
CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Charges
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*

CHRGAMT

LIQDSTAT

Misdetails

CONREFNO

LATESN

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS

- FLDNAME
- FLDVAL

Settlements

- CONREFNO
- Contract-Settlement
  - IBANACNO
  - CUSTSPREAD
  - SPREADDEFN
  - COMPNT
  - TAGCCY
  - ACCBRN
  - ACC
  - ACCCCY
  - EXRATE
  - NETIND
  - ERICCY
  - ERIAMT
  - GENMSG
  - RATECD
  - CLEARNW
  - COVERBY
  - RTGSPMNT
  - BANKPRIOR
  - RTGSNW
  - PAYBY
  - TRANSTYP
  - INSTYP
  - INSNO
  - CHGDET
  - PAYMNTDET1
  - PAYMNTDET2
  - PAYMNTDET3
  - PAYMNTDET4
  - SNDTRRCVINFO1
  - SNDTRRCVINFO2
  - SNDTRRCVINFO3
  - SNDTRRCVINFO4
  - SNDTRRCVINFO5
  - COVREQRD
  - RECVCVR
  - RECEIVER
  - REIMINST1
  - REIMINST2
  - REIMINST3

REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5

REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*

ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INSTRNO

Attribute	**Description**	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRU_DATE

Attribute	**Description**	
Name	INSTRU_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CURRENCY

Attribute	**Description**	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNT

Attribute	**Description**	
Name	AMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

REASON

Attribute	**Description**	
Name	REASON	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DT_OF_DISHONOR

Attribute	**Description**	
Name	DT_OF_DISHONOR	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

OTHRBNKCHARGS

Attribute	**Description**	
Name	OTHRBNKCHARGS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REMRKS

Attribute	**Description**	
Name	REMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description

Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String

Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	Description	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	Description	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String

Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	Description	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS5

Attribute	**Description**	
Name	TRANMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	**Description**	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS7

Attribute	**Description**	
Name	TRANMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS8

Attribute	**Description**	
Name	TRANMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description

Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	

Attribute	Description
minOccurs	1

Restrictions	

Restrictions	Description
maxLength	16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	**Description**	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	**Description**	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1

Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2

Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5

Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1

Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	**Description**	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	**Description**	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.21.QueryCashletterrealize

QueryCashletterrealize

2.21.1.RB-QueryCashletterrealize-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CASHLTRCONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.21.2.RB-QueryCashletterrealize-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-IO*
      - *CASHLTRCONREFNO*
    - *Main-Full*
      - *CASHLTRCONREFNO*
      - *EVENTCODE*
      - *CL_REF*
      - *CURRENCY*
      - *AMNT*
      - *NOSTROACC*
      - *ACCBRN*
      - *INTREMRKS*
      - *COLBANKREFNUM*
      - *Footer*
        - *MAKER*
        - *MAKDTTIME*
        - *CHKR*
        - *CHKDTTIME*
        - *RECORD_STAT*

AUTHSTATS

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTCODE

Attribute	Description

Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CL_REF

Attribute	Description
Name	CL_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Footer

Attribute	Description
Name	Footer
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,L

TOP

AUTHSTATS

Attribute	Description
Name	AUTHSTATS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description

Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.22.QueryCreatebulkfcycheck

QueryCreatebulkfcycheck

2.22.1.RB-QueryCreatebulkfcycheck-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Bulk-Cashletter-IO*
  - *BATCHREFENUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Cashletter-IO

Attribute	Description
Name	Bulk-Cashletter-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.22.2.RB-QueryCreatebulkfcycheck-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Cashletter-IO*
      - *BATCHREFENUM*
    - *Bulk-Cashletter-Full*
      - *INSTRUCODE*
      - *INSTR_DESC*
      - *PRCD*
      - *PRODDESC*
      - *BATCHREFENUM*
      - *CPTY_ID*
      - *CPTY_NAME*
      - *CPTY_AC_NO*
      - *ACCBRNRE*
      - *AC_CCYY*
      - *ACCBRN*
      - *COLL_BNK_NAME*
      - *BDTE*
      - *VAL_DATE_BANK*
      - *VALUE_DATE_CUST*

LIQDMODE
FINANCING
MARGINPERCENT
TRACK_LIMIT
CREDITLINE
NOOFINSTRUMENTS
PROCESS_STATUS
NOSTROACC
ESN
EVENT_SEQ_NO
RECORD_STAT
AUTHORIZATION_STATUS
CHECKER
CHKDTTIME
MAKER
MAKDTTIME
Bulk-Cashletter-Dtl
  CONREFNUM
  INSTRNO
  INSTRU_DATE
  ADJSTAMT
  LCY_AMT
  DISCAMT
  OTHR_PARTYNAME
  DRAWEE_BNK_NAME
  REMRKS
  PROCESS_STATUS
Summary
  AUTHSTAT
  RECORD_STAT
  INSTRUCODE
  PRCD
  CPTY_ID
  BATCHREFENUM
  NOSTROACC
  COLL_BNK_NAME
  INSTRNO
  INSTRU_DATE
  AC_CCYY
  AMNT
  BDTE
  VAL_DATE_BANK
  VALUE_DATE_CUST
  CONREFNUM

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Cashletter-IO

Attribute	Description
Name	Bulk-Cashletter-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Cashletter-Full

Attribute	Description
Name	Bulk-Cashletter-Full
Datatype	
Description	

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTR_DESC

Attribute	Description

Name	INSTR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_NAME

Attribute	**Description**	
Name	CPTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTY_AC_NO

Attribute	**Description**	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCBRNRE

Attribute	**Description**	
Name	ACCBRNRE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AC_CCYY

Attribute	**Description**	
Name	AC_CCYY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BDTE

Attribute	Description
Name	BDTE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDMODE

Attribute	Description
Name	LIQDMODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,U,

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ESN

Attribute	Description
Name	ESN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C,

TOP

AUTHORIZATION_STATUS

Attribute	Description
Name	AUTHORIZATION_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Bulk-Cashletter-Dtl

Attribute	Description
Name	Bulk-Cashletter-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description

Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,U,

TOP

Summary

Attribute	Description
Name	Summary
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C,

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BDTE

Attribute	Description
Name	BDTE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.23.QueryCreatebulkfcyreal

QueryCreatebulkfcyreal

2.23.1.RB-QueryCreatebulkfcyreal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liqd-Cashletter-IO*
    - *CASHREFNO*
    - *CASHLTRCONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liqd-Cashletter-IO

Attribute	Description
Name	Liqd-Cashletter-IO
Datatype	
Description	

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.23.2.RB-QueryCreatebulkfcyreal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Liqd-Cashletter-IO*
      - *CASHREFNO*
      - *CASHLTRCONREFNO*
    - *Liqd-Cashletter-Full*
      - *CASHREFNO*
      - *AC_CCYY*
      - *ACCBRN*
      - *VALUE_DATE_CUST*
      - *CASHLTRCONREFNO*
      - *NOSTROACC*
      - *PROCESS_STATUS*
      - *ESN*
      - *EVENT_SEQ_NO*
      - *RECORD_STAT*
      - *AUTHORIZATION_STATUS*
      - *CHECKER*
      - *CHKDTTIME*
      - *MAKER*

MAKDTTIME
Liqd-Cashletter-Dtl
CONREFNUM
CPTY_ID
INSTRNO
INSTRU_DATE
AMNT
INTREMRKS
PROCESS_STATUS
Summary
AUTHSTAT
RECORD_STAT
CASHREFNO
AC_CCYY
NOSTROACC
CONREFNUM
INSTRNO
INSTRU_DATE
AMNT
CPTY_ID
COUNTRPRYNAM
CASHLTRCONREFNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Liqd-Cashletter-IO

Attribute	Description
Name	Liqd-Cashletter-IO
Datatype	
Description	

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Liqd-Cashletter-Full

Attribute	Description
Name	Liqd-Cashletter-Full
Datatype	
Description	

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,U,

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,C,

TOP

AUTHORIZATION_STATUS

Attribute	Description
Name	AUTHORIZATION_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Liqd-Cashletter-Dtl

Attribute	Description
Name	Liqd-Cashletter-Dtl
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,U,</td></tr></table>

TOP

Summary

Attribute	Description
Name	Summary
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U,

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,C,

TOP

CASHREFNO

Attribute	**Description**	
Name	CASHREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AC_CCYY

Attribute	**Description**	
Name	AC_CCYY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

NOSTROACC

Attribute	**Description**	
Name	NOSTROACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.24.QueryFcychecksfinance

QueryFcychecksfinance

2.24.1.RB-QueryFcychecksfinance-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONTRACT_REF*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONTRACT_REF

Attribute	Description
Name	CONTRACT_REF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.24.2.RB-QueryFcychecksfinance-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-IO*
      - *CONTRACT_REF*
    - *Main-Full*
      - *CONTRACT_REF*
      - *CPTY_ID*
      - *CTR_PRTY_NAME*
      - *INSTRNO*
      - *INSTRUMENT_DATE*
      - *CURRENCY*
      - *AMNT*
      - *BOOKINGDATE*
      - *VAL_DATE_BANK*
      - *VALUE_DATE_CUST*
      - *OTHR_PARTY_NAME*
      - *DRAWEE_BNK_NAME*
      - *FINANCING*
      - *MARGINPERCENT*
      - *TRACK_LIMIT*

CRLINE
DISCOUNT_AMOUNT
MAKER
MAKDTTIME
CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
Con
  CONTREFNO
  EVENTSEQ
  Adv
    ADVNAME
    SUPRESS
    PRIOR
    MEDM
    PARTYIDEN
    PARTYNAME
    CHGREQ
    PARTTYP
Settlements
  CONREFNO
  Contract-Settlement
    IBANACNO
    CUSTSPREAD
    SPREADDEFN
    COMPNT
    TAGCCY
    ACCBRN
    ACC
    ACCCCY
    EXRATE
    NETIND
    ERICCY
    ERIAMT
    GENMSG
    RATECD
    CLEARNW
    COVERBY
    RTGSPMNT
    BANKPRIOR
    RTGSNW
    PAYBY
    TRANSTYP

INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1

ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

FREETXT1

FREETXT2

FREETXT3

PMNTCD

ADDINFOSORBNET

SNDRCUSTNAME1

SNDRCUSTNAME2

SNDRCUSTNAME3

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

Charges

CONREFNO

Charge-Association

COMPNT

CREATESN

RULE

WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4

TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6

- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Clpref

- *CONTREFNNO*
- *CONTRACT_CCY*
- *LATEVNSEQNO*
- *PRD*
- *PRDDESC*
- *COUNTERPARTY*
- *CURRENCY*
- *TENOR*
- *UNITS*
- *LOAN_CONREFNO*
- *RATECODE*
- *EXCHANGERATE*
- *RATE_TYPE*
- *MAXIMUM*
- *MINIMUM*
- *PAYMENT_MODE*
- *LOANVALDATE*
- *MATURITY_DATE*
- *Ude*
  - *USERDEID*
  - *UDEDESC*
  - *RATEASOF*
  - *USAGE*
  - *USERDEVAL*

TXNUDFDETAILS

- *FLDNAME*

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONTRACT_REF

Attribute	Description
Name	CONTRACT_REF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONTRACT_REF

Attribute	Description
Name	CONTRACT_REF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description

Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CTR_PRTY_NAME

Attribute	Description
Name	CTR_PRTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRLINE

Attribute	Description
Name	CRLINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,L,A

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

Con

Attribute	**Description**	
Name	Con	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement

Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	**Description**	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	**Description**	
Name	CLEARNW	
Datatype	String	
Description	Indicates Network Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	**Description**	
Name	COVERBY	
Datatype	String	
Description	Indicates Cover By Clearing : C Message : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	**Description**
Name	RTGSPMNT
Datatype	String

Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	Description	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1

Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	**Description**	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2

Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5

Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	**Description**
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	**Description**
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	**Description**
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	**Description**
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	Description	
Name	REGREP1	
Datatype	String	
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description	
Name	REGREP2	
Datatype	String	
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1

Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRPART

Attribute	**Description**	
Name	SNDRRCVRPART	
Datatype	Number	
Description	Indicates Sender Receiver Participant	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	Description	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	Description	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	Description	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description

Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description

Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	Description	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association

Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	**Description**	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	Description	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	Description	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	Description	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,S

TOP

EXCHANGERATE

Attribute	**Description**	
Name	EXCHANGERATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATE_TYPE

Attribute	**Description**	
Name	RATE_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

MAXIMUM

Attribute	**Description**	
Name	MAXIMUM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MINIMUM

Attribute	**Description**	
Name	MINIMUM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PAYMENT_MODE

Attribute	**Description**
Name	PAYMENT_MODE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.25.QueryFcychecksrealize

QueryFcychecksrealize

2.25.1.RB-QueryFcychecksrealize-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Main-IO*
  - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.25.2.RB-QueryFcychecksrealize-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-IO*
      - *CONREFNUM*
    - *Main-Full*
      - *CONREFNUM*
      - *CASHREFNO*
      - *CPTY_ID*
      - *CPTY_NAME*
      - *INSTRNO*
      - *INSTRU_DATE*
      - *CURRENCY*
      - *AMNT*
      - *VALUEDATE*
      - *REMRKS*
      - *MAKER*
      - *MAKDTTIME*
      - *CHKR*
      - *CHKDTTIME*
      - *RECORD_STAT*

AUTHSTAT

Con

- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*

SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4

BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*

SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT

TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN

COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3

FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CASHREFNO

Attribute	Description	
Name	CASHREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	Description	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_NAME

Attribute	Description	
Name	CPTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,L</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EVENTSEQ

Attribute	**Description**	
Name	EVENTSEQ	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Adv

Attribute	**Description**	
Name	Adv	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ADVNAME

Attribute	**Description**	
Name	ADVNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SUPRESS

Attribute	**Description**	
Name	SUPRESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr></table>

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY

Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	**Description**	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	**Description**	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String

Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description

Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	**Description**	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	**Description**	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	**Description**	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	**Description**	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2

Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3

Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2

Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String

Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2

Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	Description	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	Description	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO2

Attribute	Description	
Name	SNDRRCVRINFO2	
Datatype	String	
Description	Indicates Sender Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	**Description**	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.26.QueryInwardContract

QueryInwardContract

2.26.1.RB-QueryInwardContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNUM*
    - *USERREF_NO*
    - *XREF*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

2.26.2.RB-QueryInwardContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-IO*
      - *CONREFNUM*
      - *USERREF_NO*
      - *XREF*
    - *Contract-Details-Full*
      - *INSTRUMENT_CODE*
      - *INSTRUMENT_DESCRIPTION*
      - *PRCD*
      - *CONREFNUM*
      - *USERREF_NO*
      - *XREF*
      - *BATCHREFENUM*
      - *BATCHSEQNO*
      - *CPTY_ID*
      - *CPTY_NAME*
      - *ACCBRN*
      - *CPTY_AC_NO*
      - *INSTNO*

INSTRDATE
CCY
AMT
LCYAMT
BNKCD
BNKNAME
BRNCDE
BRNNAME
REFNO
DATE
CORRESPBNK
CORRESPACNO
OTHERPARTYIDE
OTHR_PARTYNAME
BOKNGDT
MATDT
GRACEDAYS
PAYDUEDATE
ACBRN1
ACFORREALISATION
PROTEST
AUTOLIQD
LIQWITHBUKNG
INTREMARKS
REASON_CODE
REASON
CONREFNOLOG
MAKER
MAKDTTIME
CHKR
CHKDTTIME
SE_TXNSTAT
AUTHSTAT
VERSIONNORB
LATVERNO
Contract-Parties
- *PARTYTYPE*
- *PARTYIDEN*
- *PARTYNAME*
- *COUNTRYCD*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ADDLN4*

- LANG
- Settlements
  - CONREFNO
  - Contract-Settlement
    - IBANACNO
    - CUSTSPREAD
    - SPREADDEFN
    - COMPNT
    - TAGCCY
    - ACCBRN
    - ACC
    - ACCCCY
    - EXRATE
    - NETIND
    - ERICCY
    - ERIAMT
    - GENMSG
    - RATECD
    - CLEARNW
    - COVERBY
    - RTGSPMNT
    - BANKPRIOR
    - RTGSNW
    - PAYBY
    - TRANSTYP
    - INSTYP
    - INSNO
    - CHGDET
    - PAYMNTDET1
    - PAYMNTDET2
    - PAYMNTDET3
    - PAYMNTDET4
    - SNDTRRCVINFO1
    - SNDTRRCVINFO2
    - SNDTRRCVINFO3
    - SNDTRRCVINFO4
    - SNDTRRCVINFO5
    - COVREQRD
    - RECVCVR
    - RECEIVER
    - REIMINST1
    - REIMINST2
    - REIMINST3
    - REIMINST4

RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5

RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*

ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT

LIQDSTAT

Misdetails

CONREFNO

LATESN

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10

FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME

FLDVAL

Con

CONTREFNO

EVENTSEQ

Adv

ADVNAME

SUPRESS

PRIOR

MEDM

PARTYIDEN

PARTYNAME

CHGREQ

PARTTYP

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description
Name	INSTRUMENT_DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTNO

Attribute	Description
Name	INSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BRNCDE

Attribute	Description
Name	BRNCDE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

REFNO

Attribute	Description	
Name	REFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DATE

Attribute	Description	
Name	DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CORRESPBNK

Attribute	Description	
Name	CORRESPBNK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CORRESPACNO

Attribute	Description
Name	CORRESPACNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

OTHERPARTYIDE

Attribute	Description
Name	OTHERPARTYIDE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACBRN1

Attribute	Description
Name	ACBRN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PROTEST

Attribute	Description
Name	PROTEST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQWITHBUKNG

Attribute	Description
Name	LIQWITHBUKNG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

REASON

Attribute	**Description**	
Name	REASON	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CONREFNOLOG

Attribute	**Description**	
Name	CONREFNOLOG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	**Description**	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SE_TXNSTAT

Attribute	Description
Name	SE_TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,L,R,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

VERSIONNORB

Attribute	Description
Name	VERSIONNORB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / DRAWER,PAYEE,REMITTING_BANK,DRAWEE

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRYCD

Attribute	**Description**	
Name	COUNTRYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ADDLN1

Attribute	**Description**	
Name	ADDLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDLN2

Attribute	**Description**	
Name	ADDLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO

Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String

Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	Description	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO5

Attribute	Description	
Name	SNDTRRCVINFO5	
Datatype	String	
Description	Indicates Sender To Receiver Information 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	Description	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4

Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1

Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	Description	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5

Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	

Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description

Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description	
Name	FUNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS8

Attribute	Description	
Name	FUNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS9

Attribute	Description	
Name	FUNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS10

Attribute	Description	
Name	FUNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
enumeration	Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	15

TOP

PARTYIDEN

Attribute	Description	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PARTYNAME

Attribute	Description	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CHGREQ

Attribute	Description	
Name	CHGREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTTYP

Attribute	Description	
Name	PARTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.27.QueryInwardRealize

QueryInwardRealize

2.27.1.RB-QueryInwardRealize-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Contract-Master-IO*
  - *CONTREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.27.2.RB-QueryInwardRealize-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Master-IO*
      - *CONTREFNO*
    - *Contract-Master-Full*
      - *CONTREFNO*
      - *CPTY_ID*
      - *CPTY_NAME*
      - *OTHERPARTYIDE*
      - *OTHR_PARTYNAME*
      - *INSTRUMENTNO*
      - *INSTRUMENTDATE*
      - *CONTRACTCCY*
      - *CONTRACTAMT*
      - *DUEDATE*
      - *REMBANKCODE*
      - *BANK_NAME*
      - *REMBRANCHCODE*
      - *BRANCH_NAME*
      - *REMREFNO*

REMBNKREFDT
CORRESBANK
CORRESACNO
ACCBRN
CPTY_AC_NO
CR_ACC_BR
REALISATIONAC
VALUEDATE
CHARGES_DEDUCTED
REALISEDNETAMT
DISHNRCODE
DISHONORREASON
LATVERNO
MAKER
MAKDTTIME
TXNSTAT
CHKR
CHKDTTIME
AUTHSTAT
EVENT_SEQ_NO
CURR_EVENT_CODE
CONTRCTREF_NO
Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*

PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3

BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*

ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT

CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2

TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4

COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Master-Full

Attribute	Description
Name	Contract-Master-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTY_NAME

Attribute	Description	
Name	CPTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYIDE

Attribute	Description	
Name	OTHERPARTYIDE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OTHR_PARTYNAME

Attribute	Description	
Name	OTHR_PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INSTRUMENTNO

Attribute	Description	
Name	INSTRUMENTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRUMENTDATE

Attribute	Description
Name	INSTRUMENTDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CONTRACTAMT

Attribute	Description
Name	CONTRACTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REMBANKCODE

Attribute	Description
Name	REMBANKCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BANK_NAME

Attribute	Description	
Name	BANK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

REMBRANCHCODE

Attribute	Description	
Name	REMBRANCHCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BRANCH_NAME

Attribute	Description	
Name	BRANCH_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

REMREFNO

Attribute	Description	
Name	REMREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

REMBNKREFDT

Attribute	Description
Name	REMBNKREFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CORRESBANK

Attribute	Description
Name	CORRESBANK
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CORRESACNO

Attribute	Description
Name	CORRESACNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CR_ACC_BR

Attribute	**Description**	
Name	CR_ACC_BR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REALISATIONAC

Attribute	**Description**	
Name	REALISATIONAC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

VALUEDATE

Attribute	**Description**	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHARGES_DEDUCTED

Attribute	**Description**	
Name	CHARGES_DEDUCTED	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REALISEDNETAMT

Attribute	Description
Name	REALISEDNETAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISHNRCODE

Attribute	Description
Name	DISHNRCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DISHONORREASON

Attribute	Description
Name	DISHONORREASON
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,L,R,H

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CURR_EVENT_CODE

Attribute	Description
Name	CURR_EVENT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CONTRCTREF_NO

Attribute	Description
Name	CONTRCTREF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description

Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	**Description**	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	**Description**	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	**Description**	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	**Description**
Name	CLEARNW
Datatype	String
Description	Indicates Network Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	**Description**	
Name	COVERBY	
Datatype	String	
Description	Indicates Cover By Clearing : C Message : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates RTGS Payment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	**Description**	
Name	BANKPRIOR	
Datatype	String	
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**

Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	Description	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3

Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	**Description**	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	**Description**	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	**Description**	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4

Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5

Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	**Description**	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	**Description**	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	**Description**	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number

Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	**Description**	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	**Description**	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

Con

Attribute	**Description**	
Name	Con	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNO

Attribute	**Description**	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.28.QueryOutBulkCol

QueryOutBulkCol

2.28.1.RB-QueryOutBulkCol-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-IO*
    - *BATCHREFENUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.28.2.RB-QueryOutBulkCol-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Input-IO*
      - *BATCHREFENUM*
    - *Bulk-Input-Full*
      - *CREDITLINE*
      - *OTHRPARTYLMTCHK*
      - *MARGINPERC*
      - *FINANCING*
      - *COLLATERAL*
      - *COLLPOOL*
      - *INSTRCODE*
      - *PRODCODE*
      - *CPTYIDEN*
      - *CPACCNO*
      - *CONTCCY*
      - *OTHRPTYIDEN*
      - *DRACCREAL*
      - *BANKCD*
      - *BOOKINGDATE*

PROTEST
TRACKLIMIT
INSTRUMENTDESC
PRODDESC
COUNTERPRTYNAME
OTHERPARTYNAME
BNKNAME
BRNNAME
NOOFINSTRUMENTS
BRNCODE
BATCHREFENUM
ACCBRN
DRACCBRN
PROCESSTAT
VERNUM
CVERNO
CONST
AUTHSTAT
CHKR
CHKDTTIME
MAKER
MAKDTTIME
Bulk-Input-Detail
CONTREFNO
INSTRNO
INSTRDATE
AMNT
CONTAMTLCY
MATURITYDATE
DISCAMT
COLLTVAL
INTREMARKS
PROCESSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Bulk-Input-Full

Attribute	Description
Name	Bulk-Input-Full
Datatype	
Description	

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTHRPARTYLMTCHK

Attribute	Description
Name	OTHRPARTYLMTCHK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,F,N

TOP

COLLATERAL

Attribute	**Description**	
Name	COLLATERAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,C,T,N

TOP

COLLPOOL

Attribute	**Description**	
Name	COLLPOOL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRCODE

Attribute	**Description**	
Name	INSTRCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

PRODCODE

Attribute	Description	
Name	PRODCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CPTYIDEN

Attribute	Description	
Name	CPTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPACCNO

Attribute	Description	
Name	CPACCNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CONTCCY

Attribute	Description	
Name	CONTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BANKCD

Attribute	Description
Name	BANKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRACKLIMIT

Attribute	**Description**	
Name	TRACKLIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INSTRUMENTDESC

Attribute	**Description**	
Name	INSTRUMENTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRODDESC

Attribute	**Description**	
Name	PRODDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COUNTERPRTYNAME

Attribute	**Description**	
Name	COUNTERPRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,U

TOP

VERNUM

Attribute	Description
Name	VERNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CVERNO

Attribute	Description
Name	CVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Bulk-Input-Detail

Attribute	Description
Name	Bulk-Input-Detail
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CONTAMTLCY

Attribute	Description
Name	CONTAMTLCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTVAL

Attribute	Description
Name	COLLTVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.29.QueryOutFinDet

QueryOutFinDet

2.29.1.RB-QueryOutFinDet-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Rbtbs-Contract-Master-IO*
  - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Rbtbs-Contract-Master-IO

Attribute	Description
Name	Rbtbs-Contract-Master-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.29.2.RB-QueryOutFinDet-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Rbtbs-Contract-Master-IO*
      - *CONREFNUM*
    - *Rbtbs-Contract-Master-Full*
      - *CPTYIDEN*
      - *INSTRNO*
      - *INSTRDATE*
      - *CONTCCY*
      - *AMNT*
      - *OTHRPTYIDEN*
      - *BOOKINGDATE*
      - *TRACKLIMIT*
      - *CREDITLINE*
      - *MARGINPERC*
      - *FINANCING*
      - *DISCOUNTAMT*
      - *DUEDATE*
      - *OTHERPARTYNAME*
      - *CPTYNAME*

CONREFNUM
MAKER
MAKERDT
CHKR
CHECKERDT
CONTSTAT
AUTHSTAT
OTHRPARTYLMTCHK
Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*

COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID

POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*

RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL

WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4

COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8

- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Clpref

- *CONTREFNNO*
- *CONTRACT_CCY*
- *LATEVNSEQNO*
- *PRD*
- *PRDDESC*
- *COUNTERPARTY*
- *CURRENCY*
- *TENOR*
- *UNITS*
- *LOAN_CONREFNO*
- *RATECODE*
- *EXCHANGERATE*
- *RATE_TYPE*
- *MAXIMUM*
- *MINIMUM*
- *PAYMENT_MODE*
- *LOANVALDATE*
- *MATURITY_DATE*
- *Ude*
  - *USERDEID*
  - *UDEDESC*
  - *RATEASOF*
  - *USAGE*
  - *USERDEVAL*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Con

- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*

PARTTYP

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Rbtbs-Contract-Master-IO

Attribute	Description
Name	Rbtbs-Contract-Master-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Rbtbs-Contract-Master-Full

Attribute	Description
Name	Rbtbs-Contract-Master-Full
Datatype	
Description	

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INSTRNO

Attribute	Description

Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F

TOP

DISCOUNTAMT

Attribute	**Description**	
Name	DISCOUNTAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DUEDATE

Attribute	**Description**	
Name	DUEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHERPARTYNAME

Attribute	**Description**	
Name	OTHERPARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTYNAME

Attribute	**Description**	
Name	CPTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERDT

Attribute	Description
Name	CHECKERDT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

OTHRPARTYLMTCHK

Attribute	Description
Name	OTHRPARTYLMTCHK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Settlement

Attribute	**Description**	
Name	Contract-Settlement	
Datatype		
Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	**Description**	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**

Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	**Description**	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO

Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String

Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	Description	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO5

Attribute	Description	
Name	SNDTRRCVINFO5	
Datatype	String	
Description	Indicates Sender To Receiver Information 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	Description	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4

Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1

Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	Description	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5

Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	

Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description

Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	**Description**
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	**Description**
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	**Description**
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	**Description**
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	**Description**	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS2

Attribute	**Description**	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description

Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description

Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr></table>

TOP

CHGREQ

Attribute	Description
Name	CHGREQ

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description

Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.30.QueryOutRealization

QueryOutRealization

2.30.1.RB-QueryOutRealization-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Contractdet-IO*
  - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contractdet-IO

Attribute	Description
Name	Contractdet-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.30.2.RB-QueryOutRealization-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contractdet-IO*
      - *CONREFNUM*
    - *Contractdet-Full*
      - *CONREFNUM*
      - *MAKER*
      - *MAKERDT*
      - *CHKR*
      - *CHECKERDT*
      - *CONTSTAT*
      - *AUTSTAT*
      - *CPTYIDEN*
      - *CURR*
      - *AMNT*
      - *OTHRPTYIDEN*
      - *DISCOUNTAMT*
      - *DRACCREAL*
      - *CPTYACCNUM*
      - *NETREALIZED*

OTHRBNKCHARGS
COLBANKREFNUM
VALUEDT
DUEDATE
COUNTRPRYNAM
OTHERPARTYNAME
BNKCD
BRNCODE
DRACCBRN
ACCBRN
BNKNAME
BRNNAME
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*

BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1

BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*

ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO

- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*

TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2

COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contractdet-IO

Attribute	Description
Name	Contractdet-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contractdet-Full

Attribute	Description
Name	Contractdet-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDT

Attribute	Description
Name	CHECKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L

TOP

AUTSTAT

Attribute	Description
Name	AUTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CURR

Attribute	**Description**	
Name	CURR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNT

Attribute	**Description**	
Name	AMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHRPTYIDEN

Attribute	**Description**	
Name	OTHRPTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

DISCOUNTAMT

Attribute	**Description**	
Name	DISCOUNTAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

NETREALIZED

Attribute	Description
Name	NETREALIZED
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BNKCD

Attribute	Description
Name	BNKCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BRNNAME

Attribute	**Description**
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Con

Attribute	**Description**
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	**Description**
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	**Description**
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description

Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP

Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String

Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	Description	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	Description	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	Description	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number

Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	Description	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	**Description**	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.31.QueryOutwardcollection

QueryOutwardcollection

2.31.1.RB-QueryOutwardcollection-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.31.2.RB-QueryOutwardcollection-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-IO*
      - *CONREFNUM*
    - *Contract-Details-Full*
      - *CONREFNUM*
      - *BOOKDT*
      - *USERREFNUM*
      - *BRN*
      - *PRDCD*
      - *MODULE*
      - *UDS*
      - *STOPDT*
      - *VERSIONNO*
      - *EVENTSEQ*
      - *EVENTCODE*
      - *INSTRUCODE*
      - *PRODTYP*
      - *CPTYIDEN*
      - *CPTYACCNUM*

INSTRNO
INSTRU_DATE
INITCCY
OSAMT
LCYAMT
OTHRPTYIDEN
BNKCD
BRN_D
REFERENCENO
BOOKINGDT
MATDAYS
LEADDAYS
DISPATCHDT
GRACEDAYS
PROTEST
TRACKLIMIT
CREDITLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
DISCAMT
COLLATERAL
COLLVL
COLLPOOL
ACCBRN
PAYDUEDATE
DRACCBRN
INTREMARKS
INSTRUMENT_DESCRIPTION
TXTPDTDESC
CPTYNAME
OTHERPARTYNAME
BNKNAME
BRNNAME
XREF
BATCHREFENUM
BATCHSEQNO
DRACCREAL
AUTOLIQD
CONTREFLOG
MAKER
MAKDTTIME
CHKR
CHKDTTIME

EVENTLOG
CONST
AUTHSTAT
LATVERNO
DATE
Party-Details
  PARTTYP
  PARTYIDEN
  PARTYNAME
  ADDLN1
  ADDLN2
  ADDLN3
  ADDLN4
  CNTY
  PRTYLANG
Settlements
  CONREFNO
  Contract-Settlement
    IBANACNO
    CUSTSPREAD
    SPREADDEFN
    COMPNT
    TAGCCY
    ACCBRN
    ACC
    ACCCCY
    EXRATE
    NETIND
    ERICCY
    ERIAMT
    GENMSG
    RATECD
    CLEARNW
    COVERBY
    RTGSPMNT
    BANKPRIOR
    RTGSNW
    PAYBY
    TRANSTYP
    INSTYP
    INSNO
    CHGDET
    PAYMNTDET1
    PAYMNTDET2

PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2

BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*

ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP

PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3

- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*

- *CREATESN*
- *COMPNT*
- *TGCCY*
- *TGAMT*
- *CHRGCCY*
- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Con*
  - *CONTREFNO*
  - *EVENTSEQ*
  - *Adv*
    - *ADVNAME*
    - *SUPRESS*
    - *PRIOR*
    - *MEDM*
    - *PARTYIDEN*
    - *PARTYNAME*
    - *CHGREQ*
    - *PARTTYP*
- *Clpref*
  - *CONTREFNNO*
  - *CONTRACT_CCY*
  - *LATEVNSEQNO*
  - *PRD*
  - *PRDDESC*
  - *COUNTERPARTY*
  - *CURRENCY*
  - *TENOR*
  - *UNITS*
  - *LOAN_CONREFNO*
  - *RATECODE*
  - *EXCHANGERATE*
  - *RATE_TYPE*
  - *MAXIMUM*
  - *MINIMUM*
  - *PAYMENT_MODE*

LOANVALDATE
MATURITY_DATE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BOOKDT

Attribute	Description	
Name	BOOKDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

USERREFNUM

Attribute	Description	
Name	USERREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

UDS

Attribute	Description
Name	UDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VERSIONNO

Attribute	Description
Name	VERSIONNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVENTCODE

Attribute	**Description**	
Name	EVENTCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

INSTRUCODE

Attribute	**Description**	
Name	INSTRUCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

PRODTYP

Attribute	**Description**	
Name	PRODTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

CPTYIDEN

Attribute	**Description**	
Name	CPTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTYACCNUM

Attribute	Description	
Name	CPTYACCNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRNO

Attribute	Description	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRU_DATE

Attribute	Description	
Name	INSTRU_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

INITCCY

Attribute	Description	
Name	INITCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

OSAMT

Attribute	Description
Name	OSAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BRN_D

Attribute	Description
Name	BRN_D
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BOOKINGDT

Attribute	Description
Name	BOOKINGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LEADDAYS

Attribute	Description
Name	LEADDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISPATCHDT

Attribute	Description
Name	DISPATCHDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLVL

Attribute	Description
Name	COLLVL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INTREMARKS

Attribute	Description	
Name	INTREMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description	
Name	INSTRUMENT_DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

TXTPDTDESC

Attribute	Description	
Name	TXTPDTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTYNAME

Attribute	Description	
Name	CPTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYNAME

Attribute	**Description**	
Name	OTHERPARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BNKNAME

Attribute	**Description**	
Name	BNKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONTREFLOG

Attribute	Description
Name	CONTREFLOG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

EVENTLOG

Attribute	**Description**	
Name	EVENTLOG	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONST

Attribute	**Description**	
Name	CONST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,H,R,L

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

LATVERNO

Attribute	**Description**	
Name	LATVERNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>DRAWEE,DRAWER,PAYEE,COLLECTING_BANK,</td></tr></table>

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRTYLANG

Attribute	Description
Name	PRTYLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	**Description**	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	**Description**	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1

Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2

Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5

Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1

Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	**Description**	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	**Description**	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	**Description**	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS6

Attribute	**Description**	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	**Description**	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / DRAWEE,DRAWER,PAYEE,COLLECTING_BANK,

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNNO

Attribute	**Description**	
Name	CONTREFNNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CONTRACT_CCY

Attribute	**Description**	
Name	CONTRACT_CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRD

Attribute	**Description**	
Name	PRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LOAN_CONREFNO

Attribute	**Description**	
Name	LOAN_CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RATECODE

Attribute	**Description**	
Name	RATECODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,S

TOP

EXCHANGERATE

Attribute	**Description**	
Name	EXCHANGERATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATE_TYPE

Attribute	**Description**	
Name	RATE_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

USAGE

Attribute	Description

Name	USAGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.32.QueryOverseasfinance

QueryOverseasfinance

2.32.1.RB-QueryOverseasfinance-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.32.2.RB-QueryOverseasfinance-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-IO*
      - *CONREFNUM*
    - *Main-Full*
      - *CONREFNUM*
      - *CPTY_ID*
      - *CPTY_NAME*
      - *INSTRNO*
      - *INSTRUMENT_DATE*
      - *CURRENCY*
      - *AMNT*
      - *BOOKINGDATE*
      - *OTHR_PARTY_NAME*
      - *DRAWEE_BNK_NAME*
      - *FINANCING*
      - *MARGINPERCENT*
      - *TRACK_LIMIT*
      - *CREDIT_LINE*
      - *DISCOUNT_AMOUNT*

MAKER
MAKERDTSTAMP
CHECKER
CHECKERSTAMP
RECORD_STAT
AUTHSTAT
PAYDUEDATE
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*

INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2

ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER

- *DISACCRAPPL*
- *ACCRREQD*
- *DESC*

Charge-Application

- *CREATESN*
- *COMPNT*
- *TGCCY*
- *TGAMT*
- *CHRGCCY*
- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*

Charge-Liquidation

- *ESN*
- *COMPNT*
- *CHRGCCY*
- *CHRGAMT*
- *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*

TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7

- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Clpref

- *CONTREFNNO*
- *CONTRACT_CCY*
- *LATEVNSEQNO*
- *PRD*
- *PRDDESC*
- *COUNTERPARTY*
- *CURRENCY*
- *TENOR*
- *UNITS*
- *LOAN_CONREFNO*
- *RATECODE*
- *EXCHANGERATE*
- *RATE_TYPE*
- *MAXIMUM*
- *MINIMUM*
- *PAYMENT_MODE*
- *LOANVALDATE*
- *MATURITY_DATE*
- *Ude*
  - *USERDEID*
  - *UDEDESC*
  - *RATEASOF*
  - *USAGE*
  - *USERDEVAL*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description

Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FINANCING

Attribute	Description
Name	FINANCING

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>L,A,H,</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,U,</td></tr></table>

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description

Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description

Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String

Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description

Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	**Description**	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	**Description**	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	**Description**	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	**Description**	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2

Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3

Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	**Description**	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	**Description**	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	**Description**	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2

Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	**Description**	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	**Description**	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	**Description**	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**	
Name	REGREP2	
Datatype	String	
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**
Name	REGREP3
Datatype	String

Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2

Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	**Description**	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	**Description**	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO2

Attribute	**Description**	
Name	SNDRRCVRINFO2	
Datatype	String	
Description	Indicates Sender Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	**Description**	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	**Description**	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	Description	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS2

Attribute	Description	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS3

Attribute	Description	
Name	FUNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description

Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.33.QueryOverseaspdr

QueryOverseaspdr

2.33.1.RB-QueryOverseaspdr-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.33.2.RB-QueryOverseaspdr-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-IO*
      - *CONREFNUM*
    - *Main-Full*
      - *CONREFNUM*
      - *CPTY_ID*
      - *CTR_PRTY_NAME*
      - *INSTRUMENTNORE*
      - *INSTRUMENT_DATE*
      - *CURRENCY*
      - *AMNT*
      - *MAKER*
      - *MAKERDTSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *RECORD_STAT*
      - *AUTHSTAT*
      - *OTHER_BANK_CHARGES*
      - *BNK_CODE*

REMRKS
BANK_NAME
DISHONORDATE
NOTARY_DESCRIPTION
BOOKING_DATE
DISCOUNT_AMOUNT
REASON_CODE
REASON
PROTESTDATE
RETURN_DATE
OTHR_PARTY_NAME
DRAWEE_BNK_NAME
Charges
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*

COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3

INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
  INSTRCD1

INSTRCD2
INSTRCD3
INSTRCD4
ITIMEIND1
ITIMEIND2
ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5

Lcl_Clearing

FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID

SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1

COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4

FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CTR_PRTY_NAME

Attribute	Description
Name	CTR_PRTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INSTRUMENTNORE

Attribute	Description
Name	INSTRUMENTNORE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,A,H,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,U,</td></tr></table>

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BNK_CODE

Attribute	Description
Name	BNK_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BANK_NAME

Attribute	Description
Name	BANK_NAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DISHONORDATE

Attribute	**Description**	
Name	DISHONORDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NOTARY_DESCRIPTION

Attribute	**Description**	
Name	NOTARY_DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BOOKING_DATE

Attribute	**Description**	
Name	BOOKING_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISCOUNT_AMOUNT

Attribute	**Description**	
Name	DISCOUNT_AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REASON_CODE

Attribute	**Description**
Name	REASON_CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REASON

Attribute	Description
Name	REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs: 1
Restrictions	**Restrictions** / **Description** maxLength: 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	Description	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	Description	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String

Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.34.QueryOvsbulkcontract

QueryOvsbulkcontract

2.34.1.RB-QueryOvsbulkcontract-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Bulk-Input-Overseas-IO*
  - *BATCHREFENUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Overseas-IO

Attribute	Description
Name	Bulk-Input-Overseas-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.34.2.RB-QueryOvsbulkcontract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Input-Overseas-IO*
      - *BATCHREFENUM*
    - *Bulk-Input-Overseas-Full*
      - *INSTRUMENT_CODE*
      - *INSTR_DESC*
      - *PRODCD*
      - *PRDDESC*
      - *CURRENCY*
      - *COLLECTINGBANKCIF*
      - *CBN_S*
      - *DB_ACC_REAL*
      - *ACCBRN*
      - *BOKNGDT*
      - *PAYDUEDATE*
      - *TRANSITDAYS*
      - *BATCHREFENUM*
      - *COLLBANKCODE*
      - *NOOFINSTRUMENTS*

STAT
ESN_NO
RECORD_STAT
AUTHSTAT
CHKR
CHKDTTIME
MAKER
MAKDTTIME
EVENTSEQNO
Bulk-Input-Overseas-Dtl
CONTRACTREFNO
CPTY_ID
CPTY_AC_NO
ACCBRNRE
INSTRNO
INSTRU_DATE
AMNT
LCY_AMT
OTHR_PARTYNAME
DRAWEE_BNK_NAME
AUTOLIQD
FINANCING
MARGIN_PERCENTAGE
TRACK_LIMIT
CREDIT_LINE
DISCAMT
CPTY_NAME
INTREMRKS
BATCHREFNO
BATCHSEQNO
CONTRACTCCY
PROCESS_STATUS
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Input-Overseas-IO

Attribute	Description
Name	Bulk-Input-Overseas-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Input-Overseas-Full

Attribute	Description
Name	Bulk-Input-Overseas-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

PRODCD

Attribute	Description
Name	PRODCD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLECTINGBANKCIF

Attribute	Description
Name	COLLECTINGBANKCIF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CBN_S

Attribute	Description
Name	CBN_S
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

COLLBANKCODE

Attribute	Description
Name	COLLBANKCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,U,

TOP

ESN_NO

Attribute	Description
Name	ESN_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,C,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bulk-Input-Overseas-Dtl

Attribute	Description
Name	Bulk-Input-Overseas-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRNRE

Attribute	Description
Name	ACCBRNRE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F,

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BATCHREFNO

Attribute	Description
Name	BATCHREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,H,F,

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.35.QueryOvsbulkrealize

QueryOvsbulkrealize

2.35.1.RB-QueryOvsbulkrealize-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Liqd-Overseas-IO*
    - *BULK_REAL_NUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Liqd-Overseas-IO

Attribute	Description
Name	Bulk-Liqd-Overseas-IO
Datatype	
Description	

TOP

BULK_REAL_NUM

Attribute	Description
Name	BULK_REAL_NUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.35.2.RB-QueryOvsbulkrealize-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Liqd-Overseas-IO*
      - *BULK_REAL_NUM*
    - *Bulk-Liqd-Overseas-Full*
      - *BATCHREFENUM*
      - *BULK_REAL_NUM*
      - *CURRENCY*
      - *DB_ACC_REAL*
      - *ACCBRN*
      - *COLBANK_REFNO*
      - *COLL_BNK_CIF*
      - *COLLBNKNAME*
      - *VALUEDATE*
      - *PROCSTAT*
      - *RECORD_STAT*
      - *AUTHSTAT*
      - *CHKR*
      - *CHKDTTIME*
      - *ESN_NO*

MAKER
MAKDTTIME
EVENTSEQNO
Bulk-Liqd-Overseas-Dtl
CONTRACTREFNO
CPTY_ID
CPTY_NAME
CPTY_AC_NO
ACCBRNRE
INSTRNO
INSTRU_DATE
AMNT
NET_AMT_REALISED
OTHER_BANK_CHARGES
INTREMRKS
PROCESSSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Liqd-Overseas-IO

Attribute	Description
Name	Bulk-Liqd-Overseas-IO
Datatype	
Description	

TOP

BULK_REAL_NUM

Attribute	Description
Name	BULK_REAL_NUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Liqd-Overseas-Full

Attribute	Description
Name	Bulk-Liqd-Overseas-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BULK_REAL_NUM

Attribute	Description
Name	BULK_REAL_NUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

COLBANK_REFNO

Attribute	Description
Name	COLBANK_REFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PROCSTAT

Attribute	Description
Name	PROCSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,U,

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ESN_NO

Attribute	Description
Name	ESN_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Bulk-Liqd-Overseas-Dtl

Attribute	Description
Name	Bulk-Liqd-Overseas-Dtl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTY_AC_NO

Attribute	**Description**	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCBRNRE

Attribute	**Description**	
Name	ACCBRNRE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INSTRNO

Attribute	**Description**	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRU_DATE

Attribute	**Description**	
Name	INSTRU_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / S,H,F,

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.36.QueryOvscheckspay

QueryOvscheckspay

2.36.1.RB-QueryOvscheckspay-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONTREFNO*
    - *USERREF_NO*
    - *XREF*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

2.36.2.RB-QueryOvscheckspay-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-IO*
      - *CONTREFNO*
      - *USERREF_NO*
      - *XREF*
    - *Main-Full*
      - *CONTREFNO*
      - *LATESTVERSIONNO*
      - *RECORD_STAT*
      - *AUTHSTATUS*
      - *CURR_EVENT_CODE*
      - *MAKER*
      - *MAKERDTSTAMP*
      - *CHKR*
      - *CHKDTTIME*
      - *EVENT_SEQ_NO*
      - *CONT_STAT*
      - *AUTH_STAT*
      - *CPTY_ID*

CPTY_AC_NO
INSTRNO
INSTRUMENT_DATE
CURRENCY
AMNT
NET_AMT_REALISED
OTHER_BANK_CHARGES
COLL_BNK_CIF
BOOKINGDATE
MATURITY_DATE
VALUE_DATE
TRACK_LIMIT
CREDIT_LINE
FINANCING
INT_REM
INSTRUMENT_CODE
INSTR_DESC
PRCD
PRODDESC
USERREF_NO
XREF
COUNTRPRYNAM
LCY_AMT
COLLBANKNAME
PAYDUEDATE
CONREF
EVENTSEQ
PARTYTYP
ADDRESS
PARTYADDR2
PARTYADDR3
PARTYADDR4
WALKINCUSTFLG
COLLEC_BANK_CIF
COLLBNKNAME
DISCOUNT_AMOUNT
DB_ACC_REAL
BULK_INPUT_REF_NO
DRAWEE_BNK_NAME
AUTOLIQD
OTHER_PARTY_ID
VERSION_NO
TRANSITDAYS
MARGIN_PERCENTAGE

ACC_BRANCH
OTHR_PARTY_NAME
ACCBRN
TXNUDFDETAILS
- *FLDNAME*
- *FLDVAL*

Charges
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails
- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*

REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4

- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*

GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4

ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*

TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2

REPRES3
REPRES4
RCVRACC
Clpref
CONTREFNNO
CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM
PAYMENT_MODE
LOANVALDATE
MATURITY_DATE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USERREF_NO

Attribute	Description	
Name	USERREF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Main-Full

Attribute	Description

Name	Main-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESTVERSIONNO

Attribute	Description
Name	LATESTVERSIONNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTATUS

Attribute	Description
Name	AUTHSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CURR_EVENT_CODE

Attribute	Description
Name	CURR_EVENT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description

Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONT_STAT

Attribute	Description
Name	CONT_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,L,R,H,

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,N,F

TOP

INT_REM

Attribute	**Description**	
Name	INT_REM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INSTRUMENT_CODE

Attribute	**Description**	
Name	INSTRUMENT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTR_DESC

Attribute	**Description**	
Name	INSTR_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRCD

Attribute	**Description**	
Name	PRCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLBANKNAME

Attribute	Description
Name	COLLBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREF

Attribute	Description
Name	CONREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYTYP

Attribute	**Description**	
Name	PARTYTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

ADDRESS

Attribute	**Description**	
Name	ADDRESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PARTYADDR2

Attribute	**Description**	
Name	PARTYADDR2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PARTYADDR3

Attribute	**Description**	
Name	PARTYADDR3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PARTYADDR4

Attribute	Description	
Name	PARTYADDR4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

WALKINCUSTFLG

Attribute	Description	
Name	WALKINCUSTFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COLLEC_BANK_CIF

Attribute	Description	
Name	COLLEC_BANK_CIF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COLLBNKNAME

Attribute	Description	
Name	COLLBNKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BULK_INPUT_REF_NO

Attribute	Description
Name	BULK_INPUT_REF_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

OTHER_PARTY_ID

Attribute	**Description**	
Name	OTHER_PARTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

VERSION_NO

Attribute	**Description**	
Name	VERSION_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRANSITDAYS

Attribute	**Description**	
Name	TRANSITDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MARGIN_PERCENTAGE

Attribute	**Description**	
Name	MARGIN_PERCENTAGE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACC_BRANCH

Attribute	**Description**
Name	ACC_BRANCH

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT

Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT

Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description	
Name	TRANMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	Description	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	Description	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	Description	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Clpref

Attribute	**Description**	
Name	Clpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNNO

Attribute	**Description**	
Name	CONTREFNNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CONTRACT_CCY

Attribute	**Description**	
Name	CONTRACT_CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TENOR

Attribute	Description
Name	TENOR

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description

Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.37.QueryOvsrealizecontract

QueryOvsrealizecontract

2.37.1.RB-QueryOvsrealizecontract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.37.2.RB-QueryOvsrealizecontract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-IO*
      - *CONREFNUM*
    - *Main-Full*
      - *CONREFNUM*
      - *CPTY_ID*
      - *CTR_PRTY_NAME*
      - *INSTRNO*
      - *INSTRUMENT_DATE*
      - *CURRENCY*
      - *AMNT*
      - *MAKER*
      - *MAKERDTSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *RECORD_STAT*
      - *AUTHSTAT*
      - *CPTY_AC_NO*
      - *NET_AMT_REALISED*

OTHER_BANK_CHARGES
COLL_BNK_CIF
COLBANK_REFNO
VALUE_DATE
REMARKS
DB_ACC_REAL
COLL_BNK_NAME
ACCBRN
ACC_BRANCH
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*

TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4

ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*

ENVCONT5

Lcl_Clearing

FREETXT1

FREETXT2

FREETXT3

PMNTCD

ADDINFOSORBNET

SNDRCUSTNAME1

SNDRCUSTNAME2

SNDRCUSTNAME3

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

Charges

CONREFNO

Charge-Association

COMPNT

CREATESN

RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3

TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5

COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CTR_PRTY_NAME

Attribute	Description
Name	CTR_PRTY_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,A,H,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,U,</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COLBANK_REFNO

Attribute	Description
Name	COLBANK_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACC_BRANCH

Attribute	Description
Name	ACC_BRANCH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EVENTSEQ

Attribute	**Description**	
Name	EVENTSEQ	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Adv

Attribute	**Description**	
Name	Adv	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ADVNAME

Attribute	**Description**	
Name	ADVNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SUPRESS

Attribute	**Description**	
Name	SUPRESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr></table>

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY

Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	**Description**	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	**Description**	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String

Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description

Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	**Description**	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	**Description**	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	**Description**	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2

Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3

Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	**Description**	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	**Description**	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	**Description**	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2

Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	**Description**	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**	
Name	REGREP2	
Datatype	String	
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**
Name	REGREP3
Datatype	String

Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2

Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	**Description**	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	**Description**	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO2

Attribute	**Description**	
Name	SNDRRCVRINFO2	
Datatype	String	
Description	Indicates Sender Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	**Description**	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	**Description**
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	**Description**
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	**Description**
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	**Description**
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	Description	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	Description	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	Description	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	Description	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	**Description**	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.38.DeleteInwardRealize

DeleteInwardRealize

2.38.1.RB-DeleteInwardRealize-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-Full*
    - *CONTREFNO*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *OTHERPARTYIDE*
    - *OTHR_PARTYNAME*
    - *INSTRUMENTNO*
    - *INSTRUMENTDATE*
    - *CONTRACTCCY*
    - *CONTRACTAMT*
    - *DUEDATE*
    - *REMBANKCODE*
    - *BANK_NAME*
    - *REMBRANCHCODE*
    - *BRANCH_NAME*
    - *REMREFNO*

REMBNKREFDT
CORRESBANK
CORRESACNO
ACCBRN
CPTY_AC_NO
CR_ACC_BR
REALISATIONAC
VALUEDATE
CHARGES_DEDUCTED
REALISEDNETAMT
DISHNRCODE
DISHONORREASON
LATVERNO
MAKER
MAKDTTIME
TXNSTAT
CHKR
CHKDTTIME
AUTHSTAT
EVENT_SEQ_NO
CURR_EVENT_CODE
CONTRCTREF_NO
Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*

PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3

BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*

ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT

CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2

TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4

COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master-Full

Attribute	Description
Name	Contract-Master-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHERPARTYIDE

Attribute	Description
Name	OTHERPARTYIDE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRUMENTNO

Attribute	Description

Name	INSTRUMENTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENTDATE

Attribute	Description
Name	INSTRUMENTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONTRACTAMT

Attribute	Description
Name	CONTRACTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMBANKCODE

Attribute	Description
Name	REMBANKCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANK_NAME

Attribute	Description
Name	BANK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REMBRANCHCODE

Attribute	Description
Name	REMBRANCHCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRANCH_NAME

Attribute	Description
Name	BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REMREFNO

Attribute	Description

Name	REMREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REMBNKREFDT

Attribute	Description
Name	REMBNKREFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CORRESBANK

Attribute	Description
Name	CORRESBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CORRESACNO

Attribute	Description
Name	CORRESACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CR_ACC_BR

Attribute	Description
Name	CR_ACC_BR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REALISATIONAC

Attribute	Description
Name	REALISATIONAC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHARGES_DEDUCTED

Attribute	Description
Name	CHARGES_DEDUCTED
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REALISEDNETAMT

Attribute	Description
Name	REALISEDNETAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISHNRCODE

Attribute	Description
Name	DISHNRCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DISHONORREASON

Attribute	Description
Name	DISHONORREASON
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	Description	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,L,R,H

TOP

CHKR

Attribute	Description	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,A</td></tr></table>

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CURR_EVENT_CODE

Attribute	Description
Name	CURR_EVENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CONTRCTREF_NO

Attribute	Description
Name	CONTRCTREF_NO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Settlements

Attribute	**Description**	
Name	Settlements	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Settlement

Attribute	**Description**	
Name	Contract-Settlement	
Datatype		
Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	**Description**	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	**Description**	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.38.2.RB-DeleteInwardRealize-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-IO*
    - *CONTREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.38.3.RB-DeleteInwardRealize-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-Full*
    - *CONTREFNO*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *OTHERPARTYIDE*
    - *OTHR_PARTYNAME*
    - *INSTRUMENTNO*
    - *INSTRUMENTDATE*
    - *CONTRACTCCY*
    - *CONTRACTAMT*
    - *DUEDATE*
    - *REMBANKCODE*
    - *BANK_NAME*
    - *REMBRANCHCODE*
    - *BRANCH_NAME*
    - *REMREFNO*
    - *REMBNKREFDT*
    - *CORRESBANK*
    - *CORRESACNO*

ACCBRN
CPTY_AC_NO
CR_ACC_BR
REALISATIONAC
VALUEDATE
CHARGES_DEDUCTED
REALISEDNETAMT
DISHNRCODE
DISHONORREASON
LATVERNO
MAKER
MAKDTTIME
TXNSTAT
CHKR
CHKDTTIME
AUTHSTAT
EVENT_SEQ_NO
CURR_EVENT_CODE
CONTRCTREF_NO
Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*

INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2

ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER

DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5

TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7

COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master-Full

Attribute	Description
Name	Contract-Master-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	**Description**	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_NAME

Attribute	**Description**	
Name	CPTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYIDE

Attribute	**Description**	
Name	OTHERPARTYIDE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OTHR_PARTYNAME

Attribute	**Description**	
Name	OTHR_PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INSTRUMENTNO

Attribute	Description
Name	INSTRUMENTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENTDATE

Attribute	Description
Name	INSTRUMENTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CONTRACTAMT

Attribute	Description
Name	CONTRACTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DUEDATE

Attribute	Description
Name	DUEDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMBANKCODE

Attribute	Description
Name	REMBANKCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANK_NAME

Attribute	Description
Name	BANK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REMBRANCHCODE

Attribute	Description
Name	REMBRANCHCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRANCH_NAME

Attribute	Description
Name	BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

REMREFNO

Attribute	Description
Name	REMREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

REMBNKREFDT

Attribute	Description
Name	REMBNKREFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORRESBANK

Attribute	Description
Name	CORRESBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CORRESACNO

Attribute	Description
Name	CORRESACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CR_ACC_BR

Attribute	Description
Name	CR_ACC_BR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

REALISATIONAC

Attribute	Description
Name	REALISATIONAC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHARGES_DEDUCTED

Attribute	Description
Name	CHARGES_DEDUCTED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REALISEDNETAMT

Attribute	Description
Name	REALISEDNETAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISHNRCODE

Attribute	Description
Name	DISHNRCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DISHONORREASON

Attribute	Description
Name	DISHONORREASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,L,R,H</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CURR_EVENT_CODE

Attribute	**Description**	
Name	CURR_EVENT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CONTRCTREF_NO

Attribute	Description
Name	CONTRCTREF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String

Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description	
Name	TRANMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	Description	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	Description	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	Description	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String

Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.38.4.RB-DeleteInwardRealize-Res-PK-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
CHOICE
Contract-Master-PK
CONTREFNO
Contract-Master-IO
CONTREFNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Master-PK

Attribute	Description
Name	Contract-Master-PK
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.39.DeleteOutBulkCol

DeleteOutBulkCol

2.39.1.RB-DeleteOutBulkCol-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Full*
    - *CREDITLINE*
    - *OTHRPARTYLMTCHK*
    - *MARGINPERC*
    - *FINANCING*
    - *COLLATERAL*
    - *COLLPOOL*
    - *INSTRCODE*
    - *PRODCODE*
    - *CPTYIDEN*
    - *CPACCNO*
    - *CONTCCY*
    - *OTHRPTYIDEN*
    - *DRACCREAL*
    - *BANKCD*
    - *BOOKINGDATE*

PROTEST
TRACKLIMIT
INSTRUMENTDESC
PRODDESC
COUNTERPRTYNAME
OTHERPARTYNAME
BNKNAME
BRNNAME
NOOFINSTRUMENTS
BRNCODE
BATCHREFENUM
ACCBRN
DRACCBRN
PROCESSTAT
VERNUM
CVERNO
CONST
AUTHSTAT
CHKR
CHKDTTIME
MAKER
MAKDTTIME
Bulk-Input-Detail
- *CONTREFNO*
- *INSTRNO*
- *INSTRDATE*
- *AMNT*
- *CONTAMTLCY*
- *MATURITYDATE*
- *DISCAMT*
- *COLLTVAL*
- *INTREMARKS*
- *PROCESSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Full

Attribute	Description
Name	Bulk-Input-Full
Datatype	
Description	

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

OTHRPARTYLMTCHK

Attribute	Description
Name	OTHRPARTYLMTCHK

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,F,N

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRCODE

Attribute	Description
Name	INSTRCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRODCODE

Attribute	Description
Name	PRODCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPACCNO

Attribute	Description
Name	CPACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BANKCD

Attribute	Description
Name	BANKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

INSTRUMENTDESC

Attribute	Description
Name	INSTRUMENTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COUNTERPRTYNAME

Attribute	**Description**	
Name	COUNTERPRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYNAME

Attribute	**Description**	
Name	OTHERPARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BNKNAME

Attribute	**Description**	
Name	BNKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,U</td></tr></table>

TOP

VERNUM

Attribute	Description
Name	VERNUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CVERNO

Attribute	Description
Name	CVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	enumeration	,O,C

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

CHKR

Attribute	Description	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	Description	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Bulk-Input-Detail

Attribute	Description
Name	Bulk-Input-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRDATE

Attribute	Description

Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CONTAMTLCY

Attribute	Description
Name	CONTAMTLCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTVAL

Attribute	Description
Name	COLLTVAL
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U

TOP

2.39.2.RB-DeleteOutBulkCol-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Bulk-Input-IO
BATCHREFENUM

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.39.3.RB-DeleteOutBulkCol-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Full*
    - *CREDITLINE*
    - *OTHRPARTYLMTCHK*
    - *MARGINPERC*
    - *FINANCING*
    - *COLLATERAL*
    - *COLLPOOL*
    - *INSTRCODE*
    - *PRODCODE*
    - *CPTYIDEN*
    - *CPACCNO*
    - *CONTCCY*
    - *OTHRPTYIDEN*
    - *DRACCREAL*
    - *BANKCD*
    - *BOOKINGDATE*
    - *PROTEST*
    - *TRACKLIMIT*
    - *INSTRUMENTDESC*

PRODDESC
COUNTERPRTYNAME
OTHERPARTYNAME
BNKNAME
BRNNAME
NOOFINSTRUMENTS
BRNCODE
BATCHREFENUM
ACCBRN
DRACCBRN
PROCESSTAT
VERNUM
CVERNO
CONST
AUTHSTAT
CHKR
CHKDTTIME
MAKER
MAKDTTIME
Bulk-Input-Detail
CONTREFNO
INSTRNO
INSTRDATE
AMNT
CONTAMTLCY
MATURITYDATE
DISCAMT
COLLTVAL
INTREMARKS
PROCESSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Full

Attribute	Description
Name	Bulk-Input-Full
Datatype	
Description	

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

OTHRPARTYLMTCHK

Attribute	**Description**	
Name	OTHRPARTYLMTCHK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MARGINPERC

Attribute	**Description**	
Name	MARGINPERC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,F,N

TOP

COLLATERAL

Attribute	**Description**	
Name	COLLATERAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,C,T,N

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRCODE

Attribute	Description
Name	INSTRCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRODCODE

Attribute	Description
Name	PRODCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPACCNO

Attribute	Description
Name	CPACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BANKCD

Attribute	Description
Name	BANKCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INSTRUMENTDESC

Attribute	Description
Name	INSTRUMENTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

COUNTERPRTYNAME

Attribute	Description
Name	COUNTERPRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,U

TOP

VERNUM

Attribute	Description
Name	VERNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CVERNO

Attribute	Description
Name	CVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

Bulk-Input-Detail

Attribute	Description
Name	Bulk-Input-Detail
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CONTAMTLCY

Attribute	Description
Name	CONTAMTLCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number

Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

COLLTVAL

Attribute	Description
Name	COLLTVAL
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	
Restrictions	

Restrictions	Description
maxLength	255

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	
Restrictions	

Restrictions	Description
enumeration	,P,U

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.39.4.RB-DeleteOutBulkCol-Res-PK-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *CHOICE*
  - *Bulk-Input-PK*
    - *BATCHREFENUM*
  - *Bulk-Input-IO*
    - *BATCHREFENUM*
- *FCUBS_ERROR_RESP*
  - *ERROR*
    - *ECODE*
    - *EDESC*
- *FCUBS_WARNING_RESP*
  - *WARNING*
    - *WCODE*
    - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Input-PK

Attribute	Description
Name	Bulk-Input-PK
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.40.DeleteOutFinDet

DeleteOutFinDet

2.40.1.RB-DeleteOutFinDet-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Rbtbs-Contract-Master-Full*
    - *CPTYIDEN*
    - *INSTRNO*
    - *INSTRDATE*
    - *CONTCCY*
    - *AMNT*
    - *OTHRPTYIDEN*
    - *BOOKINGDATE*
    - *TRACKLIMIT*
    - *CREDITLINE*
    - *MARGINPERC*
    - *FINANCING*
    - *DISCOUNTAMT*
    - *DUEDATE*
    - *OTHERPARTYNAME*
    - *CPTYNAME*

CONREFNUM
MAKER
MAKERDT
CHKR
CHECKERDT
CONTSTAT
AUTHSTAT
OTHRPARTYLMTCHK
Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*

COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID

POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*

RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL

WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4

COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8

- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Clpref

- *CONTREFNNO*
- *CONTRACT_CCY*
- *LATEVNSEQNO*
- *PRD*
- *PRDDESC*
- *COUNTERPARTY*
- *CURRENCY*
- *TENOR*
- *UNITS*
- *LOAN_CONREFNO*
- *RATECODE*
- *EXCHANGERATE*
- *RATE_TYPE*
- *MAXIMUM*
- *MINIMUM*
- *PAYMENT_MODE*
- *LOANVALDATE*
- *MATURITY_DATE*
- *Ude*
  - *USERDEID*
  - *UDEDESC*
  - *RATEASOF*
  - *USAGE*
  - *USERDEVAL*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Con

- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*

PARTTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Rbtbs-Contract-Master-Full

Attribute	Description
Name	Rbtbs-Contract-Master-Full
Datatype	
Description	

TOP

CPTYIDEN

Attribute	Description	
Name	CPTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INSTRNO

Attribute	Description	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRDATE

Attribute	Description	
Name	INSTRDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTCCY

Attribute	Description	
Name	CONTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNT

Attribute	Description
Name	AMNT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDT

Attribute	Description
Name	CHECKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

OTHRPARTYLMTCHK

Attribute	Description
Name	OTHRPARTYLMTCHK
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	Description	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	Description	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	Description	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description

Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description

Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
enumeration	Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

2.40.2.RB-DeleteOutFinDet-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Rbtbs-Contract-Master-IO
CONREFNUM

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Rbtbs-Contract-Master-IO

Attribute	Description
Name	Rbtbs-Contract-Master-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.40.3.RB-DeleteOutFinDet-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Rbtbs-Contract-Master-Full*
    - *CPTYIDEN*
    - *INSTRNO*
    - *INSTRDATE*
    - *CONTCCY*
    - *AMNT*
    - *OTHRPTYIDEN*
    - *BOOKINGDATE*
    - *TRACKLIMIT*
    - *CREDITLINE*
    - *MARGINPERC*
    - *FINANCING*
    - *DISCOUNTAMT*
    - *DUEDATE*
    - *OTHERPARTYNAME*
    - *CPTYNAME*
    - *CONREFNUM*
    - *MAKER*
    - *MAKERDT*

- *CHKR*
- *CHECKERDT*
- *CONTSTAT*
- *AUTHSTAT*
- *OTHRPARTYLMTCHK*
- *Settlements*
  - *CONREFNO*
  - *Contract-Settlement*
    - *IBANACNO*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *COMPNT*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *ACCCCY*
    - *EXRATE*
    - *NETIND*
    - *ERICCY*
    - *ERIAMT*
    - *GENMSG*
    - *RATECD*
    - *CLEARNW*
    - *COVERBY*
    - *RTGSPMNT*
    - *BANKPRIOR*
    - *RTGSNW*
    - *PAYBY*
    - *TRANSTYP*
    - *INSTYP*
    - *INSNO*
    - *CHGDET*
    - *PAYMNTDET1*
    - *PAYMNTDET2*
    - *PAYMNTDET3*
    - *PAYMNTDET4*
    - *SNDTRRCVINFO1*
    - *SNDTRRCVINFO2*
    - *SNDTRRCVINFO3*
    - *SNDTRRCVINFO4*
    - *SNDTRRCVINFO5*
    - *COVREQRD*
    - *RECVCVR*
    - *RECEIVER*

REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6

ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*

ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation

ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7

COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails

Compmisdetails
Fundmisdetails
Clpref
CONTREFNNO
CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM
PAYMENT_MODE
LOANVALDATE
MATURITY_DATE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR

ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Rbtbs-Contract-Master-Full

Attribute	Description
Name	Rbtbs-Contract-Master-Full
Datatype	
Description	

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERDT

Attribute	Description
Name	MAKERDT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDT

Attribute	Description
Name	CHECKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

OTHRPARTYLMTCHK

Attribute	Description
Name	OTHRPARTYLMTCHK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String

Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String

Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description

Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	**Description**	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	**Description**	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	**Description**	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2

Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3

Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2

Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	**Description**	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**	
Name	REGREP2	
Datatype	String	
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**
Name	REGREP3
Datatype	String

Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2

Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	**Description**	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	**Description**	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO2

Attribute	**Description**	
Name	SNDRRCVRINFO2	
Datatype	String	
Description	Indicates Sender Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	**Description**	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	Description	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	Description	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	Description	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	Description	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	**Description**	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description

Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.40.4.RB-DeleteOutFinDet-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Rbtbs-Contract-Master-PK*
      - *CONREFNUM*
    - *Rbtbs-Contract-Master-IO*
      - *CONREFNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Rbtbs-Contract-Master-PK

Attribute	Description
Name	Rbtbs-Contract-Master-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Rbtbs-Contract-Master-IO

Attribute	Description
Name	Rbtbs-Contract-Master-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.41.DeleteOutRealization

DeleteOutRealization

2.41.1.RB-DeleteOutRealization-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contractdet-Full*
    - *CONREFNUM*
    - *MAKER*
    - *MAKERDT*
    - *CHKR*
    - *CHECKERDT*
    - *CONTSTAT*
    - *AUTSTAT*
    - *CPTYIDEN*
    - *CURR*
    - *AMNT*
    - *OTHRPTYIDEN*
    - *DISCOUNTAMT*
    - *DRACCREAL*
    - *CPTYACCNUM*
    - *NETREALIZED*

OTHRBNKCHARGS
COLBANKREFNUM
VALUEDT
DUEDATE
COUNTRPRYNAM
OTHERPARTYNAME
BNKCD
BRNCODE
DRACCBRN
ACCBRN
BNKNAME
BRNNAME
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*

BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1

BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*

ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO

- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*

TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2

COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contractdet-Full

Attribute	Description
Name	Contractdet-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERDT

Attribute	Description
Name	CHECKERDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,L</td></tr></table>

TOP

AUTSTAT

Attribute	Description

Name	AUTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

NETREALIZED

Attribute	Description
Name	NETREALIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description

Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description

Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String

Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description

Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	**Description**	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	**Description**	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	**Description**	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2

Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3

Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	**Description**	
Name	COUNTRPRYNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

AGID

Attribute	**Description**	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	**Description**	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2

Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	**Description**	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	**Description**	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	**Description**	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**	
Name	REGREP2	
Datatype	String	
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**
Name	REGREP3
Datatype	String

Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2

Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	**Description**	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	**Description**	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO2

Attribute	**Description**	
Name	SNDRRCVRINFO2	
Datatype	String	
Description	Indicates Sender Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	**Description**	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	Description	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	Description	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	Description	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	Description	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

2.41.2.RB-DeleteOutRealization-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contractdet-IO*
    - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contractdet-IO

Attribute	Description
Name	Contractdet-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.41.3.RB-DeleteOutRealization-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contractdet-Full*
    - *CONREFNUM*
    - *MAKER*
    - *MAKERDT*
    - *CHKR*
    - *CHECKERDT*
    - *CONTSTAT*
    - *AUTSTAT*
    - *CPTYIDEN*
    - *CURR*
    - *AMNT*
    - *OTHRPTYIDEN*
    - *DISCOUNTAMT*
    - *DRACCREAL*
    - *CPTYACCNUM*
    - *NETREALIZED*
    - *OTHRBNKCHARGS*
    - *COLBANKREFNUM*
    - *VALUEDT*

DUEDATE
COUNTRPRYNAM
OTHERPARTYNAME
BNKCD
BRNCODE
DRACCBRN
ACCBRN
BNKNAME
BRNNAME
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*

TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4

ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*

ENVCONT5

Lcl_Clearing

FREETXT1

FREETXT2

FREETXT3

PMNTCD

ADDINFOSORBNET

SNDRCUSTNAME1

SNDRCUSTNAME2

SNDRCUSTNAME3

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

Charges

CONREFNO

Charge-Association

COMPNT

CREATESN

RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3

TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5

COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contractdet-Full

Attribute	Description
Name	Contractdet-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDT

Attribute	Description
Name	CHECKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L

TOP

AUTSTAT

Attribute	Description
Name	AUTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

NETREALIZED

Attribute	Description
Name	NETREALIZED

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BNKNAME

Attribute	**Description**	
Name	BNKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Con

Attribute	**Description**	
Name	Con	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description	
Name	CHGREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTTYP

Attribute	Description	
Name	PARTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Settlements

Attribute	Description	
Name	Settlements	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement

Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	**Description**	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	**Description**	
Name	CLEARNW	
Datatype	String	
Description	Indicates Network Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	**Description**	
Name	COVERBY	
Datatype	String	
Description	Indicates Cover By Clearing : C Message : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	**Description**
Name	RTGSPMNT
Datatype	String

Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1

Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	**Description**	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2

Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5

Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	**Description**
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	**Description**
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	**Description**
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	**Description**
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	Description	
Name	REGREP1	
Datatype	String	
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description	
Name	REGREP2	
Datatype	String	
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1

Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRPART

Attribute	**Description**	
Name	SNDRRCVRPART	
Datatype	Number	
Description	Indicates Sender Receiver Participant	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	Description	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	Description	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	Description	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,R,1,2</td></tr></table>

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>14</td></tr></table>

TOP

PMNTTYP

Attribute	Description

Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description

Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association

Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	**Description**	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	**Description**
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	**Description**
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	**Description**
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	**Description**
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	**Description**	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS5

Attribute	**Description**	
Name	TRANMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	**Description**	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.41.4.RB-DeleteOutRealization-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contractdet-PK*
      - *CONREFNUM*
    - *Contractdet-IO*
      - *CONREFNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contractdet-PK

Attribute	Description
Name	Contractdet-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contractdet-IO

Attribute	Description
Name	Contractdet-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.42.DeleteOutwardcollection

DeleteOutwardcollection

2.42.1.RB-DeleteOutwardcollection-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNUM*
    - *BOOKDT*
    - *USERREFNUM*
    - *BRN*
    - *PRDCD*
    - *MODULE*
    - *UDS*
    - *STOPDT*
    - *VERSIONNO*
    - *EVENTSEQ*
    - *EVENTCODE*
    - *INSTRUCODE*
    - *PRODTYP*
    - *CPTYIDEN*
    - *CPTYACCNUM*

INSTRNO
INSTRU_DATE
INITCCY
OSAMT
LCYAMT
OTHRPTYIDEN
BNKCD
BRN_D
REFERENCENO
BOOKINGDT
MATDAYS
LEADDAYS
DISPATCHDT
GRACEDAYS
PROTEST
TRACKLIMIT
CREDITLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
DISCAMT
COLLATERAL
COLLVL
COLLPOOL
ACCBRN
PAYDUEDATE
DRACCBRN
INTREMARKS
INSTRUMENT_DESCRIPTION
TXTPDTDESC
CPTYNAME
OTHERPARTYNAME
BNKNAME
BRNNAME
XREF
BATCHREFENUM
BATCHSEQNO
DRACCREAL
AUTOLIQD
CONTREFLOG
MAKER
MAKDTTIME
CHKR
CHKDTTIME

EVENTLOG
CONST
AUTHSTAT
LATVERNO
DATE
Party-Details
  PARTTYP
  PARTYIDEN
  PARTYNAME
  ADDLN1
  ADDLN2
  ADDLN3
  ADDLN4
  CNTY
  PRTYLANG
Settlements
  CONREFNO
  Contract-Settlement
    IBANACNO
    CUSTSPREAD
    SPREADDEFN
    COMPNT
    TAGCCY
    ACCBRN
    ACC
    ACCCCY
    EXRATE
    NETIND
    ERICCY
    ERIAMT
    GENMSG
    RATECD
    CLEARNW
    COVERBY
    RTGSPMNT
    BANKPRIOR
    RTGSNW
    PAYBY
    TRANSTYP
    INSTYP
    INSNO
    CHGDET
    PAYMNTDET1
    PAYMNTDET2

PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2

BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*

ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP

PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3

- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*

CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
Clpref
CONTREFNNO
CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM
PAYMENT_MODE

LOANVALDATE

MATURITY_DATE

Ude

USERDEID

UDEDESC

RATEASOF

USAGE

USERDEVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USERREFNUM

Attribute	Description
Name	USERREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDS

Attribute	Description
Name	UDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSIONNO

Attribute	Description
Name	VERSIONNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

PRODTYP

Attribute	Description
Name	PRODTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INITCCY

Attribute	Description
Name	INITCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

OSAMT

Attribute	Description
Name	OSAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BRN_D

Attribute	Description
Name	BRN_D
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKINGDT

Attribute	Description
Name	BOOKINGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LEADDAYS

Attribute	Description
Name	LEADDAYS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISPATCHDT

Attribute	Description
Name	DISPATCHDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,N,F</td></tr></table>

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COLLATERAL

Attribute	**Description**	
Name	COLLATERAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,C,T,N

TOP

COLLVL

Attribute	**Description**	
Name	COLLVL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COLLPOOL

Attribute	**Description**	
Name	COLLPOOL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description
Name	INSTRUMENT_DESCRIPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

TXTPDTDESC

Attribute	Description
Name	TXTPDTDESC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTYNAME

Attribute	**Description**	
Name	CPTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYNAME

Attribute	**Description**	
Name	OTHERPARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BNKNAME

Attribute	**Description**	
Name	BNKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CONTREFLOG

Attribute	Description
Name	CONTREFLOG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EVENTLOG

Attribute	Description
Name	EVENTLOG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,H,R,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / DRAWEE,DRAWER,PAYEE,COLLECTING_BANK,

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRTYLANG

Attribute	Description
Name	PRTYLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO

Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String

Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	Description	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO5

Attribute	Description	
Name	SNDTRRCVINFO5	
Datatype	String	
Description	Indicates Sender To Receiver Information 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	Description	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4

Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1

Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5

Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	

Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	Description	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	Description	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	Description	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	**Description**	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS7

Attribute	**Description**	
Name	TRANMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS8

Attribute	**Description**	
Name	TRANMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String

Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description

Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / DRAWEE,DRAWER,PAYEE,COLLECTING_BANK,

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description

Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.42.2.RB-DeleteOutwardcollection-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.42.3.RB-DeleteOutwardcollection-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNUM*
    - *BOOKDT*
    - *USERREFNUM*
    - *BRN*
    - *PRDCD*
    - *MODULE*
    - *UDS*
    - *STOPDT*
    - *VERSIONNO*
    - *EVENTSEQ*
    - *EVENTCODE*
    - *INSTRUCODE*
    - *PRODTYP*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *INSTRNO*
    - *INSTRU_DATE*
    - *INITCCY*

OSAMT
LCYAMT
OTHRPTYIDEN
BNKCD
BRN_D
REFERENCENO
BOOKINGDT
MATDAYS
LEADDAYS
DISPATCHDT
GRACEDAYS
PROTEST
TRACKLIMIT
CREDITLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
DISCAMT
COLLATERAL
COLLVL
COLLPOOL
ACCBRN
PAYDUEDATE
DRACCBRN
INTREMARKS
INSTRUMENT_DESCRIPTION
TXTPDTDESC
CPTYNAME
OTHERPARTYNAME
BNKNAME
BRNNAME
XREF
BATCHREFENUM
BATCHSEQNO
DRACCREAL
AUTOLIQD
CONTREFLOG
MAKER
MAKDTTIME
CHKR
CHKDTTIME
EVENTLOG
CONST
AUTHSTAT

LATVERNO
DATE
Party-Details
- *PARTTYP*
- *PARTYIDEN*
- *PARTYNAME*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ADDLN4*
- *CNTY*
- *PRTYLANG*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*

SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5

COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*

SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD

COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6

- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*

TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
Clpref
CONTREFNNO
CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM
PAYMENT_MODE
LOANVALDATE
MATURITY_DATE
Ude

USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USERREFNUM

Attribute	Description
Name	USERREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

UDS

Attribute	Description
Name	UDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

STOPDT

Attribute	Description
Name	STOPDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VERSIONNO

Attribute	Description
Name	VERSIONNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRODTYP

Attribute	Description
Name	PRODTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INITCCY

Attribute	Description
Name	INITCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OSAMT

Attribute	Description
Name	OSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BRN_D

Attribute	Description
Name	BRN_D
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BOOKINGDT

Attribute	Description
Name	BOOKINGDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LEADDAYS

Attribute	Description
Name	LEADDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISPATCHDT

Attribute	Description
Name	DISPATCHDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CREDITLINE

Attribute	**Description**	
Name	CREDITLINE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

OTHPARTYLIMIT

Attribute	**Description**	
Name	OTHPARTYLIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MARGINPERC

Attribute	**Description**	
Name	MARGINPERC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,N,F

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLVL

Attribute	Description
Name	COLLVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PAYDUEDATE

Attribute	**Description**	
Name	PAYDUEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DRACCBRN

Attribute	**Description**	
Name	DRACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INTREMARKS

Attribute	**Description**	
Name	INTREMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INSTRUMENT_DESCRIPTION

Attribute	**Description**	
Name	INSTRUMENT_DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

TXTPDTDESC

Attribute	Description
Name	TXTPDTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONTREFLOG

Attribute	Description
Name	CONTREFLOG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVENTLOG

Attribute	Description
Name	EVENTLOG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,H,R,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / DRAWEE,DRAWER,PAYEE,COLLECTING_BANK,

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN3

Attribute	Description	
Name	ADDLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDLN4

Attribute	Description	
Name	ADDLN4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CNTY

Attribute	Description	
Name	CNTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRTYLANG

Attribute	Description	
Name	PRTYLANG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	**Description**
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	**Description**
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	**Description**
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	**Description**
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	**Description**
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	**Description**
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	**Description**
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	**Description**
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS10

Attribute	**Description**	
Name	FUNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Txnmisdetails

Attribute	**Description**	
Name	Txnmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Compmisdetails

Attribute	**Description**	
Name	Compmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Fundmisdetails

Attribute	**Description**	
Name	Fundmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number

Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY

Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description	
Name	PARTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	DRAWEE,DRAWER,PAYEE,COLLECTING_BANK,

TOP

Clpref

Attribute	Description	
Name	Clpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNNO

Attribute	Description	
Name	CONTREFNNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CONTRACT_CCY

Attribute	Description	
Name	CONTRACT_CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LATEVNSEQNO

Attribute	Description

Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

RATEASOF

Attribute	Description	
Name	RATEASOF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

USAGE

Attribute	Description	
Name	USAGE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

USERDEVAL

Attribute	Description	
Name	USERDEVAL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.42.4.RB-DeleteOutwardcollection-Res-PK-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
CHOICE
Contract-Details-PK
CONREFNUM
Contract-Details-IO
CONREFNUM
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.43.DeleteOverseasfinance

DeleteOverseasfinance

2.43.1.RB-DeleteOverseasfinance-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *INSTRNO*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *BOOKINGDATE*
    - *OTHR_PARTY_NAME*
    - *DRAWEE_BNK_NAME*
    - *FINANCING*
    - *MARGINPERCENT*
    - *TRACK_LIMIT*
    - *CREDIT_LINE*
    - *DISCOUNT_AMOUNT*

MAKER
MAKERDTSTAMP
CHECKER
CHECKERSTAMP
RECORD_STAT
AUTHSTAT
PAYDUEDATE
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*

INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2

ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER

- *DISACCRAPPL*
- *ACCRREQD*
- *DESC*

Charge-Application

- *CREATESN*
- *COMPNT*
- *TGCCY*
- *TGAMT*
- *CHRGCCY*
- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*

Charge-Liquidation

- *ESN*
- *COMPNT*
- *CHRGCCY*
- *CHRGAMT*
- *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*

TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7

- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Clpref

- *CONTREFNNO*
- *CONTRACT_CCY*
- *LATEVNSEQNO*
- *PRD*
- *PRDDESC*
- *COUNTERPARTY*
- *CURRENCY*
- *TENOR*
- *UNITS*
- *LOAN_CONREFNO*
- *RATECODE*
- *EXCHANGERATE*
- *RATE_TYPE*
- *MAXIMUM*
- *MINIMUM*
- *PAYMENT_MODE*
- *LOANVALDATE*
- *MATURITY_DATE*
- *Ude*
  - *USERDEID*
  - *UDEDESC*
  - *RATEASOF*
  - *USAGE*
  - *USERDEVAL*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	Description	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_NAME

Attribute	Description	
Name	CPTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INSTRNO

Attribute	Description	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,A,H,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr></table>

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Settlement

Attribute	**Description**	
Name	Contract-Settlement	
Datatype		
Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	**Description**	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description

Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	**Description**	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	**Description**	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	**Description**	
Name	CLEARNW	
Datatype	String	
Description	Indicates Network Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	**Description**
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates RTGS Payment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	**Description**	
Name	BANKPRIOR	
Datatype	String	
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1

Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC

Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	**Description**	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1

Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String

Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description

Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	**Description**	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	**Description**	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	**Description**	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PMNTTYP

Attribute	Description	
Name	PMNTTYP	
Datatype	String	
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	Description	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	Description	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description

Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY

Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	**Description**	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS6

Attribute	**Description**	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	**Description**	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.43.2.RB-DeleteOverseasfinance-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.43.3.RB-DeleteOverseasfinance-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *INSTRNO*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *BOOKINGDATE*
    - *OTHR_PARTY_NAME*
    - *DRAWEE_BNK_NAME*
    - *FINANCING*
    - *MARGINPERCENT*
    - *TRACK_LIMIT*
    - *CREDIT_LINE*
    - *DISCOUNT_AMOUNT*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHECKER*

CHECKERSTAMP
RECORD_STAT
AUTHSTAT
PAYDUEDATE
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*

PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1

BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*

PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC

- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*

TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10

FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
Clpref
CONTREFNNO
CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM
PAYMENT_MODE
LOANVALDATE
MATURITY_DATE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description

Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,A,H,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SUPRESS

Attribute	**Description**	
Name	SUPRESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number

Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String

Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	Description	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	Description	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description

Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	**Description**	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	**Description**	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1

Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5

Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	**Description**	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	**Description**	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description

Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	**Description**	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS2

Attribute	**Description**	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description

Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.43.4.RB-DeleteOverseasfinance-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONREFNUM*
    - *Main-IO*
      - *CONREFNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.44.DeleteOverseaspdr

DeleteOverseaspdr

2.44.1.RB-DeleteOverseaspdr-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *INSTRUMENTNORE*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *OTHER_BANK_CHARGES*
    - *BNK_CODE*

REMRKS
BANK_NAME
DISHONORDATE
NOTARY_DESCRIPTION
BOOKING_DATE
DISCOUNT_AMOUNT
REASON_CODE
REASON
PROTESTDATE
RETURN_DATE
OTHR_PARTY_NAME
DRAWEE_BNK_NAME
Charges
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*

COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3

INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
  INSTRCD1

INSTRCD2
INSTRCD3
INSTRCD4
ITIMEIND1
ITIMEIND2
ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID

SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1

COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4

FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	Description	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CTR_PRTY_NAME

Attribute	Description
Name	CTR_PRTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRUMENTNORE

Attribute	Description
Name	INSTRUMENTNORE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,A,H,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BNK_CODE

Attribute	Description
Name	BNK_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REMRKS

Attribute	Description
Name	REMRKS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BANK_NAME

Attribute	Description
Name	BANK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DISHONORDATE

Attribute	Description
Name	DISHONORDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTARY_DESCRIPTION

Attribute	Description
Name	NOTARY_DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BOOKING_DATE

Attribute	Description
Name	BOOKING_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REASON

Attribute	Description
Name	REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHR_PARTY_NAME

Attribute	**Description**	
Name	OTHR_PARTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRAWEE_BNK_NAME

Attribute	**Description**	
Name	DRAWEE_BNK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**
Name	Charge-Application
Datatype	
Description	Includes Charge Application details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	**Description**	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**

Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String

Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	**Description**	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	Description	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	Description	
Name	CLEARNW	
Datatype	String	
Description	Indicates Network Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	Description	
Name	COVERBY	
Datatype	String	
Description	Indicates Cover By Clearing : C Message : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	**Description**	
Name	BANKPRIOR	
Datatype	String	
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	Description	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	**Description**	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	**Description**	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	**Description**	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	**Description**
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	**Description**
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	**Description**
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	**Description**
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	Description	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	Description	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	**Description**	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS5

Attribute	**Description**	
Name	TRANMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	**Description**	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	Description	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	Description	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	Description	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

2.44.2.RB-DeleteOverseaspdr-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.44.3.RB-DeleteOverseaspdr-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *INSTRUMENTNORE*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *OTHER_BANK_CHARGES*
    - *BNK_CODE*
    - *REMRKS*
    - *BANK_NAME*
    - *DISHONORDATE*

NOTARY_DESCRIPTION
BOOKING_DATE
DISCOUNT_AMOUNT
REASON_CODE
REASON
PROTESTDATE
RETURN_DATE
OTHR_PARTY_NAME
DRAWEE_BNK_NAME
Charges
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*

ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2

ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*

ITIMEIND1
ITIMEIND2
ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3

SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3

COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7

FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CTR_PRTY_NAME

Attribute	Description
Name	CTR_PRTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRUMENTNORE

Attribute	Description
Name	INSTRUMENTNORE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>L,A,H,</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,U,</td></tr></table>

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BNK_CODE

Attribute	Description
Name	BNK_CODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REMRKS

Attribute	**Description**	
Name	REMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BANK_NAME

Attribute	**Description**	
Name	BANK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DISHONORDATE

Attribute	**Description**	
Name	DISHONORDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NOTARY_DESCRIPTION

Attribute	**Description**	
Name	NOTARY_DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BOOKING_DATE

Attribute	Description
Name	BOOKING_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REASON

Attribute	Description
Name	REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RETURN_DATE

Attribute	**Description**	
Name	RETURN_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHR_PARTY_NAME

Attribute	**Description**	
Name	OTHR_PARTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRAWEE_BNK_NAME

Attribute	**Description**	
Name	DRAWEE_BNK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description

Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	**Description**	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1

Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	**Description**
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	**Description**
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	**Description**
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	**Description**
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC

Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1

Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String

Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description

Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	**Description**	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	**Description**	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	**Description**	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	Description	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	Description	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	**Description**
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	**Description**
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	**Description**
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	**Description**
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	**Description**	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS2

Attribute	**Description**	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
enumeration	Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	15

TOP

PARTYIDEN

Attribute	Description	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	Description	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CHGREQ

Attribute	Description	
Name	CHGREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTTYP

Attribute	Description	
Name	PARTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *CHOICE*
  - *Main-PK*
    - *CONREFNUM*
  - *Main-IO*
    - *CONREFNUM*
- *FCUBS_ERROR_RESP*
  - *ERROR*
    - *ECODE*
    - *EDESC*
- *FCUBS_WARNING_RESP*
  - *WARNING*
    - *WCODE*
    - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.45.DeleteOvsbulkcontract

DeleteOvsbulkcontract

2.45.1.RB-DeleteOvsbulkcontract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Overseas-Full*
    - *INSTRUMENT_CODE*
    - *INSTR_DESC*
    - *PRODCD*
    - *PRDDESC*
    - *CURRENCY*
    - *COLLECTINGBANKCIF*
    - *CBN_S*
    - *DB_ACC_REAL*
    - *ACCBRN*
    - *BOKNGDT*
    - *PAYDUEDATE*
    - *TRANSITDAYS*
    - *BATCHREFENUM*
    - *COLLBANKCODE*
    - *NOOFINSTRUMENTS*

STAT
ESN_NO
RECORD_STAT
AUTHSTAT
CHKR
CHKDTTIME
MAKER
MAKDTTIME
EVENTSEQNO
Bulk-Input-Overseas-Dtl
- *CONTRACTREFNO*
- *CPTY_ID*
- *CPTY_AC_NO*
- *ACCBRNRE*
- *INSTRNO*
- *INSTRU_DATE*
- *AMNT*
- *LCY_AMT*
- *OTHR_PARTYNAME*
- *DRAWEE_BNK_NAME*
- *AUTOLIQD*
- *FINANCING*
- *MARGIN_PERCENTAGE*
- *TRACK_LIMIT*
- *CREDIT_LINE*
- *DISCAMT*
- *CPTY_NAME*
- *INTREMRKS*
- *BATCHREFNO*
- *BATCHSEQNO*
- *CONTRACTCCY*
- *PROCESS_STATUS*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Overseas-Full

Attribute	Description
Name	Bulk-Input-Overseas-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRODCD

Attribute	Description
Name	PRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLECTINGBANKCIF

Attribute	Description
Name	COLLECTINGBANKCIF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CBN_S

Attribute	**Description**	
Name	CBN_S	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

DB_ACC_REAL

Attribute	**Description**	
Name	DB_ACC_REAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BOKNGDT

Attribute	**Description**	
Name	BOKNGDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 1

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

COLLBANKCODE

Attribute	Description
Name	COLLBANKCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,U,

TOP

ESN_NO

Attribute	Description
Name	ESN_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,C,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bulk-Input-Overseas-Dtl

Attribute	Description
Name	Bulk-Input-Overseas-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCBRNRE

Attribute	Description
Name	ACCBRNRE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHR_PARTYNAME

Attribute	**Description**	
Name	OTHR_PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRAWEE_BNK_NAME

Attribute	**Description**	
Name	DRAWEE_BNK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AUTOLIQD

Attribute	**Description**	
Name	AUTOLIQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,N,F,

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INTREMRKS

Attribute	**Description**	
Name	INTREMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BATCHREFNO

Attribute	**Description**	
Name	BATCHREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BATCHSEQNO

Attribute	**Description**	
Name	BATCHSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTRACTCCY

Attribute	**Description**	
Name	CONTRACTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,H,F,</td></tr></table>

TOP

2.45.2.RB-DeleteOvsbulkcontract-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Bulk-Input-Overseas-IO
BATCHREFENUM

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Overseas-IO

Attribute	Description
Name	Bulk-Input-Overseas-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.45.3.RB-DeleteOvsbulkcontract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Overseas-Full*
    - *INSTRUMENT_CODE*
    - *INSTR_DESC*
    - *PRODCD*
    - *PRDDESC*
    - *CURRENCY*
    - *COLLECTINGBANKCIF*
    - *CBN_S*
    - *DB_ACC_REAL*
    - *ACCBRN*
    - *BOKNGDT*
    - *PAYDUEDATE*
    - *TRANSITDAYS*
    - *BATCHREFENUM*
    - *COLLBANKCODE*
    - *NOOFINSTRUMENTS*
    - *STAT*
    - *ESN_NO*
    - *RECORD_STAT*

AUTHSTAT
CHKR
CHKDTTIME
MAKER
MAKDTTIME
EVENTSEQNO
Bulk-Input-Overseas-Dtl
CONTRACTREFNO
CPTY_ID
CPTY_AC_NO
ACCBRNRE
INSTRNO
INSTRU_DATE
AMNT
LCY_AMT
OTHR_PARTYNAME
DRAWEE_BNK_NAME
AUTOLIQD
FINANCING
MARGIN_PERCENTAGE
TRACK_LIMIT
CREDIT_LINE
DISCAMT
CPTY_NAME
INTREMRKS
BATCHREFNO
BATCHSEQNO
CONTRACTCCY
PROCESS_STATUS
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Overseas-Full

Attribute	Description
Name	Bulk-Input-Overseas-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRODCD

Attribute	Description
Name	PRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

COLLECTINGBANKCIF

Attribute	Description	
Name	COLLECTINGBANKCIF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CBN_S

Attribute	Description	
Name	CBN_S	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

DB_ACC_REAL

Attribute	Description	
Name	DB_ACC_REAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COLLBANKCODE

Attribute	Description
Name	COLLBANKCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,U,

TOP

ESN_NO

Attribute	Description
Name	ESN_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,C,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

EVENTSEQNO

Attribute	**Description**	
Name	EVENTSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Bulk-Input-Overseas-Dtl

Attribute	**Description**	
Name	Bulk-Input-Overseas-Dtl	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

CONTRACTREFNO

Attribute	**Description**	
Name	CONTRACTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	**Description**	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRNRE

Attribute	Description
Name	ACCBRNRE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,N,F,</td></tr></table>

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BATCHREFNO

Attribute	Description
Name	BATCHREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,H,F,

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Input-Overseas-PK*
      - *BATCHREFENUM*
    - *Bulk-Input-Overseas-IO*
      - *BATCHREFENUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Input-Overseas-PK

Attribute	Description
Name	Bulk-Input-Overseas-PK
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Input-Overseas-IO

Attribute	Description
Name	Bulk-Input-Overseas-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.46.DeleteOvsbulkrealize

DeleteOvsbulkrealize

2.46.1.RB-DeleteOvsbulkrealize-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Liqd-Overseas-Full*
    - *BATCHREFENUM*
    - *BULK_REAL_NUM*
    - *CURRENCY*
    - *DB_ACC_REAL*
    - *ACCBRN*
    - *COLBANK_REFNO*
    - *COLL_BNK_CIF*
    - *COLLBNKNAME*
    - *VALUEDATE*
    - *PROCSTAT*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *CHKR*
    - *CHKDTTIME*
    - *ESN_NO*

MAKER
MAKDTTIME
EVENTSEQNO
Bulk-Liqd-Overseas-Dtl
CONTRACTREFNO
CPTY_ID
CPTY_NAME
CPTY_AC_NO
ACCBRNRE
INSTRNO
INSTRU_DATE
AMNT
NET_AMT_REALISED
OTHER_BANK_CHARGES
INTREMRKS
PROCESSSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Liqd-Overseas-Full

Attribute	Description
Name	Bulk-Liqd-Overseas-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BULK_REAL_NUM

Attribute	Description
Name	BULK_REAL_NUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLBANK_REFNO

Attribute	Description
Name	COLBANK_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

PROCSTAT

Attribute	Description
Name	PROCSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,U,</td></tr></table>

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>O,C,</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U,

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ESN_NO

Attribute	**Description**	
Name	ESN_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

Bulk-Liqd-Overseas-Dtl

Attribute	Description
Name	Bulk-Liqd-Overseas-Dtl
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRNRE

Attribute	Description
Name	ACCBRNRE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,H,F,</td></tr></table>

TOP

2.46.2.RB-DeleteOvsbulkrealize-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Bulk-Liqd-Overseas-IO
BULK_REAL_NUM

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Liqd-Overseas-IO

Attribute	Description
Name	Bulk-Liqd-Overseas-IO
Datatype	
Description	

TOP

BULK_REAL_NUM

Attribute	Description
Name	BULK_REAL_NUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.46.3.RB-DeleteOvsbulkrealize-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Liqd-Overseas-Full*
    - *BATCHREFENUM*
    - *BULK_REAL_NUM*
    - *CURRENCY*
    - *DB_ACC_REAL*
    - *ACCBRN*
    - *COLBANK_REFNO*
    - *COLL_BNK_CIF*
    - *COLLBNKNAME*
    - *VALUEDATE*
    - *PROCSTAT*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *CHKR*
    - *CHKDTTIME*
    - *ESN_NO*
    - *MAKER*
    - *MAKDTTIME*
    - *EVENTSEQNO*

Bulk-Liqd-Overseas-Dtl

CONTRACTREFNO

CPTY_ID

CPTY_NAME

CPTY_AC_NO

ACCBRNRE

INSTRNO

INSTRU_DATE

AMNT

NET_AMT_REALISED

OTHER_BANK_CHARGES

INTREMRKS

PROCESSSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Liqd-Overseas-Full

Attribute	Description
Name	Bulk-Liqd-Overseas-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BULK_REAL_NUM

Attribute	Description
Name	BULK_REAL_NUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CURRENCY

Attribute	Description

Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLBANK_REFNO

Attribute	Description
Name	COLBANK_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

COLLBNKNAME

Attribute	**Description**	
Name	COLLBNKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

VALUEDATE

Attribute	**Description**	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

PROCSTAT

Attribute	**Description**	
Name	PROCSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,U,

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,C,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ESN_NO

Attribute	Description
Name	ESN_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bulk-Liqd-Overseas-Dtl

Attribute	Description
Name	Bulk-Liqd-Overseas-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY_ID

Attribute	Description	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_NAME

Attribute	Description	
Name	CPTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTY_AC_NO

Attribute	Description	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCBRNRE

Attribute	Description	
Name	ACCBRNRE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,H,F,

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *CHOICE*
  - *Bulk-Liqd-Overseas-PK*
    - *BULK_REAL_NUM*
  - *Bulk-Liqd-Overseas-IO*
    - *BULK_REAL_NUM*
- *FCUBS_ERROR_RESP*
  - *ERROR*
    - *ECODE*
    - *EDESC*
- *FCUBS_WARNING_RESP*
  - *WARNING*
    - *WCODE*
    - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Liqd-Overseas-PK

Attribute	Description
Name	Bulk-Liqd-Overseas-PK
Datatype	
Description	

TOP

BULK_REAL_NUM

Attribute	Description
Name	BULK_REAL_NUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Liqd-Overseas-IO

Attribute	Description
Name	Bulk-Liqd-Overseas-IO
Datatype	
Description	

TOP

BULK_REAL_NUM

Attribute	Description
Name	BULK_REAL_NUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.47.DeleteOvscheckspay

DeleteOvscheckspay

2.47.1.RB-DeleteOvscheckspay-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONTREFNO*
    - *LATESTVERSIONNO*
    - *RECORD_STAT*
    - *AUTHSTATUS*
    - *CURR_EVENT_CODE*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHKR*
    - *CHKDTTIME*
    - *EVENT_SEQ_NO*
    - *CONT_STAT*
    - *AUTH_STAT*
    - *CPTY_ID*
    - *CPTY_AC_NO*
    - *INSTRNO*

INSTRUMENT_DATE
CURRENCY
AMNT
NET_AMT_REALISED
OTHER_BANK_CHARGES
COLL_BNK_CIF
BOOKINGDATE
MATURITY_DATE
VALUE_DATE
TRACK_LIMIT
CREDIT_LINE
FINANCING
INT_REM
INSTRUMENT_CODE
INSTR_DESC
PRCD
PRODDESC
USERREF_NO
XREF
COUNTRPRYNAM
LCY_AMT
COLLBANKNAME
PAYDUEDATE
CONREF
EVENTSEQ
PARTYTYP
ADDRESS
PARTYADDR2
PARTYADDR3
PARTYADDR4
WALKINCUSTFLG
COLLEC_BANK_CIF
COLLBNKNAME
DISCOUNT_AMOUNT
DB_ACC_REAL
BULK_INPUT_REF_NO
DRAWEE_BNK_NAME
AUTOLIQD
OTHER_PARTY_ID
VERSION_NO
TRANSITDAYS
MARGIN_PERCENTAGE
ACC_BRANCH
OTHR_PARTY_NAME

ACCBRN

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*

COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6

- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*

CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2

ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*

REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4

RCVRACC

Clpref

CONTREFNNO

CONTRACT_CCY

LATEVNSEQNO

PRD

PRDDESC

COUNTERPARTY

CURRENCY

TENOR

UNITS

LOAN_CONREFNO

RATECODE

EXCHANGERATE

RATE_TYPE

MAXIMUM

MINIMUM

PAYMENT_MODE

LOANVALDATE

MATURITY_DATE

Ude

USERDEID

UDEDESC

RATEASOF

USAGE

USERDEVAL

Con

CONTREFNO

EVENTSEQ

Adv

ADVNAME

SUPRESS

PRIOR

MEDM

PARTYIDEN

PARTYNAME

CHGREQ

PARTTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESTVERSIONNO

Attribute	**Description**	
Name	LATESTVERSIONNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTATUS

Attribute	**Description**	
Name	AUTHSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CURR_EVENT_CODE

Attribute	**Description**	
Name	CURR_EVENT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONT_STAT

Attribute	Description
Name	CONT_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,L,R,H,</td></tr></table>

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,U,</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRNO

Attribute	**Description**	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRUMENT_DATE

Attribute	**Description**	
Name	INSTRUMENT_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

CURRENCY

Attribute	**Description**	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNT

Attribute	**Description**	
Name	AMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,N,F</td></tr></table>

TOP

INT_REM

Attribute	Description
Name	INT_REM
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLBANKNAME

Attribute	Description
Name	COLLBANKNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREF

Attribute	Description
Name	CONREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

ADDRESS

Attribute	Description	
Name	ADDRESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PARTYADDR2

Attribute	Description	
Name	PARTYADDR2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PARTYADDR3

Attribute	Description	
Name	PARTYADDR3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PARTYADDR4

Attribute	Description	
Name	PARTYADDR4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

WALKINCUSTFLG

Attribute	Description
Name	WALKINCUSTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COLLEC_BANK_CIF

Attribute	Description
Name	COLLEC_BANK_CIF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BULK_INPUT_REF_NO

Attribute	Description
Name	BULK_INPUT_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OTHER_PARTY_ID

Attribute	Description
Name	OTHER_PARTY_ID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

VERSION_NO

Attribute	Description	
Name	VERSION_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRANSITDAYS

Attribute	Description	
Name	TRANSITDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MARGIN_PERCENTAGE

Attribute	Description	
Name	MARGIN_PERCENTAGE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACC_BRANCH

Attribute	Description	
Name	ACC_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs: 1
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs: 1
Restrictions	**Restrictions** / **Description** maxLength: 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD

Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	**Description**	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	**Description**
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	**Description**
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	**Description**
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	**Description**
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	Description	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	Description	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	Description	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	Description	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	Description	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	**Description**
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	**Description**
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	**Description**
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	**Description**
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	**Description**
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	**Description**
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Con

Attribute	**Description**
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	**Description**
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CHGREQ

Attribute	**Description**	
Name	CHGREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.47.2.RB-DeleteOvscheckspay-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONTREFNO*
    - *CPTY_AC_NO*
    - *NET_AMT_REALISED*
    - *COLL_BNK_CIF*
    - *BOOKINGDATE*
    - *TRACK_LIMIT*
    - *CREDIT_LINE*
    - *FINANCING*
    - *INT_REM*
    - *COUNTRPRYNAM*
    - *LCY_AMT*
    - *COLLBANKNAME*
    - *PAYDUEDATE*
    - *ADDRESS*
    - *PARTYADDR2*
    - *PARTYADDR3*
    - *PARTYADDR4*
    - *COLLEC_BANK_CIF*

COLLBNKNAME
DISCOUNT_AMOUNT
DRAWEE_BNK_NAME
AUTOLIQD
OTHER_PARTY_ID

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description

Name	Main-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,N,F

TOP

INT_REM

Attribute	Description
Name	INT_REM
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLBANKNAME

Attribute	Description
Name	COLLBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDRESS

Attribute	Description
Name	ADDRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTYADDR2

Attribute	Description
Name	PARTYADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTYADDR3

Attribute	Description
Name	PARTYADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTYADDR4

Attribute	Description
Name	PARTYADDR4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COLLEC_BANK_CIF

Attribute	Description

Name	COLLEC_BANK_CIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

OTHER_PARTY_ID

Attribute	Description
Name	OTHER_PARTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

2.47.3.RB-DeleteOvscheckspay-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONTREFNO*
    - *LATESTVERSIONNO*
    - *RECORD_STAT*
    - *AUTHSTATUS*
    - *CURR_EVENT_CODE*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHKR*
    - *CHKDTTIME*
    - *EVENT_SEQ_NO*
    - *CONT_STAT*
    - *AUTH_STAT*
    - *CPTY_ID*
    - *CPTY_AC_NO*
    - *INSTRNO*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*

NET_AMT_REALISED
OTHER_BANK_CHARGES
COLL_BNK_CIF
BOOKINGDATE
MATURITY_DATE
VALUE_DATE
TRACK_LIMIT
CREDIT_LINE
FINANCING
INT_REM
INSTRUMENT_CODE
INSTR_DESC
PRCD
PRODDESC
USERREF_NO
XREF
COUNTRPRYNAM
LCY_AMT
COLLBANKNAME
PAYDUEDATE
CONREF
EVENTSEQ
PARTYTYP
ADDRESS
PARTYADDR2
PARTYADDR3
PARTYADDR4
WALKINCUSTFLG
COLLEC_BANK_CIF
COLLBNKNAME
DISCOUNT_AMOUNT
DB_ACC_REAL
BULK_INPUT_REF_NO
DRAWEE_BNK_NAME
AUTOLIQD
OTHER_PARTY_ID
VERSION_NO
TRANSITDAYS
MARGIN_PERCENTAGE
ACC_BRANCH
OTHR_PARTY_NAME
ACCBRN
TXNUDFDETAILS
  FLDNAME

- *FLDVAL*
- *Charges*
  - *CONREFNO*
  - *Charge-Association*
    - *COMPNT*
    - *CREATESN*
    - *RULE*
    - *WAIVER*
    - *DISACCRAPPL*
    - *ACCRREQD*
    - *DESC*
  - *Charge-Application*
    - *CREATESN*
    - *COMPNT*
    - *TGCCY*
    - *TGAMT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *DISACCRAPPL*
    - *WAIVER*
    - *LIQDIND*
  - *Charge-Liquidation*
    - *ESN*
    - *COMPNT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *LIQDSTAT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*

COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9

- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*

BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1

BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*

ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Clpref
CONTREFNNO

CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM
PAYMENT_MODE
LOANVALDATE
MATURITY_DATE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESTVERSIONNO

Attribute	Description
Name	LATESTVERSIONNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTATUS

Attribute	Description
Name	AUTHSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CURR_EVENT_CODE

Attribute	Description
Name	CURR_EVENT_CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONT_STAT

Attribute	**Description**	
Name	CONT_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,L,R,H,

TOP

AUTH_STAT

Attribute	**Description**	
Name	AUTH_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U,

TOP

CPTY_ID

Attribute	**Description**	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

INT_REM

Attribute	Description	
Name	INT_REM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INSTRUMENT_CODE

Attribute	Description	
Name	INSTRUMENT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTR_DESC

Attribute	Description	
Name	INSTR_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRCD

Attribute	Description	
Name	PRCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLBANKNAME

Attribute	Description
Name	COLLBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREF

Attribute	Description
Name	CONREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

ADDRESS

Attribute	Description
Name	ADDRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTYADDR2

Attribute	Description
Name	PARTYADDR2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTYADDR3

Attribute	Description
Name	PARTYADDR3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTYADDR4

Attribute	Description
Name	PARTYADDR4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINCUSTFLG

Attribute	Description
Name	WALKINCUSTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COLLEC_BANK_CIF

Attribute	Description
Name	COLLEC_BANK_CIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DB_ACC_REAL

Attribute	**Description**	
Name	DB_ACC_REAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BULK_INPUT_REF_NO

Attribute	**Description**	
Name	BULK_INPUT_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DRAWEE_BNK_NAME

Attribute	**Description**	
Name	DRAWEE_BNK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AUTOLIQD

Attribute	**Description**	
Name	AUTOLIQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

OTHER_PARTY_ID

Attribute	Description
Name	OTHER_PARTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACC_BRANCH

Attribute	Description
Name	ACC_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Clpref

Attribute	**Description**	
Name	Clpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNNO

Attribute	**Description**	
Name	CONTREFNNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CONTRACT_CCY

Attribute	**Description**	
Name	CONTRACT_CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TENOR

Attribute	Description
Name	TENOR

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description

Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.47.4.RB-DeleteOvscheckspay-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONTREFNO*
    - *Main-IO*
      - *CONTREFNO*
      - *CPTY_AC_NO*
      - *NET_AMT_REALISED*
      - *COLL_BNK_CIF*
      - *BOOKINGDATE*
      - *TRACK_LIMIT*
      - *CREDIT_LINE*
      - *FINANCING*
      - *INT_REM*
      - *COUNTRPRYNAM*
      - *LCY_AMT*
      - *COLLBANKNAME*
      - *PAYDUEDATE*
      - *ADDRESS*
      - *PARTYADDR2*

PARTYADDR3
PARTYADDR4
COLLEC_BANK_CIF
COLLBNKNAME
DISCOUNT_AMOUNT
DRAWEE_BNK_NAME
AUTOLIQD
OTHER_PARTY_ID
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_AC_NO

Attribute	**Description**	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

NET_AMT_REALISED

Attribute	**Description**	
Name	NET_AMT_REALISED	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COLL_BNK_CIF

Attribute	**Description**	
Name	COLL_BNK_CIF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BOOKINGDATE

Attribute	**Description**	
Name	BOOKINGDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,N,F</td></tr></table>

TOP

INT_REM

Attribute	Description
Name	INT_REM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLBANKNAME

Attribute	Description
Name	COLLBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDRESS

Attribute	Description
Name	ADDRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTYADDR2

Attribute	Description
Name	PARTYADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYADDR3

Attribute	Description
Name	PARTYADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYADDR4

Attribute	Description
Name	PARTYADDR4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COLLEC_BANK_CIF

Attribute	Description
Name	COLLEC_BANK_CIF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

OTHER_PARTY_ID

Attribute	Description
Name	OTHER_PARTY_ID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.48.DeleteOvsrealizecontract

DeleteOvsrealizecontract

2.48.1.RB-DeleteOvsrealizecontract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *INSTRNO*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *CPTY_AC_NO*
    - *NET_AMT_REALISED*

OTHER_BANK_CHARGES
COLL_BNK_CIF
COLBANK_REFNO
VALUE_DATE
REMARKS
DB_ACC_REAL
COLL_BNK_NAME
ACCBRN
ACC_BRANCH
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*

TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4

ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*

ENVCONT5

Lcl_Clearing

FREETXT1

FREETXT2

FREETXT3

PMNTCD

ADDINFOSORBNET

SNDRCUSTNAME1

SNDRCUSTNAME2

SNDRCUSTNAME3

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

Charges

CONREFNO

Charge-Association

COMPNT

CREATESN

- *RULE*
- *WAIVER*
- *DISACCRAPPL*
- *ACCRREQD*
- *DESC*

Charge-Application

- *CREATESN*
- *COMPNT*
- *TGCCY*
- *TGAMT*
- *CHRGCCY*
- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*

Charge-Liquidation

- *ESN*
- *COMPNT*
- *CHRGCCY*
- *CHRGAMT*
- *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*

TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5

COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	Description	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CTR_PRTY_NAME

Attribute	Description

Name	CTR_PRTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>L,A,H,</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,U,</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COLL_BNK_CIF

Attribute	**Description**	
Name	COLL_BNK_CIF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

COLBANK_REFNO

Attribute	**Description**	
Name	COLBANK_REFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VALUE_DATE

Attribute	**Description**	
Name	VALUE_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACC_BRANCH

Attribute	Description
Name	ACC_BRANCH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Con

Attribute	Description
Name	Con

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1

Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2

Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5

Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1

Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	**Description**	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	**Description**	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application

Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	**Description**	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	Description	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	Description	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS2

Attribute	Description	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs — unbounded minOccurs — 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs — unbounded minOccurs — 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs — unbounded minOccurs — 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs — unbounded minOccurs — 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength — 105 minLength — 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL

Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.48.2.RB-DeleteOvsrealizecontract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.48.3.RB-DeleteOvsrealizecontract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *INSTRNO*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *CPTY_AC_NO*
    - *NET_AMT_REALISED*
    - *OTHER_BANK_CHARGES*
    - *COLL_BNK_CIF*
    - *COLBANK_REFNO*

VALUE_DATE
REMARKS
DB_ACC_REAL
COLL_BNK_NAME
ACCBRN
ACC_BRANCH
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*

CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3

ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*

FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL

ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6

TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8

COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CTR_PRTY_NAME

Attribute	Description	
Name	CTR_PRTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INSTRNO

Attribute	Description	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRUMENT_DATE

Attribute	Description	
Name	INSTRUMENT_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNT

Attribute	Description
Name	AMNT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,A,H,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

COLBANK_REFNO

Attribute	Description
Name	COLBANK_REFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC_BRANCH

Attribute	Description
Name	ACC_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SUPRESS

Attribute	Description	
Name	SUPRESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	Description	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	Description	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	Description	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number

Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String

Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	Description	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	Description	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description

Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1

Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5

Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	**Description**
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	**Description**
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	**Description**
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	**Description**
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description

Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONREFNUM*
    - *Main-IO*
      - *CONREFNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.49.DeletePDCContract

DeletePDCContract

2.49.1.RB-DeletePDCContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNUM*
    - *BOOKDT*
    - *USERREFNUM*
    - *XREF*
    - *PRDCD*
    - *MODCOD*
    - *UDSTAT*
    - *STOPDT*
    - *EVENTCD*
    - *INSTRUCODE*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *INSTRNO*
    - *INSTRDATE*
    - *CONTCCY*

AMOUNT
LCYAMT
OTHRPTYIDEN
BOOKINGDT
ACTDATE
VALUEDT
TRACKLIMIT
CRDLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
DISCOUNTAMT
COLLATERAL
COLLATVAL
COLLPOOL
ISRBNK
ISSUERBRN
CLGBANK
CLGBRN
SECTORCD
ENDPNT
INTREMARKS
ACCBRN
ROUTNO
DRACCBRN
INSTR_DESC
PRDDESC
CPTYNAME
OTHERPARTYNAME
ISSBANKNAME
ISSBRNCNAME
CLEARBANKNAME
AUTOLIQD
CLEARBRNCNAME
MAKER
MAKDTTIME
CHKR
CHKDTTIME
CONST
AUTHSTAT
BATCHREFENUM
BATCHSEQNO
DRACCREAL
CLGPRD

- *Party-Details*
  - *PRTYTYP*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *PARTYREFNO*
  - *COUNTRYCD*
  - *ADDLN1*
  - *ADDLN2*
  - *ADDLN3*
  - *ADDLN4*
  - *PARTLANG*
- *Settlements*
  - *CONREFNO*
  - *Contract-Settlement*
    - *IBANACNO*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *COMPNT*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *ACCCCY*
    - *EXRATE*
    - *NETIND*
    - *ERICCY*
    - *ERIAMT*
    - *GENMSG*
    - *RATECD*
    - *CLEARNW*
    - *COVERBY*
    - *RTGSPMNT*
    - *BANKPRIOR*
    - *RTGSNW*
    - *PAYBY*
    - *TRANSTYP*
    - *INSTYP*
    - *INSNO*
    - *CHGDET*
    - *PAYMNTDET1*
    - *PAYMNTDET2*
    - *PAYMNTDET3*
    - *PAYMNTDET4*
    - *SNDTRRCVINFO1*
    - *SNDTRRCVINFO2*

SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC

COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*

SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT

CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10

COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5

- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Con

- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Clpref

- *CONTREFNNO*
- *CONTRACT_CCY*
- *LATEVNSEQNO*
- *PRD*
- *PRDDESC*
- *COUNTERPARTY*
- *CURRENCY*
- *TENOR*
- *UNITS*
- *LOAN_CONREFNO*
- *RATECODE*
- *EXCHANGERATE*
- *RATE_TYPE*
- *MAXIMUM*
- *MINIMUM*
- *PAYMENT_MODE*
- *LOANVALDATE*
- *MATURITY_DATE*
- *Ude*
  - *USERDEID*

UDEDESC
RATEASOF
USAGE
USERDEVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description

Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USERREFNUM

Attribute	Description
Name	USERREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

MODCOD

Attribute	Description
Name	MODCOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BOOKINGDT

Attribute	**Description**	
Name	BOOKINGDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACTDATE

Attribute	**Description**	
Name	ACTDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALUEDT

Attribute	**Description**	
Name	VALUEDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRACKLIMIT

Attribute	**Description**	
Name	TRACKLIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CRDLINE

Attribute	**Description**
Name	CRDLINE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,F,N

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLATVAL

Attribute	Description
Name	COLLATVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ISRBNK

Attribute	Description
Name	ISRBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ISSUERBRN

Attribute	Description
Name	ISSUERBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBANK

Attribute	Description
Name	CLGBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBRN

Attribute	Description
Name	CLGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ENDPNT

Attribute	Description
Name	ENDPNT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTREMARKS

Attribute	**Description**	
Name	INTREMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ROUTNO

Attribute	**Description**	
Name	ROUTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	27

TOP

DRACCBRN

Attribute	**Description**	
Name	DRACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INSTR_DESC

Attribute	**Description**	
Name	INSTR_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTYNAME

Attribute	**Description**	
Name	CPTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYNAME

Attribute	**Description**	
Name	OTHERPARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ISSBANKNAME

Attribute	Description
Name	ISSBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ISSBRNCNAME

Attribute	Description
Name	ISSBRNCNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CLEARBANKNAME

Attribute	Description
Name	CLEARBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CLEARBRNCNAME

Attribute	Description
Name	CLEARBRNCNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,H,R,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DRACCREAL

Attribute	**Description**	
Name	DRACCREAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CLGPRD

Attribute	**Description**	
Name	CLGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Party-Details

Attribute	**Description**	
Name	Party-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRTYTYP

Attribute	**Description**	
Name	PRTYTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	DRAWER,PAYEE

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTYREFNO

Attribute	Description
Name	PARTYREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ADDLN1

Attribute	Description

Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTLANG

Attribute	Description
Name	PARTLANG
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	**Description**	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	**Description**
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	**Description**
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	**Description**
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	**Description**
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,S</td></tr></table>

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.49.2.RB-DeletePDCContract-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Contract-Details-IO
CONREFNUM

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.49.3.RB-DeletePDCContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNUM*
    - *BOOKDT*
    - *USERREFNUM*
    - *XREF*
    - *PRDCD*
    - *MODCOD*
    - *UDSTAT*
    - *STOPDT*
    - *EVENTCD*
    - *INSTRUCODE*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *INSTRNO*
    - *INSTRDATE*
    - *CONTCCY*
    - *AMOUNT*
    - *LCYAMT*
    - *OTHRPTYIDEN*

BOOKINGDT
ACTDATE
VALUEDT
TRACKLIMIT
CRDLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
DISCOUNTAMT
COLLATERAL
COLLATVAL
COLLPOOL
ISRBNK
ISSUERBRN
CLGBANK
CLGBRN
SECTORCD
ENDPNT
INTREMARKS
ACCBRN
ROUTNO
DRACCBRN
INSTR_DESC
PRDDESC
CPTYNAME
OTHERPARTYNAME
ISSBANKNAME
ISSBRNCNAME
CLEARBANKNAME
AUTOLIQD
CLEARBRNCNAME
MAKER
MAKDTTIME
CHKR
CHKDTTIME
CONST
AUTHSTAT
BATCHREFENUM
BATCHSEQNO
DRACCREAL
CLGPRD
Party-Details
  PRTYTYP
  PARTYIDEN

- *PARTYNAME*
- *PARTYREFNO*
- *COUNTRYCD*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ADDLN4*
- *PARTLANG*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*

COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID

POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*

RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL

- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*
  - *COSTCD4*
  - *COSTCD5*
  - *TXNMIS1*
  - *TXNMIS10*
  - *TXNMIS2*
  - *TXNMIS3*
  - *TXNMIS4*
  - *TXNMIS5*
  - *TXNMIS6*
  - *TXNMIS7*
  - *TXNMIS8*
  - *TXNMIS9*
  - *MISGRPCOMP*
  - *MISGRPTXN*
  - *COMPMIS1*
  - *COMPMIS10*
  - *COMPMIS2*
  - *COMPMIS3*
  - *COMPMIS4*

COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8

- FUNMIS9
- FUNMIS10
- Txnmisdetails
- Compmisdetails
- Fundmisdetails

TXNUDFDETAILS

- FLDNAME
- FLDVAL

Con

- CONTREFNO
- EVENTSEQ
- Adv
  - ADVNAME
  - SUPRESS
  - PRIOR
  - MEDM
  - PARTYIDEN
  - PARTYNAME
  - CHGREQ
  - PARTTYP

Clpref

- CONTREFNNO
- CONTRACT_CCY
- LATEVNSEQNO
- PRD
- PRDDESC
- COUNTERPARTY
- CURRENCY
- TENOR
- UNITS
- LOAN_CONREFNO
- RATECODE
- EXCHANGERATE
- RATE_TYPE
- MAXIMUM
- MINIMUM
- PAYMENT_MODE
- LOANVALDATE
- MATURITY_DATE
- Ude
  - USERDEID
  - UDEDESC
  - RATEASOF
  - USAGE

USERDEVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

USERREFNUM

Attribute	Description
Name	USERREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MODCOD

Attribute	Description
Name	MODCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BOOKINGDT

Attribute	Description
Name	BOOKINGDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACTDATE

Attribute	Description
Name	ACTDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,F,N

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLATVAL

Attribute	Description
Name	COLLATVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ISRBNK

Attribute	Description
Name	ISRBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ISSUERBRN

Attribute	Description
Name	ISSUERBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBANK

Attribute	Description
Name	CLGBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBRN

Attribute	Description
Name	CLGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ENDPNT

Attribute	Description
Name	ENDPNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>27</td></tr></table>

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ISSBANKNAME

Attribute	**Description**	
Name	ISSBANKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ISSBRNCNAME

Attribute	**Description**	
Name	ISSBRNCNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CLEARBANKNAME

Attribute	**Description**	
Name	CLEARBANKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

AUTOLIQD

Attribute	**Description**	
Name	AUTOLIQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CLEARBRNCNAME

Attribute	Description
Name	CLEARBRNCNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,H,R,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CLGPRD

Attribute	Description
Name	CLGPRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	DRAWER,PAYEE

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PARTYREFNO

Attribute	**Description**	
Name	PARTYREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COUNTRYCD

Attribute	**Description**	
Name	COUNTRYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTLANG

Attribute	Description
Name	PARTLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String

Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	Description	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,S</td></tr></table>

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.49.4.RB-DeletePDCContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNUM*
    - *Contract-Details-IO*
      - *CONREFNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.50.DeletePDR

DeletePDR

2.50.1.RB-DeletePDR-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-Full*
    - *CONREFNUM*
    - *CPTYIDEN*
    - *INSTRNO*
    - *INSTRDATE*
    - *CCY*
    - *AMNT*
    - *OTHRBNKCHARGS*
    - *OTHRPTYIDEN*
    - *BANKCODE*
    - *BOOKINGDATE*
    - *DISCOUNTAMT*
    - *CHARGESCLAIMED*
    - *COLLATVAL*
    - *REASONCODE*
    - *REASON*

DISHONORDATE
PROTESTDATE
RETURNDATE
REMARK
MAKER
MAKDTTIME
CHKR
CHKDTTIME
CONTSTAT
AUTHSTAT
CPTYNAME
OTHERPARTYNAME
BANKNAME
NOTARYDESCRIPTION
NOTARYCODE
Charges
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements
- *CONREFNO*
- *Contract-Settlement*

IBANACNO
CUSTSPREAD
SPREADDEFN
COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4

INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5

DRCRIND

Settlement-Detail

- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*
- *SUPPID*
- *PAYERID*

PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9

MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1

FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INSTRNO

Attribute	**Description**	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRDATE

Attribute	**Description**	
Name	INSTRDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNT

Attribute	**Description**	
Name	AMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BANKCODE

Attribute	Description
Name	BANKCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHARGESCLAIMED

Attribute	Description
Name	CHARGESCLAIMED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLATVAL

Attribute	Description
Name	COLLATVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REASONCODE

Attribute	Description
Name	REASONCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REASON

Attribute	Description
Name	REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DISHONORDATE

Attribute	Description
Name	DISHONORDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RETURNDATE

Attribute	Description
Name	RETURNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARK

Attribute	Description
Name	REMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

CPTYNAME

Attribute	**Description**	
Name	CPTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYNAME

Attribute	**Description**	
Name	OTHERPARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BANKNAME

Attribute	**Description**	
Name	BANKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

NOTARYDESCRIPTION

Attribute	**Description**	
Name	NOTARYDESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT

Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs — unbounded minOccurs — 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs — unbounded minOccurs — 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength — 105 minLength — 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs — 0
Restrictions	**Restrictions** / **Description** maxLength — 255 minLength — 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs — 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.50.2.RB-DeletePDR-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-IO*
    - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.50.3.RB-DeletePDR-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-Full*
    - *CONREFNUM*
    - *CPTYIDEN*
    - *INSTRNO*
    - *INSTRDATE*
    - *CCY*
    - *AMNT*
    - *OTHRBNKCHARGS*
    - *OTHRPTYIDEN*
    - *BANKCODE*
    - *BOOKINGDATE*
    - *DISCOUNTAMT*
    - *CHARGESCLAIMED*
    - *COLLATVAL*
    - *REASONCODE*
    - *REASON*
    - *DISHONORDATE*
    - *PROTESTDATE*
    - *RETURNDATE*

REMARK
MAKER
MAKDTTIME
CHKR
CHKDTTIME
CONTSTAT
AUTHSTAT
CPTYNAME
OTHERPARTYNAME
BANKNAME
NOTARYDESCRIPTION
NOTARYCODE
Charges
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*

COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3

INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
  INSTRCD1

INSTRCD2
INSTRCD3
INSTRCD4
ITIMEIND1
ITIMEIND2
ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID

SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1

COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4

FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BANKCODE

Attribute	Description
Name	BANKCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHARGESCLAIMED

Attribute	Description
Name	CHARGESCLAIMED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLATVAL

Attribute	Description
Name	COLLATVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REASONCODE

Attribute	Description
Name	REASONCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

REASON

Attribute	Description
Name	REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DISHONORDATE

Attribute	Description
Name	DISHONORDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RETURNDATE

Attribute	Description
Name	RETURNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARK

Attribute	Description
Name	REMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,H</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BANKNAME

Attribute	Description
Name	BANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

NOTARYDESCRIPTION

Attribute	Description
Name	NOTARYDESCRIPTION
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	**Description**	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Settlements

Attribute	**Description**	
Name	Settlements	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Settlement

Attribute	**Description**	
Name	Contract-Settlement	
Datatype		
Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	**Description**

Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String

Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description

Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	**Description**	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	**Description**	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	**Description**	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2

Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3

Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	**Description**	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	**Description**	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	**Description**	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2

Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	**Description**	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	**Description**	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	**Description**	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**	
Name	REGREP2	
Datatype	String	
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**
Name	REGREP3
Datatype	String

Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2

Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	**Description**	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	**Description**	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO2

Attribute	**Description**	
Name	SNDRRCVRINFO2	
Datatype	String	
Description	Indicates Sender Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	**Description**	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr></table>

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.50.4.RB-DeletePDR-Res-PK-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *CHOICE*
  - *Master-PK*
    - *CONREFNUM*
  - *Master-IO*
    - *CONREFNUM*
- *FCUBS_ERROR_RESP*
  - *ERROR*
    - *ECODE*
    - *EDESC*
- *FCUBS_WARNING_RESP*
  - *WARNING*
    - *WCODE*
    - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Master-PK

Attribute	Description
Name	Master-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.51.DeleteStatusChg

DeleteStatusChg

2.51.1.RB-DeleteStatusChg-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-Full*
    - *CONTREFNO*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *INSTRUMENTNO*
    - *INSTRULOC*
    - *INSTRSTAT*
    - *INSTRDATE*
    - *CCY*
    - *CONTRACTAMT*
    - *OTHRPTYIDEN*
    - *BANKCD*
    - *BRNCODE*
    - *BOOKINGDATE*
    - *MATURITYDATE*
    - *MAKER*

MAKDTTIME
CHKR
CHKDTTIME
CONTSTAT
AUTHSTAT
INTREMRKS
DRACFORREALISATION
COUNTRPRYNAM
OTHERPARTYNAME
BNKNAME
BRNNAME

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRUMENTNO

Attribute	Description
Name	INSTRUMENTNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRULOC

Attribute	Description
Name	INSTRULOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRSTAT

Attribute	Description
Name	INSTRSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONTRACTAMT

Attribute	Description
Name	CONTRACTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BANKCD

Attribute	Description
Name	BANKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CONTSTAT

Attribute	**Description**	
Name	CONTSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,H

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

INTREMRKS

Attribute	**Description**	
Name	INTREMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DRACFORREALISATION

Attribute	Description
Name	DRACFORREALISATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

2.51.2.RB-DeleteStatusChg-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-IO*
    - *CONTREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.51.3.RB-DeleteStatusChg-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-Full*
    - *CONTREFNO*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *INSTRUMENTNO*
    - *INSTRULOC*
    - *INSTRSTAT*
    - *INSTRDATE*
    - *CCY*
    - *CONTRACTAMT*
    - *OTHRPTYIDEN*
    - *BANKCD*
    - *BRNCODE*
    - *BOOKINGDATE*
    - *MATURITYDATE*
    - *MAKER*
    - *MAKDTTIME*
    - *CHKR*
    - *CHKDTTIME*

CONTSTAT
AUTHSTAT
INTREMRKS
DRACFORREALISATION
COUNTRPRYNAM
OTHERPARTYNAME
BNKNAME
BRNNAME
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 20

TOP

INSTRUMENTNO

Attribute	Description
Name	INSTRUMENTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRULOC

Attribute	Description
Name	INSTRULOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRSTAT

Attribute	Description
Name	INSTRSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONTRACTAMT

Attribute	Description
Name	CONTRACTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BANKCD

Attribute	Description
Name	BANKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DRACFORREALISATION

Attribute	**Description**	
Name	DRACFORREALISATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	**Description**	
Name	COUNTRPRYNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYNAME

Attribute	**Description**	
Name	OTHERPARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BNKNAME

Attribute	**Description**	
Name	BNKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.51.4.RB-DeleteStatusChg-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Master-PK*
      - *CONTREFNO*
    - *Master-IO*
      - *CONTREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Master-PK

Attribute	Description
Name	Master-PK
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.52.Deletefcychecksinput

Deletefcychecksinput

2.52.1.RB-Deletefcychecksinput-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *INSTRUMENT_CODE*
    - *INSTR_DESC*
    - *PRODUCT_CODE*
    - *PRDDESC*
    - *CONREFNUM*
    - *USERREF_NO1*
    - *XREF*
    - *BATCHREFENUM*
    - *BATCH_SEQ_NO*
    - *CASHLETTER_REFNUM*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *CPTY_AC_NO*
    - *ACC_BRANCH*
    - *INSTRUMENTNORE*

INSTRUMENT_DATE
CURRENCY
AMNT
LCY_AMOUNT
NOSTROACC
ACCBRN
COLLECTINGBANKCIF
COLL_BNK_NAME
BOOKINGDATE
VAL_DATE_BANK
VALUE_DATE_CUST
OTHR_PARTY_NAME
DRAWEE_BNK_NAME
AUTOLIQD
INTREMRKS
FINANCING
MARGIN_PERCENTAGE
TRACK_LIMIT
CRLINE
DISCOUNTAMT
MAKER
MAKDTTIME
CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
VERSION_NO
LATVERNO
Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*

RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1

ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*

REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3

- *REPRES4*
- *RCVRACC*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*

COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8

TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Clpref
CONTREFNNO
CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM

PAYMENT_MODE
LOANVALDATE
MATURITY_DATE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PRODUCT_CODE

Attribute	Description

Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BATCHREFENUM

Attribute	**Description**	
Name	BATCHREFENUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BATCH_SEQ_NO

Attribute	**Description**	
Name	BATCH_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CASHLETTER_REFNUM

Attribute	**Description**	
Name	CASHLETTER_REFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	**Description**	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CTR_PRTY_NAME

Attribute	Description	
Name	CTR_PRTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTY_AC_NO

Attribute	Description	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACC_BRANCH

Attribute	Description	
Name	ACC_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INSTRUMENTNORE

Attribute	Description	
Name	INSTRUMENTNORE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

COLLECTINGBANKCIF

Attribute	Description
Name	COLLECTINGBANKCIF
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 255

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRLINE

Attribute	Description
Name	CRLINE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,L,R,H,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String

Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	Description	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

2.52.2.RB-Deletefcychecksinput-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONREFNUM*
    - *USERREF_NO1*
    - *XREF*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

XREF

Attribute	**Description**
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

2.52.3.RB-Deletefcychecksinput-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *INSTRUMENT_CODE*
    - *INSTR_DESC*
    - *PRODUCT_CODE*
    - *PRDDESC*
    - *CONREFNUM*
    - *USERREF_NO1*
    - *XREF*
    - *BATCHREFENUM*
    - *BATCH_SEQ_NO*
    - *CASHLETTER_REFNUM*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *CPTY_AC_NO*
    - *ACC_BRANCH*
    - *INSTRUMENTNORE*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*

LCY_AMOUNT
NOSTROACC
ACCBRN
COLLECTINGBANKCIF
COLL_BNK_NAME
BOOKINGDATE
VAL_DATE_BANK
VALUE_DATE_CUST
OTHR_PARTY_NAME
DRAWEE_BNK_NAME
AUTOLIQD
INTREMRKS
FINANCING
MARGIN_PERCENTAGE
TRACK_LIMIT
CRLINE
DISCOUNTAMT
MAKER
MAKDTTIME
CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
VERSION_NO
LATVERNO
Settlements
  CONREFNO
  Contract-Settlement
    IBANACNO
    CUSTSPREAD
    SPREADDEFN
    COMPNT
    TAGCCY
    ACCBRN
    ACC
    ACCCCY
    EXRATE
    NETIND
    ERICCY
    ERIAMT
    GENMSG
    RATECD
    CLEARNW
    COVERBY

RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4

BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*

ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*

TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1

COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Clpref
CONTREFNNO
CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM
PAYMENT_MODE
LOANVALDATE
MATURITY_DATE

Ude

USERDEID

UDEDESC

RATEASOF

USAGE

USERDEVAL

Con

CONTREFNO

EVENTSEQ

Adv

ADVNAME

SUPRESS

PRIOR

MEDM

PARTYIDEN

PARTYNAME

CHGREQ

PARTTYP

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PRODUCT_CODE

Attribute	Description	
Name	PRODUCT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CONREFNUM

Attribute	Description	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USERREF_NO1

Attribute	Description	
Name	USERREF_NO1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCH_SEQ_NO

Attribute	Description
Name	BATCH_SEQ_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CASHLETTER_REFNUM

Attribute	Description
Name	CASHLETTER_REFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CTR_PRTY_NAME

Attribute	**Description**	
Name	CTR_PRTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTY_AC_NO

Attribute	**Description**	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACC_BRANCH

Attribute	**Description**	
Name	ACC_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INSTRUMENTNORE

Attribute	**Description**	
Name	INSTRUMENTNORE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

COLLECTINGBANKCIF

Attribute	**Description**	
Name	COLLECTINGBANKCIF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

COLL_BNK_NAME

Attribute	**Description**	
Name	COLL_BNK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BOOKINGDATE

Attribute	**Description**	
Name	BOOKINGDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTREMRKS

Attribute	**Description**	
Name	INTREMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,N,F

TOP

MARGIN_PERCENTAGE

Attribute	**Description**	
Name	MARGIN_PERCENTAGE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRACK_LIMIT

Attribute	**Description**	
Name	TRACK_LIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CRLINE

Attribute	Description
Name	CRLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,L,R,H,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String

Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ADVNAME

Attribute	**Description**	
Name	ADVNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SUPRESS

Attribute	**Description**	
Name	SUPRESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.52.4.RB-Deletefcychecksinput-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONREFNUM*
      - *USERREF_NO1*
      - *XREF*
    - *Main-IO*
      - *CONREFNUM*
      - *USERREF_NO1*
      - *XREF*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description

Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.53.ModifyInwardContract

ModifyInwardContract

2.53.1.RB-ModifyInwardContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *INSTRUMENT_CODE*
    - *INSTRUMENT_DESCRIPTION*
    - *PRCD*
    - *CONREFNUM*
    - *USERREF_NO*
    - *XREF*
    - *BATCHREFENUM*
    - *BATCHSEQNO*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *ACCBRN*
    - *CPTY_AC_NO*
    - *INSTNO*
    - *INSTRDATE*
    - *CCY*

AMT
LCYAMT
BNKCD
BNKNAME
BRNCDE
BRNNAME
REFNO
DATE
CORRESPBNK
CORRESPACNO
OTHERPARTYIDE
OTHR_PARTYNAME
BOKNGDT
MATDT
GRACEDAYS
PAYDUEDATE
ACBRN1
ACFORREALISATION
PROTEST
AUTOLIQD
LIQWITHBUKNG
INTREMARKS
REASON_CODE
REASON
CONREFNOLOG
MAKER
MAKDTTIME
CHKR
CHKDTTIME
SE_TXNSTAT
AUTHSTAT
VERSIONNORB
LATVERNO
Contract-Parties
- *PARTYTYPE*
- *PARTYIDEN*
- *PARTYNAME*
- *COUNTRYCD*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ADDLN4*
- *LANG*

Settlements

CONREFNO

Contract-Settlement

- *IBANACNO*
- *CUSTSPREAD*
- *SPREADDEFN*
- *COMPNT*
- *TAGCCY*
- *ACCBRN*
- *ACC*
- *ACCCCY*
- *EXRATE*
- *NETIND*
- *ERICCY*
- *ERIAMT*
- *GENMSG*
- *RATECD*
- *CLEARNW*
- *COVERBY*
- *RTGSPMNT*
- *BANKPRIOR*
- *RTGSNW*
- *PAYBY*
- *TRANSTYP*
- *INSTYP*
- *INSNO*
- *CHGDET*
- *PAYMNTDET1*
- *PAYMNTDET2*
- *PAYMNTDET3*
- *PAYMNTDET4*
- *SNDTRRCVINFO1*
- *SNDTRRCVINFO2*
- *SNDTRRCVINFO3*
- *SNDTRRCVINFO4*
- *SNDTRRCVINFO5*
- *COVREQRD*
- *RECVCVR*
- *RECEIVER*
- *REIMINST1*
- *REIMINST2*
- *REIMINST3*
- *REIMINST4*
- *RCVRCORRS1*
- *RCVRCORRS2*

RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5

ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*

SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Charges

CONREFNO

Charge-Association

COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC

Charge-Application

CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND

Charge-Liquidation

ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3

FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con

CONTREFNO

EVENTSEQ

Adv

- *ADVNAME*
- *SUPRESS*
- *PRIOR*
- *MEDM*
- *PARTYIDEN*
- *PARTYNAME*
- *CHGREQ*
- *PARTTYP*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description
Name	INSTRUMENT_DESCRIPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHSEQNO

Attribute	Description

Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTNO

Attribute	Description
Name	INSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BRNCDE

Attribute	Description
Name	BRNCDE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORRESPBNK

Attribute	Description
Name	CORRESPBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CORRESPACNO

Attribute	Description
Name	CORRESPACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

OTHERPARTYIDE

Attribute	Description
Name	OTHERPARTYIDE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

ACBRN1

Attribute	Description
Name	ACBRN1
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 20

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: Y,N

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQWITHBUKNG

Attribute	Description
Name	LIQWITHBUKNG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REASON

Attribute	Description
Name	REASON
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CONREFNOLOG

Attribute	**Description**	
Name	CONREFNOLOG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	**Description**	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SE_TXNSTAT

Attribute	Description
Name	SE_TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,L,R,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

VERSIONNORB

Attribute	Description
Name	VERSIONNORB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>DRAWER,PAYEE,REMITTING_BANK,DRAWEE</td></tr></table>

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRYCD

Attribute	**Description**	
Name	COUNTRYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ADDLN1

Attribute	**Description**	
Name	ADDLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDLN2

Attribute	**Description**	
Name	ADDLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDLN3

Attribute	**Description**	
Name	ADDLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	**Description**	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	**Description**	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1

Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2

Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5

Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	Description	
Name	REGREP1	
Datatype	String	
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1

Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	**Description**	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	**Description**	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application

Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	**Description**	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	Description	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	Description	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	Description	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	Description	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL

Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

2.53.2.RB-ModifyInwardContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *INSTRUMENT_DESCRIPTION*
    - *CONREFNUM*
    - *BATCHREFENUM*
    - *BATCHSEQNO*
    - *CPTY_NAME*
    - *INSTNO*
    - *INSTRDATE*
    - *AMT*
    - *LCYAMT*
    - *BNKCD*
    - *BNKNAME*
    - *BRNCDE*
    - *BRNNAME*
    - *REFNO*
    - *DATE*
    - *CORRESPBNK*
    - *CORRESPACNO*
    - *OTHERPARTYIDE*

OTHR_PARTYNAME
BOKNGDT
MATDT
PAYDUEDATE
PROTEST
AUTOLIQD
INTREMARKS
DISHONORDATE
MAKER
MAKDTTIME
CHKR
CHKDTTIME
SE_TXNSTAT
AUTHSTAT
LESN
VERSIONNORB
LATVERNO
ESQN
EVTCD
LOC
INSTRSTAT
SUBSYSSTAT
Contract-Parties
  TRN_REF_NO
  PESN
  PARTYTYPE
  PARTYIDEN
  PARTYNAME
  COUNTRYCD
  PRTYREF
  ADDLN1
  ADDLN2
  ADDLN3
  ADDLN4
  WALKIN_CUSTOMER_FLAG
  LANG
Settlements
  CONREFNO
  LATEVNSEQNO
  Contract-Settlement
    IBANACNO
    CUSTSPREAD
    SPREADDEFN
    COMPNT

TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *CONTREFNO*
- *ESN*
- *COMPNT*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *AMTTAG*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*

ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
LATEVNSEQNO
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation

CHRGCCY
CHRGAMT
LIQDSTAT

Misdetails

CONREFNO
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFXRATE
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9

FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description
Name	INSTRUMENT_DESCRIPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTNO

Attribute	Description
Name	INSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BRNCDE

Attribute	Description
Name	BRNCDE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

REFNO

Attribute	**Description**	
Name	REFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DATE

Attribute	**Description**	
Name	DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CORRESPBNK

Attribute	**Description**	
Name	CORRESPBNK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CORRESPACNO

Attribute	Description
Name	CORRESPACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

OTHERPARTYIDE

Attribute	Description
Name	OTHERPARTYIDE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DISHONORDATE

Attribute	Description
Name	DISHONORDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SE_TXNSTAT

Attribute	Description
Name	SE_TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,L,R,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

LESN

Attribute	Description
Name	LESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VERSIONNORB

Attribute	Description
Name	VERSIONNORB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESQN

Attribute	Description
Name	ESQN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVTCD

Attribute	Description
Name	EVTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LOC

Attribute	Description
Name	LOC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRSTAT

Attribute	Description
Name	INSTRSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SUBSYSSTAT

Attribute	Description
Name	SUBSYSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRN_REF_NO

Attribute	Description
Name	TRN_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PESN

Attribute	Description
Name	PESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	
Attributes	**Attribute**: minOccurs; **Description**: 1
Restrictions	**Restrictions**: enumeration; **Description**: DRAWER,PAYEE,REMITTING_BANK,DRAWEE

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute**: minOccurs; **Description**: 0
Restrictions	**Restrictions**: maxLength; **Description**: 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute**: minOccurs; **Description**: 0
Restrictions	**Restrictions**: maxLength; **Description**: 105

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute**: minOccurs; **Description**: 0
Restrictions	**Restrictions**: maxLength; **Description**: 3

TOP

PRTYREF

Attribute	Description
Name	PRTYREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDLN4

Attribute	Description
Name	ADDLN4

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKIN_CUSTOMER_FLAG

Attribute	Description
Name	WALKIN_CUSTOMER_FLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String

Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description

Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	**Description**	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CONTREFNO

Attribute	**Description**	
Name	CONTREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTTAG

Attribute	Description	
Name	AMTTAG	
Datatype	String	
Description	Indicates Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2

Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRPART

Attribute	**Description**	
Name	SNDRRCVRPART	
Datatype	Number	
Description	Indicates Sender Receiver Participant	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	**Description**	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3

Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number

Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description

Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	**Description**	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	Description	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	Description	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	Description	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	1

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	1

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.53.3.RB-ModifyInwardContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *INSTRUMENT_CODE*
    - *INSTRUMENT_DESCRIPTION*
    - *PRCD*
    - *CONREFNUM*
    - *USERREF_NO*
    - *XREF*
    - *BATCHREFENUM*
    - *BATCHSEQNO*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *ACCBRN*
    - *CPTY_AC_NO*
    - *INSTNO*
    - *INSTRDATE*
    - *CCY*
    - *AMT*
    - *LCYAMT*
    - *BNKCD*

BNKNAME
BRNCDE
BRNNAME
REFNO
DATE
CORRESPBNK
CORRESPACNO
OTHERPARTYIDE
OTHR_PARTYNAME
BOKNGDT
MATDT
GRACEDAYS
PAYDUEDATE
ACBRN1
ACFORREALISATION
PROTEST
AUTOLIQD
LIQWITHBUKNG
INTREMARKS
REASON_CODE
REASON
CONREFNOLOG
MAKER
MAKDTTIME
CHKR
CHKDTTIME
SE_TXNSTAT
AUTHSTAT
VERSIONNORB
LATVERNO
Contract-Parties
  PARTYTYPE
  PARTYIDEN
  PARTYNAME
  COUNTRYCD
  ADDLN1
  ADDLN2
  ADDLN3
  ADDLN4
  LANG
Settlements
  CONREFNO
  Contract-Settlement
    IBANACNO

CUSTSPREAD
SPREADDEFN
COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1

INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND

Settlement-Detail

- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*

- NOOFDEC
- ADDID
- SNDRRCVRINFO1
- SNDRRCVRINFO2
- SNDRRCVRINFO3
- SNDRRCVRINFO4
- SNDRRCVRINFO5
- SNDRRCVRINFO6
- DECLARTION
- REPRES1
- REPRES2
- REPRES3
- REPRES4
- RCVRACC

Charges

- CONREFNO
- Charge-Association
  - COMPNT
  - CREATESN
  - RULE
  - WAIVER
  - DISACCRAPPL
  - ACCRREQD
  - DESC
- Charge-Application
  - CREATESN
  - COMPNT
  - TGCCY
  - TGAMT
  - CHRGCCY
  - CHRGAMT
  - DISACCRAPPL
  - WAIVER
  - LIQDIND
- Charge-Liquidation
  - ESN
  - COMPNT
  - CHRGCCY
  - CHRGAMT
  - LIQDSTAT

Misdetails

- CONREFNO
- LATESN
- MISGRP

RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6

FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv

ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description
Name	INSTRUMENT_DESCRIPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTNO

Attribute	**Description**	
Name	INSTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRDATE

Attribute	**Description**	
Name	INSTRDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BRNCDE

Attribute	Description
Name	BRNCDE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

REFNO

Attribute	**Description**	
Name	REFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DATE

Attribute	**Description**	
Name	DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CORRESPBNK

Attribute	**Description**	
Name	CORRESPBNK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CORRESPACNO

Attribute	**Description**	
Name	CORRESPACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

OTHERPARTYIDE

Attribute	Description
Name	OTHERPARTYIDE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PAYDUEDATE

Attribute	**Description**	
Name	PAYDUEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACBRN1

Attribute	**Description**	
Name	ACBRN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACFORREALISATION

Attribute	**Description**	
Name	ACFORREALISATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

PROTEST

Attribute	**Description**	
Name	PROTEST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

LIQWITHBUKNG

Attribute	Description
Name	LIQWITHBUKNG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

REASON

Attribute	Description
Name	REASON

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CONREFNOLOG

Attribute	Description
Name	CONREFNOLOG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SE_TXNSTAT

Attribute	**Description**	
Name	SE_TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,L,R,H

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

VERSIONNORB

Attribute	**Description**	
Name	VERSIONNORB	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / DRAWER,PAYEE,REMITTING_BANK,DRAWEE

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	**Description**	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	**Description**	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	**Description**	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	**Description**	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1

Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2

Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDINST5

Attribute	Description
Name	ORDINST5

Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1

Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	**Description**	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	**Description**	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application

Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	**Description**	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL

Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.53.4.RB-ModifyInwardContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNUM*
    - *Contract-Details-IO*
      - *INSTRUMENT_DESCRIPTION*
      - *CONREFNUM*
      - *BATCHREFENUM*
      - *BATCHSEQNO*
      - *CPTY_NAME*
      - *INSTNO*
      - *INSTRDATE*
      - *AMT*
      - *LCYAMT*
      - *BNKCD*
      - *BNKNAME*
      - *BRNCDE*
      - *BRNNAME*
      - *REFNO*
      - *DATE*

CORRESPBNK
CORRESPACNO
OTHERPARTYIDE
OTHR_PARTYNAME
BOKNGDT
MATDT
PAYDUEDATE
PROTEST
AUTOLIQD
INTREMARKS
DISHONORDATE
MAKER
MAKDTTIME
CHKR
CHKDTTIME
SE_TXNSTAT
AUTHSTAT
LESN
VERSIONNORB
LATVERNO
ESQN
EVTCD
LOC
INSTRSTAT
SUBSYSSTAT
Contract-Parties
- *TRN_REF_NO*
- *PESN*
- *PARTYTYPE*
- *PARTYIDEN*
- *PARTYNAME*
- *COUNTRYCD*
- *PRTYREF*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ADDLN4*
- *WALKIN_CUSTOMER_FLAG*
- *LANG*

Settlements
- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *IBANACNO*

CUSTSPREAD
SPREADDEFN
COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *CONTREFNO*
- *ESN*
- *COMPNT*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *AMTTAG*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*

RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
LATEVNSEQNO
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL

WAIVER
LIQDIND
Charge-Liquidation
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFXRATE
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6

COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description
Name	INSTRUMENT_DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTNO

Attribute	Description
Name	INSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BRNCDE

Attribute	Description
Name	BRNCDE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

REFNO

Attribute	**Description**	
Name	REFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DATE

Attribute	**Description**	
Name	DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CORRESPBNK

Attribute	**Description**	
Name	CORRESPBNK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CORRESPACNO

Attribute	**Description**	
Name	CORRESPACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

OTHERPARTYIDE

Attribute	Description
Name	OTHERPARTYIDE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PROTEST

Attribute	**Description**	
Name	PROTEST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOLIQD

Attribute	**Description**	
Name	AUTOLIQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTREMARKS

Attribute	**Description**	
Name	INTREMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DISHONORDATE

Attribute	**Description**	
Name	DISHONORDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SE_TXNSTAT

Attribute	Description
Name	SE_TXNSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,L,R,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

LESN

Attribute	Description
Name	LESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VERSIONNORB

Attribute	Description
Name	VERSIONNORB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ESQN

Attribute	Description
Name	ESQN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVTCD

Attribute	Description
Name	EVTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

LOC

Attribute	Description
Name	LOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRSTAT

Attribute	Description
Name	INSTRSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SUBSYSSTAT

Attribute	Description
Name	SUBSYSSTAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

Contract-Parties

Attribute	**Description**	
Name	Contract-Parties	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

TRN_REF_NO

Attribute	**Description**	
Name	TRN_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PESN

Attribute	**Description**	
Name	PESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYTYPE

Attribute	**Description**	
Name	PARTYTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	DRAWER,PAYEE,REMITTING_BANK,DRAWEE

TOP

PARTYIDEN

Attribute	Description	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PARTYNAME

Attribute	Description	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRYCD

Attribute	Description	
Name	COUNTRYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRTYREF

Attribute	Description	
Name	PRTYREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

WALKIN_CUSTOMER_FLAG

Attribute	Description
Name	WALKIN_CUSTOMER_FLAG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BANKOPERCD

Attribute	**Description**	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	**Description**	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3

Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String

Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	1

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.54.CreatePDR

CreatePDR

2.54.1.RB-CreatePDR-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-Full*
    - *CONREFNUM*
    - *CPTYIDEN*
    - *INSTRNO*
    - *INSTRDATE*
    - *CCY*
    - *AMNT*
    - *OTHRBNKCHARGS*
    - *OTHRPTYIDEN*
    - *BANKCODE*
    - *BOOKINGDATE*
    - *DISCOUNTAMT*
    - *CHARGESCLAIMED*
    - *COLLATVAL*
    - *REASONCODE*
    - *REASON*

DISHONORDATE
PROTESTDATE
RETURNDATE
REMARK
MAKER
MAKDTTIME
CHKR
CHKDTTIME
CONTSTAT
AUTHSTAT
CPTYNAME
OTHERPARTYNAME
BANKNAME
NOTARYDESCRIPTION
NOTARYCODE
Charges
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements
- *CONREFNO*
- *Contract-Settlement*

IBANACNO
CUSTSPREAD
SPREADDEFN
COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4

INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5

DRCRIND

Settlement-Detail

- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*
- *SUPPID*
- *PAYERID*

PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9

MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1

FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INSTRNO

Attribute	**Description**	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRDATE

Attribute	**Description**	
Name	INSTRDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNT

Attribute	**Description**	
Name	AMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BANKCODE

Attribute	Description
Name	BANKCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHARGESCLAIMED

Attribute	Description
Name	CHARGESCLAIMED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLATVAL

Attribute	Description
Name	COLLATVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REASONCODE

Attribute	Description
Name	REASONCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REASON

Attribute	Description
Name	REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DISHONORDATE

Attribute	Description
Name	DISHONORDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RETURNDATE

Attribute	Description
Name	RETURNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARK

Attribute	Description
Name	REMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

CPTYNAME

Attribute	**Description**	
Name	CPTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYNAME

Attribute	**Description**	
Name	OTHERPARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BANKNAME

Attribute	**Description**	
Name	BANKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

NOTARYDESCRIPTION

Attribute	**Description**	
Name	NOTARYDESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT

Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	**Description**	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	**Description**	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	**Description**	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	**Description**	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description	
Name	SNDRCUSTNAME2	
Datatype	String	
Description	Indicates Sender Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.54.2.RB-CreatePDR-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-IO*
    - *CONREFNUM*
    - *OTHRBNKCHARGS*
    - *CHARGESCLAIMED*
    - *REASONCODE*
    - *DISHONORDATE*
    - *PROTESTDATE*
    - *RETURNDATE*
    - *REMARK*
    - *NOTARYDESCRIPTION*
    - *NOTARYCODE*
    - *Charges*
      - *LATEVNSEQNO*
      - *CONREFNO*
      - *Charge-Association*
        - *WAIVER*
        - *DISACCRAPPL*
        - *ACCRREQD*
        - *DESC*

- *Charge-Application*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*

RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6

ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *ULTBANDCD*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*
- *NOOFDEC*
- *ADDID*
- *SNDRRCVRINFO1*
- *SNDRRCVRINFO2*
- *SNDRRCVRINFO3*
- *SNDRRCVRINFO4*

SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4

COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
SUPRESS
PRIOR
MEDM
CHGREQ

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHARGESCLAIMED

Attribute	Description
Name	CHARGESCLAIMED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REASONCODE

Attribute	Description
Name	REASONCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DISHONORDATE

Attribute	Description
Name	DISHONORDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RETURNDATE

Attribute	Description
Name	RETURNDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARK

Attribute	Description
Name	REMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

NOTARYDESCRIPTION

Attribute	Description
Name	NOTARYDESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Settlements

Attribute	**Description**	
Name	Settlements	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String

Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description

Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1

Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5

Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD

Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3

Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

2.54.3.RB-CreatePDR-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-Full*
    - *CONREFNUM*
    - *CPTYIDEN*
    - *INSTRNO*
    - *INSTRDATE*
    - *CCY*
    - *AMNT*
    - *OTHRBNKCHARGS*
    - *OTHRPTYIDEN*
    - *BANKCODE*
    - *BOOKINGDATE*
    - *DISCOUNTAMT*
    - *CHARGESCLAIMED*
    - *COLLATVAL*
    - *REASONCODE*
    - *REASON*
    - *DISHONORDATE*
    - *PROTESTDATE*
    - *RETURNDATE*

REMARK
MAKER
MAKDTTIME
CHKR
CHKDTTIME
CONTSTAT
AUTHSTAT
CPTYNAME
OTHERPARTYNAME
BANKNAME
NOTARYDESCRIPTION
NOTARYCODE
Charges
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*

COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3

INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
  INSTRCD1

INSTRCD2
INSTRCD3
INSTRCD4
ITIMEIND1
ITIMEIND2
ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID

SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1

COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4

FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BANKCODE

Attribute	Description
Name	BANKCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHARGESCLAIMED

Attribute	**Description**	
Name	CHARGESCLAIMED	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COLLATVAL

Attribute	**Description**	
Name	COLLATVAL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REASONCODE

Attribute	**Description**	
Name	REASONCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

REASON

Attribute	**Description**	
Name	REASON	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DISHONORDATE

Attribute	**Description**
Name	DISHONORDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RETURNDATE

Attribute	Description
Name	RETURNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARK

Attribute	Description
Name	REMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,H</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BANKNAME

Attribute	Description
Name	BANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

NOTARYDESCRIPTION

Attribute	Description
Name	NOTARYDESCRIPTION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

NOTARYCODE

Attribute	**Description**	
Name	NOTARYCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	**Description**	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Settlements

Attribute	**Description**	
Name	Settlements	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Settlement

Attribute	**Description**	
Name	Contract-Settlement	
Datatype		
Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	**Description**

Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String

Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description

Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	**Description**	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	**Description**	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	**Description**	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	**Description**	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2

Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3

Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2

Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	**Description**	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**	
Name	REGREP2	
Datatype	String	
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**
Name	REGREP3
Datatype	String

Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2

Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	**Description**	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	**Description**	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO2

Attribute	**Description**	
Name	SNDRRCVRINFO2	
Datatype	String	
Description	Indicates Sender Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	**Description**
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	**Description**
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	**Description**
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	**Description**
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	Description	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	Description	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	Description	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	**Description**	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr></table>

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.54.4.RB-CreatePDR-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Master-PK*
      - *CONREFNUM*
    - *Master-IO*
      - *CONREFNUM*
      - *OTHRBNKCHARGS*
      - *CHARGESCLAIMED*
      - *REASONCODE*
      - *DISHONORDATE*
      - *PROTESTDATE*
      - *RETURNDATE*
      - *REMARK*
      - *NOTARYDESCRIPTION*
      - *NOTARYCODE*
      - *Charges*
        - *LATEVNSEQNO*
        - *CONREFNO*
        - *Charge-Association*
          - *WAIVER*

DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
CHRGAMT
LIQDSTAT
Settlements
CONREFNO
LATEVNSEQNO
Contract-Settlement
CUSTSPREAD
SPREADDEFN
TAGCCY
ACCBRN
ACC
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3

SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID

POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *ULTBANDCD*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*
- *NOOFDEC*
- *ADDID*
- *SNDRRCVRINFO1*

SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10

COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
SUPRESS
PRIOR
MEDM
CHGREQ
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Master-PK

Attribute	Description
Name	Master-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

OTHRBNKCHARGS

Attribute	Description	
Name	OTHRBNKCHARGS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHARGESCLAIMED

Attribute	Description	
Name	CHARGESCLAIMED	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REASONCODE

Attribute	Description
Name	REASONCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DISHONORDATE

Attribute	Description
Name	DISHONORDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RETURNDATE

Attribute	Description
Name	RETURNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARK

Attribute	Description
Name	REMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

NOTARYDESCRIPTION

Attribute	Description
Name	NOTARYDESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String

Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description

Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	**Description**	
Name	COVERBY	
Datatype	String	
Description	Indicates Cover By Clearing : C Message : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates RTGS Payment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	**Description**	
Name	BANKPRIOR	
Datatype	String	
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**

Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	Description	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1

Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	**Description**	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2

Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	Description	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	Description	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5

Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	**Description**	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	**Description**	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

Con

Attribute	**Description**	
Name	Con	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNO

Attribute	**Description**	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.55.CreateStatusChg

CreateStatusChg

2.55.1.RB-CreateStatusChg-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-Full*
    - *CONTREFNO*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *INSTRUMENTNO*
    - *INSTRULOC*
    - *INSTRSTAT*
    - *INSTRDATE*
    - *CCY*
    - *CONTRACTAMT*
    - *OTHRPTYIDEN*
    - *BANKCD*
    - *BRNCODE*
    - *BOOKINGDATE*
    - *MATURITYDATE*
    - *MAKER*

MAKDTTIME
CHKR
CHKDTTIME
CONTSTAT
AUTHSTAT
INTREMRKS
DRACFORREALISATION
COUNTRPRYNAM
OTHERPARTYNAME
BNKNAME
BRNNAME

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTYIDEN

Attribute	Description	
Name	CPTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTYACCNUM

Attribute	Description	
Name	CPTYACCNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRUMENTNO

Attribute	Description
Name	INSTRUMENTNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRULOC

Attribute	Description
Name	INSTRULOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRSTAT

Attribute	Description
Name	INSTRSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONTRACTAMT

Attribute	Description
Name	CONTRACTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BANKCD

Attribute	Description
Name	BANKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CONTSTAT

Attribute	**Description**	
Name	CONTSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,H

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

INTREMRKS

Attribute	**Description**	
Name	INTREMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DRACFORREALISATION

Attribute	Description
Name	DRACFORREALISATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-IO*
    - *CONTREFNO*
    - *INSTRULOC*
    - *INSTRSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

INSTRULOC

Attribute	Description
Name	INSTRULOC
Datatype	String
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRSTAT

Attribute	Description
Name	INSTRSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

2.55.3.RB-CreateStatusChg-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-Full*
    - *CONTREFNO*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *INSTRUMENTNO*
    - *INSTRULOC*
    - *INSTRSTAT*
    - *INSTRDATE*
    - *CCY*
    - *CONTRACTAMT*
    - *OTHRPTYIDEN*
    - *BANKCD*
    - *BRNCODE*
    - *BOOKINGDATE*
    - *MATURITYDATE*
    - *MAKER*
    - *MAKDTTIME*
    - *CHKR*
    - *CHKDTTIME*

CONTSTAT
AUTHSTAT
INTREMRKS
DRACFORREALISATION
COUNTRPRYNAM
OTHERPARTYNAME
BNKNAME
BRNNAME
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRUMENTNO

Attribute	Description
Name	INSTRUMENTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRULOC

Attribute	Description
Name	INSTRULOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRSTAT

Attribute	Description
Name	INSTRSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONTRACTAMT

Attribute	Description
Name	CONTRACTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BANKCD

Attribute	Description
Name	BANKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DRACFORREALISATION

Attribute	**Description**	
Name	DRACFORREALISATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	**Description**	
Name	COUNTRPRYNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYNAME

Attribute	**Description**	
Name	OTHERPARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BNKNAME

Attribute	**Description**	
Name	BNKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Master-PK*
      - *CONTREFNO*
    - *Master-IO*
      - *CONTREFNO*
      - *INSTRULOC*
      - *INSTRSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Master-PK

Attribute	Description
Name	Master-PK
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

INSTRULOC

Attribute	Description
Name	INSTRULOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRSTAT

Attribute	Description
Name	INSTRSTAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.56.Createfcychecksinput

Createfcychecksinput

2.56.1.RB-Createfcychecksinput-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *INSTRUMENT_CODE*
    - *INSTR_DESC*
    - *PRODUCT_CODE*
    - *PRDDESC*
    - *CONREFNUM*
    - *USERREF_NO1*
    - *XREF*
    - *BATCHREFENUM*
    - *BATCH_SEQ_NO*
    - *CASHLETTER_REFNUM*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *CPTY_AC_NO*
    - *ACC_BRANCH*
    - *INSTRUMENTNORE*

INSTRUMENT_DATE
CURRENCY
AMNT
LCY_AMOUNT
NOSTROACC
ACCBRN
COLLECTINGBANKCIF
COLL_BNK_NAME
BOOKINGDATE
VAL_DATE_BANK
VALUE_DATE_CUST
OTHR_PARTY_NAME
DRAWEE_BNK_NAME
AUTOLIQD
INTREMRKS
FINANCING
MARGIN_PERCENTAGE
TRACK_LIMIT
CRLINE
DISCOUNTAMT
MAKER
MAKDTTIME
CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
VERSION_NO
LATVERNO
Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*

RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1

ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*

REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3

- *REPRES4*
- *RCVRACC*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*

COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8

TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Clpref
CONTREFNNO
CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM

PAYMENT_MODE
LOANVALDATE
MATURITY_DATE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRODUCT_CODE

Attribute	Description

Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BATCHREFENUM

Attribute	**Description**	
Name	BATCHREFENUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BATCH_SEQ_NO

Attribute	**Description**	
Name	BATCH_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CASHLETTER_REFNUM

Attribute	**Description**	
Name	CASHLETTER_REFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	**Description**	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CTR_PRTY_NAME

Attribute	Description	
Name	CTR_PRTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTY_AC_NO

Attribute	Description	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACC_BRANCH

Attribute	Description	
Name	ACC_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INSTRUMENTNORE

Attribute	Description	
Name	INSTRUMENTNORE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLECTINGBANKCIF

Attribute	Description
Name	COLLECTINGBANKCIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRLINE

Attribute	Description
Name	CRLINE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,L,R,H,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String

Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

2.56.2.RB-Createfcychecksinput-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *INSTRUMENT_CODE*
    - *PRODUCT_CODE*
    - *CONREFNUM*
    - *USERREF_NO1*
    - *XREF*
    - *BATCHREFENUM*
    - *CPTY_ID*
    - *CPTY_AC_NO*
    - *INSTRUMENTNORE*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *VALUE_DATE_CUST*
    - *OTHR_PARTY_NAME*
    - *DRAWEE_BNK_NAME*
    - *AUTOLIQD*
    - *INTREMRKS*
    - *FINANCING*

MARGIN_PERCENTAGE
TRACK_LIMIT
CRLINE
Settlements
- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*
  - *RECVCVR*
  - *RECEIVER*
  - *REIMINST1*
  - *REIMINST4*
  - *RCVRCORRS1*
  - *RCVRCORRS2*

RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5

ORDINST5

ULTBEN5

Settlement-Detail

- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *ULTBANDCD*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*
- *NOOFDEC*
- *ADDID*
- *SNDRRCVRINFO1*
- *SNDRRCVRINFO2*
- *SNDRRCVRINFO3*
- *SNDRRCVRINFO4*
- *SNDRRCVRINFO5*
- *SNDRRCVRINFO6*
- *DECLARTION*
- *REPRES1*
- *REPRES2*
- *REPRES3*

REPRES4
RCVRACC
Charges
LATEVNSEQNO
CONREFNO
Charge-Association
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5

- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*
- *MISGRPTXN*
- *COMPMIS1*
- *COMPMIS10*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *FUNDMIS1*
- *FUNDMIS10*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *MISGRPFUN*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Clpref

- *CONTREFNNO*
- *LOAN_CONREFNO*
- *RATECODE*
- *EXCHANGERATE*
- *RATE_TYPE*
- *Ude*
  - *USERDEID*
  - *UDEDESC*
  - *RATEASOF*
  - *USAGE*

USERDEVAL

Con

CONTREFNO

EVENTSEQ

Adv

SUPRESS

PRIOR

MEDM

CHGREQ

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRODUCT_CODE

Attribute	Description
Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENTNORE

Attribute	Description
Name	INSTRUMENTNORE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,N,F

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRLINE

Attribute	Description
Name	CRLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String

Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	Description	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	**Description**
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	**Description**
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	**Description**
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	**Description**
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP

Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2

Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Txnmisdetails

Attribute	**Description**	
Name	Txnmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Compmisdetails

Attribute	**Description**	
Name	Compmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

RATEASOF

Attribute	Description
Name	RATEASOF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

2.56.3.RB-Createfcychecksinput-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *INSTRUMENT_CODE*
    - *INSTR_DESC*
    - *PRODUCT_CODE*
    - *PRDDESC*
    - *CONREFNUM*
    - *USERREF_NO1*
    - *XREF*
    - *BATCHREFENUM*
    - *BATCH_SEQ_NO*
    - *CASHLETTER_REFNUM*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *CPTY_AC_NO*
    - *ACC_BRANCH*
    - *INSTRUMENTNORE*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*

LCY_AMOUNT
NOSTROACC
ACCBRN
COLLECTINGBANKCIF
COLL_BNK_NAME
BOOKINGDATE
VAL_DATE_BANK
VALUE_DATE_CUST
OTHR_PARTY_NAME
DRAWEE_BNK_NAME
AUTOLIQD
INTREMRKS
FINANCING
MARGIN_PERCENTAGE
TRACK_LIMIT
CRLINE
DISCOUNTAMT
MAKER
MAKDTTIME
CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
VERSION_NO
LATVERNO
Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*

RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4

BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*

ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*

TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1

- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Clpref

- *CONTREFNNO*
- *CONTRACT_CCY*
- *LATEVNSEQNO*
- *PRD*
- *PRDDESC*
- *COUNTERPARTY*
- *CURRENCY*
- *TENOR*
- *UNITS*
- *LOAN_CONREFNO*
- *RATECODE*
- *EXCHANGERATE*
- *RATE_TYPE*
- *MAXIMUM*
- *MINIMUM*
- *PAYMENT_MODE*
- *LOANVALDATE*
- *MATURITY_DATE*

Ude

USERDEID

UDEDESC

RATEASOF

USAGE

USERDEVAL

Con

CONTREFNO

EVENTSEQ

Adv

ADVNAME

SUPRESS

PRIOR

MEDM

PARTYIDEN

PARTYNAME

CHGREQ

PARTTYP

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PRODUCT_CODE

Attribute	Description	
Name	PRODUCT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CONREFNUM

Attribute	Description	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USERREF_NO1

Attribute	Description	
Name	USERREF_NO1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCH_SEQ_NO

Attribute	Description
Name	BATCH_SEQ_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CASHLETTER_REFNUM

Attribute	Description
Name	CASHLETTER_REFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CTR_PRTY_NAME

Attribute	**Description**	
Name	CTR_PRTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTY_AC_NO

Attribute	**Description**	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACC_BRANCH

Attribute	**Description**	
Name	ACC_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INSTRUMENTNORE

Attribute	**Description**	
Name	INSTRUMENTNORE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

COLLECTINGBANKCIF

Attribute	**Description**	
Name	COLLECTINGBANKCIF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

COLL_BNK_NAME

Attribute	**Description**	
Name	COLL_BNK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BOOKINGDATE

Attribute	**Description**	
Name	BOOKINGDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTREMRKS

Attribute	**Description**	
Name	INTREMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,N,F

TOP

MARGIN_PERCENTAGE

Attribute	**Description**	
Name	MARGIN_PERCENTAGE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRACK_LIMIT

Attribute	**Description**	
Name	TRACK_LIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CRLINE

Attribute	Description
Name	CRLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,L,R,H,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATVERNO

Attribute	**Description**	
Name	LATVERNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Settlements

Attribute	**Description**	
Name	Settlements	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Settlement

Attribute	**Description**	
Name	Contract-Settlement	
Datatype		
Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	**Description**
Name	IBANACNO
Datatype	String

Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	Description	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	Description	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	Description	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS5

Attribute	Description	
Name	FUNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS6

Attribute	Description	
Name	FUNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS7

Attribute	Description	
Name	FUNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS8

Attribute	Description	
Name	FUNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.56.4.RB-Createfcychecksinput-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONREFNUM*
      - *USERREF_NO1*
      - *XREF*
    - *Main-IO*
      - *INSTRUMENT_CODE*
      - *PRODUCT_CODE*
      - *CONREFNUM*
      - *USERREF_NO1*
      - *XREF*
      - *BATCHREFENUM*
      - *CPTY_ID*
      - *CPTY_AC_NO*
      - *INSTRUMENTNORE*
      - *INSTRUMENT_DATE*
      - *CURRENCY*
      - *AMNT*
      - *VALUE_DATE_CUST*

OTHR_PARTY_NAME
DRAWEE_BNK_NAME
AUTOLIQD
INTREMRKS
FINANCING
MARGIN_PERCENTAGE
TRACK_LIMIT
CRLINE
Settlements
- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*
  - *RECVCVR*

RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5

BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *ULTBANDCD*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*
- *NOOFDEC*
- *ADDID*
- *SNDRRCVRINFO1*
- *SNDRRCVRINFO2*
- *SNDRRCVRINFO3*
- *SNDRRCVRINFO4*
- *SNDRRCVRINFO5*

- *SNDRRCVRINFO6*
- *DECLARTION*
- *REPRES1*
- *REPRES2*
- *REPRES3*
- *REPRES4*
- *RCVRACC*

Charges

- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*

TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Clpref
CONTREFNNO
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE

Ude

USERDEID

UDEDESC

RATEASOF

USAGE

USERDEVAL

Con

CONTREFNO

EVENTSEQ

Adv

SUPRESS

PRIOR

MEDM

CHGREQ

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRODUCT_CODE

Attribute	Description
Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENTNORE

Attribute	Description
Name	INSTRUMENTNORE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRLINE

Attribute	Description
Name	CRLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement

Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	**Description**	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2

Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3

Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	**Description**	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5

Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID

Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1

Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO

Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

CHGREQ

Attribute	**Description**	
Name	CHGREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	**Description**

Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.57.DeleteBulkInwardInput

DeleteBulkInwardInput

2.57.1.RB-DeleteBulkInwardInput-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Full*
    - *INSTRUMENT_CODE*
    - *BATCHREFENUM*
    - *PRDCD*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *ACCBRN*
    - *CPTY_AC_NO*
    - *OTHRPTY_ID*
    - *OTHRPTY_NM*
    - *BNKCD*
    - *BRNCODE*
    - *CORRESPBNK*
    - *CORRESPACNO*
    - *BOKNGDT*
    - *PROTEST*

AUTOLIQD
NOOFINSTRUMENTS
ACFORREALISATION
CRACCBRN
CCY
PROCESSSTAT
EVENTSEQNO
ESNLOG
RECORDSTAT
AUTHSTAT
CHKR
CHKDTTIME
BULKREF
MAKER
MAKDTTIME
Bulkinput-Detail
- *CONREFNUM*
- *INSTRNO*
- *INSTRU_DATE*
- *CURRENCY*
- *AMNT*
- *REMITBANK_REF*
- *REM_BNK_DT*
- *LCY_AMOUNTT*
- *MATURITYDATE*
- *GRACEDAYS*
- *REMARKS*
- *PROCESSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Full

Attribute	Description
Name	Bulk-Input-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRDCD

Attribute	**Description**	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CPTY_ID

Attribute	**Description**	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_NAME

Attribute	**Description**	
Name	CPTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

OTHRPTY_ID

Attribute	Description
Name	OTHRPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OTHRPTY_NM

Attribute	Description
Name	OTHRPTY_NM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

CORRESPBNK

Attribute	Description
Name	CORRESPBNK
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

CORRESPACNO

Attribute	Description
Name	CORRESPACNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 20

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

PROTEST

Attribute	Description
Name	PROTEST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRACCBRN

Attribute	Description
Name	CRACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESNLOG

Attribute	Description
Name	ESNLOG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BULKREF

Attribute	Description
Name	BULKREF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Bulkinput-Detail

Attribute	Description
Name	Bulkinput-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

REM_BNK_DT

Attribute	**Description**	
Name	REM_BNK_DT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCY_AMOUNTT

Attribute	**Description**	
Name	LCY_AMOUNTT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MATURITYDATE

Attribute	**Description**	
Name	MATURITYDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GRACEDAYS

Attribute	**Description**	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,S,U,F,H</td></tr></table>

TOP

2.57.2.RB-DeleteBulkInwardInput-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-IO*
    - *BATCHREFENUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.57.3.RB-DeleteBulkInwardInput-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Full*
    - *INSTRUMENT_CODE*
    - *BATCHREFENUM*
    - *PRDCD*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *ACCBRN*
    - *CPTY_AC_NO*
    - *OTHRPTY_ID*
    - *OTHRPTY_NM*
    - *BNKCD*
    - *BRNCODE*
    - *CORRESPBNK*
    - *CORRESPACNO*
    - *BOKNGDT*
    - *PROTEST*
    - *AUTOLIQD*
    - *NOOFINSTRUMENTS*
    - *ACFORREALISATION*

CRACCBRN
CCY
PROCESSSTAT
EVENTSEQNO
ESNLOG
RECORDSTAT
AUTHSTAT
CHKR
CHKDTTIME
BULKREF
MAKER
MAKDTTIME
Bulkinput-Detail
CONREFNUM
INSTRNO
INSTRU_DATE
CURRENCY
AMNT
REMITBANK_REF
REM_BNK_DT
LCY_AMOUNTT
MATURITYDATE
GRACEDAYS
REMARKS
PROCESSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Full

Attribute	Description
Name	Bulk-Input-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CPTY_AC_NO

Attribute	**Description**	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

OTHRPTY_ID

Attribute	**Description**	
Name	OTHRPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OTHRPTY_NM

Attribute	**Description**	
Name	OTHRPTY_NM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BNKCD

Attribute	**Description**	
Name	BNKCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CORRESPBNK

Attribute	Description
Name	CORRESPBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CORRESPACNO

Attribute	Description
Name	CORRESPACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CRACCBRN

Attribute	Description
Name	CRACCBRN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PROCESSSTAT

Attribute	**Description**	
Name	PROCESSSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,U

TOP

EVENTSEQNO

Attribute	**Description**	
Name	EVENTSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ESNLOG

Attribute	**Description**	
Name	ESNLOG	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,O,C</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BULKREF

Attribute	Description
Name	BULKREF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Bulkinput-Detail

Attribute	Description
Name	Bulkinput-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REM_BNK_DT

Attribute	Description
Name	REM_BNK_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCY_AMOUNTT

Attribute	Description
Name	LCY_AMOUNTT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,U,F,H

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description

Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.57.4.RB-DeleteBulkInwardInput-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Input-PK*
      - *BATCHREFENUM*
    - *Bulk-Input-IO*
      - *BATCHREFENUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Input-PK

Attribute	Description
Name	Bulk-Input-PK
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.58.DeleteBulkInwardPDR

DeleteBulkInwardPDR

2.58.1.RB-DeleteBulkInwardPDR-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Pdr-Full*
    - *BATCHREFENUM*
    - *BULKPDRREFNO*
    - *ACTION*
    - *PRDTY*
    - *CPTY_ID*
    - *COUNTRPRYNAM*
    - *OTHRPTY_ID*
    - *OTHRPTY_NM*
    - *BANK_CODE*
    - *BANK_NAME*
    - *BRNCODE*
    - *BRANCH_NAME*
    - *VALUEDT*
    - *RETURN_DATE*
    - *PROCESSSTAT*

SEQNO
ESN
TXNSTAT
AUTHSTAT
CHKR
CHKDTTIME
MKRID
MKRDT
Bulk-Pdr-Detail
- *CONREFNUM*
- *INSTRNO*
- *INSTRUMENT_DATE*
- *REMITBANK_REF*
- *CCY*
- *AMT*
- *REASON_CODE*
- *DISHONOUR_DATE*
- *NOTARYCODE*
- *PROTESTDATE*
- *REMARKS*
- *PROCESSSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Pdr-Full

Attribute	Description
Name	Bulk-Pdr-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

PRDTY

Attribute	Description
Name	PRDTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHRPTY_ID

Attribute	Description
Name	OTHRPTY_ID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OTHRPTY_NM

Attribute	**Description**	
Name	OTHRPTY_NM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BANK_CODE

Attribute	**Description**	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANK_NAME

Attribute	**Description**	
Name	BANK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNCODE

Attribute	**Description**	
Name	BRNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRANCH_NAME

Attribute	Description
Name	BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,P

TOP

SEQNO

Attribute	Description
Name	SEQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MKRID

Attribute	Description
Name	MKRID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MKRDT

Attribute	Description
Name	MKRDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Bulk-Pdr-Detail

Attribute	Description
Name	Bulk-Pdr-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description

Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DISHONOUR_DATE

Attribute	Description
Name	DISHONOUR_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,P

TOP

2.58.2.RB-DeleteBulkInwardPDR-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Pdr-IO*
    - *BULKPDRREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Pdr-IO

Attribute	Description
Name	Bulk-Pdr-IO
Datatype	
Description	

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.58.3.RB-DeleteBulkInwardPDR-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Pdr-Full*
    - *BATCHREFENUM*
    - *BULKPDRREFNO*
    - *ACTION*
    - *PRDTY*
    - *CPTY_ID*
    - *COUNTRPRYNAM*
    - *OTHRPTY_ID*
    - *OTHRPTY_NM*
    - *BANK_CODE*
    - *BANK_NAME*
    - *BRNCODE*
    - *BRANCH_NAME*
    - *VALUEDT*
    - *RETURN_DATE*
    - *PROCESSSTAT*
    - *SEQNO*
    - *ESN*
    - *TXNSTAT*

AUTHSTAT
CHKR
CHKDTTIME
MKRID
MKRDT
Bulk-Pdr-Detail
CONREFNUM
INSTRNO
INSTRUMENT_DATE
REMITBANK_REF
CCY
AMT
REASON_CODE
DISHONOUR_DATE
NOTARYCODE
PROTESTDATE
REMARKS
PROCESSSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Pdr-Full

Attribute	Description
Name	Bulk-Pdr-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

PRDTY

Attribute	Description	
Name	PRDTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CPTY_ID

Attribute	Description	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHRPTY_ID

Attribute	Description
Name	OTHRPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

OTHRPTY_NM

Attribute	Description
Name	OTHRPTY_NM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BANK_CODE

Attribute	Description
Name	BANK_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BANK_NAME

Attribute	Description
Name	BANK_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BRNCODE

Attribute	Description
Name	BRNCODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRANCH_NAME

Attribute	Description
Name	BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,P

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MKRID

Attribute	Description
Name	MKRID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKRDT

Attribute	Description
Name	MKRDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Bulk-Pdr-Detail

Attribute	Description
Name	Bulk-Pdr-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CCY

Attribute	Description
Name	CCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DISHONOUR_DATE

Attribute	Description
Name	DISHONOUR_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,P</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.58.4.RB-DeleteBulkInwardPDR-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Pdr-PK*
      - *BULKPDRREFNO*
    - *Bulk-Pdr-IO*
      - *BULKPDRREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Pdr-PK

Attribute	Description
Name	Bulk-Pdr-PK
Datatype	
Description	

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Pdr-IO

Attribute	Description
Name	Bulk-Pdr-IO
Datatype	
Description	

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.59.DeleteBulkInwardReal

DeleteBulkInwardReal

2.59.1.RB-DeleteBulkInwardReal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liq-Master-Full*
    - *BATCHREFENUM*
    - *BULKREALNUM*
    - *CPTY_ID*
    - *DUP_CPTY_NAME*
    - *CCY*
    - *OTHRPTY_ID*
    - *OTHRPTY_NM*
    - *BNKCD*
    - *BANK_NAME*
    - *BRNCODE*
    - *BRNNAME*
    - *CPTY_AC_NO*
    - *ACFORREALISATION*
    - *CRACCBRN*
    - *VALUEDATE*

ACCBRN
CORRESPBNK
CORRESPACNO
NETAMT_REAL
PROCESSSTAT
EVENTSEQNO
RECORDSTAT
AUTHSTAT
CKRID
CHKDTTIME
BULKREF
ESN
MAKER
MAKDTTIME
Liq-Detail
- *CONREFNUM*
- *INSTRNO*
- *INSTRUMENT_DATE*
- *REMITBANK_REF*
- *REM_BNK_DT*
- *AMNT*
- *REMRKS*
- *PROCESSSTAT*
- *OTHRBNKCHARGS*
- *NETAMT_REAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liq-Master-Full

Attribute	Description
Name	Liq-Master-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DUP_CPTY_NAME

Attribute	Description
Name	DUP_CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OTHRPTY_ID

Attribute	Description
Name	OTHRPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OTHRPTY_NM

Attribute	Description
Name	OTHRPTY_NM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BANK_NAME

Attribute	Description
Name	BANK_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BRNNAME

Attribute	Description
Name	BRNNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRACCBRN

Attribute	Description
Name	CRACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

ACCBRN

Attribute	**Description**
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CORRESPBNK

Attribute	**Description**
Name	CORRESPBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CORRESPACNO

Attribute	**Description**
Name	CORRESPACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

NETAMT_REAL

Attribute	**Description**
Name	NETAMT_REAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,P</td></tr></table>

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,O,C</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

CKRID

Attribute	Description
Name	CKRID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BULKREF

Attribute	**Description**	
Name	BULKREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	Description	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Liq-Detail

Attribute	Description	
Name	Liq-Detail	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CONREFNUM

Attribute	Description	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INSTRNO

Attribute	Description	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRUMENT_DATE

Attribute	Description

Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REM_BNK_DT

Attribute	Description
Name	REM_BNK_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,P</td></tr></table>

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NETAMT_REAL

Attribute	Description
Name	NETAMT_REAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.59.2.RB-DeleteBulkInwardReal-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Liq-Master-IO*
  - *BULKREALNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liq-Master-IO

Attribute	Description
Name	Liq-Master-IO
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.59.3.RB-DeleteBulkInwardReal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liq-Master-Full*
    - *BATCHREFENUM*
    - *BULKREALNUM*
    - *CPTY_ID*
    - *DUP_CPTY_NAME*
    - *CCY*
    - *OTHRPTY_ID*
    - *OTHRPTY_NM*
    - *BNKCD*
    - *BANK_NAME*
    - *BRNCODE*
    - *BRNNAME*
    - *CPTY_AC_NO*
    - *ACFORREALISATION*
    - *CRACCBRN*
    - *VALUEDATE*
    - *ACCBRN*
    - *CORRESPBNK*
    - *CORRESPACNO*

NETAMT_REAL
PROCESSSTAT
EVENTSEQNO
RECORDSTAT
AUTHSTAT
CKRID
CHKDTTIME
BULKREF
ESN
MAKER
MAKDTTIME
Liq-Detail
CONREFNUM
INSTRNO
INSTRUMENT_DATE
REMITBANK_REF
REM_BNK_DT
AMNT
REMRKS
PROCESSSTAT
OTHRBNKCHARGS
NETAMT_REAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liq-Master-Full

Attribute	Description
Name	Liq-Master-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DUP_CPTY_NAME

Attribute	Description
Name	DUP_CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OTHRPTY_ID

Attribute	Description
Name	OTHRPTY_ID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OTHRPTY_NM

Attribute	**Description**	
Name	OTHRPTY_NM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BNKCD

Attribute	**Description**	
Name	BNKCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANK_NAME

Attribute	**Description**	
Name	BANK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNCODE

Attribute	**Description**	
Name	BRNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTY_AC_NO

Attribute	**Description**	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACFORREALISATION

Attribute	**Description**	
Name	ACFORREALISATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CRACCBRN

Attribute	**Description**	
Name	CRACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CORRESPBNK

Attribute	Description
Name	CORRESPBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CORRESPACNO

Attribute	Description
Name	CORRESPACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

NETAMT_REAL

Attribute	Description
Name	NETAMT_REAL

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,P

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CKRID

Attribute	Description
Name	CKRID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BULKREF

Attribute	Description
Name	BULKREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Liq-Detail

Attribute	Description
Name	Liq-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

REM_BNK_DT

Attribute	Description
Name	REM_BNK_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PROCESSSTAT

Attribute	**Description**	
Name	PROCESSSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,P

TOP

OTHRBNKCHARGS

Attribute	**Description**	
Name	OTHRBNKCHARGS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETAMT_REAL

Attribute	**Description**	
Name	NETAMT_REAL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**

Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.59.4.RB-DeleteBulkInwardReal-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Liq-Master-PK*
      - *BULKREALNUM*
    - *Liq-Master-IO*
      - *BULKREALNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Liq-Master-PK

Attribute	Description
Name	Liq-Master-PK
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Liq-Master-IO

Attribute	Description
Name	Liq-Master-IO
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.60.DeleteBulkOutClearing

DeleteBulkOutClearing

2.60.1.RB-DeleteBulkOutClearing-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Full*
    - *CRDLINE*
    - *OTHPARTYLIMIT*
    - *MARGINPERC*
    - *FINANCING*
    - *COLLATERAL*
    - *COLLPOOL*
    - *INSTRUCODE*
    - *PRDCODE*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *CURRENCY*
    - *OTHRPTYIDEN*
    - *DRACCREAL*
    - *NOOFINSTRUMENTS*
    - *CLGPRD*

ISRBNK
ISSUERBRN
CLRBNK
CLGBRN
SECTORCR
ENDPOINT
ROUTNO
CHECKINSERIES
FIRSTINSTRNO
BOOKINGDATE
TRACKLIMIT
INSTRUMENT_DESCRIPTION
INSTRDESC
COUNTRPRYNAM
OTHERPARTYNAME
ISSBANKNAME
ISSBRNCNAME
CLEARBANKNAME
CLEARBRNCNAME
BATCHREFENUM
ACCBRN
PROCESSTAT
CONTSTATUS
AUTSTAT
CHECKER
CHECKERDT
VERSIONNUM
MKER
MAKERDT
DRACCBRN
VERNUMBER
Input-Detail
- *CONREFNUM*
- *INSTRNO*
- *INSTRDATE*
- *LCYAMT*
- *AMNT*
- *VALUEDATE*
- *DISCAMT*
- *COLLTVAL*
- *INTREMRKS*
- *PROCESSSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Full

Attribute	Description
Name	Bulk-Input-Full
Datatype	
Description	

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,F,N</td></tr></table>

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CLGPRD

Attribute	Description
Name	CLGPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ISRBNK

Attribute	Description
Name	ISRBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ISSUERBRN

Attribute	Description
Name	ISSUERBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CLRBNK

Attribute	Description
Name	CLRBNK

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBRN

Attribute	Description
Name	CLGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SECTORCR

Attribute	Description
Name	SECTORCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	27

TOP

CHECKINSERIES

Attribute	**Description**	
Name	CHECKINSERIES	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FIRSTINSTRNO

Attribute	**Description**	
Name	FIRSTINSTRNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKINGDATE

Attribute	**Description**	
Name	BOOKINGDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRACKLIMIT

Attribute	**Description**	
Name	TRACKLIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description
Name	INSTRUMENT_DESCRIPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

INSTRDESC

Attribute	Description
Name	INSTRDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ISSBANKNAME

Attribute	Description
Name	ISSBANKNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSBRNCNAME

Attribute	Description
Name	ISSBRNCNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CLEARBANKNAME

Attribute	Description
Name	CLEARBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CLEARBRNCNAME

Attribute	Description
Name	CLEARBRNCNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,E

TOP

CONTSTATUS

Attribute	Description
Name	CONTSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,O,C

TOP

AUTSTAT

Attribute	Description
Name	AUTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDT

Attribute	Description	
Name	CHECKERDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

VERSIONNUM

Attribute	Description	
Name	VERSIONNUM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MKER

Attribute	Description	
Name	MKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VERNUMBER

Attribute	Description
Name	VERNUMBER
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Input-Detail

Attribute	Description
Name	Input-Detail
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTVAL

Attribute	Description
Name	COLLTVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,F,H

TOP

2.60.2.RB-DeleteBulkOutClearing-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-IO*
    - *BATCHREFENUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.60.3.RB-DeleteBulkOutClearing-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Full*
    - *CRDLINE*
    - *OTHPARTYLIMIT*
    - *MARGINPERC*
    - *FINANCING*
    - *COLLATERAL*
    - *COLLPOOL*
    - *INSTRUCODE*
    - *PRDCODE*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *CURRENCY*
    - *OTHRPTYIDEN*
    - *DRACCREAL*
    - *NOOFINSTRUMENTS*
    - *CLGPRD*
    - *ISRBNK*
    - *ISSUERBRN*
    - *CLRBNK*

- *CLGBRN*
- *SECTORCR*
- *ENDPOINT*
- *ROUTNO*
- *CHECKINSERIES*
- *FIRSTINSTRNO*
- *BOOKINGDATE*
- *TRACKLIMIT*
- *INSTRUMENT_DESCRIPTION*
- *INSTRDESC*
- *COUNTRPRYNAM*
- *OTHERPARTYNAME*
- *ISSBANKNAME*
- *ISSBRNCNAME*
- *CLEARBANKNAME*
- *CLEARBRNCNAME*
- *BATCHREFENUM*
- *ACCBRN*
- *PROCESSTAT*
- *CONTSTATUS*
- *AUTSTAT*
- *CHECKER*
- *CHECKERDT*
- *VERSIONNUM*
- *MKER*
- *MAKERDT*
- *DRACCBRN*
- *VERNUMBER*
- *Input-Detail*
  - *CONREFNUM*
  - *INSTRNO*
  - *INSTRDATE*
  - *LCYAMT*
  - *AMNT*
  - *VALUEDATE*
  - *DISCAMT*
  - *COLLTVAL*
  - *INTREMRKS*
  - *PROCESSSTAT*

FCUBS_ERROR_RESP

- *ERROR*
  - *ECODE*
  - *EDESC*

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Full

Attribute	Description

Name	Bulk-Input-Full
Datatype	
Description	

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,F,N

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTYIDEN

Attribute	Description

Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

NOOFINSTRUMENTS

Attribute	**Description**	
Name	NOOFINSTRUMENTS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

CLGPRD

Attribute	**Description**	
Name	CLGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ISRBNK

Attribute	**Description**	
Name	ISRBNK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ISSUERBRN

Attribute	**Description**	
Name	ISSUERBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CLRBNK

Attribute	Description
Name	CLRBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBRN

Attribute	Description
Name	CLGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SECTORCR

Attribute	Description
Name	SECTORCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>27</td></tr></table>

TOP

CHECKINSERIES

Attribute	Description
Name	CHECKINSERIES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

FIRSTINSTRNO

Attribute	Description
Name	FIRSTINSTRNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description
Name	INSTRUMENT_DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSTRDESC

Attribute	Description
Name	INSTRDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ISSBANKNAME

Attribute	Description
Name	ISSBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSBRNCNAME

Attribute	Description
Name	ISSBRNCNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CLEARBANKNAME

Attribute	Description
Name	CLEARBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CLEARBRNCNAME

Attribute	Description
Name	CLEARBRNCNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,E</td></tr></table>

TOP

CONTSTATUS

Attribute	Description
Name	CONTSTATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,O,C</td></tr></table>

TOP

AUTSTAT

Attribute	Description
Name	AUTSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDT

Attribute	Description
Name	CHECKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VERSIONNUM

Attribute	Description
Name	VERSIONNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MKER

Attribute	Description
Name	MKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDT

Attribute	Description	
Name	MAKERDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DRACCBRN

Attribute	Description	
Name	DRACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

VERNUMBER

Attribute	Description	
Name	VERNUMBER	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Input-Detail

Attribute	Description	
Name	Input-Detail	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CONREFNUM

Attribute	Description

Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTVAL

Attribute	Description
Name	COLLTVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,S,F,H

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.60.4.RB-DeleteBulkOutClearing-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Input-PK*
      - *BATCHREFENUM*
    - *Bulk-Input-IO*
      - *BATCHREFENUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Input-PK

Attribute	Description
Name	Bulk-Input-PK
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.61.DeleteBulkPDRContract

DeleteBulkPDRContract

2.61.1.RB-DeleteBulkPDRContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulkpdr-Full*
    - *BANK_CODE*
    - *BRNCODE*
    - *BANKNAME*
    - *BRNNAME*
    - *ACTION*
    - *DISPATCHLOTREFNO*
    - *BULKPDRREFNO*
    - *PROCESSTAT*
    - *AUTHSTAT*
    - *CHKR*
    - *CHKDTTIME*
    - *EVSEQNO*
    - *MAKER*
    - *MAKDTTIME*
    - *RECORDSTAT*

ESNUI

Bulkpdrdetail

CONREFNUM

ACC_CCY

AMNT

DISHONOUR_DATE

NOTARYCODE

PROTESTDATE

INTREMRKS

DISHONOUR_REASON

RETURN_DATE

CPTYIDEN

OTHRPTYIDEN

CPTYNAME

OTHERPARTYNAME

INSTRNO

PROCESSSTAT

PRDTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	**Description**	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulkpdr-Full

Attribute	Description
Name	Bulkpdr-Full
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description	Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BRNCODE

Attribute	Description	
Name	BRNCODE	
Datatype	String	
Description	Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BANKNAME

Attribute	Description	
Name	BANKNAME	
Datatype	String	
Description	Bank Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

DISPATCHLOTREFNO

Attribute	**Description**	
Name	DISPATCHLOTREFNO	
Datatype	String	
Description	Dispatch Lot Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BULKPDRREFNO

Attribute	**Description**	
Name	BULKPDRREFNO	
Datatype	String	
Description	Bulk Dishonor / Protest / Return Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PROCESSTAT

Attribute	Description	
Name	PROCESSTAT	
Datatype	String	
Description	Process Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,U

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

CHKR

Attribute	Description	
Name	CHKR	
Datatype	String	
Description	Checker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	Description	
Name	CHKDTTIME	
Datatype	String	
Description	Date Time	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

EVSEQNO

Attribute	Description
Name	EVSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	Date Time
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	Record Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,O,C</td></tr></table>

TOP

ESNUI

Attribute	Description
Name	ESNUI
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bulkpdrdetail

Attribute	Description
Name	Bulkpdrdetail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISHONOUR_DATE

Attribute	Description

Name	DISHONOUR_DATE
Datatype	Date
Description	Dishonour Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	Notary Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	Protest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Internal Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DISHONOUR_REASON

Attribute	Description
Name	DISHONOUR_REASON
Datatype	String
Description	Dishonor Reason
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	Return Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	CounterParty Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	Other Party Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	CounterParty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME

Datatype	String
Description	Other Party Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	Instrument Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,H,S,F

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Product Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

2.61.2.RB-DeleteBulkPDRContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulkpdr-IO*
    - *BULKPDRREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulkpdr-IO

Attribute	Description
Name	Bulkpdr-IO
Datatype	
Description	

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	Bulk Dishonor / Protest / Return Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.61.3.RB-DeleteBulkPDRContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulkpdr-Full*
    - *BANK_CODE*
    - *BRNCODE*
    - *BANKNAME*
    - *BRNNAME*
    - *ACTION*
    - *DISPATCHLOTREFNO*
    - *BULKPDRREFNO*
    - *PROCESSTAT*
    - *AUTHSTAT*
    - *CHKR*
    - *CHKDTTIME*
    - *EVSEQNO*
    - *MAKER*
    - *MAKDTTIME*
    - *RECORDSTAT*
    - *ESNUI*
    - *Bulkpdrdetail*
      - *CONREFNUM*

ACC_CCY
AMNT
DISHONOUR_DATE
NOTARYCODE
PROTESTDATE
INTREMRKS
DISHONOUR_REASON
RETURN_DATE
CPTYIDEN
OTHRPTYIDEN
CPTYNAME
OTHERPARTYNAME
INSTRNO
PROCESSSTAT
PRDTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulkpdr-Full

Attribute	Description
Name	Bulkpdr-Full
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description	Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BRNCODE

Attribute	Description	
Name	BRNCODE	
Datatype	String	
Description	Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BANKNAME

Attribute	Description	
Name	BANKNAME	
Datatype	String	
Description	Bank Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description	Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

DISPATCHLOTREFNO

Attribute	Description	
Name	DISPATCHLOTREFNO	
Datatype	String	
Description	Dispatch Lot Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BULKPDRREFNO

Attribute	Description

Name	BULKPDRREFNO
Datatype	String
Description	Bulk Dishonor / Protest / Return Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,U

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	Checker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	Date Time

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVSEQNO

Attribute	Description
Name	EVSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	Date Time
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,O,C

TOP

ESNUI

Attribute	Description
Name	ESNUI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bulkpdrdetail

Attribute	Description
Name	Bulkpdrdetail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number

Description	Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISHONOUR_DATE

Attribute	Description
Name	DISHONOUR_DATE
Datatype	Date
Description	Dishonour Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	Notary Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	Protest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Internal Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DISHONOUR_REASON

Attribute	Description

Name	DISHONOUR_REASON
Datatype	String
Description	Dishonor Reason
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	Return Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	CounterParty Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	Other Party Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	CounterParty Name
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYNAME

Attribute	**Description**	
Name	OTHERPARTYNAME	
Datatype	String	
Description	Other Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INSTRNO

Attribute	**Description**	
Name	INSTRNO	
Datatype	String	
Description	Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

PROCESSSTAT

Attribute	**Description**	
Name	PROCESSSTAT	
Datatype	String	
Description	Process Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,H,S,F

TOP

PRDTYP

Attribute	**Description**	
Name	PRDTYP	
Datatype	String	
Description	Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.61.4.RB-DeleteBulkPDRContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulkpdr-PK*
      - *BULKPDRREFNO*
    - *Bulkpdr-IO*
      - *BULKPDRREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulkpdr-PK

Attribute	Description
Name	Bulkpdr-PK
Datatype	
Description	

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	Bulk Dishonor / Protest / Return Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Bulkpdr-IO

Attribute	Description
Name	Bulkpdr-IO
Datatype	
Description	

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	Bulk Dishonor / Protest / Return Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.62.DeleteBulkRealization

DeleteBulkRealization

2.62.1.RB-DeleteBulkRealization-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-Full*
    - *BULKREALNUM*
    - *DISLOTREF*
    - *DRACFORREALISATION*
    - *COLBANKREFNUM*
    - *VDATE*
    - *CURRENCY*
    - *TOTNETREAL*
    - *DRACCBRN*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *CHKR*
    - *CHKDTTIME*
    - *EVENSEQNO*
    - *MAKER*
    - *MAKDTTIME*

PROCESSTAT

MAXESN

Detail

CONREFNUM

AMUNT

INTREMRKS

NETREALAMT

CUSTNUMBER1

OTHRBNKCHARGS

INSTRNO

PROCESSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	Bulk Realization Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

DISLOTREF

Attribute	Description
Name	DISLOTREF
Datatype	String
Description	Dispatch Lot Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

DRACFORREALISATION

Attribute	Description
Name	DRACFORREALISATION
Datatype	String
Description	Debit Account for Realization
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	Collecting Bank Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VDATE

Attribute	Description
Name	VDATE
Datatype	Date
Description	Value date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TOTNETREAL

Attribute	Description
Name	TOTNETREAL
Datatype	Number
Description	Total Net Realized
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Debit Account Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,O,C,H

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description	Checker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description	Date Time	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVENSEQNO

Attribute	Description
Name	EVENSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	Date Time
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U,F

TOP

MAXESN

Attribute	Description
Name	MAXESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Detail

Attribute	Description
Name	Detail
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

AMUNT

Attribute	Description
Name	AMUNT
Datatype	Number
Description	Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Internal Remarks
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

NETREALAMT

Attribute	Description
Name	NETREALAMT
Datatype	Number
Description	Net Realized Amount
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CUSTNUMBER1

Attribute	Description
Name	CUSTNUMBER1
Datatype	String
Description	Customer Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	Other Bank Charges
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	Instrument Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT

Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U,F

TOP

2.62.2.RB-DeleteBulkRealization-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-IO*
    - *BULKREALNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	Bulk Realization Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.62.3.RB-DeleteBulkRealization-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-Full*
    - *BULKREALNUM*
    - *DISLOTREF*
    - *DRACFORREALISATION*
    - *COLBANKREFNUM*
    - *VDATE*
    - *CURRENCY*
    - *TOTNETREAL*
    - *DRACCBRN*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *CHKR*
    - *CHKDTTIME*
    - *EVENSEQNO*
    - *MAKER*
    - *MAKDTTIME*
    - *PROCESSTAT*
    - *MAXESN*
    - *Detail*

CONREFNUM
AMUNT
INTREMRKS
NETREALAMT
CUSTNUMBER1
OTHRBNKCHARGS
INSTRNO
PROCESSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	Bulk Realization Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DISLOTREF

Attribute	Description
Name	DISLOTREF
Datatype	String
Description	Dispatch Lot Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRACFORREALISATION

Attribute	Description
Name	DRACFORREALISATION
Datatype	String
Description	Debit Account for Realization
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	Collecting Bank Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VDATE

Attribute	Description
Name	VDATE
Datatype	Date
Description	Value date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TOTNETREAL

Attribute	Description
Name	TOTNETREAL
Datatype	Number
Description	Total Net Realized
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Debit Account Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,O,C,H

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description	Checker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description	Date Time	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVENSEQNO

Attribute	Description
Name	EVENSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	Date Time
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U,F

TOP

MAXESN

Attribute	Description
Name	MAXESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Detail

Attribute	Description
Name	Detail
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

AMUNT

Attribute	Description
Name	AMUNT
Datatype	Number
Description	Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Internal Remarks
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

NETREALAMT

Attribute	Description
Name	NETREALAMT
Datatype	Number
Description	Net Realized Amount
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CUSTNUMBER1

Attribute	Description
Name	CUSTNUMBER1
Datatype	String
Description	Customer Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	Other Bank Charges
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT

Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U,F

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.62.4.RB-DeleteBulkRealization-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Master-PK*
      - *BULKREALNUM*
    - *Master-IO*
      - *BULKREALNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Master-PK

Attribute	Description
Name	Master-PK
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	Bulk Realization Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	Bulk Realization Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.63.DeleteCashletterdishonour

DeleteCashletterdishonour

2.63.1.RB-DeleteCashletterdishonour-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CASHREFNO*
    - *CPTY_ID*
    - *COUNTRPRYNAM*
    - *INSTRNO*
    - *INSTRU_DATE*
    - *CURRENCY*
    - *AMNT*
    - *COLLBNKNAME*
    - *BOKNGDT*
    - *OTHR_PARTYNAME*
    - *DRAWEE_BNK_NAME*
    - *REASON_CODE*
    - *REASON*
    - *DT_OF_DISHONOR*

OTHRBNKCHARGS
REMRKS
MAKER
MAKDTTIME
CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Charges
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*

CHRGAMT

LIQDSTAT

Misdetails

CONREFNO

LATESN

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*
  - *RECVCVR*
  - *RECEIVER*
  - *REIMINST1*
  - *REIMINST2*
  - *REIMINST3*

REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5

REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*

ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REASON

Attribute	Description
Name	REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DT_OF_DISHONOR

Attribute	Description
Name	DT_OF_DISHONOR
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,L,A</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr></table>

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description

Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description

Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	**Description**
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	**Description**
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	**Description**
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	**Description**
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	Description	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	Description	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	Description	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRPART

Attribute	Description	
Name	SNDRRCVRPART	
Datatype	Number	
Description	Indicates Sender Receiver Participant	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	Description	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

2.63.2.RB-DeleteCashletterdishonour-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Main-IO
CONREFNUM

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.63.3.RB-DeleteCashletterdishonour-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CASHREFNO*
    - *CPTY_ID*
    - *COUNTRPRYNAM*
    - *INSTRNO*
    - *INSTRU_DATE*
    - *CURRENCY*
    - *AMNT*
    - *COLLBNKNAME*
    - *BOKNGDT*
    - *OTHR_PARTYNAME*
    - *DRAWEE_BNK_NAME*
    - *REASON_CODE*
    - *REASON*
    - *DT_OF_DISHONOR*
    - *OTHRBNKCHARGS*
    - *REMRKS*
    - *MAKER*

MAKDTTIME
CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
Con
  CONTREFNO
  EVENTSEQ
  Adv
    ADVNAME
    SUPRESS
    PRIOR
    MEDM
    PARTYIDEN
    PARTYNAME
    CHGREQ
    PARTTYP
Charges
  CONREFNO
  Charge-Association
    COMPNT
    CREATESN
    RULE
    WAIVER
    DISACCRAPPL
    ACCRREQD
    DESC
  Charge-Application
    CREATESN
    COMPNT
    TGCCY
    TGAMT
    CHRGCCY
    CHRGAMT
    DISACCRAPPL
    WAIVER
    LIQDIND
  Charge-Liquidation
    ESN
    COMPNT
    CHRGCCY
    CHRGAMT
    LIQDSTAT
Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3

FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Settlements

CONREFNO

Contract-Settlement

- *IBANACNO*
- *CUSTSPREAD*
- *SPREADDEFN*
- *COMPNT*
- *TAGCCY*
- *ACCBRN*
- *ACC*
- *ACCCCY*
- *EXRATE*
- *NETIND*
- *ERICCY*
- *ERIAMT*
- *GENMSG*
- *RATECD*
- *CLEARNW*
- *COVERBY*
- *RTGSPMNT*
- *BANKPRIOR*
- *RTGSNW*
- *PAYBY*
- *TRANSTYP*
- *INSTYP*
- *INSNO*
- *CHGDET*
- *PAYMNTDET1*
- *PAYMNTDET2*
- *PAYMNTDET3*
- *PAYMNTDET4*
- *SNDTRRCVINFO1*
- *SNDTRRCVINFO2*
- *SNDTRRCVINFO3*
- *SNDTRRCVINFO4*
- *SNDTRRCVINFO5*
- *COVREQRD*
- *RECVCVR*
- *RECEIVER*
- *REIMINST1*
- *REIMINST2*
- *REIMINST3*
- *REIMINST4*
- *RCVRCORRS1*
- *RCVRCORRS2*

RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5

ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*

SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REASON

Attribute	Description
Name	REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DT_OF_DISHONOR

Attribute	Description
Name	DT_OF_DISHONOR
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association

Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	**Description**	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	Description	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	**Description**	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS5

Attribute	**Description**	
Name	TRANMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	**Description**	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	Description	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	Description	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP

Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String

Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	**Description**
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	**Description**
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	**Description**
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	**Description**
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *CHOICE*
  - *Main-PK*
    - *CONREFNUM*
  - *Main-IO*
    - *CONREFNUM*
- *FCUBS_ERROR_RESP*
  - *ERROR*
    - *ECODE*
    - *EDESC*
- *FCUBS_WARNING_RESP*
  - *WARNING*
    - *WCODE*
    - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.64.DeleteCashletterrealize

DeleteCashletterrealize

2.64.1.RB-DeleteCashletterrealize-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CASHLTRCONREFNO*
    - *EVENTCODE*
    - *CL_REF*
    - *CURRENCY*
    - *AMNT*
    - *NOSTROACC*
    - *ACCBRN*
    - *INTREMRKS*
    - *COLBANKREFNUM*
    - *Footer*
      - *MAKER*
      - *MAKDTTIME*
      - *CHKR*
      - *CHKDTTIME*
      - *RECORD_STAT*

AUTHSTATS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CL_REF

Attribute	Description
Name	CL_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Footer

Attribute	Description	
Name	Footer	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	Description	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKR

Attribute	Description	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	Description	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RECORD_STAT

Attribute	Description	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,L

TOP

AUTHSTATS

Attribute	Description	
Name	AUTHSTATS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

2.64.2.RB-DeleteCashletterrealize-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CASHLTRCONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.64.3.RB-DeleteCashletterrealize-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CASHLTRCONREFNO*
    - *EVENTCODE*
    - *CL_REF*
    - *CURRENCY*
    - *AMNT*
    - *NOSTROACC*
    - *ACCBRN*
    - *INTREMRKS*
    - *COLBANKREFNUM*
    - *Footer*
      - *MAKER*
      - *MAKDTTIME*
      - *CHKR*
      - *CHKDTTIME*
      - *RECORD_STAT*
      - *AUTHSTATS*
  - *FCUBS_ERROR_RESP*
    - *ERROR*

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CL_REF

Attribute	Description
Name	CL_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNT

Attribute	Description	
Name	AMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NOSTROACC

Attribute	Description	
Name	NOSTROACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INTREMRKS

Attribute	Description	
Name	INTREMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Footer

Attribute	Description
Name	Footer
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,L

TOP

AUTHSTATS

Attribute	Description
Name	AUTHSTATS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *CHOICE*
  - *Main-PK*
    - *CASHLTRCONREFNO*
  - *Main-IO*
    - *CASHLTRCONREFNO*
- *FCUBS_ERROR_RESP*
  - *ERROR*
    - *ECODE*
    - *EDESC*
- *FCUBS_WARNING_RESP*
  - *WARNING*
    - *WCODE*
    - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.65.DeleteCreatebulkfcycheck

DeleteCreatebulkfcycheck

2.65.1.RB-DeleteCreatebulkfcycheck-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Cashletter-Full*
    - *INSTRUCODE*
    - *INSTR_DESC*
    - *PRCD*
    - *PRODDESC*
    - *BATCHREFENUM*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *CPTY_AC_NO*
    - *ACCBRNRE*
    - *AC_CCYY*
    - *ACCBRN*
    - *COLL_BNK_NAME*
    - *BDTE*
    - *VAL_DATE_BANK*
    - *VALUE_DATE_CUST*

LIQDMODE
FINANCING
MARGINPERCENT
TRACK_LIMIT
CREDITLINE
NOOFINSTRUMENTS
PROCESS_STATUS
NOSTROACC
ESN
EVENT_SEQ_NO
RECORD_STAT
AUTHORIZATION_STATUS
CHECKER
CHKDTTIME
MAKER
MAKDTTIME
Bulk-Cashletter-Dtl
  CONREFNUM
  INSTRNO
  INSTRU_DATE
  ADJSTAMT
  LCY_AMT
  DISCAMT
  OTHR_PARTYNAME
  DRAWEE_BNK_NAME
  REMRKS
  PROCESS_STATUS
Summary
  AUTHSTAT
  RECORD_STAT
  INSTRUCODE
  PRCD
  CPTY_ID
  BATCHREFENUM
  NOSTROACC
  COLL_BNK_NAME
  INSTRNO
  INSTRU_DATE
  AC_CCYY
  AMNT
  BDTE
  VAL_DATE_BANK
  VALUE_DATE_CUST
  CONREFNUM

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Cashletter-Full

Attribute	Description
Name	Bulk-Cashletter-Full
Datatype	
Description	

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCBRNRE

Attribute	Description
Name	ACCBRNRE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BDTE

Attribute	Description
Name	BDTE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDMODE

Attribute	Description
Name	LIQDMODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,U,

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C,

TOP

AUTHORIZATION_STATUS

Attribute	Description
Name	AUTHORIZATION_STATUS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	**Description**
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	**Description**
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Bulk-Cashletter-Dtl

Attribute	Description
Name	Bulk-Cashletter-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

ADJSTAMT

Attribute	Description

Name	ADJSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,U,

TOP

Summary

Attribute	Description
Name	Summary
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,C,

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BDTE

Attribute	Description
Name	BDTE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.65.2.RB-DeleteCreatebulkfcycheck-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Bulk-Cashletter-IO
BATCHREFENUM

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Cashletter-IO

Attribute	Description
Name	Bulk-Cashletter-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.65.3.RB-DeleteCreatebulkfcycheck-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Cashletter-Full*
    - *INSTRUCODE*
    - *INSTR_DESC*
    - *PRCD*
    - *PRODDESC*
    - *BATCHREFENUM*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *CPTY_AC_NO*
    - *ACCBRNRE*
    - *AC_CCYY*
    - *ACCBRN*
    - *COLL_BNK_NAME*
    - *BDTE*
    - *VAL_DATE_BANK*
    - *VALUE_DATE_CUST*
    - *LIQDMODE*
    - *FINANCING*
    - *MARGINPERCENT*

- *TRACK_LIMIT*
- *CREDITLINE*
- *NOOFINSTRUMENTS*
- *PROCESS_STATUS*
- *NOSTROACC*
- *ESN*
- *EVENT_SEQ_NO*
- *RECORD_STAT*
- *AUTHORIZATION_STATUS*
- *CHECKER*
- *CHKDTTIME*
- *MAKER*
- *MAKDTTIME*
- *Bulk-Cashletter-Dtl*
  - *CONREFNUM*
  - *INSTRNO*
  - *INSTRU_DATE*
  - *ADJSTAMT*
  - *LCY_AMT*
  - *DISCAMT*
  - *OTHR_PARTYNAME*
  - *DRAWEE_BNK_NAME*
  - *REMRKS*
  - *PROCESS_STATUS*
- *Summary*
  - *AUTHSTAT*
  - *RECORD_STAT*
  - *INSTRUCODE*
  - *PRCD*
  - *CPTY_ID*
  - *BATCHREFENUM*
  - *NOSTROACC*
  - *COLL_BNK_NAME*
  - *INSTRNO*
  - *INSTRU_DATE*
  - *AC_CCYY*
  - *AMNT*
  - *BDTE*
  - *VAL_DATE_BANK*
  - *VALUE_DATE_CUST*
  - *CONREFNUM*

FCUBS_ERROR_RESP

- *ERROR*
  - *ECODE*

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Cashletter-Full

Attribute	Description

Name	Bulk-Cashletter-Full
Datatype	
Description	

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BATCHREFENUM

Attribute	Description	
Name	BATCHREFENUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	Description	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_NAME

Attribute	Description	
Name	CPTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTY_AC_NO

Attribute	Description	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCBRNRE

Attribute	Description
Name	ACCBRNRE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BDTE

Attribute	Description
Name	BDTE

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDMODE

Attribute	Description
Name	LIQDMODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / P,U,

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,C,

TOP

AUTHORIZATION_STATUS

Attribute	Description
Name	AUTHORIZATION_STATUS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Bulk-Cashletter-Dtl

Attribute	Description
Name	Bulk-Cashletter-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,U,

TOP

Summary

Attribute	Description
Name	Summary
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>O,C,</td></tr></table>

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BDTE

Attribute	Description
Name	BDTE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Cashletter-PK*
      - *BATCHREFENUM*
    - *Bulk-Cashletter-IO*
      - *BATCHREFENUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Cashletter-PK

Attribute	Description
Name	Bulk-Cashletter-PK
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Cashletter-IO

Attribute	Description
Name	Bulk-Cashletter-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.66.DeleteCreatebulkfcyreal

DeleteCreatebulkfcyreal

2.66.1.RB-DeleteCreatebulkfcyreal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liqd-Cashletter-Full*
    - *CASHREFNO*
    - *AC_CCYY*
    - *ACCBRN*
    - *VALUE_DATE_CUST*
    - *CASHLTRCONREFNO*
    - *NOSTROACC*
    - *PROCESS_STATUS*
    - *ESN*
    - *EVENT_SEQ_NO*
    - *RECORD_STAT*
    - *AUTHORIZATION_STATUS*
    - *CHECKER*
    - *CHKDTTIME*
    - *MAKER*
    - *MAKDTTIME*

Liqd-Cashletter-Dtl

CONREFNUM

CPTY_ID

INSTRNO

INSTRU_DATE

AMNT

INTREMRKS

PROCESS_STATUS

Summary

AUTHSTAT

RECORD_STAT

CASHREFNO

AC_CCYY

NOSTROACC

CONREFNUM

INSTRNO

INSTRU_DATE

AMNT

CPTY_ID

COUNTRPRYNAM

CASHLTRCONREFNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liqd-Cashletter-Full

Attribute	Description
Name	Liqd-Cashletter-Full
Datatype	
Description	

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACCBRN

Attribute	Description

Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,U,

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,C,

TOP

AUTHORIZATION_STATUS

Attribute	Description
Name	AUTHORIZATION_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Liqd-Cashletter-Dtl

Attribute	Description
Name	Liqd-Cashletter-Dtl
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,U,</td></tr></table>

TOP

Summary

Attribute	Description
Name	Summary
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U,

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,C,

TOP

CASHREFNO

Attribute	**Description**	
Name	CASHREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AC_CCYY

Attribute	**Description**	
Name	AC_CCYY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

NOSTROACC

Attribute	**Description**	
Name	NOSTROACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

2.66.2.RB-DeleteCreatebulkfcyreal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liqd-Cashletter-IO*
    - *CASHLTRCONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liqd-Cashletter-IO

Attribute	Description
Name	Liqd-Cashletter-IO
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.66.3.RB-DeleteCreatebulkfcyreal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liqd-Cashletter-Full*
    - *CASHREFNO*
    - *AC_CCYY*
    - *ACCBRN*
    - *VALUE_DATE_CUST*
    - *CASHLTRCONREFNO*
    - *NOSTROACC*
    - *PROCESS_STATUS*
    - *ESN*
    - *EVENT_SEQ_NO*
    - *RECORD_STAT*
    - *AUTHORIZATION_STATUS*
    - *CHECKER*
    - *CHKDTTIME*
    - *MAKER*
    - *MAKDTTIME*
    - *Liqd-Cashletter-Dtl*
      - *CONREFNUM*
      - *CPTY_ID*

INSTRNO
INSTRU_DATE
AMNT
INTREMRKS
PROCESS_STATUS
Summary
AUTHSTAT
RECORD_STAT
CASHREFNO
AC_CCYY
NOSTROACC
CONREFNUM
INSTRNO
INSTRU_DATE
AMNT
CPTY_ID
COUNTRPRYNAM
CASHLTRCONREFNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liqd-Cashletter-Full

Attribute	Description
Name	Liqd-Cashletter-Full
Datatype	
Description	

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,U,

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,C,

TOP

AUTHORIZATION_STATUS

Attribute	Description
Name	AUTHORIZATION_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Liqd-Cashletter-Dtl

Attribute	Description
Name	Liqd-Cashletter-Dtl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date

Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	255

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
enumeration	P,U,

TOP

Summary

Attribute	Description
Name	Summary
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

AUTHSTAT

Attribute	Description

Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C,

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CONREFNUM

Attribute	**Description**	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INSTRNO

Attribute	**Description**	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRU_DATE

Attribute	**Description**	
Name	INSTRU_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMNT

Attribute	**Description**	
Name	AMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.66.4.RB-DeleteCreatebulkfcyreal-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Liqd-Cashletter-PK*
      - *CASHLTRCONREFNO*
    - *Liqd-Cashletter-IO*
      - *CASHLTRCONREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Liqd-Cashletter-PK

Attribute	Description
Name	Liqd-Cashletter-PK
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Liqd-Cashletter-IO

Attribute	Description
Name	Liqd-Cashletter-IO
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.67.DeleteFcychecksfinance

DeleteFcychecksfinance

2.67.1.RB-DeleteFcychecksfinance-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONTRACT_REF*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *INSTRNO*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *BOOKINGDATE*
    - *VAL_DATE_BANK*
    - *VALUE_DATE_CUST*
    - *OTHR_PARTY_NAME*
    - *DRAWEE_BNK_NAME*
    - *FINANCING*
    - *MARGINPERCENT*
    - *TRACK_LIMIT*

CRLINE
DISCOUNT_AMOUNT
MAKER
MAKDTTIME
CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*

INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1

ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

FREETXT1

FREETXT2

FREETXT3

PMNTCD

ADDINFOSORBNET

SNDRCUSTNAME1

SNDRCUSTNAME2

SNDRCUSTNAME3

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

Charges

CONREFNO

Charge-Association

COMPNT

CREATESN

RULE

- *WAIVER*
- *DISACCRAPPL*
- *ACCRREQD*
- *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*
  - *COSTCD4*
  - *COSTCD5*
  - *TXNMIS1*
  - *TXNMIS10*
  - *TXNMIS2*
  - *TXNMIS3*
  - *TXNMIS4*

TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6

- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Clpref

- *CONTREFNNO*
- *CONTRACT_CCY*
- *LATEVNSEQNO*
- *PRD*
- *PRDDESC*
- *COUNTERPARTY*
- *CURRENCY*
- *TENOR*
- *UNITS*
- *LOAN_CONREFNO*
- *RATECODE*
- *EXCHANGERATE*
- *RATE_TYPE*
- *MAXIMUM*
- *MINIMUM*
- *PAYMENT_MODE*
- *LOANVALDATE*
- *MATURITY_DATE*
- *Ude*
  - *USERDEID*
  - *UDEDESC*
  - *RATEASOF*
  - *USAGE*
  - *USERDEVAL*

TXNUDFDETAILS

- *FLDNAME*

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONTRACT_REF

Attribute	Description
Name	CONTRACT_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CTR_PRTY_NAME

Attribute	Description
Name	CTR_PRTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRLINE

Attribute	Description
Name	CRLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L,A

TOP

AUTHSTAT

Attribute	Description

Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Settlement

Attribute	**Description**	
Name	Contract-Settlement	
Datatype		
Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	**Description**	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**

Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	**Description**	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO

Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String

Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4

Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1

Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5

Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	

Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description

Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description

Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.67.2.RB-DeleteFcychecksfinance-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONTRACT_REF*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONTRACT_REF

Attribute	Description
Name	CONTRACT_REF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.67.3.RB-DeleteFcychecksfinance-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONTRACT_REF*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *INSTRNO*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *BOOKINGDATE*
    - *VAL_DATE_BANK*
    - *VALUE_DATE_CUST*
    - *OTHR_PARTY_NAME*
    - *DRAWEE_BNK_NAME*
    - *FINANCING*
    - *MARGINPERCENT*
    - *TRACK_LIMIT*
    - *CRLINE*
    - *DISCOUNT_AMOUNT*
    - *MAKER*

MAKDTTIME
CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
Con
  CONTREFNO
  EVENTSEQ
  Adv
    ADVNAME
    SUPRESS
    PRIOR
    MEDM
    PARTYIDEN
    PARTYNAME
    CHGREQ
    PARTTYP
Settlements
  CONREFNO
  Contract-Settlement
    IBANACNO
    CUSTSPREAD
    SPREADDEFN
    COMPNT
    TAGCCY
    ACCBRN
    ACC
    ACCCCY
    EXRATE
    NETIND
    ERICCY
    ERIAMT
    GENMSG
    RATECD
    CLEARNW
    COVERBY
    RTGSPMNT
    BANKPRIOR
    RTGSNW
    PAYBY
    TRANSTYP
    INSTYP
    INSNO
    CHGDET

PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4

BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*

FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD

- *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*

TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9

- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Clpref

- *CONTREFNNO*
- *CONTRACT_CCY*
- *LATEVNSEQNO*
- *PRD*
- *PRDDESC*
- *COUNTERPARTY*
- *CURRENCY*
- *TENOR*
- *UNITS*
- *LOAN_CONREFNO*
- *RATECODE*
- *EXCHANGERATE*
- *RATE_TYPE*
- *MAXIMUM*
- *MINIMUM*
- *PAYMENT_MODE*
- *LOANVALDATE*
- *MATURITY_DATE*
- *Ude*
  - *USERDEID*
  - *UDEDESC*
  - *RATEASOF*
  - *USAGE*
  - *USERDEVAL*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONTRACT_REF

Attribute	Description
Name	CONTRACT_REF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CTR_PRTY_NAME

Attribute	Description
Name	CTR_PRTY_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRLINE

Attribute	Description
Name	CRLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	**Description**	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / ,L,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTYIDEN

Attribute	Description	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	Description	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CHGREQ

Attribute	Description	
Name	CHGREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTTYP

Attribute	Description	
Name	PARTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	Description	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	Description	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	**Description**
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	**Description**
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	**Description**
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	**Description**
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number

Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	Description	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	Description	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	**Description**
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	**Description**
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	**Description**
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	**Description**
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNNO

Attribute	**Description**	
Name	CONTREFNNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CONTRACT_CCY

Attribute	**Description**	
Name	CONTRACT_CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRD

Attribute	**Description**	
Name	PRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LOAN_CONREFNO

Attribute	**Description**	
Name	LOAN_CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RATECODE

Attribute	**Description**	
Name	RATECODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,S

TOP

EXCHANGERATE

Attribute	**Description**	
Name	EXCHANGERATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATE_TYPE

Attribute	**Description**	
Name	RATE_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

USAGE

Attribute	Description

Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.67.4.RB-DeleteFcychecksfinance-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONTRACT_REF*
    - *Main-IO*
      - *CONTRACT_REF*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONTRACT_REF

Attribute	Description
Name	CONTRACT_REF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONTRACT_REF

Attribute	Description
Name	CONTRACT_REF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.68.DeleteFcychecksrealize

DeleteFcychecksrealize

2.68.1.RB-DeleteFcychecksrealize-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CASHREFNO*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *INSTRNO*
    - *INSTRU_DATE*
    - *CURRENCY*
    - *AMNT*
    - *VALUEDATE*
    - *REMRKS*
    - *MAKER*
    - *MAKDTTIME*
    - *CHKR*
    - *CHKDTTIME*
    - *RECORD_STAT*

AUTHSTAT

Con

- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*

SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4

BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*

SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT

TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN

COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3

FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

AMNT

Attribute	Description
Name	AMNT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr></table>

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Settlement

Attribute	**Description**	
Name	Contract-Settlement	
Datatype		
Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	**Description**	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description

Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	**Description**	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	**Description**	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	**Description**	
Name	CLEARNW	
Datatype	String	
Description	Indicates Network Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	**Description**
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates RTGS Payment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	**Description**	
Name	BANKPRIOR	
Datatype	String	
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1

Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC

Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	**Description**	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1

Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String

Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description

Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	**Description**	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	**Description**	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	**Description**	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description

Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY

Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	**Description**	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS6

Attribute	**Description**	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	**Description**	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	**Description**	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS2

Attribute	**Description**	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.68.2.RB-DeleteFcychecksrealize-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Main-IO*
  - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.68.3.RB-DeleteFcychecksrealize-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CASHREFNO*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *INSTRNO*
    - *INSTRU_DATE*
    - *CURRENCY*
    - *AMNT*
    - *VALUEDATE*
    - *REMRKS*
    - *MAKER*
    - *MAKDTTIME*
    - *CHKR*
    - *CHKDTTIME*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *Con*
      - *CONTREFNO*

- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*
- *Settlements*
  - *CONREFNO*
  - *Contract-Settlement*
    - *IBANACNO*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *COMPNT*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *ACCCCY*
    - *EXRATE*
    - *NETIND*
    - *ERICCY*
    - *ERIAMT*
    - *GENMSG*
    - *RATECD*
    - *CLEARNW*
    - *COVERBY*
    - *RTGSPMNT*
    - *BANKPRIOR*
    - *RTGSNW*
    - *PAYBY*
    - *TRANSTYP*
    - *INSTYP*
    - *INSNO*
    - *CHGDET*
    - *PAYMNTDET1*
    - *PAYMNTDET2*
    - *PAYMNTDET3*
    - *PAYMNTDET4*
    - *SNDTRRCVINFO1*
    - *SNDTRRCVINFO2*
    - *SNDTRRCVINFO3*

SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC

COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*

RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY

- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*
  - *COSTCD4*
  - *COSTCD5*
  - *TXNMIS1*
  - *TXNMIS10*
  - *TXNMIS2*
  - *TXNMIS3*
  - *TXNMIS4*
  - *TXNMIS5*
  - *TXNMIS6*
  - *TXNMIS7*
  - *TXNMIS8*
  - *TXNMIS9*
  - *MISGRPCOMP*
  - *MISGRPTXN*
  - *COMPMIS1*
  - *COMPMIS10*
  - *COMPMIS2*

COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6

FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SUPRESS

Attribute	**Description**	
Name	SUPRESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number

Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String

Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	Description	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	Description	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description

Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	**Description**	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	**Description**	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1

Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5

Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	**Description**	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	**Description**	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description

Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.68.4.RB-DeleteFcychecksrealize-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONREFNUM*
    - *Main-IO*
      - *CONREFNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.69.DeleteInwardContract

DeleteInwardContract

2.69.1.RB-DeleteInwardContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *INSTRUMENT_CODE*
    - *INSTRUMENT_DESCRIPTION*
    - *PRCD*
    - *CONREFNUM*
    - *USERREF_NO*
    - *XREF*
    - *BATCHREFENUM*
    - *BATCHSEQNO*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *ACCBRN*
    - *CPTY_AC_NO*
    - *INSTNO*
    - *INSTRDATE*
    - *CCY*

AMT
LCYAMT
BNKCD
BNKNAME
BRNCDE
BRNNAME
REFNO
DATE
CORRESPBNK
CORRESPACNO
OTHERPARTYIDE
OTHR_PARTYNAME
BOKNGDT
MATDT
GRACEDAYS
PAYDUEDATE
ACBRN1
ACFORREALISATION
PROTEST
AUTOLIQD
LIQWITHBUKNG
INTREMARKS
REASON_CODE
REASON
CONREFNOLOG
MAKER
MAKDTTIME
CHKR
CHKDTTIME
SE_TXNSTAT
AUTHSTAT
VERSIONNORB
LATVERNO
Contract-Parties
- *PARTYTYPE*
- *PARTYIDEN*
- *PARTYNAME*
- *COUNTRYCD*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ADDLN4*
- *LANG*

Settlements

CONREFNO

Contract-Settlement

- *IBANACNO*
- *CUSTSPREAD*
- *SPREADDEFN*
- *COMPNT*
- *TAGCCY*
- *ACCBRN*
- *ACC*
- *ACCCCY*
- *EXRATE*
- *NETIND*
- *ERICCY*
- *ERIAMT*
- *GENMSG*
- *RATECD*
- *CLEARNW*
- *COVERBY*
- *RTGSPMNT*
- *BANKPRIOR*
- *RTGSNW*
- *PAYBY*
- *TRANSTYP*
- *INSTYP*
- *INSNO*
- *CHGDET*
- *PAYMNTDET1*
- *PAYMNTDET2*
- *PAYMNTDET3*
- *PAYMNTDET4*
- *SNDTRRCVINFO1*
- *SNDTRRCVINFO2*
- *SNDTRRCVINFO3*
- *SNDTRRCVINFO4*
- *SNDTRRCVINFO5*
- *COVREQRD*
- *RECVCVR*
- *RECEIVER*
- *REIMINST1*
- *REIMINST2*
- *REIMINST3*
- *REIMINST4*
- *RCVRCORRS1*
- *RCVRCORRS2*

RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5

ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*

SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Charges

CONREFNO

Charge-Association

COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC

Charge-Application

CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND

Charge-Liquidation

ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3

FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con

CONTREFNO

EVENTSEQ

Adv

- *ADVNAME*
- *SUPRESS*
- *PRIOR*
- *MEDM*
- *PARTYIDEN*
- *PARTYNAME*
- *CHGREQ*
- *PARTTYP*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description
Name	INSTRUMENT_DESCRIPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHSEQNO

Attribute	Description

Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTNO

Attribute	Description
Name	INSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRNCDE

Attribute	Description
Name	BRNCDE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORRESPBNK

Attribute	Description
Name	CORRESPBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CORRESPACNO

Attribute	Description
Name	CORRESPACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

OTHERPARTYIDE

Attribute	Description
Name	OTHERPARTYIDE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACBRN1

Attribute	Description
Name	ACBRN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQWITHBUKNG

Attribute	Description
Name	LIQWITHBUKNG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REASON

Attribute	Description
Name	REASON
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CONREFNOLOG

Attribute	Description
Name	CONREFNOLOG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SE_TXNSTAT

Attribute	Description
Name	SE_TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,L,R,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

VERSIONNORB

Attribute	Description
Name	VERSIONNORB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>DRAWER,PAYEE,REMITTING_BANK,DRAWEE</td></tr></table>

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRYCD

Attribute	**Description**	
Name	COUNTRYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ADDLN1

Attribute	**Description**	
Name	ADDLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDLN2

Attribute	**Description**	
Name	ADDLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDLN3

Attribute	**Description**	
Name	ADDLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	**Description**	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	**Description**	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1

Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2

Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDINST5

Attribute	Description
Name	ORDINST5

Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1

Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	**Description**	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	**Description**	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application

Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	**Description**	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs — unbounded minOccurs — 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs — unbounded minOccurs — 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs — unbounded minOccurs — 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs — unbounded minOccurs — 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength — 105 minLength — 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL

Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

2.69.2.RB-DeleteInwardContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.69.3.RB-DeleteInwardContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *INSTRUMENT_CODE*
    - *INSTRUMENT_DESCRIPTION*
    - *PRCD*
    - *CONREFNUM*
    - *USERREF_NO*
    - *XREF*
    - *BATCHREFENUM*
    - *BATCHSEQNO*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *ACCBRN*
    - *CPTY_AC_NO*
    - *INSTNO*
    - *INSTRDATE*
    - *CCY*
    - *AMT*
    - *LCYAMT*
    - *BNKCD*

BNKNAME
BRNCDE
BRNNAME
REFNO
DATE
CORRESPBNK
CORRESPACNO
OTHERPARTYIDE
OTHR_PARTYNAME
BOKNGDT
MATDT
GRACEDAYS
PAYDUEDATE
ACBRN1
ACFORREALISATION
PROTEST
AUTOLIQD
LIQWITHBUKNG
INTREMARKS
REASON_CODE
REASON
CONREFNOLOG
MAKER
MAKDTTIME
CHKR
CHKDTTIME
SE_TXNSTAT
AUTHSTAT
VERSIONNORB
LATVERNO
Contract-Parties
- *PARTYTYPE*
- *PARTYIDEN*
- *PARTYNAME*
- *COUNTRYCD*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ADDLN4*
- *LANG*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*

CUSTSPREAD
SPREADDEFN
COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1

INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND

Settlement-Detail

- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*

- NOOFDEC
- ADDID
- SNDRRCVRINFO1
- SNDRRCVRINFO2
- SNDRRCVRINFO3
- SNDRRCVRINFO4
- SNDRRCVRINFO5
- SNDRRCVRINFO6
- DECLARTION
- REPRES1
- REPRES2
- REPRES3
- REPRES4
- RCVRACC

Charges

- CONREFNO
- Charge-Association
  - COMPNT
  - CREATESN
  - RULE
  - WAIVER
  - DISACCRAPPL
  - ACCRREQD
  - DESC
- Charge-Application
  - CREATESN
  - COMPNT
  - TGCCY
  - TGAMT
  - CHRGCCY
  - CHRGAMT
  - DISACCRAPPL
  - WAIVER
  - LIQDIND
- Charge-Liquidation
  - ESN
  - COMPNT
  - CHRGCCY
  - CHRGAMT
  - LIQDSTAT

Misdetails

- CONREFNO
- LATESN
- MISGRP

RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6

FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv

ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description
Name	INSTRUMENT_DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CONREFNUM

Attribute	Description	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USERREF_NO

Attribute	Description	
Name	USERREF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BATCHREFENUM

Attribute	Description	
Name	BATCHREFENUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTNO

Attribute	**Description**	
Name	INSTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRDATE

Attribute	**Description**	
Name	INSTRDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BRNCDE

Attribute	Description
Name	BRNCDE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

REFNO

Attribute	**Description**	
Name	REFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DATE

Attribute	**Description**	
Name	DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CORRESPBNK

Attribute	**Description**	
Name	CORRESPBNK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CORRESPACNO

Attribute	**Description**	
Name	CORRESPACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

OTHERPARTYIDE

Attribute	Description
Name	OTHERPARTYIDE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PAYDUEDATE

Attribute	**Description**	
Name	PAYDUEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACBRN1

Attribute	**Description**	
Name	ACBRN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACFORREALISATION

Attribute	**Description**	
Name	ACFORREALISATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

PROTEST

Attribute	**Description**	
Name	PROTEST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

LIQWITHBUKNG

Attribute	Description
Name	LIQWITHBUKNG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

REASON

Attribute	Description
Name	REASON

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CONREFNOLOG

Attribute	Description
Name	CONREFNOLOG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SE_TXNSTAT

Attribute	**Description**	
Name	SE_TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,L,R,H

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

VERSIONNORB

Attribute	**Description**	
Name	VERSIONNORB	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / DRAWER,PAYEE,REMITTING_BANK,DRAWEE

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	**Description**	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	**Description**	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1

Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2

Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDINST5

Attribute	Description
Name	ORDINST5

Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1

Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	**Description**	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	**Description**	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application

Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	**Description**	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	

Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL

Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.69.4.RB-DeleteInwardContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNUM*
    - *Contract-Details-IO*
      - *CONREFNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.70.CreateCreatebulkfcyreal

CreateCreatebulkfcyreal

2.70.1.RB-CreateCreatebulkfcyreal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liqd-Cashletter-Full*
    - *CASHREFNO*
    - *AC_CCYY*
    - *ACCBRN*
    - *VALUE_DATE_CUST*
    - *CASHLTRCONREFNO*
    - *NOSTROACC*
    - *PROCESS_STATUS*
    - *ESN*
    - *EVENT_SEQ_NO*
    - *RECORD_STAT*
    - *AUTHORIZATION_STATUS*
    - *CHECKER*
    - *CHKDTTIME*
    - *MAKER*
    - *MAKDTTIME*

Liqd-Cashletter-Dtl

CONREFNUM

CPTY_ID

INSTRNO

INSTRU_DATE

AMNT

INTREMRKS

PROCESS_STATUS

Summary

AUTHSTAT

RECORD_STAT

CASHREFNO

AC_CCYY

NOSTROACC

CONREFNUM

INSTRNO

INSTRU_DATE

AMNT

CPTY_ID

COUNTRPRYNAM

CASHLTRCONREFNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liqd-Cashletter-Full

Attribute	Description
Name	Liqd-Cashletter-Full
Datatype	
Description	

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACCBRN

Attribute	Description

Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,U,

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,C,

TOP

AUTHORIZATION_STATUS

Attribute	Description
Name	AUTHORIZATION_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Liqd-Cashletter-Dtl

Attribute	Description
Name	Liqd-Cashletter-Dtl
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,U,</td></tr></table>

TOP

Summary

Attribute	Description
Name	Summary
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U,

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,C,

TOP

CASHREFNO

Attribute	**Description**	
Name	CASHREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AC_CCYY

Attribute	**Description**	
Name	AC_CCYY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

NOSTROACC

Attribute	**Description**	
Name	NOSTROACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

2.70.2.RB-CreateCreatebulkfcyreal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liqd-Cashletter-IO*
    - *VALUE_DATE_CUST*
    - *CASHLTRCONREFNO*
    - *Liqd-Cashletter-Dtl*
      - *INTREMRKS*
    - *Summary*
      - *AUTHSTAT*
      - *RECORD_STAT*
      - *CASHREFNO*
      - *AC_CCYY*
      - *NOSTROACC*
      - *CONREFNUM*
      - *INSTRNO*
      - *INSTRU_DATE*
      - *AMNT*
      - *CPTY_ID*
      - *COUNTRPRYNAM*
      - *CASHLTRCONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liqd-Cashletter-IO

Attribute	Description
Name	Liqd-Cashletter-IO
Datatype	
Description	

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Liqd-Cashletter-Dtl

Attribute	Description
Name	Liqd-Cashletter-Dtl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Summary

Attribute	Description
Name	Summary
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U,

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,C

TOP

CASHREFNO

Attribute	**Description**	
Name	CASHREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AC_CCYY

Attribute	**Description**	
Name	AC_CCYY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

2.70.3.RB-CreateCreatebulkfcyreal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liqd-Cashletter-Full*
    - *CASHREFNO*
    - *AC_CCYY*
    - *ACCBRN*
    - *VALUE_DATE_CUST*
    - *CASHLTRCONREFNO*
    - *NOSTROACC*
    - *PROCESS_STATUS*
    - *ESN*
    - *EVENT_SEQ_NO*
    - *RECORD_STAT*
    - *AUTHORIZATION_STATUS*
    - *CHECKER*
    - *CHKDTTIME*
    - *MAKER*
    - *MAKDTTIME*
    - *Liqd-Cashletter-Dtl*
      - *CONREFNUM*
      - *CPTY_ID*

INSTRNO
INSTRU_DATE
AMNT
INTREMRKS
PROCESS_STATUS
Summary
AUTHSTAT
RECORD_STAT
CASHREFNO
AC_CCYY
NOSTROACC
CONREFNUM
INSTRNO
INSTRU_DATE
AMNT
CPTY_ID
COUNTRPRYNAM
CASHLTRCONREFNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liqd-Cashletter-Full

Attribute	Description
Name	Liqd-Cashletter-Full
Datatype	
Description	

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,U,

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C,

TOP

AUTHORIZATION_STATUS

Attribute	Description
Name	AUTHORIZATION_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Liqd-Cashletter-Dtl

Attribute	Description
Name	Liqd-Cashletter-Dtl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date

Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	255

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
enumeration	P,U,

TOP

Summary

Attribute	Description
Name	Summary
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

AUTHSTAT

Attribute	Description

Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C,

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.70.4.RB-CreateCreatebulkfcyreal-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Liqd-Cashletter-PK*
      - *CASHLTRCONREFNO*
    - *Liqd-Cashletter-IO*
      - *VALUE_DATE_CUST*
      - *CASHLTRCONREFNO*
      - *Liqd-Cashletter-Dtl*
        - *INTREMRKS*
      - *Summary*
        - *AUTHSTAT*
        - *RECORD_STAT*
        - *CASHREFNO*
        - *AC_CCYY*
        - *NOSTROACC*
        - *CONREFNUM*
        - *INSTRNO*
        - *INSTRU_DATE*
        - *AMNT*
        - *CPTY_ID*

COUNTRPRYNAM

CASHLTRCONREFNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Liqd-Cashletter-PK

Attribute	Description
Name	Liqd-Cashletter-PK
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Liqd-Cashletter-IO

Attribute	Description
Name	Liqd-Cashletter-IO
Datatype	
Description	

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Liqd-Cashletter-Dtl

Attribute	Description
Name	Liqd-Cashletter-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Summary

Attribute	Description
Name	Summary
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

RECORD_STAT

Attribute	Description	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,C

TOP

CASHREFNO

Attribute	Description	
Name	CASHREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AC_CCYY

Attribute	Description	
Name	AC_CCYY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

NOSTROACC

Attribute	Description	
Name	NOSTROACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description

Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.71.CreateFcychecksfinance

CreateFcychecksfinance

2.71.1.RB-CreateFcychecksfinance-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONTRACT_REF*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *INSTRNO*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *BOOKINGDATE*
    - *VAL_DATE_BANK*
    - *VALUE_DATE_CUST*
    - *OTHR_PARTY_NAME*
    - *DRAWEE_BNK_NAME*
    - *FINANCING*
    - *MARGINPERCENT*
    - *TRACK_LIMIT*

CRLINE
DISCOUNT_AMOUNT
MAKER
MAKDTTIME
CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*

INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1

ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

FREETXT1

FREETXT2

FREETXT3

PMNTCD

ADDINFOSORBNET

SNDRCUSTNAME1

SNDRCUSTNAME2

SNDRCUSTNAME3

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

Charges

CONREFNO

Charge-Association

COMPNT

CREATESN

RULE

WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4

TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6

- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Clpref

- *CONTREFNNO*
- *CONTRACT_CCY*
- *LATEVNSEQNO*
- *PRD*
- *PRDDESC*
- *COUNTERPARTY*
- *CURRENCY*
- *TENOR*
- *UNITS*
- *LOAN_CONREFNO*
- *RATECODE*
- *EXCHANGERATE*
- *RATE_TYPE*
- *MAXIMUM*
- *MINIMUM*
- *PAYMENT_MODE*
- *LOANVALDATE*
- *MATURITY_DATE*
- *Ude*
  - *USERDEID*
  - *UDEDESC*
  - *RATEASOF*
  - *USAGE*
  - *USERDEVAL*

TXNUDFDETAILS

- *FLDNAME*

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONTRACT_REF

Attribute	Description	
Name	CONTRACT_REF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	Description	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CTR_PRTY_NAME

Attribute	Description	
Name	CTR_PRTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INSTRNO

Attribute	Description	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRLINE

Attribute	Description
Name	CRLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L,A

TOP

AUTHSTAT

Attribute	Description

Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Settlement

Attribute	**Description**	
Name	Contract-Settlement	
Datatype		
Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	**Description**	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**

Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	**Description**	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO

Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String

Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	Description	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO5

Attribute	Description	
Name	SNDTRRCVINFO5	
Datatype	String	
Description	Indicates Sender To Receiver Information 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	Description	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4

Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1

Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	Description	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5

Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	

Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description

Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	Description	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	Description	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description

Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.71.2.RB-CreateFcychecksfinance-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONTRACT_REF*
    - *FINANCING*
    - *MARGINPERCENT*
    - *TRACK_LIMIT*
    - *CRLINE*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *Con*
      - *CONTREFNO*
      - *EVENTSEQ*
      - *Adv*
        - *SUPRESS*
        - *PRIOR*
        - *MEDM*
        - *CHGREQ*
    - *Settlements*
      - *CONREFNO*
      - *LATEVNSEQNO*

Contract-Settlement

- *CUSTSPREAD*
- *SPREADDEFN*
- *TAGCCY*
- *ACCBRN*
- *ACC*
- *EXRATE*
- *NETIND*
- *ERICCY*
- *ERIAMT*
- *GENMSG*
- *RATECD*
- *CLEARNW*
- *COVERBY*
- *RTGSPMNT*
- *BANKPRIOR*
- *RTGSNW*
- *PAYBY*
- *TRANSTYP*
- *INSTYP*
- *INSNO*
- *CHGDET*
- *PAYMNTDET1*
- *PAYMNTDET2*
- *PAYMNTDET3*
- *PAYMNTDET4*
- *SNDTRRCVINFO1*
- *SNDTRRCVINFO2*
- *SNDTRRCVINFO3*
- *SNDTRRCVINFO4*
- *SNDTRRCVINFO5*
- *COVREQRD*
- *RECVCVR*
- *RECEIVER*
- *REIMINST1*
- *REIMINST4*
- *RCVRCORRS1*
- *RCVRCORRS2*
- *RCVRCORRS3*
- *RCVRCORRS4*
- *INTERMEDIARY1*
- *INTERMEDIARY2*
- *INTERMEDIARY3*
- *INTERMEDIARY4*

ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*

INSTRCD4
ITIMEIND1
ITIMEIND2
ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
LATEVNSEQNO
CONREFNO
Charge-Association

- *WAIVER*
- *DISACCRAPPL*
- *ACCRREQD*
- *DESC*

Charge-Application

- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*

Charge-Liquidation

- *ESN*
- *CHRGAMT*
- *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*
- *MISGRPTXN*

COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
Clpref
CONTREFNNO
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONTRACT_REF

Attribute	Description
Name	CONTRACT_REF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,N,F

TOP

MARGINPERCENT

Attribute	**Description**	
Name	MARGINPERCENT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRACK_LIMIT

Attribute	**Description**	
Name	TRACK_LIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CRLINE

Attribute	**Description**	
Name	CRLINE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT

Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String

Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	Description	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	Description	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,CRED,SPAY,SPRI,SSTD</td></tr></table>

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID

Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1

Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO

Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RATECODE

Attribute	**Description**	
Name	RATECODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,S

TOP

EXCHANGERATE

Attribute	**Description**	
Name	EXCHANGERATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATE_TYPE

Attribute	**Description**	
Name	RATE_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

Ude

Attribute	**Description**	
Name	Ude	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description

Name	USERDEVAL
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

2.71.3.RB-CreateFcychecksfinance-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONTRACT_REF*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *INSTRNO*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *BOOKINGDATE*
    - *VAL_DATE_BANK*
    - *VALUE_DATE_CUST*
    - *OTHR_PARTY_NAME*
    - *DRAWEE_BNK_NAME*
    - *FINANCING*
    - *MARGINPERCENT*
    - *TRACK_LIMIT*
    - *CRLINE*
    - *DISCOUNT_AMOUNT*
    - *MAKER*

MAKDTTIME
CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
Con
  CONTREFNO
  EVENTSEQ
  Adv
    ADVNAME
    SUPRESS
    PRIOR
    MEDM
    PARTYIDEN
    PARTYNAME
    CHGREQ
    PARTTYP
Settlements
  CONREFNO
  Contract-Settlement
    IBANACNO
    CUSTSPREAD
    SPREADDEFN
    COMPNT
    TAGCCY
    ACCBRN
    ACC
    ACCCCY
    EXRATE
    NETIND
    ERICCY
    ERIAMT
    GENMSG
    RATECD
    CLEARNW
    COVERBY
    RTGSPMNT
    BANKPRIOR
    RTGSNW
    PAYBY
    TRANSTYP
    INSTYP
    INSNO
    CHGDET

PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4

BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*

FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD

- *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*

TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9

- COMMIS10
- FUNMIS1
- FUNMIS2
- FUNMIS3
- FUNMIS4
- FUNMIS5
- FUNMIS6
- FUNMIS7
- FUNMIS8
- FUNMIS9
- FUNMIS10
- Txnmisdetails
- Compmisdetails
- Fundmisdetails

Clpref

- CONTREFNNO
- CONTRACT_CCY
- LATEVNSEQNO
- PRD
- PRDDESC
- COUNTERPARTY
- CURRENCY
- TENOR
- UNITS
- LOAN_CONREFNO
- RATECODE
- EXCHANGERATE
- RATE_TYPE
- MAXIMUM
- MINIMUM
- PAYMENT_MODE
- LOANVALDATE
- MATURITY_DATE
- Ude
  - USERDEID
  - UDEDESC
  - RATEASOF
  - USAGE
  - USERDEVAL

TXNUDFDETAILS

- FLDNAME
- FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONTRACT_REF

Attribute	Description
Name	CONTRACT_REF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CTR_PRTY_NAME

Attribute	Description
Name	CTR_PRTY_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRLINE

Attribute	Description
Name	CRLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	**Description**	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / ,L,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	Description	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	Description	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	**Description**
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	**Description**
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	**Description**
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	**Description**
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number

Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	Description	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	Description	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	Description	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	**Description**	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNNO

Attribute	**Description**	
Name	CONTREFNNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CONTRACT_CCY

Attribute	**Description**	
Name	CONTRACT_CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRD

Attribute	**Description**	
Name	PRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LOAN_CONREFNO

Attribute	**Description**	
Name	LOAN_CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RATECODE

Attribute	**Description**	
Name	RATECODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,S

TOP

EXCHANGERATE

Attribute	**Description**	
Name	EXCHANGERATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATE_TYPE

Attribute	**Description**	
Name	RATE_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

USAGE

Attribute	Description

Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.71.4.RB-CreateFcychecksfinance-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONTRACT_REF*
    - *Main-IO*
      - *CONTRACT_REF*
      - *FINANCING*
      - *MARGINPERCENT*
      - *TRACK_LIMIT*
      - *CRLINE*
      - *RECORD_STAT*
      - *AUTHSTAT*
      - *Con*
        - *CONTREFNO*
        - *EVENTSEQ*
        - *Adv*
          - *SUPRESS*
          - *PRIOR*
          - *MEDM*
          - *CHGREQ*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*
  - *RECVCVR*
  - *RECEIVER*
  - *REIMINST1*
  - *REIMINST4*
  - *RCVRCORRS1*
  - *RCVRCORRS2*
  - *RCVRCORRS3*
  - *RCVRCORRS4*
  - *INTERMEDIARY1*

INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail

INSTRCD1
INSTRCD2
INSTRCD3
INSTRCD4
ITIMEIND1
ITIMEIND2
ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges

- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*

TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
Clpref
CONTREFNNO
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONTRACT_REF

Attribute	Description
Name	CONTRACT_REF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONTRACT_REF

Attribute	Description
Name	CONTRACT_REF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FINANCING

Attribute	Description
Name	FINANCING

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRLINE

Attribute	Description
Name	CRLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,L,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	**Description**	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String

Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	**Description**	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	**Description**	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3

Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4

Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	**Description**	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	**Description**	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	Description	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail

Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String

Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**
Name	LATESN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	16

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.72.CreateFcychecksrealize

CreateFcychecksrealize

2.72.1.RB-CreateFcychecksrealize-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CASHREFNO*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *INSTRNO*
    - *INSTRU_DATE*
    - *CURRENCY*
    - *AMNT*
    - *VALUEDATE*
    - *REMRKS*
    - *MAKER*
    - *MAKDTTIME*
    - *CHKR*
    - *CHKDTTIME*
    - *RECORD_STAT*

AUTHSTAT

Con

- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*

SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4

BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*

SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT

TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN

COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3

FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

AMNT

Attribute	Description
Name	AMNT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr></table>

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Settlement

Attribute	**Description**	
Name	Contract-Settlement	
Datatype		
Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	**Description**	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description

Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	**Description**	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	**Description**	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	**Description**	
Name	CLEARNW	
Datatype	String	
Description	Indicates Network Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	**Description**
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates RTGS Payment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	**Description**	
Name	BANKPRIOR	
Datatype	String	
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1

Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC

Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	**Description**	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1

Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String

Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description

Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description

Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY

Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	Description	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	Description	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	Description	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	Description	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	Description	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	**Description**	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	**Description**	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS2

Attribute	**Description**	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.72.2.RB-CreateFcychecksrealize-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONREFNUM*
    - *REMRKS*
    - *MAKER*
    - *MAKDTTIME*
    - *CHKR*
    - *CHKDTTIME*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *Con*
      - *CONTREFNO*
      - *EVENTSEQ*
      - *Adv*
        - *SUPRESS*
        - *PRIOR*
        - *MEDM*
        - *CHGREQ*
    - *Settlements*
      - *CONREFNO*

LATEVNSEQNO

Contract-Settlement

- *CUSTSPREAD*
- *SPREADDEFN*
- *TAGCCY*
- *ACCBRN*
- *ACC*
- *EXRATE*
- *NETIND*
- *ERICCY*
- *ERIAMT*
- *GENMSG*
- *RATECD*
- *CLEARNW*
- *COVERBY*
- *RTGSPMNT*
- *BANKPRIOR*
- *RTGSNW*
- *PAYBY*
- *TRANSTYP*
- *INSTYP*
- *INSNO*
- *CHGDET*
- *PAYMNTDET1*
- *PAYMNTDET2*
- *PAYMNTDET3*
- *PAYMNTDET4*
- *SNDTRRCVINFO1*
- *SNDTRRCVINFO2*
- *SNDTRRCVINFO3*
- *SNDTRRCVINFO4*
- *SNDTRRCVINFO5*
- *COVREQRD*
- *RECVCVR*
- *RECEIVER*
- *REIMINST1*
- *REIMINST4*
- *RCVRCORRS1*
- *RCVRCORRS2*
- *RCVRCORRS3*
- *RCVRCORRS4*
- *INTERMEDIARY1*
- *INTERMEDIARY2*
- *INTERMEDIARY3*

INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
  INSTRCD1
  INSTRCD2

INSTRCD3
INSTRCD4
ITIMEIND1
ITIMEIND2
ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
LATEVNSEQNO
CONREFNO

- *Charge-Association*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*

MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement

Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	**Description**	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	Description	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO5

Attribute	Description	
Name	SNDTRRCVINFO5	
Datatype	String	
Description	Indicates Sender To Receiver Information 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	Description	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2

Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3

Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	**Description**	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5

Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID

Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1

Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO

Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Txnmisdetails

Attribute	**Description**	
Name	Txnmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

2.72.3.RB-CreateFcychecksrealize-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CASHREFNO*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *INSTRNO*
    - *INSTRU_DATE*
    - *CURRENCY*
    - *AMNT*
    - *VALUEDATE*
    - *REMRKS*
    - *MAKER*
    - *MAKDTTIME*
    - *CHKR*
    - *CHKDTTIME*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *Con*
      - *CONTREFNO*

- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*
- *Settlements*
  - *CONREFNO*
  - *Contract-Settlement*
    - *IBANACNO*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *COMPNT*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *ACCCCY*
    - *EXRATE*
    - *NETIND*
    - *ERICCY*
    - *ERIAMT*
    - *GENMSG*
    - *RATECD*
    - *CLEARNW*
    - *COVERBY*
    - *RTGSPMNT*
    - *BANKPRIOR*
    - *RTGSNW*
    - *PAYBY*
    - *TRANSTYP*
    - *INSTYP*
    - *INSNO*
    - *CHGDET*
    - *PAYMNTDET1*
    - *PAYMNTDET2*
    - *PAYMNTDET3*
    - *PAYMNTDET4*
    - *SNDTRRCVINFO1*
    - *SNDTRRCVINFO2*
    - *SNDTRRCVINFO3*

SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC

COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*

RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Charges

CONREFNO

Charge-Association

COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC

Charge-Application

CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY

CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2

COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6

FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CASHREFNO

Attribute	Description	
Name	CASHREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	Description	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SUPRESS

Attribute	**Description**	
Name	SUPRESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number

Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String

Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	Description	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	Description	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description

Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	**Description**	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	**Description**	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1

Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5

Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	**Description**	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	**Description**	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description

Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	Description	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	Description	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	**Description**	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS2

Attribute	**Description**	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.72.4.RB-CreateFcychecksrealize-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONREFNUM*
    - *Main-IO*
      - *CONREFNUM*
      - *REMRKS*
      - *MAKER*
      - *MAKDTTIME*
      - *CHKR*
      - *CHKDTTIME*
      - *RECORD_STAT*
      - *AUTHSTAT*
      - *Con*
        - *CONTREFNO*
        - *EVENTSEQ*
        - *Adv*
          - *SUPRESS*
          - *PRIOR*
          - *MEDM*

- CHGREQ
- Settlements
  - CONREFNO
  - LATEVNSEQNO
  - Contract-Settlement
    - CUSTSPREAD
    - SPREADDEFN
    - TAGCCY
    - ACCBRN
    - ACC
    - EXRATE
    - NETIND
    - ERICCY
    - ERIAMT
    - GENMSG
    - RATECD
    - CLEARNW
    - COVERBY
    - RTGSPMNT
    - BANKPRIOR
    - RTGSNW
    - PAYBY
    - TRANSTYP
    - INSTYP
    - INSNO
    - CHGDET
    - PAYMNTDET1
    - PAYMNTDET2
    - PAYMNTDET3
    - PAYMNTDET4
    - SNDTRRCVINFO1
    - SNDTRRCVINFO2
    - SNDTRRCVINFO3
    - SNDTRRCVINFO4
    - SNDTRRCVINFO5
    - COVREQRD
    - RECVCVR
    - RECEIVER
    - REIMINST1
    - REIMINST4
    - RCVRCORRS1
    - RCVRCORRS2
    - RCVRCORRS3
    - RCVRCORRS4

INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5

Settlement-Detail

- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *ULTBANDCD*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*
- *NOOFDEC*
- *ADDID*
- *SNDRRCVRINFO1*
- *SNDRRCVRINFO2*
- *SNDRRCVRINFO3*
- *SNDRRCVRINFO4*
- *SNDRRCVRINFO5*
- *SNDRRCVRINFO6*
- *DECLARTION*
- *REPRES1*
- *REPRES2*
- *REPRES3*
- *REPRES4*
- *RCVRACC*

- *Charges*
  - *LATEVNSEQNO*
  - *CONREFNO*
  - *Charge-Association*
    - *WAIVER*
    - *DISACCRAPPL*
    - *ACCRREQD*
    - *DESC*
  - *Charge-Application*
    - *CHRGAMT*
    - *DISACCRAPPL*
    - *WAIVER*
    - *LIQDIND*
  - *Charge-Liquidation*
    - *ESN*
    - *CHRGAMT*
    - *LIQDSTAT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*
  - *COSTCD4*
  - *COSTCD5*
  - *TXNMIS1*
  - *TXNMIS10*
  - *TXNMIS2*
  - *TXNMIS3*
  - *TXNMIS4*
  - *TXNMIS5*
  - *TXNMIS6*
  - *TXNMIS7*

TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	**Description**	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / ,A,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
enumeration	Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	15

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
enumeration	Y,N

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	**Description**	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String

Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	**Description**	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	**Description**	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3

Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4

Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	**Description**	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	**Description**	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	Description	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail

Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	**Description**	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description	
Name	REGREP2	
Datatype	String	
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description	
Name	REGREP3	
Datatype	String	
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String

Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**
Name	LATESN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.73.CreateInwardContract

CreateInwardContract

2.73.1.RB-CreateInwardContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *INSTRUMENT_CODE*
    - *INSTRUMENT_DESCRIPTION*
    - *PRCD*
    - *CONREFNUM*
    - *USERREF_NO*
    - *XREF*
    - *BATCHREFENUM*
    - *BATCHSEQNO*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *ACCBRN*
    - *CPTY_AC_NO*
    - *INSTNO*
    - *INSTRDATE*
    - *CCY*

AMT
LCYAMT
BNKCD
BNKNAME
BRNCDE
BRNNAME
REFNO
DATE
CORRESPBNK
CORRESPACNO
OTHERPARTYIDE
OTHR_PARTYNAME
BOKNGDT
MATDT
GRACEDAYS
PAYDUEDATE
ACBRN1
ACFORREALISATION
PROTEST
AUTOLIQD
LIQWITHBUKNG
INTREMARKS
REASON_CODE
REASON
CONREFNOLOG
MAKER
MAKDTTIME
CHKR
CHKDTTIME
SE_TXNSTAT
AUTHSTAT
VERSIONNORB
LATVERNO
Contract-Parties
- *PARTYTYPE*
- *PARTYIDEN*
- *PARTYNAME*
- *COUNTRYCD*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ADDLN4*
- *LANG*

Settlements

CONREFNO

Contract-Settlement

- *IBANACNO*
- *CUSTSPREAD*
- *SPREADDEFN*
- *COMPNT*
- *TAGCCY*
- *ACCBRN*
- *ACC*
- *ACCCCY*
- *EXRATE*
- *NETIND*
- *ERICCY*
- *ERIAMT*
- *GENMSG*
- *RATECD*
- *CLEARNW*
- *COVERBY*
- *RTGSPMNT*
- *BANKPRIOR*
- *RTGSNW*
- *PAYBY*
- *TRANSTYP*
- *INSTYP*
- *INSNO*
- *CHGDET*
- *PAYMNTDET1*
- *PAYMNTDET2*
- *PAYMNTDET3*
- *PAYMNTDET4*
- *SNDTRRCVINFO1*
- *SNDTRRCVINFO2*
- *SNDTRRCVINFO3*
- *SNDTRRCVINFO4*
- *SNDTRRCVINFO5*
- *COVREQRD*
- *RECVCVR*
- *RECEIVER*
- *REIMINST1*
- *REIMINST2*
- *REIMINST3*
- *REIMINST4*
- *RCVRCORRS1*
- *RCVRCORRS2*

RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5

ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*

SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Charges

CONREFNO

Charge-Association

COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC

Charge-Application

CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND

Charge-Liquidation

ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3

FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con

CONTREFNO

EVENTSEQ

Adv

- *ADVNAME*
- *SUPRESS*
- *PRIOR*
- *MEDM*
- *PARTYIDEN*
- *PARTYNAME*
- *CHGREQ*
- *PARTTYP*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description
Name	INSTRUMENT_DESCRIPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHSEQNO

Attribute	Description

Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTNO

Attribute	Description
Name	INSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRNCDE

Attribute	Description
Name	BRNCDE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORRESPBNK

Attribute	Description
Name	CORRESPBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CORRESPACNO

Attribute	Description
Name	CORRESPACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

OTHERPARTYIDE

Attribute	Description
Name	OTHERPARTYIDE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACBRN1

Attribute	Description
Name	ACBRN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQWITHBUKNG

Attribute	Description
Name	LIQWITHBUKNG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REASON

Attribute	Description
Name	REASON
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CONREFNOLOG

Attribute	**Description**
Name	CONREFNOLOG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	**Description**
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	**Description**
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SE_TXNSTAT

Attribute	Description
Name	SE_TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,L,R,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

VERSIONNORB

Attribute	Description
Name	VERSIONNORB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>DRAWER,PAYEE,REMITTING_BANK,DRAWEE</td></tr></table>

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRYCD

Attribute	**Description**	
Name	COUNTRYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ADDLN1

Attribute	**Description**	
Name	ADDLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDLN2

Attribute	**Description**	
Name	ADDLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDLN3

Attribute	**Description**	
Name	ADDLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	**Description**	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	**Description**	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	**Description**	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	**Description**	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1

Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2

Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5

Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1

Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	**Description**	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	**Description**	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application

Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	**Description**	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	Description	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	Description	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	Description	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	Description	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	

Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL

Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

2.73.2.RB-CreateInwardContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *INSTRUMENT_CODE*
    - *PRCD*
    - *CONREFNUM*
    - *USERREF_NO*
    - *XREF*
    - *BATCHREFENUM*
    - *CPTY_ID*
    - *CPTY_AC_NO*
    - *INSTNO*
    - *INSTRDATE*
    - *CCY*
    - *AMT*
    - *BNKCD*
    - *REFNO*
    - *DATE*
    - *CORRESPBNK*
    - *CORRESPACNO*
    - *OTHERPARTYIDE*

MATDT
GRACEDAYS
ACFORREALISATION
PROTEST
AUTOLIQD
LIQWITHBUKNG
INTREMARKS
REASON_CODE
Contract-Parties
- *PARTYNAME*
- *COUNTRYCD*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ADDLN4*
- *LANG*

Settlements
- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*

PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5

COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *ULTBANDCD*
- *SUPPID*
- *PAYERID*

PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Charges
- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails
- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*

REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS

FLDNAME

FLDVAL

Con

CONTREFNO

EVENTSEQ

Adv

SUPRESS

PRIOR

MEDM

CHGREQ

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BATCHREFENUM

Attribute	**Description**	
Name	BATCHREFENUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	**Description**	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_AC_NO

Attribute	**Description**	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTNO

Attribute	Description
Name	INSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BNKCD

Attribute	Description
Name	BNKCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CORRESPBNK

Attribute	Description
Name	CORRESPBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CORRESPACNO

Attribute	Description
Name	CORRESPACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

OTHERPARTYIDE

Attribute	Description
Name	OTHERPARTYIDE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PROTEST

Attribute	Description
Name	PROTEST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQWITHBUKNG

Attribute	Description
Name	LIQWITHBUKNG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Contract-Parties

Attribute	**Description**	
Name	Contract-Parties	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRYCD

Attribute	**Description**	
Name	COUNTRYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ADDLN1

Attribute	**Description**	
Name	ADDLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDLN2

Attribute	Description	
Name	ADDLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDLN3

Attribute	Description	
Name	ADDLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDLN4

Attribute	Description	
Name	ADDLN4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

LANG

Attribute	Description	
Name	LANG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	**Description**	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	**Description**	
Name	CLEARNW	
Datatype	String	
Description	Indicates Network Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	**Description**	
Name	COVERBY	
Datatype	String	
Description	Indicates Cover By Clearing : C Message : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	**Description**
Name	RTGSPMNT
Datatype	String

Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP

Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2

Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Txnmisdetails

Attribute	**Description**	
Name	Txnmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Compmisdetails

Attribute	**Description**	
Name	Compmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Con

Attribute	Description
Name	Con
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

2.73.3.RB-CreateInwardContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *INSTRUMENT_CODE*
    - *INSTRUMENT_DESCRIPTION*
    - *PRCD*
    - *CONREFNUM*
    - *USERREF_NO*
    - *XREF*
    - *BATCHREFENUM*
    - *BATCHSEQNO*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *ACCBRN*
    - *CPTY_AC_NO*
    - *INSTNO*
    - *INSTRDATE*
    - *CCY*
    - *AMT*
    - *LCYAMT*
    - *BNKCD*

BNKNAME
BRNCDE
BRNNAME
REFNO
DATE
CORRESPBNK
CORRESPACNO
OTHERPARTYIDE
OTHR_PARTYNAME
BOKNGDT
MATDT
GRACEDAYS
PAYDUEDATE
ACBRN1
ACFORREALISATION
PROTEST
AUTOLIQD
LIQWITHBUKNG
INTREMARKS
REASON_CODE
REASON
CONREFNOLOG
MAKER
MAKDTTIME
CHKR
CHKDTTIME
SE_TXNSTAT
AUTHSTAT
VERSIONNORB
LATVERNO
Contract-Parties
- *PARTYTYPE*
- *PARTYIDEN*
- *PARTYNAME*
- *COUNTRYCD*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ADDLN4*
- *LANG*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*

CUSTSPREAD
SPREADDEFN
COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1

INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND

Settlement-Detail

- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*

- NOOFDEC
- ADDID
- SNDRRCVRINFO1
- SNDRRCVRINFO2
- SNDRRCVRINFO3
- SNDRRCVRINFO4
- SNDRRCVRINFO5
- SNDRRCVRINFO6
- DECLARTION
- REPRES1
- REPRES2
- REPRES3
- REPRES4
- RCVRACC

Charges

- CONREFNO
- Charge-Association
  - COMPNT
  - CREATESN
  - RULE
  - WAIVER
  - DISACCRAPPL
  - ACCRREQD
  - DESC
- Charge-Application
  - CREATESN
  - COMPNT
  - TGCCY
  - TGAMT
  - CHRGCCY
  - CHRGAMT
  - DISACCRAPPL
  - WAIVER
  - LIQDIND
- Charge-Liquidation
  - ESN
  - COMPNT
  - CHRGCCY
  - CHRGAMT
  - LIQDSTAT

Misdetails

- CONREFNO
- LATESN
- MISGRP

RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6

FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv

ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 20

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description
Name	INSTRUMENT_DESCRIPTION
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 255

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 4

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTNO

Attribute	**Description**	
Name	INSTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRDATE

Attribute	**Description**	
Name	INSTRDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BRNCDE

Attribute	Description
Name	BRNCDE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

REFNO

Attribute	**Description**	
Name	REFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DATE

Attribute	**Description**	
Name	DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CORRESPBNK

Attribute	**Description**	
Name	CORRESPBNK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CORRESPACNO

Attribute	**Description**	
Name	CORRESPACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

OTHERPARTYIDE

Attribute	Description
Name	OTHERPARTYIDE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PAYDUEDATE

Attribute	**Description**	
Name	PAYDUEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACBRN1

Attribute	**Description**	
Name	ACBRN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACFORREALISATION

Attribute	**Description**	
Name	ACFORREALISATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

PROTEST

Attribute	**Description**	
Name	PROTEST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

LIQWITHBUKNG

Attribute	Description
Name	LIQWITHBUKNG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

REASON

Attribute	Description
Name	REASON

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CONREFNOLOG

Attribute	Description
Name	CONREFNOLOG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SE_TXNSTAT

Attribute	**Description**	
Name	SE_TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,L,R,H

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

VERSIONNORB

Attribute	**Description**	
Name	VERSIONNORB	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / DRAWER,PAYEE,REMITTING_BANK,DRAWEE

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	**Description**	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	**Description**	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1

Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2

Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDINST5

Attribute	Description
Name	ORDINST5

Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	Description	
Name	REGREP1	
Datatype	String	
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1

Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	**Description**	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	**Description**	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application

Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	**Description**	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	

Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL

Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	**Description**	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.73.4.RB-CreateInwardContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNUM*
    - *Contract-Details-IO*
      - *INSTRUMENT_CODE*
      - *PRCD*
      - *CONREFNUM*
      - *USERREF_NO*
      - *XREF*
      - *BATCHREFENUM*
      - *CPTY_ID*
      - *CPTY_AC_NO*
      - *INSTNO*
      - *INSTRDATE*
      - *CCY*
      - *AMT*
      - *BNKCD*
      - *REFNO*
      - *DATE*

CORRESPBNK
CORRESPACNO
OTHERPARTYIDE
MATDT
GRACEDAYS
ACFORREALISATION
PROTEST
AUTOLIQD
LIQWITHBUKNG
INTREMARKS
REASON_CODE
Contract-Parties
  PARTYNAME
  COUNTRYCD
  ADDLN1
  ADDLN2
  ADDLN3
  ADDLN4
  LANG
Settlements
  CONREFNO
  LATEVNSEQNO
  Contract-Settlement
    CUSTSPREAD
    SPREADDEFN
    TAGCCY
    ACCBRN
    ACC
    EXRATE
    NETIND
    ERICCY
    ERIAMT
    GENMSG
    RATECD
    CLEARNW
    COVERBY
    RTGSPMNT
    BANKPRIOR
    RTGSNW
    PAYBY
    TRANSTYP
    INSTYP
    INSNO
    CHGDET

PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2

BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
  INSTRCD1
  INSTRCD2
  INSTRCD3
  INSTRCD4
  ITIMEIND1
  ITIMEIND2
  ITIMEIND3
  INSTRCD5
  BANKOPERCD
  INSTRCD6
  TRNSTYPCD
  REGREP1
  REGREP2
  REGREP3
  ENVCONT1
  ENVCONT2
  ENVCONT3
  ENVCONT4
  ENVCONT5
Lcl_Clearing
  FREETXT1
  FREETXT2
  FREETXT3
  PMNTCD
  ADDINFOSORBNET

ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Charges
- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails
- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*

REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails

Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
SUPRESS
PRIOR
MEDM
CHGREQ
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description	
Name	INSTRUMENT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

PRCD

Attribute	Description	
Name	PRCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CONREFNUM

Attribute	Description	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USERREF_NO

Attribute	Description	
Name	USERREF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTNO

Attribute	Description
Name	INSTNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CORRESPBNK

Attribute	Description
Name	CORRESPBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CORRESPACNO

Attribute	Description
Name	CORRESPACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

OTHERPARTYIDE

Attribute	Description
Name	OTHERPARTYIDE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQWITHBUKNG

Attribute	Description
Name	LIQWITHBUKNG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	**Description**	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String

Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description

Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	**Description**	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	**Description**	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	**Description**	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4

Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5

Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	**Description**	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1

Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	**Description**	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	**Description**
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	**Description**	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String

Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3

Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	**Description**	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	**Description**	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	**Description**	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number

Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	**Description**
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	**Description**
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	**Description**
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	**Description**
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

CHGREQ

Attribute	**Description**	
Name	CHGREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	**Description**

Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.74.CreateInwardRealize

CreateInwardRealize

2.74.1.RB-CreateInwardRealize-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-Full*
    - *CONTREFNO*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *OTHERPARTYIDE*
    - *OTHR_PARTYNAME*
    - *INSTRUMENTNO*
    - *INSTRUMENTDATE*
    - *CONTRACTCCY*
    - *CONTRACTAMT*
    - *DUEDATE*
    - *REMBANKCODE*
    - *BANK_NAME*
    - *REMBRANCHCODE*
    - *BRANCH_NAME*
    - *REMREFNO*

REMBNKREFDT
CORRESBANK
CORRESACNO
ACCBRN
CPTY_AC_NO
CR_ACC_BR
REALISATIONAC
VALUEDATE
CHARGES_DEDUCTED
REALISEDNETAMT
DISHNRCODE
DISHONORREASON
LATVERNO
MAKER
MAKDTTIME
TXNSTAT
CHKR
CHKDTTIME
AUTHSTAT
EVENT_SEQ_NO
CURR_EVENT_CODE
CONTRCTREF_NO
Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*

PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3

BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*

ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT

CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2

TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4

COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master-Full

Attribute	Description
Name	Contract-Master-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHERPARTYIDE

Attribute	Description
Name	OTHERPARTYIDE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRUMENTNO

Attribute	Description

Name	INSTRUMENTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENTDATE

Attribute	Description
Name	INSTRUMENTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONTRACTAMT

Attribute	Description
Name	CONTRACTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMBANKCODE

Attribute	Description
Name	REMBANKCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANK_NAME

Attribute	Description
Name	BANK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REMBRANCHCODE

Attribute	Description
Name	REMBRANCHCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRANCH_NAME

Attribute	Description
Name	BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REMREFNO

Attribute	Description

Name	REMREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REMBNKREFDT

Attribute	Description
Name	REMBNKREFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CORRESBANK

Attribute	Description
Name	CORRESBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CORRESACNO

Attribute	Description
Name	CORRESACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CR_ACC_BR

Attribute	Description
Name	CR_ACC_BR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REALISATIONAC

Attribute	Description
Name	REALISATIONAC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHARGES_DEDUCTED

Attribute	Description
Name	CHARGES_DEDUCTED
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REALISEDNETAMT

Attribute	Description
Name	REALISEDNETAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISHNRCODE

Attribute	Description
Name	DISHNRCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DISHONORREASON

Attribute	Description
Name	DISHONORREASON
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	Description	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,L,R,H

TOP

CHKR

Attribute	Description	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,A</td></tr></table>

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CURR_EVENT_CODE

Attribute	Description
Name	CURR_EVENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CONTRCTREF_NO

Attribute	Description
Name	CONTRCTREF_NO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Settlements

Attribute	**Description**	
Name	Settlements	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Settlement

Attribute	**Description**	
Name	Contract-Settlement	
Datatype		
Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	**Description**	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	**Description**	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	Description	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	**Description**
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	**Description**
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	**Description**
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	**Description**
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.74.2.RB-CreateInwardRealize-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-IO*
    - *CONTREFNO*
    - *CORRESBANK*
    - *CORRESACNO*
    - *CPTY_AC_NO*
    - *REALISATIONAC*
    - *VALUEDATE*
    - *CHARGES_DEDUCTED*
    - *DISHNRCODE*
    - *EVENT_SEQ_NO*
    - *CURR_EVENT_CODE*
    - *CONTRCTREF_NO*
    - *Settlements*
      - *CONREFNO*
      - *LATEVNSEQNO*
      - *Contract-Settlement*
        - *CUSTSPREAD*
        - *SPREADDEFN*
        - *TAGCCY*

ACCBRN
ACC
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4

ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*

INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
LATEVNSEQNO
CONREFNO
Charge-Association
WAIVER
DISACCRAPPL
ACCRREQD
DESC

- *Charge-Application*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*
- *MISGRPTXN*
- *COMPMIS1*
- *COMPMIS10*
- *COMPMIS2*
- *COMPMIS3*

COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
SUPRESS
PRIOR
MEDM
CHGREQ

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CORRESBANK

Attribute	Description
Name	CORRESBANK

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CORRESACNO

Attribute	Description
Name	CORRESACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REALISATIONAC

Attribute	Description
Name	REALISATIONAC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHARGES_DEDUCTED

Attribute	**Description**	
Name	CHARGES_DEDUCTED	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISHNRCODE

Attribute	**Description**	
Name	DISHNRCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CURR_EVENT_CODE

Attribute	**Description**	
Name	CURR_EVENT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CONTRCTREF_NO

Attribute	**Description**
Name	CONTRCTREF_NO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String

Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	Description	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	Description	
Name	CLEARNW	
Datatype	String	
Description	Indicates Network Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	Description	
Name	COVERBY	
Datatype	String	
Description	Indicates Cover By Clearing : C Message : M	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4

Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String

Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing

Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ULTBANDCD

Attribute	Description	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SUPPID

Attribute	Description	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	Description	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String

Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**
Name	LATESN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

2.74.3.RB-CreateInwardRealize-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-Full*
    - *CONTREFNO*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *OTHERPARTYIDE*
    - *OTHR_PARTYNAME*
    - *INSTRUMENTNO*
    - *INSTRUMENTDATE*
    - *CONTRACTCCY*
    - *CONTRACTAMT*
    - *DUEDATE*
    - *REMBANKCODE*
    - *BANK_NAME*
    - *REMBRANCHCODE*
    - *BRANCH_NAME*
    - *REMREFNO*
    - *REMBNKREFDT*
    - *CORRESBANK*
    - *CORRESACNO*

ACCBRN
CPTY_AC_NO
CR_ACC_BR
REALISATIONAC
VALUEDATE
CHARGES_DEDUCTED
REALISEDNETAMT
DISHNRCODE
DISHONORREASON
LATVERNO
MAKER
MAKDTTIME
TXNSTAT
CHKR
CHKDTTIME
AUTHSTAT
EVENT_SEQ_NO
CURR_EVENT_CODE
CONTRCTREF_NO
Settlements
  CONREFNO
  Contract-Settlement
    IBANACNO
    CUSTSPREAD
    SPREADDEFN
    COMPNT
    TAGCCY
    ACCBRN
    ACC
    ACCCCY
    EXRATE
    NETIND
    ERICCY
    ERIAMT
    GENMSG
    RATECD
    CLEARNW
    COVERBY
    RTGSPMNT
    BANKPRIOR
    RTGSNW
    PAYBY
    TRANSTYP
    INSTYP

INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2

ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER

- *DISACCRAPPL*
- *ACCRREQD*
- *DESC*

Charge-Application

- *CREATESN*
- *COMPNT*
- *TGCCY*
- *TGAMT*
- *CHRGCCY*
- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*

Charge-Liquidation

- *ESN*
- *COMPNT*
- *CHRGCCY*
- *CHRGAMT*
- *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*

TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7

COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master-Full

Attribute	Description
Name	Contract-Master-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	**Description**	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_NAME

Attribute	**Description**	
Name	CPTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYIDE

Attribute	**Description**	
Name	OTHERPARTYIDE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OTHR_PARTYNAME

Attribute	**Description**	
Name	OTHR_PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INSTRUMENTNO

Attribute	Description
Name	INSTRUMENTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENTDATE

Attribute	Description
Name	INSTRUMENTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CONTRACTAMT

Attribute	Description
Name	CONTRACTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DUEDATE

Attribute	Description
Name	DUEDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMBANKCODE

Attribute	Description
Name	REMBANKCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANK_NAME

Attribute	Description
Name	BANK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REMBRANCHCODE

Attribute	Description
Name	REMBRANCHCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRANCH_NAME

Attribute	Description
Name	BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

REMREFNO

Attribute	Description
Name	REMREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

REMBNKREFDT

Attribute	Description
Name	REMBNKREFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORRESBANK

Attribute	Description
Name	CORRESBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CORRESACNO

Attribute	Description
Name	CORRESACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CR_ACC_BR

Attribute	Description
Name	CR_ACC_BR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

REALISATIONAC

Attribute	Description
Name	REALISATIONAC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHARGES_DEDUCTED

Attribute	Description
Name	CHARGES_DEDUCTED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REALISEDNETAMT

Attribute	Description
Name	REALISEDNETAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISHNRCODE

Attribute	Description
Name	DISHNRCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DISHONORREASON

Attribute	Description
Name	DISHONORREASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,L,R,H</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CURR_EVENT_CODE

Attribute	**Description**	
Name	CURR_EVENT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CONTRCTREF_NO

Attribute	Description	
Name	CONTRCTREF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Settlements

Attribute	Description	
Name	Settlements	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Settlement

Attribute	Description	
Name	Contract-Settlement	
Datatype		
Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String

Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String

Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.74.4.RB-CreateInwardRealize-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Master-PK*
      - *CONTREFNO*
    - *Contract-Master-IO*
      - *CONTREFNO*
      - *CORRESBANK*
      - *CORRESACNO*
      - *CPTY_AC_NO*
      - *REALISATIONAC*
      - *VALUEDATE*
      - *CHARGES_DEDUCTED*
      - *DISHNRCODE*
      - *EVENT_SEQ_NO*
      - *CURR_EVENT_CODE*
      - *CONTRCTREF_NO*
      - *Settlements*
        - *CONREFNO*
        - *LATEVNSEQNO*
        - *Contract-Settlement*

CUSTSPREAD
SPREADDEFN
TAGCCY
ACCBRN
ACC
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1

ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*

ITIMEIND1
ITIMEIND2
ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
LATEVNSEQNO
CONREFNO
Charge-Association
WAIVER

DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1

COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
SUPRESS
PRIOR
MEDM
CHGREQ
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Master-PK

Attribute	Description
Name	Contract-Master-PK
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CORRESBANK

Attribute	Description
Name	CORRESBANK
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CORRESACNO

Attribute	Description
Name	CORRESACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REALISATIONAC

Attribute	Description
Name	REALISATIONAC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHARGES_DEDUCTED

Attribute	Description
Name	CHARGES_DEDUCTED

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISHNRCODE

Attribute	Description
Name	DISHNRCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURR_EVENT_CODE

Attribute	Description
Name	CURR_EVENT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CONTRCTREF_NO

Attribute	Description
Name	CONTRCTREF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	**Description**	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String

Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	**Description**	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	**Description**	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3

Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4

Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	**Description**	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	**Description**	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	Description	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail

Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	**Description**	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description	
Name	REGREP2	
Datatype	String	
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description	
Name	REGREP3	
Datatype	String	
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String

Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**
Name	LATESN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	Description	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	Description	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description

Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.75.CreateOutBulkCol

CreateOutBulkCol

2.75.1.RB-CreateOutBulkCol-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Full*
    - *CREDITLINE*
    - *OTHRPARTYLMTCHK*
    - *MARGINPERC*
    - *FINANCING*
    - *COLLATERAL*
    - *COLLPOOL*
    - *INSTRCODE*
    - *PRODCODE*
    - *CPTYIDEN*
    - *CPACCNO*
    - *CONTCCY*
    - *OTHRPTYIDEN*
    - *DRACCREAL*
    - *BANKCD*
    - *BOOKINGDATE*

PROTEST
TRACKLIMIT
INSTRUMENTDESC
PRODDESC
COUNTERPRTYNAME
OTHERPARTYNAME
BNKNAME
BRNNAME
NOOFINSTRUMENTS
BRNCODE
BATCHREFENUM
ACCBRN
DRACCBRN
PROCESSTAT
VERNUM
CVERNO
CONST
AUTHSTAT
CHKR
CHKDTTIME
MAKER
MAKDTTIME
Bulk-Input-Detail
- *CONTREFNO*
- *INSTRNO*
- *INSTRDATE*
- *AMNT*
- *CONTAMTLCY*
- *MATURITYDATE*
- *DISCAMT*
- *COLLTVAL*
- *INTREMARKS*
- *PROCESSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Full

Attribute	Description
Name	Bulk-Input-Full
Datatype	
Description	

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

OTHRPARTYLMTCHK

Attribute	Description
Name	OTHRPARTYLMTCHK

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,F,N

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRCODE

Attribute	Description
Name	INSTRCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRODCODE

Attribute	Description
Name	PRODCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPACCNO

Attribute	Description
Name	CPACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CONTCCY

Attribute	Description	
Name	CONTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

OTHRPTYIDEN

Attribute	Description	
Name	OTHRPTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

DRACCREAL

Attribute	Description	
Name	DRACCREAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BANKCD

Attribute	Description	
Name	BANKCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

INSTRUMENTDESC

Attribute	Description
Name	INSTRUMENTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COUNTERPRTYNAME

Attribute	**Description**	
Name	COUNTERPRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYNAME

Attribute	**Description**	
Name	OTHERPARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BNKNAME

Attribute	**Description**	
Name	BNKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,U</td></tr></table>

TOP

VERNUM

Attribute	Description
Name	VERNUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CVERNO

Attribute	Description
Name	CVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	enumeration	,O,C

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

CHKR

Attribute	Description	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	Description	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

Bulk-Input-Detail

Attribute	Description
Name	Bulk-Input-Detail
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 20

TOP

INSTRDATE

Attribute	Description

Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CONTAMTLCY

Attribute	Description
Name	CONTAMTLCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTVAL

Attribute	Description
Name	COLLTVAL
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U

TOP

2.75.2.RB-CreateOutBulkCol-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-IO*
    - *CREDITLINE*
    - *OTHRPARTYLMTCHK*
    - *MARGINPERC*
    - *FINANCING*
    - *COLLATERAL*
    - *COLLPOOL*
    - *INSTRCODE*
    - *PRODCODE*
    - *CPTYIDEN*
    - *CPACCNO*
    - *CONTCCY*
    - *OTHRPTYIDEN*
    - *DRACCREAL*
    - *BANKCD*
    - *PROTEST*
    - *TRACKLIMIT*
    - *NOOFINSTRUMENTS*
    - *BATCHREFENUM*

Bulk-Input-Detail

INSTRNO

INSTRDATE

AMNT

MATURITYDATE

INTREMARKS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

OTHRPARTYLMTCHK

Attribute	Description
Name	OTHRPARTYLMTCHK
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / E,F,N

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,C,T,N

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRCODE

Attribute	Description
Name	INSTRCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRODCODE

Attribute	Description
Name	PRODCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTYIDEN

Attribute	Description	
Name	CPTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPACCNO

Attribute	Description	
Name	CPACCNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CONTCCY

Attribute	Description	
Name	CONTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

OTHRPTYIDEN

Attribute	Description	
Name	OTHRPTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BANKCD

Attribute	Description
Name	BANKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Bulk-Input-Detail

Attribute	Description
Name	Bulk-Input-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

2.75.3.RB-CreateOutBulkCol-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Full*
    - *CREDITLINE*
    - *OTHRPARTYLMTCHK*
    - *MARGINPERC*
    - *FINANCING*
    - *COLLATERAL*
    - *COLLPOOL*
    - *INSTRCODE*
    - *PRODCODE*
    - *CPTYIDEN*
    - *CPACCNO*
    - *CONTCCY*
    - *OTHRPTYIDEN*
    - *DRACCREAL*
    - *BANKCD*
    - *BOOKINGDATE*
    - *PROTEST*
    - *TRACKLIMIT*
    - *INSTRUMENTDESC*

PRODDESC
COUNTERPRTYNAME
OTHERPARTYNAME
BNKNAME
BRNNAME
NOOFINSTRUMENTS
BRNCODE
BATCHREFENUM
ACCBRN
DRACCBRN
PROCESSTAT
VERNUM
CVERNO
CONST
AUTHSTAT
CHKR
CHKDTTIME
MAKER
MAKDTTIME
Bulk-Input-Detail
CONTREFNO
INSTRNO
INSTRDATE
AMNT
CONTAMTLCY
MATURITYDATE
DISCAMT
COLLTVAL
INTREMARKS
PROCESSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Full

Attribute	Description
Name	Bulk-Input-Full
Datatype	
Description	

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

OTHRPARTYLMTCHK

Attribute	**Description**	
Name	OTHRPARTYLMTCHK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MARGINPERC

Attribute	**Description**	
Name	MARGINPERC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,F,N

TOP

COLLATERAL

Attribute	**Description**	
Name	COLLATERAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,C,T,N

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRCODE

Attribute	Description
Name	INSTRCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRODCODE

Attribute	Description
Name	PRODCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPACCNO

Attribute	Description
Name	CPACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BANKCD

Attribute	Description
Name	BANKCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INSTRUMENTDESC

Attribute	Description
Name	INSTRUMENTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

COUNTERPRTYNAME

Attribute	Description
Name	COUNTERPRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,U

TOP

VERNUM

Attribute	Description
Name	VERNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CVERNO

Attribute	Description
Name	CVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

Bulk-Input-Detail

Attribute	Description
Name	Bulk-Input-Detail
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CONTAMTLCY

Attribute	Description
Name	CONTAMTLCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number

Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

COLLTVAL

Attribute	Description
Name	COLLTVAL
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	255

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
enumeration	,P,U

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.75.4.RB-CreateOutBulkCol-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Input-PK*
      - *BATCHREFENUM*
    - *Bulk-Input-IO*
      - *CREDITLINE*
      - *OTHRPARTYLMTCHK*
      - *MARGINPERC*
      - *FINANCING*
      - *COLLATERAL*
      - *COLLPOOL*
      - *INSTRCODE*
      - *PRODCODE*
      - *CPTYIDEN*
      - *CPACCNO*
      - *CONTCCY*
      - *OTHRPTYIDEN*
      - *DRACCREAL*
      - *BANKCD*
      - *PROTEST*

TRACKLIMIT
NOOFINSTRUMENTS
BATCHREFENUM
Bulk-Input-Detail
INSTRNO
INSTRDATE
AMNT
MATURITYDATE
INTREMARKS
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Input-PK

Attribute	Description
Name	Bulk-Input-PK
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

OTHRPARTYLMTCHK

Attribute	**Description**	
Name	OTHRPARTYLMTCHK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MARGINPERC

Attribute	**Description**	
Name	MARGINPERC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,F,N

TOP

COLLATERAL

Attribute	**Description**	
Name	COLLATERAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,C,T,N

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRCODE

Attribute	Description
Name	INSTRCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRODCODE

Attribute	Description
Name	PRODCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPACCNO

Attribute	Description
Name	CPACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BANKCD

Attribute	Description
Name	BANKCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Bulk-Input-Detail

Attribute	Description
Name	Bulk-Input-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date

Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.76.CreateOutFinDet

CreateOutFinDet

2.76.1.RB-CreateOutFinDet-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Rbtbs-Contract-Master-Full*
    - *CPTYIDEN*
    - *INSTRNO*
    - *INSTRDATE*
    - *CONTCCY*
    - *AMNT*
    - *OTHRPTYIDEN*
    - *BOOKINGDATE*
    - *TRACKLIMIT*
    - *CREDITLINE*
    - *MARGINPERC*
    - *FINANCING*
    - *DISCOUNTAMT*
    - *DUEDATE*
    - *OTHERPARTYNAME*
    - *CPTYNAME*

CONREFNUM
MAKER
MAKERDT
CHKR
CHECKERDT
CONTSTAT
AUTHSTAT
OTHRPARTYLMTCHK
Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*

COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID

POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*

RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL

WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4

COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8

- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Clpref

- *CONTREFNNO*
- *CONTRACT_CCY*
- *LATEVNSEQNO*
- *PRD*
- *PRDDESC*
- *COUNTERPARTY*
- *CURRENCY*
- *TENOR*
- *UNITS*
- *LOAN_CONREFNO*
- *RATECODE*
- *EXCHANGERATE*
- *RATE_TYPE*
- *MAXIMUM*
- *MINIMUM*
- *PAYMENT_MODE*
- *LOANVALDATE*
- *MATURITY_DATE*
- *Ude*
  - *USERDEID*
  - *UDEDESC*
  - *RATEASOF*
  - *USAGE*
  - *USERDEVAL*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Con

- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*

PARTTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Rbtbs-Contract-Master-Full

Attribute	Description
Name	Rbtbs-Contract-Master-Full
Datatype	
Description	

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTYNAME

Attribute	**Description**	
Name	CPTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CONREFNUM

Attribute	**Description**	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDT

Attribute	**Description**	
Name	MAKERDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDT

Attribute	Description
Name	CHECKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

OTHRPARTYLMTCHK

Attribute	Description
Name	OTHRPARTYLMTCHK
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	**Description**	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS5

Attribute	**Description**	
Name	TRANMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	**Description**	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS7

Attribute	**Description**	
Name	TRANMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description

Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description

Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	
Restrictions	

Restrictions	Description
maxLength	15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	
Restrictions	

Restrictions	Description
enumeration	Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	
Restrictions	

Restrictions	Description
maxLength	15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

2.76.2.RB-CreateOutFinDet-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Rbtbs-Contract-Master-IO*
    - *TRACKLIMIT*
    - *CREDITLINE*
    - *MARGINPERC*
    - *CONREFNUM*
    - *OTHRPARTYLMTCHK*
    - *Settlements*
      - *CONREFNO*
      - *LATEVNSEQNO*
      - *Contract-Settlement*
        - *CUSTSPREAD*
        - *SPREADDEFN*
        - *TAGCCY*
        - *ACCBRN*
        - *ACC*
        - *EXRATE*
        - *NETIND*
        - *ERICCY*
        - *ERIAMT*

GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2

ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*

REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
LATEVNSEQNO
CONREFNO
Charge-Association
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation

ESN
CHRGAMT
LIQDSTAT

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9

FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
Clpref
CONTREFNNO
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
SUPRESS
PRIOR
MEDM
CHGREQ

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Rbtbs-Contract-Master-IO

Attribute	Description
Name	Rbtbs-Contract-Master-IO
Datatype	
Description	

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CREDITLINE

Attribute	**Description**	
Name	CREDITLINE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

MARGINPERC

Attribute	**Description**	
Name	MARGINPERC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNUM

Attribute	**Description**	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

OTHRPARTYLMTCHK

Attribute	**Description**	
Name	OTHRPARTYLMTCHK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	**Description**	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String

Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	Description	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	Description	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3

Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4

Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	**Description**	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	**Description**	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	Description	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail

Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	**Description**	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String

Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**
Name	LATESN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	Description	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	Description	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	16

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description

Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

2.76.3.RB-CreateOutFinDet-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Rbtbs-Contract-Master-Full*
    - *CPTYIDEN*
    - *INSTRNO*
    - *INSTRDATE*
    - *CONTCCY*
    - *AMNT*
    - *OTHRPTYIDEN*
    - *BOOKINGDATE*
    - *TRACKLIMIT*
    - *CREDITLINE*
    - *MARGINPERC*
    - *FINANCING*
    - *DISCOUNTAMT*
    - *DUEDATE*
    - *OTHERPARTYNAME*
    - *CPTYNAME*
    - *CONREFNUM*
    - *MAKER*
    - *MAKERDT*

CHKR
CHECKERDT
CONTSTAT
AUTHSTAT
OTHRPARTYLMTCHK
Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*
  - *RECVCVR*
  - *RECEIVER*

REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6

ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*

ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation

- *ESN*
- *COMPNT*
- *CHRGCCY*
- *CHRGAMT*
- *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*
- *MISGRPTXN*
- *COMPMIS1*
- *COMPMIS10*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*

COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails

Compmisdetails
Fundmisdetails
Clpref
CONTREFNNO
CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM
PAYMENT_MODE
LOANVALDATE
MATURITY_DATE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Rbtbs-Contract-Master-Full

Attribute	Description
Name	Rbtbs-Contract-Master-Full
Datatype	
Description	

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERDT

Attribute	Description
Name	MAKERDT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDT

Attribute	Description
Name	CHECKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

OTHRPARTYLMTCHK

Attribute	Description
Name	OTHRPARTYLMTCHK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String

Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String

Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description

Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	**Description**	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	**Description**	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	**Description**	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	**Description**	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2

Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3

Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	**Description**	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	**Description**	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	**Description**	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2

Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	**Description**	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	**Description**	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	**Description**	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**	
Name	REGREP2	
Datatype	String	
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**
Name	REGREP3
Datatype	String

Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2

Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	**Description**	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	**Description**	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO2

Attribute	**Description**	
Name	SNDRRCVRINFO2	
Datatype	String	
Description	Indicates Sender Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	**Description**	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	**Description**	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description

Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.76.4.RB-CreateOutFinDet-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Rbtbs-Contract-Master-PK*
      - *CONREFNUM*
    - *Rbtbs-Contract-Master-IO*
      - *TRACKLIMIT*
      - *CREDITLINE*
      - *MARGINPERC*
      - *CONREFNUM*
      - *OTHRPARTYLMTCHK*
      - *Settlements*
        - *CONREFNO*
        - *LATEVNSEQNO*
        - *Contract-Settlement*
          - *CUSTSPREAD*
          - *SPREADDEFN*
          - *TAGCCY*
          - *ACCBRN*
          - *ACC*
          - *EXRATE*

NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3

ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*

TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
LATEVNSEQNO
CONREFNO
Charge-Association
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CHRGAMT
DISACCRAPPL

- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*
- *MISGRPTXN*
- *COMPMIS1*
- *COMPMIS10*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*

COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
Clpref
CONTREFNNO
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
SUPRESS
PRIOR
MEDM
CHGREQ
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Rbtbs-Contract-Master-PK

Attribute	Description
Name	Rbtbs-Contract-Master-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

Rbtbs-Contract-Master-IO

Attribute	Description
Name	Rbtbs-Contract-Master-IO
Datatype	
Description	

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: Y,N

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

OTHRPARTYLMTCHK

Attribute	Description
Name	OTHRPARTYLMTCHK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String

Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description

Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1

Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	Description	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5

Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD

Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3

Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	Description	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATEVNSEQNO

Attribute	Description	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	Indicates Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Clpref

Attribute	Description

Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description

Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
enumeration	Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	15

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
enumeration	Y,N

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.77.CreateOutRealization

CreateOutRealization

2.77.1.RB-CreateOutRealization-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contractdet-Full*
    - *CONREFNUM*
    - *MAKER*
    - *MAKERDT*
    - *CHKR*
    - *CHECKERDT*
    - *CONTSTAT*
    - *AUTSTAT*
    - *CPTYIDEN*
    - *CURR*
    - *AMNT*
    - *OTHRPTYIDEN*
    - *DISCOUNTAMT*
    - *DRACCREAL*
    - *CPTYACCNUM*
    - *NETREALIZED*

OTHRBNKCHARGS
COLBANKREFNUM
VALUEDT
DUEDATE
COUNTRPRYNAM
OTHERPARTYNAME
BNKCD
BRNCODE
DRACCBRN
ACCBRN
BNKNAME
BRNNAME
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*

BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1

BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*

ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO

- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*

TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2

COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contractdet-Full

Attribute	Description
Name	Contractdet-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERDT

Attribute	Description
Name	CHECKERDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,L</td></tr></table>

TOP

AUTSTAT

Attribute	Description

Name	AUTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

NETREALIZED

Attribute	Description
Name	NETREALIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description

Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description

Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String

Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description

Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	**Description**	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	**Description**	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	**Description**	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2

Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3

Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	**Description**	
Name	COUNTRPRYNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

AGID

Attribute	**Description**	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	**Description**	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2

Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	**Description**	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**	
Name	REGREP2	
Datatype	String	
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**
Name	REGREP3
Datatype	String

Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2

Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	**Description**	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	**Description**	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO2

Attribute	**Description**	
Name	SNDRRCVRINFO2	
Datatype	String	
Description	Indicates Sender Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	**Description**	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

2.77.2.RB-CreateOutRealization-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contractdet-IO*
    - *CONREFNUM*
    - *DRACCREAL*
    - *CPTYACCNUM*
    - *NETREALIZED*
    - *COLBANKREFNUM*
    - *VALUEDT*
    - *Con*
      - *CONTREFNO*
      - *EVENTSEQ*
      - *Adv*
        - *SUPRESS*
        - *PRIOR*
        - *MEDM*
        - *CHGREQ*
    - *Settlements*
      - *CONREFNO*
      - *LATEVNSEQNO*
      - *Contract-Settlement*

CUSTSPREAD
SPREADDEFN
TAGCCY
ACCBRN
ACC
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1

ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*

ITIMEIND1
ITIMEIND2
ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
LATEVNSEQNO
CONREFNO
Charge-Association
WAIVER

- *DISACCRAPPL*
- *ACCRREQD*
- *DESC*
- *Charge-Application*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*
- *MISGRPTXN*
- *COMPMIS1*

COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contractdet-IO

Attribute	Description
Name	Contractdet-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

NETREALIZED

Attribute	Description
Name	NETREALIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNO

Attribute	**Description**	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EVENTSEQ

Attribute	**Description**	
Name	EVENTSEQ	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Adv

Attribute	**Description**	
Name	Adv	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SUPRESS

Attribute	**Description**	
Name	SUPRESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**

Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	**Description**	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	Description	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	Description	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP

Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String

Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1

Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2

Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5

Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**
Name	Charge-Application
Datatype	
Description	Includes Charge Application details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description

Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String

Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.77.3.RB-CreateOutRealization-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contractdet-Full*
    - *CONREFNUM*
    - *MAKER*
    - *MAKERDT*
    - *CHKR*
    - *CHECKERDT*
    - *CONTSTAT*
    - *AUTSTAT*
    - *CPTYIDEN*
    - *CURR*
    - *AMNT*
    - *OTHRPTYIDEN*
    - *DISCOUNTAMT*
    - *DRACCREAL*
    - *CPTYACCNUM*
    - *NETREALIZED*
    - *OTHRBNKCHARGS*
    - *COLBANKREFNUM*
    - *VALUEDT*

DUEDATE
COUNTRPRYNAM
OTHERPARTYNAME
BNKCD
BRNCODE
DRACCBRN
ACCBRN
BNKNAME
BRNNAME
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*

TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4

ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*

ENVCONT5

Lcl_Clearing

FREETXT1

FREETXT2

FREETXT3

PMNTCD

ADDINFOSORBNET

SNDRCUSTNAME1

SNDRCUSTNAME2

SNDRCUSTNAME3

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

Charges

CONREFNO

Charge-Association

COMPNT

CREATESN

- *RULE*
- *WAIVER*
- *DISACCRAPPL*
- *ACCRREQD*
- *DESC*

Charge-Application

- *CREATESN*
- *COMPNT*
- *TGCCY*
- *TGAMT*
- *CHRGCCY*
- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*

Charge-Liquidation

- *ESN*
- *COMPNT*
- *CHRGCCY*
- *CHRGAMT*
- *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*

TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5

COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contractdet-Full

Attribute	Description
Name	Contractdet-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDT

Attribute	Description
Name	CHECKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,L

TOP

AUTSTAT

Attribute	**Description**	
Name	AUTSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

CPTYIDEN

Attribute	**Description**	
Name	CPTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CURR

Attribute	**Description**	
Name	CURR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNT

Attribute	**Description**	
Name	AMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

NETREALIZED

Attribute	Description
Name	NETREALIZED

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	**Description**
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BNKNAME

Attribute	**Description**
Name	BNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BRNNAME

Attribute	**Description**
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Con

Attribute	**Description**
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement

Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	**Description**	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	**Description**	
Name	CLEARNW	
Datatype	String	
Description	Indicates Network Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	**Description**	
Name	COVERBY	
Datatype	String	
Description	Indicates Cover By Clearing : C Message : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	**Description**
Name	RTGSPMNT
Datatype	String

Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	Description	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1

Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	**Description**	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2

Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5

Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	**Description**
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	**Description**
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	**Description**
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	**Description**
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1

Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRPART

Attribute	**Description**	
Name	SNDRRCVRPART	
Datatype	Number	
Description	Indicates Sender Receiver Participant	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	Description	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	Description	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	Description	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description

Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description

Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	Description	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association

Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	**Description**	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	**Description**
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	**Description**
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	**Description**
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	**Description**
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	**Description**	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS5

Attribute	**Description**	
Name	TRANMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	**Description**	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.77.4.RB-CreateOutRealization-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contractdet-PK*
      - *CONREFNUM*
    - *Contractdet-IO*
      - *CONREFNUM*
      - *DRACCREAL*
      - *CPTYACCNUM*
      - *NETREALIZED*
      - *COLBANKREFNUM*
      - *VALUEDT*
      - *Con*
        - *CONTREFNO*
        - *EVENTSEQ*
        - *Adv*
          - *SUPRESS*
          - *PRIOR*
          - *MEDM*
          - *CHGREQ*
      - *Settlements*

CONREFNO

LATEVNSEQNO

Contract-Settlement

- *CUSTSPREAD*
- *SPREADDEFN*
- *TAGCCY*
- *ACCBRN*
- *ACC*
- *EXRATE*
- *NETIND*
- *ERICCY*
- *ERIAMT*
- *GENMSG*
- *RATECD*
- *CLEARNW*
- *COVERBY*
- *RTGSPMNT*
- *BANKPRIOR*
- *RTGSNW*
- *PAYBY*
- *TRANSTYP*
- *INSTYP*
- *INSNO*
- *CHGDET*
- *PAYMNTDET1*
- *PAYMNTDET2*
- *PAYMNTDET3*
- *PAYMNTDET4*
- *SNDTRRCVINFO1*
- *SNDTRRCVINFO2*
- *SNDTRRCVINFO3*
- *SNDTRRCVINFO4*
- *SNDTRRCVINFO5*
- *COVREQRD*
- *RECVCVR*
- *RECEIVER*
- *REIMINST1*
- *REIMINST4*
- *RCVRCORRS1*
- *RCVRCORRS2*
- *RCVRCORRS3*
- *RCVRCORRS4*
- *INTERMEDIARY1*
- *INTERMEDIARY2*

INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
  INSTRCD1

INSTRCD2
INSTRCD3
INSTRCD4
ITIMEIND1
ITIMEIND2
ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
LATEVNSEQNO

- *CONREFNO*
- *Charge-Association*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*

MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contractdet-PK

Attribute	Description
Name	Contractdet-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contractdet-IO

Attribute	Description
Name	Contractdet-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

NETREALIZED

Attribute	Description
Name	NETREALIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number

Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String

Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	**Description**	
Name	COVERBY	
Datatype	String	
Description	Indicates Cover By Clearing : C Message : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates RTGS Payment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	**Description**	
Name	BANKPRIOR	
Datatype	String	
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**

Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1

Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	**Description**	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2

Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	Description	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	Description	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5

Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	**Description**	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**
Name	Charge-Application
Datatype	
Description	Includes Charge Application details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description

Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String

Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.78.CreateOutwardcollection

CreateOutwardcollection

2.78.1.RB-CreateOutwardcollection-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNUM*
    - *BOOKDT*
    - *USERREFNUM*
    - *BRN*
    - *PRDCD*
    - *MODULE*
    - *UDS*
    - *STOPDT*
    - *VERSIONNO*
    - *EVENTSEQ*
    - *EVENTCODE*
    - *INSTRUCODE*
    - *PRODTYP*
    - *CPTYIDEN*
    - *CPTYACCNUM*

INSTRNO
INSTRU_DATE
INITCCY
OSAMT
LCYAMT
OTHRPTYIDEN
BNKCD
BRN_D
REFERENCENO
BOOKINGDT
MATDAYS
LEADDAYS
DISPATCHDT
GRACEDAYS
PROTEST
TRACKLIMIT
CREDITLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
DISCAMT
COLLATERAL
COLLVL
COLLPOOL
ACCBRN
PAYDUEDATE
DRACCBRN
INTREMARKS
INSTRUMENT_DESCRIPTION
TXTPDTDESC
CPTYNAME
OTHERPARTYNAME
BNKNAME
BRNNAME
XREF
BATCHREFENUM
BATCHSEQNO
DRACCREAL
AUTOLIQD
CONTREFLOG
MAKER
MAKDTTIME
CHKR
CHKDTTIME

EVENTLOG
CONST
AUTHSTAT
LATVERNO
DATE
Party-Details
  PARTTYP
  PARTYIDEN
  PARTYNAME
  ADDLN1
  ADDLN2
  ADDLN3
  ADDLN4
  CNTY
  PRTYLANG
Settlements
  CONREFNO
  Contract-Settlement
    IBANACNO
    CUSTSPREAD
    SPREADDEFN
    COMPNT
    TAGCCY
    ACCBRN
    ACC
    ACCCCY
    EXRATE
    NETIND
    ERICCY
    ERIAMT
    GENMSG
    RATECD
    CLEARNW
    COVERBY
    RTGSPMNT
    BANKPRIOR
    RTGSNW
    PAYBY
    TRANSTYP
    INSTYP
    INSNO
    CHGDET
    PAYMNTDET1
    PAYMNTDET2

PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2

BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*

ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP

PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3

- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*

CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
Clpref
CONTREFNNO
CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM
PAYMENT_MODE

LOANVALDATE

MATURITY_DATE

Ude

USERDEID

UDEDESC

RATEASOF

USAGE

USERDEVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USERREFNUM

Attribute	Description
Name	USERREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDS

Attribute	Description
Name	UDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSIONNO

Attribute	Description
Name	VERSIONNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

PRODTYP

Attribute	Description
Name	PRODTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INITCCY

Attribute	Description
Name	INITCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

OSAMT

Attribute	Description
Name	OSAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BRN_D

Attribute	Description
Name	BRN_D
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKINGDT

Attribute	Description
Name	BOOKINGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LEADDAYS

Attribute	Description
Name	LEADDAYS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISPATCHDT

Attribute	Description
Name	DISPATCHDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,N,F</td></tr></table>

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COLLATERAL

Attribute	**Description**	
Name	COLLATERAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,C,T,N

TOP

COLLVL

Attribute	**Description**	
Name	COLLVL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COLLPOOL

Attribute	**Description**	
Name	COLLPOOL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description
Name	INSTRUMENT_DESCRIPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

TXTPDTDESC

Attribute	Description
Name	TXTPDTDESC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTYNAME

Attribute	**Description**	
Name	CPTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYNAME

Attribute	**Description**	
Name	OTHERPARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BNKNAME

Attribute	**Description**	
Name	BNKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CONTREFLOG

Attribute	Description
Name	CONTREFLOG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EVENTLOG

Attribute	Description
Name	EVENTLOG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,H,R,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / DRAWEE,DRAWER,PAYEE,COLLECTING_BANK,

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRTYLANG

Attribute	Description
Name	PRTYLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	**Description**
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	**Description**
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO

Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String

Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	Description	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO5

Attribute	Description	
Name	SNDTRRCVINFO5	
Datatype	String	
Description	Indicates Sender To Receiver Information 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	Description	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4

Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1

Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	Description	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5

Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	

Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String

Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description

Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CHGREQ

Attribute	**Description**	
Name	CHGREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTTYP

Attribute	**Description**	
Name	PARTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / DRAWEE,DRAWER,PAYEE,COLLECTING_BANK,

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description

Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNITS

Attribute	**Description**	
Name	UNITS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LOAN_CONREFNO

Attribute	**Description**	
Name	LOAN_CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RATECODE

Attribute	**Description**	
Name	RATECODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,S

TOP

EXCHANGERATE

Attribute	**Description**	
Name	EXCHANGERATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.78.2.RB-CreateOutwardcollection-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNUM*
    - *BOOKDT*
    - *USERREFNUM*
    - *BRN*
    - *PRDCD*
    - *MODULE*
    - *UDS*
    - *STOPDT*
    - *EVENTSEQ*
    - *EVENTCODE*
    - *INSTRUCODE*
    - *PRODTYP*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *INSTRNO*
    - *INSTRU_DATE*
    - *INITCCY*
    - *OSAMT*

OTHRPTYIDEN
BNKCD
REFERENCENO
MATDAYS
LEADDAYS
GRACEDAYS
PROTEST
TRACKLIMIT
CREDITLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
COLLATERAL
COLLPOOL
INTREMARKS
XREF
BATCHREFENUM
DRACCREAL
AUTOLIQD
CONTREFLOG
EVENTLOG
DATE
Party-Details
- *PARTYNAME*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ADDLN4*
- *CNTY*
- *PRTYLANG*

Settlements
- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*

RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3

ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*

ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1

COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Charges

LATEVNSEQNO
CONREFNO
Charge-Association
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
CHRGAMT
LIQDSTAT
Con
CONTREFNO
EVENTSEQ
Adv
SUPRESS
PRIOR
MEDM
CHGREQ
Clpref
CONTREFNNO
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BOOKDT

Attribute	Description	
Name	BOOKDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

USERREFNUM

Attribute	Description	
Name	USERREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

UDS

Attribute	Description
Name	UDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRODTYP

Attribute	Description
Name	PRODTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INITCCY

Attribute	Description
Name	INITCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

OSAMT

Attribute	Description
Name	OSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LEADDAYS

Attribute	Description
Name	LEADDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONTREFLOG

Attribute	Description
Name	CONTREFLOG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTLOG

Attribute	Description
Name	EVENTLOG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PRTYLANG

Attribute	Description
Name	PRTYLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String

Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: enumeration Description: ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: enumeration Description: M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description

Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1

Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	Description	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5

Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD

Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3

Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	**Description**	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	**Description**	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	Description	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	Description	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String

Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RATECODE

Attribute	**Description**	
Name	RATECODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,S

TOP

EXCHANGERATE

Attribute	**Description**	
Name	EXCHANGERATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATE_TYPE

Attribute	**Description**	
Name	RATE_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

Ude

Attribute	**Description**	
Name	Ude	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description

Name	USERDEVAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.78.3.RB-CreateOutwardcollection-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNUM*
    - *BOOKDT*
    - *USERREFNUM*
    - *BRN*
    - *PRDCD*
    - *MODULE*
    - *UDS*
    - *STOPDT*
    - *VERSIONNO*
    - *EVENTSEQ*
    - *EVENTCODE*
    - *INSTRUCODE*
    - *PRODTYP*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *INSTRNO*
    - *INSTRU_DATE*
    - *INITCCY*

OSAMT
LCYAMT
OTHRPTYIDEN
BNKCD
BRN_D
REFERENCENO
BOOKINGDT
MATDAYS
LEADDAYS
DISPATCHDT
GRACEDAYS
PROTEST
TRACKLIMIT
CREDITLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
DISCAMT
COLLATERAL
COLLVL
COLLPOOL
ACCBRN
PAYDUEDATE
DRACCBRN
INTREMARKS
INSTRUMENT_DESCRIPTION
TXTPDTDESC
CPTYNAME
OTHERPARTYNAME
BNKNAME
BRNNAME
XREF
BATCHREFENUM
BATCHSEQNO
DRACCREAL
AUTOLIQD
CONTREFLOG
MAKER
MAKDTTIME
CHKR
CHKDTTIME
EVENTLOG
CONST
AUTHSTAT

LATVERNO
DATE
Party-Details
- *PARTTYP*
- *PARTYIDEN*
- *PARTYNAME*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ADDLN4*
- *CNTY*
- *PRTYLANG*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*

SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5

COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*

SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD

COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6

- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*

TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
Clpref
CONTREFNNO
CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM
PAYMENT_MODE
LOANVALDATE
MATURITY_DATE
Ude

USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USERREFNUM

Attribute	Description
Name	USERREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

UDS

Attribute	Description
Name	UDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

STOPDT

Attribute	Description
Name	STOPDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSIONNO

Attribute	Description
Name	VERSIONNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRODTYP

Attribute	Description
Name	PRODTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INITCCY

Attribute	Description
Name	INITCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OSAMT

Attribute	Description
Name	OSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BRN_D

Attribute	Description
Name	BRN_D
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BOOKINGDT

Attribute	Description
Name	BOOKINGDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LEADDAYS

Attribute	Description
Name	LEADDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISPATCHDT

Attribute	Description
Name	DISPATCHDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CREDITLINE

Attribute	**Description**	
Name	CREDITLINE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

OTHPARTYLIMIT

Attribute	**Description**	
Name	OTHPARTYLIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MARGINPERC

Attribute	**Description**	
Name	MARGINPERC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,N,F

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLVL

Attribute	Description
Name	COLLVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PAYDUEDATE

Attribute	**Description**	
Name	PAYDUEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DRACCBRN

Attribute	**Description**	
Name	DRACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INTREMARKS

Attribute	**Description**	
Name	INTREMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INSTRUMENT_DESCRIPTION

Attribute	**Description**	
Name	INSTRUMENT_DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

TXTPDTDESC

Attribute	Description
Name	TXTPDTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CONTREFLOG

Attribute	Description
Name	CONTREFLOG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVENTLOG

Attribute	Description
Name	EVENTLOG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,H,R,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / DRAWEE,DRAWER,PAYEE,COLLECTING_BANK,

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRTYLANG

Attribute	Description
Name	PRTYLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	Description	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	Description	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	**Description**
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	**Description**
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	**Description**
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	**Description**
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	**Description**
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	**Description**
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	**Description**
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	**Description**
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number

Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY

Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description	
Name	PARTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	DRAWEE,DRAWER,PAYEE,COLLECTING_BANK,

TOP

Clpref

Attribute	Description	
Name	Clpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNNO

Attribute	Description	
Name	CONTREFNNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CONTRACT_CCY

Attribute	Description	
Name	CONTRACT_CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LATEVNSEQNO

Attribute	Description

Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.78.4.RB-CreateOutwardcollection-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNUM*
    - *Contract-Details-IO*
      - *CONREFNUM*
      - *BOOKDT*
      - *USERREFNUM*
      - *BRN*
      - *PRDCD*
      - *MODULE*
      - *UDS*
      - *STOPDT*
      - *EVENTSEQ*
      - *EVENTCODE*
      - *INSTRUCODE*
      - *PRODTYP*
      - *CPTYIDEN*
      - *CPTYACCNUM*
      - *INSTRNO*

INSTRU_DATE
INITCCY
OSAMT
OTHRPTYIDEN
BNKCD
REFERENCENO
MATDAYS
LEADDAYS
GRACEDAYS
PROTEST
TRACKLIMIT
CREDITLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
COLLATERAL
COLLPOOL
INTREMARKS
XREF
BATCHREFENUM
DRACCREAL
AUTOLIQD
CONTREFLOG
EVENTLOG
DATE
Party-Details
  PARTYNAME
  ADDLN1
  ADDLN2
  ADDLN3
  ADDLN4
  CNTY
  PRTYLANG
Settlements
  CONREFNO
  LATEVNSEQNO
  Contract-Settlement
    CUSTSPREAD
    SPREADDEFN
    TAGCCY
    ACCBRN
    ACC
    EXRATE
    NETIND

ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4

ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*

REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH

REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS

FLDNAME
FLDVAL
Charges
LATEVNSEQNO
CONREFNO
Charge-Association
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
CHRGAMT
LIQDSTAT
Con
CONTREFNO
EVENTSEQ
Adv
SUPRESS
PRIOR
MEDM
CHGREQ
Clpref
CONTREFNNO
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

USERREFNUM

Attribute	Description
Name	USERREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

UDS

Attribute	Description
Name	UDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

PRODTYP

Attribute	Description	
Name	PRODTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

CPTYIDEN

Attribute	Description	
Name	CPTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTYACCNUM

Attribute	Description	
Name	CPTYACCNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRNO

Attribute	Description	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INITCCY

Attribute	Description
Name	INITCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OSAMT

Attribute	Description
Name	OSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LEADDAYS

Attribute	Description
Name	LEADDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,N,F

TOP

COLLATERAL

Attribute	**Description**	
Name	COLLATERAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,C,T,N

TOP

COLLPOOL

Attribute	**Description**	
Name	COLLPOOL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INTREMARKS

Attribute	**Description**	
Name	INTREMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONTREFLOG

Attribute	Description
Name	CONTREFLOG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTLOG

Attribute	Description
Name	EVENTLOG
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PRTYLANG

Attribute	Description
Name	PRTYLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO

Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY

Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	**Description**	
Name	COVERBY	
Datatype	String	
Description	Indicates Cover By Clearing : C Message : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates RTGS Payment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	**Description**	
Name	BANKPRIOR	
Datatype	String	
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**

Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1

Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	**Description**	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2

Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5

Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	**Description**	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	**Description**	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**

Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String

Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHGREQ

Attribute	Description

Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description

Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.79.CreateOverseasfinance

CreateOverseasfinance

2.79.1.RB-CreateOverseasfinance-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *INSTRNO*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *BOOKINGDATE*
    - *OTHR_PARTY_NAME*
    - *DRAWEE_BNK_NAME*
    - *FINANCING*
    - *MARGINPERCENT*
    - *TRACK_LIMIT*
    - *CREDIT_LINE*
    - *DISCOUNT_AMOUNT*

MAKER
MAKERDTSTAMP
CHECKER
CHECKERSTAMP
RECORD_STAT
AUTHSTAT
PAYDUEDATE
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*

INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2

ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Charges

CONREFNO

Charge-Association

COMPNT
CREATESN
RULE
WAIVER

- *DISACCRAPPL*
- *ACCRREQD*
- *DESC*

Charge-Application

- *CREATESN*
- *COMPNT*
- *TGCCY*
- *TGAMT*
- *CHRGCCY*
- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*

Charge-Liquidation

- *ESN*
- *COMPNT*
- *CHRGCCY*
- *CHRGAMT*
- *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*

TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7

- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Clpref

- *CONTREFNNO*
- *CONTRACT_CCY*
- *LATEVNSEQNO*
- *PRD*
- *PRDDESC*
- *COUNTERPARTY*
- *CURRENCY*
- *TENOR*
- *UNITS*
- *LOAN_CONREFNO*
- *RATECODE*
- *EXCHANGERATE*
- *RATE_TYPE*
- *MAXIMUM*
- *MINIMUM*
- *PAYMENT_MODE*
- *LOANVALDATE*
- *MATURITY_DATE*
- *Ude*
  - *USERDEID*
  - *UDEDESC*
  - *RATEASOF*
  - *USAGE*
  - *USERDEVAL*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,A,H,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr></table>

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Settlement

Attribute	**Description**	
Name	Contract-Settlement	
Datatype		
Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	**Description**	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description

Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	**Description**	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	**Description**	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	**Description**	
Name	CLEARNW	
Datatype	String	
Description	Indicates Network Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	**Description**
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates RTGS Payment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	**Description**	
Name	BANKPRIOR	
Datatype	String	
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1

Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC

Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	**Description**	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1

Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String

Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description

Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PMNTTYP

Attribute	Description	
Name	PMNTTYP	
Datatype	String	
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	Description	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	Description	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description

Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY

Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.79.2.RB-CreateOverseasfinance-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONREFNUM*
    - *FINANCING*
    - *MARGINPERCENT*
    - *TRACK_LIMIT*
    - *CREDIT_LINE*
    - *Con*
      - *CONTREFNO*
      - *EVENTSEQ*
      - *Adv*
        - *SUPRESS*
        - *PRIOR*
        - *MEDM*
        - *CHGREQ*
    - *Settlements*
      - *CONREFNO*
      - *LATEVNSEQNO*
      - *Contract-Settlement*
        - *CUSTSPREAD*

SPREADDEFN
TAGCCY
ACCBRN
ACC
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2

ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*

ITIMEIND2
ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
LATEVNSEQNO
CONREFNO
Charge-Association
WAIVER
DISACCRAPPL

ACCRREQD
DESC
Charge-Application
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10

COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
Clpref
CONTREFNNO
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,N,F

TOP

MARGINPERCENT

Attribute	**Description**	
Name	MARGINPERCENT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRACK_LIMIT

Attribute	**Description**	
Name	TRACK_LIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CREDIT_LINE

Attribute	**Description**	
Name	CREDIT_LINE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

CHGREQ

Attribute	**Description**	
Name	CHGREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Settlements

Attribute	**Description**	
Name	Settlements	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String

Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description

Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	**Description**	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	**Description**	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	**Description**	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4

Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5

Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	**Description**	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	**Description**	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1

Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String

Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3

Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ULTBANDCD

Attribute	Description	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SUPPID

Attribute	Description	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	Description	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number

Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	**Description**	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

2.79.3.RB-CreateOverseasfinance-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *INSTRNO*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *BOOKINGDATE*
    - *OTHR_PARTY_NAME*
    - *DRAWEE_BNK_NAME*
    - *FINANCING*
    - *MARGINPERCENT*
    - *TRACK_LIMIT*
    - *CREDIT_LINE*
    - *DISCOUNT_AMOUNT*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHECKER*

CHECKERSTAMP
RECORD_STAT
AUTHSTAT
PAYDUEDATE
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*

PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1

BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*

PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC

- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*

TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10

FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
Clpref
CONTREFNNO
CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM
PAYMENT_MODE
LOANVALDATE
MATURITY_DATE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description

Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,A,H,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SUPRESS

Attribute	**Description**	
Name	SUPRESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs Description: 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: enumeration Description: Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number

Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String

Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description

Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	**Description**	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	**Description**	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1

Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

BENINST5

Attribute	Description
Name	BENINST5

Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description

Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description

Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.79.4.RB-CreateOverseasfinance-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONREFNUM*
    - *Main-IO*
      - *CONREFNUM*
      - *FINANCING*
      - *MARGINPERCENT*
      - *TRACK_LIMIT*
      - *CREDIT_LINE*
      - *Con*
        - *CONTREFNO*
        - *EVENTSEQ*
        - *Adv*
          - *SUPRESS*
          - *PRIOR*
          - *MEDM*
          - *CHGREQ*
      - *Settlements*
        - *CONREFNO*

LATEVNSEQNO

Contract-Settlement

- *CUSTSPREAD*
- *SPREADDEFN*
- *TAGCCY*
- *ACCBRN*
- *ACC*
- *EXRATE*
- *NETIND*
- *ERICCY*
- *ERIAMT*
- *GENMSG*
- *RATECD*
- *CLEARNW*
- *COVERBY*
- *RTGSPMNT*
- *BANKPRIOR*
- *RTGSNW*
- *PAYBY*
- *TRANSTYP*
- *INSTYP*
- *INSNO*
- *CHGDET*
- *PAYMNTDET1*
- *PAYMNTDET2*
- *PAYMNTDET3*
- *PAYMNTDET4*
- *SNDTRRCVINFO1*
- *SNDTRRCVINFO2*
- *SNDTRRCVINFO3*
- *SNDTRRCVINFO4*
- *SNDTRRCVINFO5*
- *COVREQRD*
- *RECVCVR*
- *RECEIVER*
- *REIMINST1*
- *REIMINST4*
- *RCVRCORRS1*
- *RCVRCORRS2*
- *RCVRCORRS3*
- *RCVRCORRS4*
- *INTERMEDIARY1*
- *INTERMEDIARY2*
- *INTERMEDIARY3*

INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*

INSTRCD3
INSTRCD4
ITIMEIND1
ITIMEIND2
ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
LATEVNSEQNO
CONREFNO

- *Charge-Association*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*

MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
Clpref
CONTREFNNO
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0

Restrictions	**Restrictions** / **Description** enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number

Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String

Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	**Description**	
Name	COVERBY	
Datatype	String	
Description	Indicates Cover By Clearing : C Message : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates RTGS Payment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	**Description**	
Name	BANKPRIOR	
Datatype	String	
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**

Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1

Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	**Description**	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2

Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5

Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	**Description**	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**
Name	Charge-Application
Datatype	
Description	Includes Charge Application details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description

Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LOAN_CONREFNO

Attribute	**Description**	
Name	LOAN_CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RATECODE

Attribute	**Description**	
Name	RATECODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,S

TOP

EXCHANGERATE

Attribute	**Description**	
Name	EXCHANGERATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATE_TYPE

Attribute	**Description**	
Name	RATE_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

USAGE

Attribute	Description

Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.80.CreateOverseaspdr

CreateOverseaspdr

2.80.1.RB-CreateOverseaspdr-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *INSTRUMENTNORE*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *OTHER_BANK_CHARGES*
    - *BNK_CODE*

REMRKS
BANK_NAME
DISHONORDATE
NOTARY_DESCRIPTION
BOOKING_DATE
DISCOUNT_AMOUNT
REASON_CODE
REASON
PROTESTDATE
RETURN_DATE
OTHR_PARTY_NAME
DRAWEE_BNK_NAME
Charges
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*

COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3

INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
  INSTRCD1

INSTRCD2
INSTRCD3
INSTRCD4
ITIMEIND1
ITIMEIND2
ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID

SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1

COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4

FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	Description	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CTR_PRTY_NAME

Attribute	Description
Name	CTR_PRTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRUMENTNORE

Attribute	Description
Name	INSTRUMENTNORE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,A,H,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BNK_CODE

Attribute	Description
Name	BNK_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REMRKS

Attribute	Description
Name	REMRKS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BANK_NAME

Attribute	Description
Name	BANK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DISHONORDATE

Attribute	Description
Name	DISHONORDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTARY_DESCRIPTION

Attribute	Description
Name	NOTARY_DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BOOKING_DATE

Attribute	Description
Name	BOOKING_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REASON

Attribute	Description
Name	REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHR_PARTY_NAME

Attribute	**Description**	
Name	OTHR_PARTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRAWEE_BNK_NAME

Attribute	**Description**	
Name	DRAWEE_BNK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**
Name	Charge-Application
Datatype	
Description	Includes Charge Application details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	**Description**	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**

Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String

Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	**Description**	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	**Description**	
Name	BANKPRIOR	
Datatype	String	
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	**Description**	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	**Description**	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	**Description**	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	**Description**
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	**Description**
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	**Description**
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	**Description**
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	Description	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	Description	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	Description	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

2.80.2.RB-CreateOverseaspdr-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONREFNUM*
    - *OTHER_BANK_CHARGES*
    - *REMRKS*
    - *DISHONORDATE*
    - *NOTARY_DESCRIPTION*
    - *REASON_CODE*
    - *PROTESTDATE*
    - *RETURN_DATE*
    - *Charges*
      - *LATEVNSEQNO*
      - *CONREFNO*
      - *Charge-Association*
        - *WAIVER*
        - *DISACCRAPPL*
        - *ACCRREQD*
        - *DESC*
      - *Charge-Application*
        - *CHRGAMT*

- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Settlements*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Contract-Settlement*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *EXRATE*
    - *NETIND*
    - *ERICCY*
    - *ERIAMT*
    - *GENMSG*
    - *RATECD*
    - *CLEARNW*
    - *COVERBY*
    - *RTGSPMNT*
    - *BANKPRIOR*
    - *RTGSNW*
    - *PAYBY*
    - *TRANSTYP*
    - *INSTYP*
    - *INSNO*
    - *CHGDET*
    - *PAYMNTDET1*
    - *PAYMNTDET2*
    - *PAYMNTDET3*
    - *PAYMNTDET4*
    - *SNDTRRCVINFO1*
    - *SNDTRRCVINFO2*
    - *SNDTRRCVINFO3*
    - *SNDTRRCVINFO4*
    - *SNDTRRCVINFO5*
    - *COVREQRD*
    - *RECVCVR*
    - *RECEIVER*

REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5

INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *ULTBANDCD*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*
- *NOOFDEC*
- *ADDID*
- *SNDRRCVRINFO1*
- *SNDRRCVRINFO2*
- *SNDRRCVRINFO3*
- *SNDRRCVRINFO4*
- *SNDRRCVRINFO5*
- *SNDRRCVRINFO6*

DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6

COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
SUPRESS
PRIOR
MEDM
CHGREQ

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DISHONORDATE

Attribute	Description
Name	DISHONORDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTARY_DESCRIPTION

Attribute	Description
Name	NOTARY_DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Settlements

Attribute	Description	
Name	Settlements	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT

Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String

Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	Description	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	Description	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID

Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1

Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	Description	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	Description	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	Description	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

2.80.3.RB-CreateOverseaspdr-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *INSTRUMENTNORE*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *OTHER_BANK_CHARGES*
    - *BNK_CODE*
    - *REMRKS*
    - *BANK_NAME*
    - *DISHONORDATE*

NOTARY_DESCRIPTION
BOOKING_DATE
DISCOUNT_AMOUNT
REASON_CODE
REASON
PROTESTDATE
RETURN_DATE
OTHR_PARTY_NAME
DRAWEE_BNK_NAME
Charges
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*

ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2

ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*

ITIMEIND1
ITIMEIND2
ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3

SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3

COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7

FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CTR_PRTY_NAME

Attribute	Description
Name	CTR_PRTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRUMENTNORE

Attribute	Description
Name	INSTRUMENTNORE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>L,A,H,</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,U,</td></tr></table>

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BNK_CODE

Attribute	Description
Name	BNK_CODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REMRKS

Attribute	**Description**	
Name	REMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BANK_NAME

Attribute	**Description**	
Name	BANK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DISHONORDATE

Attribute	**Description**	
Name	DISHONORDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NOTARY_DESCRIPTION

Attribute	**Description**	
Name	NOTARY_DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BOOKING_DATE

Attribute	Description
Name	BOOKING_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REASON

Attribute	Description
Name	REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RETURN_DATE

Attribute	**Description**	
Name	RETURN_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHR_PARTY_NAME

Attribute	**Description**	
Name	OTHR_PARTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRAWEE_BNK_NAME

Attribute	**Description**	
Name	DRAWEE_BNK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description

Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	**Description**	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDINST1

Attribute	Description
Name	ORDINST1

Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC

Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	**Description**	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1

Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String

Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description

Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	**Description**
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	**Description**
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	**Description**
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	**Description**
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	**Description**	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS2

Attribute	**Description**	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

TOP

PARTYIDEN

Attribute	Description	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	Description	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CHGREQ

Attribute	Description	
Name	CHGREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTTYP

Attribute	Description	
Name	PARTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.80.4.RB-CreateOverseaspdr-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONREFNUM*
    - *Main-IO*
      - *CONREFNUM*
      - *OTHER_BANK_CHARGES*
      - *REMRKS*
      - *DISHONORDATE*
      - *NOTARY_DESCRIPTION*
      - *REASON_CODE*
      - *PROTESTDATE*
      - *RETURN_DATE*
      - *Charges*
        - *LATEVNSEQNO*
        - *CONREFNO*
        - *Charge-Association*
          - *WAIVER*
          - *DISACCRAPPL*
          - *ACCRREQD*

DESC

Charge-Application

CHRGAMT

DISACCRAPPL

WAIVER

LIQDIND

Charge-Liquidation

ESN

CHRGAMT

LIQDSTAT

Settlements

CONREFNO

LATEVNSEQNO

Contract-Settlement

CUSTSPREAD

SPREADDEFN

TAGCCY

ACCBRN

ACC

EXRATE

NETIND

ERICCY

ERIAMT

GENMSG

RATECD

CLEARNW

COVERBY

RTGSPMNT

BANKPRIOR

RTGSNW

PAYBY

TRANSTYP

INSTYP

INSNO

CHGDET

PAYMNTDET1

PAYMNTDET2

PAYMNTDET3

PAYMNTDET4

SNDTRRCVINFO1

SNDTRRCVINFO2

SNDTRRCVINFO3

SNDTRRCVINFO4

SNDTRRCVINFO5

COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW

SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *ULTBANDCD*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*
- *NOOFDEC*
- *ADDID*
- *SNDRRCVRINFO1*
- *SNDRRCVRINFO2*
- *SNDRRCVRINFO3*

SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3

COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
SUPRESS
PRIOR
MEDM
CHGREQ
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

OTHER_BANK_CHARGES

Attribute	Description	
Name	OTHER_BANK_CHARGES	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REMRKS

Attribute	Description	
Name	REMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DISHONORDATE

Attribute	Description
Name	DISHONORDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTARY_DESCRIPTION

Attribute	Description
Name	NOTARY_DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description

Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String

Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	**Description**	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	**Description**	
Name	CLEARNW	
Datatype	String	
Description	Indicates Network Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	**Description**	
Name	COVERBY	
Datatype	String	
Description	Indicates Cover By Clearing : C Message : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	**Description**
Name	RTGSPMNT
Datatype	String

Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	Description	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP

Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2

Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description
Name	LATESN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description

Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.81.CreateOvsbulkcontract

CreateOvsbulkcontract

2.81.1.RB-CreateOvsbulkcontract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Overseas-Full*
    - *INSTRUMENT_CODE*
    - *INSTR_DESC*
    - *PRODCD*
    - *PRDDESC*
    - *CURRENCY*
    - *COLLECTINGBANKCIF*
    - *CBN_S*
    - *DB_ACC_REAL*
    - *ACCBRN*
    - *BOKNGDT*
    - *PAYDUEDATE*
    - *TRANSITDAYS*
    - *BATCHREFENUM*
    - *COLLBANKCODE*
    - *NOOFINSTRUMENTS*

STAT
ESN_NO
RECORD_STAT
AUTHSTAT
CHKR
CHKDTTIME
MAKER
MAKDTTIME
EVENTSEQNO
Bulk-Input-Overseas-Dtl
- *CONTRACTREFNO*
- *CPTY_ID*
- *CPTY_AC_NO*
- *ACCBRNRE*
- *INSTRNO*
- *INSTRU_DATE*
- *AMNT*
- *LCY_AMT*
- *OTHR_PARTYNAME*
- *DRAWEE_BNK_NAME*
- *AUTOLIQD*
- *FINANCING*
- *MARGIN_PERCENTAGE*
- *TRACK_LIMIT*
- *CREDIT_LINE*
- *DISCAMT*
- *CPTY_NAME*
- *INTREMRKS*
- *BATCHREFNO*
- *BATCHSEQNO*
- *CONTRACTCCY*
- *PROCESS_STATUS*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Overseas-Full

Attribute	Description
Name	Bulk-Input-Overseas-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRODCD

Attribute	Description
Name	PRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLECTINGBANKCIF

Attribute	Description
Name	COLLECTINGBANKCIF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CBN_S

Attribute	**Description**
Name	CBN_S
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DB_ACC_REAL

Attribute	**Description**
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCBRN

Attribute	**Description**
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BOKNGDT

Attribute	**Description**
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 1

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

COLLBANKCODE

Attribute	Description
Name	COLLBANKCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STAT

Attribute	**Description**	
Name	STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,U,

TOP

ESN_NO

Attribute	**Description**	
Name	ESN_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,C,

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U,

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bulk-Input-Overseas-Dtl

Attribute	Description
Name	Bulk-Input-Overseas-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCBRNRE

Attribute	Description
Name	ACCBRNRE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHR_PARTYNAME

Attribute	**Description**	
Name	OTHR_PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRAWEE_BNK_NAME

Attribute	**Description**	
Name	DRAWEE_BNK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AUTOLIQD

Attribute	**Description**	
Name	AUTOLIQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,N,F,

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INTREMRKS

Attribute	**Description**	
Name	INTREMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BATCHREFNO

Attribute	**Description**	
Name	BATCHREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BATCHSEQNO

Attribute	**Description**	
Name	BATCHSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTRACTCCY

Attribute	**Description**	
Name	CONTRACTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,H,F,</td></tr></table>

TOP

2.81.2.RB-CreateOvsbulkcontract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Overseas-IO*
    - *INSTRUMENT_CODE*
    - *PRODCD*
    - *CURRENCY*
    - *COLLECTINGBANKCIF*
    - *DB_ACC_REAL*
    - *BATCHREFENUM*
    - *COLLBANKCODE*
    - *NOOFINSTRUMENTS*
    - *Bulk-Input-Overseas-Dtl*
      - *CPTY_ID*
      - *CPTY_AC_NO*
      - *INSTRNO*
      - *INSTRU_DATE*
      - *AMNT*
      - *OTHR_PARTYNAME*
      - *DRAWEE_BNK_NAME*
      - *AUTOLIQD*
      - *FINANCING*

MARGIN_PERCENTAGE
TRACK_LIMIT
CREDIT_LINE
INTREMRKS
BATCHREFNO
BATCHSEQNO
CONTRACTCCY

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Overseas-IO

Attribute	Description
Name	Bulk-Input-Overseas-IO
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

PRODCD

Attribute	Description
Name	PRODCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

COLLECTINGBANKCIF

Attribute	Description
Name	COLLECTINGBANKCIF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COLLBANKCODE

Attribute	Description
Name	COLLBANKCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bulk-Input-Overseas-Dtl

Attribute	Description
Name	Bulk-Input-Overseas-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description

Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F,

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BATCHREFNO

Attribute	Description
Name	BATCHREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

2.81.3.RB-CreateOvsbulkcontract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Overseas-Full*
    - *INSTRUMENT_CODE*
    - *INSTR_DESC*
    - *PRODCD*
    - *PRDDESC*
    - *CURRENCY*
    - *COLLECTINGBANKCIF*
    - *CBN_S*
    - *DB_ACC_REAL*
    - *ACCBRN*
    - *BOKNGDT*
    - *PAYDUEDATE*
    - *TRANSITDAYS*
    - *BATCHREFENUM*
    - *COLLBANKCODE*
    - *NOOFINSTRUMENTS*
    - *STAT*
    - *ESN_NO*
    - *RECORD_STAT*

AUTHSTAT
CHKR
CHKDTTIME
MAKER
MAKDTTIME
EVENTSEQNO
Bulk-Input-Overseas-Dtl
CONTRACTREFNO
CPTY_ID
CPTY_AC_NO
ACCBRNRE
INSTRNO
INSTRU_DATE
AMNT
LCY_AMT
OTHR_PARTYNAME
DRAWEE_BNK_NAME
AUTOLIQD
FINANCING
MARGIN_PERCENTAGE
TRACK_LIMIT
CREDIT_LINE
DISCAMT
CPTY_NAME
INTREMRKS
BATCHREFNO
BATCHSEQNO
CONTRACTCCY
PROCESS_STATUS
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Overseas-Full

Attribute	Description
Name	Bulk-Input-Overseas-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTR_DESC

Attribute	**Description**	
Name	INSTR_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

PRODCD

Attribute	**Description**	
Name	PRODCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CURRENCY

Attribute	**Description**	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLECTINGBANKCIF

Attribute	Description
Name	COLLECTINGBANKCIF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CBN_S

Attribute	Description
Name	CBN_S
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COLLBANKCODE

Attribute	Description
Name	COLLBANKCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,U,

TOP

ESN_NO

Attribute	Description
Name	ESN_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,C,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

EVENTSEQNO

Attribute	**Description**	
Name	EVENTSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Bulk-Input-Overseas-Dtl

Attribute	**Description**	
Name	Bulk-Input-Overseas-Dtl	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

CONTRACTREFNO

Attribute	**Description**	
Name	CONTRACTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	**Description**	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRNRE

Attribute	Description
Name	ACCBRNRE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F,

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BATCHREFNO

Attribute	Description
Name	BATCHREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,H,F,

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.81.4.RB-CreateOvsbulkcontract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Input-Overseas-PK*
      - *BATCHREFENUM*
    - *Bulk-Input-Overseas-IO*
      - *INSTRUMENT_CODE*
      - *PRODCD*
      - *CURRENCY*
      - *COLLECTINGBANKCIF*
      - *DB_ACC_REAL*
      - *BATCHREFENUM*
      - *COLLBANKCODE*
      - *NOOFINSTRUMENTS*
      - *Bulk-Input-Overseas-Dtl*
        - *CPTY_ID*
        - *CPTY_AC_NO*
        - *INSTRNO*
        - *INSTRU_DATE*
        - *AMNT*
        - *OTHR_PARTYNAME*

DRAWEE_BNK_NAME
AUTOLIQD
FINANCING
MARGIN_PERCENTAGE
TRACK_LIMIT
CREDIT_LINE
INTREMRKS
BATCHREFNO
BATCHSEQNO
CONTRACTCCY
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Input-Overseas-PK

Attribute	Description
Name	Bulk-Input-Overseas-PK
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Input-Overseas-IO

Attribute	Description
Name	Bulk-Input-Overseas-IO
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

PRODCD

Attribute	**Description**	
Name	PRODCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CURRENCY

Attribute	**Description**	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

COLLECTINGBANKCIF

Attribute	**Description**	
Name	COLLECTINGBANKCIF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DB_ACC_REAL

Attribute	**Description**	
Name	DB_ACC_REAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

COLLBANKCODE

Attribute	Description
Name	COLLBANKCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bulk-Input-Overseas-Dtl

Attribute	Description
Name	Bulk-Input-Overseas-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

CPTY_ID

Attribute	Description

Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

OTHR_PARTYNAME

Attribute	Description	
Name	OTHR_PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRAWEE_BNK_NAME

Attribute	Description	
Name	DRAWEE_BNK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AUTOLIQD

Attribute	Description	
Name	AUTOLIQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FINANCING

Attribute	Description	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,N,F,

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BATCHREFNO

Attribute	Description
Name	BATCHREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BATCHSEQNO

Attribute	**Description**	
Name	BATCHSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTRACTCCY

Attribute	**Description**	
Name	CONTRACTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	**Description**

Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.82.CreateOvsbulkrealize

CreateOvsbulkrealize

2.82.1.RB-CreateOvsbulkrealize-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Liqd-Overseas-Full*
    - *BATCHREFENUM*
    - *BULK_REAL_NUM*
    - *CURRENCY*
    - *DB_ACC_REAL*
    - *ACCBRN*
    - *COLBANK_REFNO*
    - *COLL_BNK_CIF*
    - *COLLBNKNAME*
    - *VALUEDATE*
    - *PROCSTAT*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *CHKR*
    - *CHKDTTIME*
    - *ESN_NO*

MAKER
MAKDTTIME
EVENTSEQNO
Bulk-Liqd-Overseas-Dtl
CONTRACTREFNO
CPTY_ID
CPTY_NAME
CPTY_AC_NO
ACCBRNRE
INSTRNO
INSTRU_DATE
AMNT
NET_AMT_REALISED
OTHER_BANK_CHARGES
INTREMRKS
PROCESSSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Liqd-Overseas-Full

Attribute	Description
Name	Bulk-Liqd-Overseas-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BULK_REAL_NUM

Attribute	Description
Name	BULK_REAL_NUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLBANK_REFNO

Attribute	Description
Name	COLBANK_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

PROCSTAT

Attribute	Description
Name	PROCSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,U,</td></tr></table>

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>O,C,</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U,

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ESN_NO

Attribute	**Description**	
Name	ESN_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

Bulk-Liqd-Overseas-Dtl

Attribute	Description
Name	Bulk-Liqd-Overseas-Dtl
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRNRE

Attribute	Description
Name	ACCBRNRE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,H,F,</td></tr></table>

TOP

2.82.2.RB-CreateOvsbulkrealize-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Liqd-Overseas-IO*
    - *BATCHREFENUM*
    - *BULK_REAL_NUM*
    - *DB_ACC_REAL*
    - *COLBANK_REFNO*
    - *VALUEDATE*
    - *Bulk-Liqd-Overseas-Dtl*
      - *CPTY_AC_NO*
      - *NET_AMT_REALISED*
      - *INTREMRKS*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 8 pattern: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 128 pattern: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Liqd-Overseas-IO

Attribute	Description
Name	Bulk-Liqd-Overseas-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BULK_REAL_NUM

Attribute	Description
Name	BULK_REAL_NUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COLBANK_REFNO

Attribute	Description
Name	COLBANK_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

Bulk-Liqd-Overseas-Dtl

Attribute	Description
Name	Bulk-Liqd-Overseas-Dtl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

2.82.3.RB-CreateOvsbulkrealize-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Liqd-Overseas-Full*
    - *BATCHREFENUM*
    - *BULK_REAL_NUM*
    - *CURRENCY*
    - *DB_ACC_REAL*
    - *ACCBRN*
    - *COLBANK_REFNO*
    - *COLL_BNK_CIF*
    - *COLLBNKNAME*
    - *VALUEDATE*
    - *PROCSTAT*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *CHKR*
    - *CHKDTTIME*
    - *ESN_NO*
    - *MAKER*
    - *MAKDTTIME*
    - *EVENTSEQNO*

Bulk-Liqd-Overseas-Dtl

CONTRACTREFNO

CPTY_ID

CPTY_NAME

CPTY_AC_NO

ACCBRNRE

INSTRNO

INSTRU_DATE

AMNT

NET_AMT_REALISED

OTHER_BANK_CHARGES

INTREMRKS

PROCESSSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Liqd-Overseas-Full

Attribute	Description
Name	Bulk-Liqd-Overseas-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BULK_REAL_NUM

Attribute	Description
Name	BULK_REAL_NUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CURRENCY

Attribute	Description

Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLBANK_REFNO

Attribute	Description
Name	COLBANK_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

COLLBNKNAME

Attribute	**Description**	
Name	COLLBNKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

VALUEDATE

Attribute	**Description**	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

PROCSTAT

Attribute	**Description**	
Name	PROCSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,U,

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,C,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ESN_NO

Attribute	Description
Name	ESN_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bulk-Liqd-Overseas-Dtl

Attribute	Description
Name	Bulk-Liqd-Overseas-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY_ID

Attribute	Description	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_NAME

Attribute	Description	
Name	CPTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTY_AC_NO

Attribute	Description	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCBRNRE

Attribute	Description	
Name	ACCBRNRE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,H,F,

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.82.4.RB-CreateOvsbulkrealize-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Liqd-Overseas-PK*
      - *BULK_REAL_NUM*
    - *Bulk-Liqd-Overseas-IO*
      - *BATCHREFENUM*
      - *BULK_REAL_NUM*
      - *DB_ACC_REAL*
      - *COLBANK_REFNO*
      - *VALUEDATE*
      - *Bulk-Liqd-Overseas-Dtl*
        - *CPTY_AC_NO*
        - *NET_AMT_REALISED*
        - *INTREMRKS*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Bulk-Liqd-Overseas-PK

Attribute	Description
Name	Bulk-Liqd-Overseas-PK
Datatype	
Description	

TOP

BULK_REAL_NUM

Attribute	Description
Name	BULK_REAL_NUM
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

Bulk-Liqd-Overseas-IO

Attribute	Description
Name	Bulk-Liqd-Overseas-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

BULK_REAL_NUM

Attribute	Description
Name	BULK_REAL_NUM
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COLBANK_REFNO

Attribute	Description
Name	COLBANK_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

Bulk-Liqd-Overseas-Dtl

Attribute	Description
Name	Bulk-Liqd-Overseas-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CPTY_AC_NO

Attribute	Description

Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.83.CreateOvscheckspay

CreateOvscheckspay

2.83.1.RB-CreateOvscheckspay-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONTREFNO*
    - *LATESTVERSIONNO*
    - *RECORD_STAT*
    - *AUTHSTATUS*
    - *CURR_EVENT_CODE*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHKR*
    - *CHKDTTIME*
    - *EVENT_SEQ_NO*
    - *CONT_STAT*
    - *AUTH_STAT*
    - *CPTY_ID*
    - *CPTY_AC_NO*
    - *INSTRNO*

INSTRUMENT_DATE
CURRENCY
AMNT
NET_AMT_REALISED
OTHER_BANK_CHARGES
COLL_BNK_CIF
BOOKINGDATE
MATURITY_DATE
VALUE_DATE
TRACK_LIMIT
CREDIT_LINE
FINANCING
INT_REM
INSTRUMENT_CODE
INSTR_DESC
PRCD
PRODDESC
USERREF_NO
XREF
COUNTRPRYNAM
LCY_AMT
COLLBANKNAME
PAYDUEDATE
CONREF
EVENTSEQ
PARTYTYP
ADDRESS
PARTYADDR2
PARTYADDR3
PARTYADDR4
WALKINCUSTFLG
COLLEC_BANK_CIF
COLLBNKNAME
DISCOUNT_AMOUNT
DB_ACC_REAL
BULK_INPUT_REF_NO
DRAWEE_BNK_NAME
AUTOLIQD
OTHER_PARTY_ID
VERSION_NO
TRANSITDAYS
MARGIN_PERCENTAGE
ACC_BRANCH
OTHR_PARTY_NAME

ACCBRN

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*

COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6

- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*

CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2

ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*

REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4

RCVRACC

Clpref

CONTREFNNO

CONTRACT_CCY

LATEVNSEQNO

PRD

PRDDESC

COUNTERPARTY

CURRENCY

TENOR

UNITS

LOAN_CONREFNO

RATECODE

EXCHANGERATE

RATE_TYPE

MAXIMUM

MINIMUM

PAYMENT_MODE

LOANVALDATE

MATURITY_DATE

Ude

USERDEID

UDEDESC

RATEASOF

USAGE

USERDEVAL

Con

CONTREFNO

EVENTSEQ

Adv

ADVNAME

SUPRESS

PRIOR

MEDM

PARTYIDEN

PARTYNAME

CHGREQ

PARTTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESTVERSIONNO

Attribute	**Description**	
Name	LATESTVERSIONNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTATUS

Attribute	**Description**	
Name	AUTHSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CURR_EVENT_CODE

Attribute	**Description**	
Name	CURR_EVENT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONT_STAT

Attribute	Description
Name	CONT_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,L,R,H,</td></tr></table>

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,U,</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRNO

Attribute	**Description**	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRUMENT_DATE

Attribute	**Description**	
Name	INSTRUMENT_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

CURRENCY

Attribute	**Description**	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNT

Attribute	**Description**	
Name	AMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,N,F</td></tr></table>

TOP

INT_REM

Attribute	Description
Name	INT_REM
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLBANKNAME

Attribute	Description
Name	COLLBANKNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREF

Attribute	Description
Name	CONREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

ADDRESS

Attribute	**Description**	
Name	ADDRESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PARTYADDR2

Attribute	**Description**	
Name	PARTYADDR2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PARTYADDR3

Attribute	**Description**	
Name	PARTYADDR3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PARTYADDR4

Attribute	**Description**	
Name	PARTYADDR4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

WALKINCUSTFLG

Attribute	Description
Name	WALKINCUSTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COLLEC_BANK_CIF

Attribute	Description
Name	COLLEC_BANK_CIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BULK_INPUT_REF_NO

Attribute	Description
Name	BULK_INPUT_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OTHER_PARTY_ID

Attribute	Description
Name	OTHER_PARTY_ID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACC_BRANCH

Attribute	Description
Name	ACC_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD

Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	**Description**
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	**Description**
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	**Description**
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	**Description**
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	**Description**
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	**Description**
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	**Description**
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	**Description**
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COUNTERPARTY

Attribute	**Description**	
Name	COUNTERPARTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CURRENCY

Attribute	**Description**	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TENOR

Attribute	**Description**	
Name	TENOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CHGREQ

Attribute	**Description**	
Name	CHGREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.83.2.RB-CreateOvscheckspay-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONTREFNO*
    - *LATESTVERSIONNO*
    - *RECORD_STAT*
    - *AUTHSTATUS*
    - *CURR_EVENT_CODE*
    - *EVENT_SEQ_NO*
    - *CPTY_ID*
    - *CPTY_AC_NO*
    - *INSTRNO*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *NET_AMT_REALISED*
    - *OTHER_BANK_CHARGES*
    - *COLL_BNK_CIF*
    - *MATURITY_DATE*
    - *VALUE_DATE*
    - *TRACK_LIMIT*

CREDIT_LINE
FINANCING
INT_REM
INSTRUMENT_CODE
PRCD
USERREF_NO
XREF
EVENTSEQ
PARTYTYP
ADDRESS
PARTYADDR2
PARTYADDR3
PARTYADDR4
WALKINCUSTFLG
DB_ACC_REAL
BULK_INPUT_REF_NO
DRAWEE_BNK_NAME
AUTOLIQD
OTHER_PARTY_ID
VERSION_NO
MARGIN_PERCENTAGE
OTHR_PARTY_NAME
TXNUDFDETAILS
  FLDNAME
  FLDVAL
Charges
  LATEVNSEQNO
  CONREFNO
  Charge-Association
    WAIVER
    DISACCRAPPL
    ACCRREQD
    DESC
  Charge-Application
    CHRGAMT
    DISACCRAPPL
    WAIVER
    LIQDIND
  Charge-Liquidation
    ESN
    CHRGAMT
    LIQDSTAT
Misdetails
  CONREFNO

LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4

- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *MISGRPFUN*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*

RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6

ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *ULTBANDCD*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*
- *NOOFDEC*
- *ADDID*
- *SNDRRCVRINFO1*
- *SNDRRCVRINFO2*
- *SNDRRCVRINFO3*
- *SNDRRCVRINFO4*

SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Clpref
CONTREFNNO
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
Con
CONTREFNO
EVENTSEQ
Adv
SUPRESS
PRIOR
MEDM
CHGREQ

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATESTVERSIONNO

Attribute	Description
Name	LATESTVERSIONNO
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTATUS

Attribute	**Description**	
Name	AUTHSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CURR_EVENT_CODE

Attribute	**Description**	
Name	CURR_EVENT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

INT_REM

Attribute	Description
Name	INT_REM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

ADDRESS

Attribute	Description
Name	ADDRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTYADDR2

Attribute	Description
Name	PARTYADDR2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PARTYADDR3

Attribute	**Description**	
Name	PARTYADDR3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PARTYADDR4

Attribute	**Description**	
Name	PARTYADDR4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

WALKINCUSTFLG

Attribute	**Description**	
Name	WALKINCUSTFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DB_ACC_REAL

Attribute	**Description**	
Name	DB_ACC_REAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BULK_INPUT_REF_NO

Attribute	Description
Name	BULK_INPUT_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

OTHER_PARTY_ID

Attribute	Description
Name	OTHER_PARTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	Description	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Settlements

Attribute	**Description**	
Name	Settlements	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Settlement

Attribute	**Description**	
Name	Contract-Settlement	
Datatype		
Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CUSTSPREAD

Attribute	**Description**
Name	CUSTSPREAD

Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3

Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4

Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	**Description**	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	**Description**	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	Description	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail

Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Clpref

Attribute	**Description**	
Name	Clpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNNO

Attribute	**Description**	
Name	CONTREFNNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

Ude

Attribute	Description
Name	Ude

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

2.83.3.RB-CreateOvscheckspay-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONTREFNO*
    - *LATESTVERSIONNO*
    - *RECORD_STAT*
    - *AUTHSTATUS*
    - *CURR_EVENT_CODE*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHKR*
    - *CHKDTTIME*
    - *EVENT_SEQ_NO*
    - *CONT_STAT*
    - *AUTH_STAT*
    - *CPTY_ID*
    - *CPTY_AC_NO*
    - *INSTRNO*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*

NET_AMT_REALISED
OTHER_BANK_CHARGES
COLL_BNK_CIF
BOOKINGDATE
MATURITY_DATE
VALUE_DATE
TRACK_LIMIT
CREDIT_LINE
FINANCING
INT_REM
INSTRUMENT_CODE
INSTR_DESC
PRCD
PRODDESC
USERREF_NO
XREF
COUNTRPRYNAM
LCY_AMT
COLLBANKNAME
PAYDUEDATE
CONREF
EVENTSEQ
PARTYTYP
ADDRESS
PARTYADDR2
PARTYADDR3
PARTYADDR4
WALKINCUSTFLG
COLLEC_BANK_CIF
COLLBNKNAME
DISCOUNT_AMOUNT
DB_ACC_REAL
BULK_INPUT_REF_NO
DRAWEE_BNK_NAME
AUTOLIQD
OTHER_PARTY_ID
VERSION_NO
TRANSITDAYS
MARGIN_PERCENTAGE
ACC_BRANCH
OTHR_PARTY_NAME
ACCBRN
TXNUDFDETAILS
  FLDNAME

- *FLDVAL*
- *Charges*
  - *CONREFNO*
  - *Charge-Association*
    - *COMPNT*
    - *CREATESN*
    - *RULE*
    - *WAIVER*
    - *DISACCRAPPL*
    - *ACCRREQD*
    - *DESC*
  - *Charge-Application*
    - *CREATESN*
    - *COMPNT*
    - *TGCCY*
    - *TGAMT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *DISACCRAPPL*
    - *WAIVER*
    - *LIQDIND*
  - *Charge-Liquidation*
    - *ESN*
    - *COMPNT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *LIQDSTAT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*

COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9

- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*

BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1

BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*

ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Clpref
CONTREFNNO

CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM
PAYMENT_MODE
LOANVALDATE
MATURITY_DATE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESTVERSIONNO

Attribute	Description
Name	LATESTVERSIONNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTATUS

Attribute	Description
Name	AUTHSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CURR_EVENT_CODE

Attribute	Description
Name	CURR_EVENT_CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONT_STAT

Attribute	**Description**	
Name	CONT_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,L,R,H,

TOP

AUTH_STAT

Attribute	**Description**	
Name	AUTH_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U,

TOP

CPTY_ID

Attribute	**Description**	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

INT_REM

Attribute	Description	
Name	INT_REM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INSTRUMENT_CODE

Attribute	Description	
Name	INSTRUMENT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTR_DESC

Attribute	Description	
Name	INSTR_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRCD

Attribute	Description	
Name	PRCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLBANKNAME

Attribute	Description
Name	COLLBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREF

Attribute	Description
Name	CONREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

ADDRESS

Attribute	Description
Name	ADDRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTYADDR2

Attribute	Description
Name	PARTYADDR2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTYADDR3

Attribute	Description
Name	PARTYADDR3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTYADDR4

Attribute	Description
Name	PARTYADDR4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINCUSTFLG

Attribute	Description
Name	WALKINCUSTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COLLEC_BANK_CIF

Attribute	Description
Name	COLLEC_BANK_CIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DB_ACC_REAL

Attribute	**Description**	
Name	DB_ACC_REAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BULK_INPUT_REF_NO

Attribute	**Description**	
Name	BULK_INPUT_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DRAWEE_BNK_NAME

Attribute	**Description**	
Name	DRAWEE_BNK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AUTOLIQD

Attribute	**Description**	
Name	AUTOLIQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

OTHER_PARTY_ID

Attribute	Description
Name	OTHER_PARTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACC_BRANCH

Attribute	Description
Name	ACC_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Clpref

Attribute	**Description**	
Name	Clpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNNO

Attribute	**Description**	
Name	CONTREFNNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CONTRACT_CCY

Attribute	**Description**	
Name	CONTRACT_CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TENOR

Attribute	Description
Name	TENOR

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description

Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.83.4.RB-CreateOvscheckspay-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONTREFNO*
    - *Main-IO*
      - *CONTREFNO*
      - *LATESTVERSIONNO*
      - *RECORD_STAT*
      - *AUTHSTATUS*
      - *CURR_EVENT_CODE*
      - *EVENT_SEQ_NO*
      - *CPTY_ID*
      - *CPTY_AC_NO*
      - *INSTRNO*
      - *INSTRUMENT_DATE*
      - *CURRENCY*
      - *AMNT*
      - *NET_AMT_REALISED*
      - *OTHER_BANK_CHARGES*
      - *COLL_BNK_CIF*

MATURITY_DATE
VALUE_DATE
TRACK_LIMIT
CREDIT_LINE
FINANCING
INT_REM
INSTRUMENT_CODE
PRCD
USERREF_NO
XREF
EVENTSEQ
PARTYTYP
ADDRESS
PARTYADDR2
PARTYADDR3
PARTYADDR4
WALKINCUSTFLG
DB_ACC_REAL
BULK_INPUT_REF_NO
DRAWEE_BNK_NAME
AUTOLIQD
OTHER_PARTY_ID
VERSION_NO
MARGIN_PERCENTAGE
OTHR_PARTY_NAME
TXNUDFDETAILS
  FLDNAME
  FLDVAL
Charges
  LATEVNSEQNO
  CONREFNO
  Charge-Association
    WAIVER
    DISACCRAPPL
    ACCRREQD
    DESC
  Charge-Application
    CHRGAMT
    DISACCRAPPL
    WAIVER
    LIQDIND
  Charge-Liquidation
    ESN
    CHRGAMT

LIQDSTAT

Misdetails

CONREFNO

LATESN

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10

- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *MISGRPFUN*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*

SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID

POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *ULTBANDCD*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*
- *NOOFDEC*
- *ADDID*
- *SNDRRCVRINFO1*

SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Clpref
CONTREFNNO
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
Con
CONTREFNO
EVENTSEQ
Adv
SUPRESS
PRIOR
MEDM
CHGREQ
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESTVERSIONNO

Attribute	Description	
Name	LATESTVERSIONNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RECORD_STAT

Attribute	Description	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTATUS

Attribute	Description
Name	AUTHSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CURR_EVENT_CODE

Attribute	Description
Name	CURR_EVENT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRACK_LIMIT

Attribute	**Description**	
Name	TRACK_LIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CREDIT_LINE

Attribute	**Description**	
Name	CREDIT_LINE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,N,F

TOP

INT_REM

Attribute	**Description**	
Name	INT_REM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INSTRUMENT_CODE

Attribute	Description	
Name	INSTRUMENT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

PRCD

Attribute	Description	
Name	PRCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

USERREF_NO

Attribute	Description	
Name	USERREF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

ADDRESS

Attribute	Description
Name	ADDRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTYADDR2

Attribute	Description
Name	PARTYADDR2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTYADDR3

Attribute	Description
Name	PARTYADDR3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PARTYADDR4

Attribute	**Description**	
Name	PARTYADDR4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

WALKINCUSTFLG

Attribute	**Description**	
Name	WALKINCUSTFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DB_ACC_REAL

Attribute	**Description**	
Name	DB_ACC_REAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BULK_INPUT_REF_NO

Attribute	**Description**	
Name	BULK_INPUT_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

OTHER_PARTY_ID

Attribute	Description
Name	OTHER_PARTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description

Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**

Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description

Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description

Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1

Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	Description	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5

Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD

Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3

Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Clpref

Attribute	Description	
Name	Clpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNNO

Attribute	Description	
Name	CONTREFNNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LOAN_CONREFNO

Attribute	Description	
Name	LOAN_CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RATECODE

Attribute	Description
Name	RATECODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Con

Attribute	Description
Name	Con

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.84.CreateOvsrealizecontract

CreateOvsrealizecontract

2.84.1.RB-CreateOvsrealizecontract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *INSTRNO*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *CPTY_AC_NO*
    - *NET_AMT_REALISED*

OTHER_BANK_CHARGES
COLL_BNK_CIF
COLBANK_REFNO
VALUE_DATE
REMARKS
DB_ACC_REAL
COLL_BNK_NAME
ACCBRN
ACC_BRANCH
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*

TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4

ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*

ENVCONT5

Lcl_Clearing

FREETXT1

FREETXT2

FREETXT3

PMNTCD

ADDINFOSORBNET

SNDRCUSTNAME1

SNDRCUSTNAME2

SNDRCUSTNAME3

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

Charges

CONREFNO

Charge-Association

COMPNT

CREATESN

- *RULE*
- *WAIVER*
- *DISACCRAPPL*
- *ACCRREQD*
- *DESC*

Charge-Application

- *CREATESN*
- *COMPNT*
- *TGCCY*
- *TGAMT*
- *CHRGCCY*
- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*

Charge-Liquidation

- *ESN*
- *COMPNT*
- *CHRGCCY*
- *CHRGAMT*
- *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*

TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5

COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CTR_PRTY_NAME

Attribute	Description

Name	CTR_PRTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>L,A,H,</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,U,</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COLL_BNK_CIF

Attribute	**Description**	
Name	COLL_BNK_CIF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

COLBANK_REFNO

Attribute	**Description**	
Name	COLBANK_REFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VALUE_DATE

Attribute	**Description**	
Name	VALUE_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACC_BRANCH

Attribute	Description
Name	ACC_BRANCH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Con

Attribute	Description
Name	Con

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	**Description**	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	**Description**	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1

Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2

Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5

Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1

Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	**Description**	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	**Description**	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application

Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL

Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.84.2.RB-CreateOvsrealizecontract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONREFNUM*
    - *CPTY_AC_NO*
    - *NET_AMT_REALISED*
    - *COLBANK_REFNO*
    - *VALUE_DATE*
    - *REMARKS*
    - *DB_ACC_REAL*
    - *Con*
      - *CONTREFNO*
      - *EVENTSEQ*
      - *Adv*
        - *SUPRESS*
        - *PRIOR*
        - *MEDM*
        - *CHGREQ*
    - *Settlements*
      - *CONREFNO*
      - *LATEVNSEQNO*

Contract-Settlement

- *CUSTSPREAD*
- *SPREADDEFN*
- *TAGCCY*
- *ACCBRN*
- *ACC*
- *EXRATE*
- *NETIND*
- *ERICCY*
- *ERIAMT*
- *GENMSG*
- *RATECD*
- *CLEARNW*
- *COVERBY*
- *RTGSPMNT*
- *BANKPRIOR*
- *RTGSNW*
- *PAYBY*
- *TRANSTYP*
- *INSTYP*
- *INSNO*
- *CHGDET*
- *PAYMNTDET1*
- *PAYMNTDET2*
- *PAYMNTDET3*
- *PAYMNTDET4*
- *SNDTRRCVINFO1*
- *SNDTRRCVINFO2*
- *SNDTRRCVINFO3*
- *SNDTRRCVINFO4*
- *SNDTRRCVINFO5*
- *COVREQRD*
- *RECVCVR*
- *RECEIVER*
- *REIMINST1*
- *REIMINST4*
- *RCVRCORRS1*
- *RCVRCORRS2*
- *RCVRCORRS3*
- *RCVRCORRS4*
- *INTERMEDIARY1*
- *INTERMEDIARY2*
- *INTERMEDIARY3*
- *INTERMEDIARY4*

ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*

INSTRCD4
ITIMEIND1
ITIMEIND2
ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
LATEVNSEQNO
CONREFNO
Charge-Association

- *WAIVER*
- *DISACCRAPPL*
- *ACCRREQD*
- *DESC*
- *Charge-Application*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*
  - *COSTCD4*
  - *COSTCD5*
  - *TXNMIS1*
  - *TXNMIS10*
  - *TXNMIS2*
  - *TXNMIS3*
  - *TXNMIS4*
  - *TXNMIS5*
  - *TXNMIS6*
  - *TXNMIS7*
  - *TXNMIS8*
  - *TXNMIS9*
  - *MISGRPCOMP*
  - *MISGRPTXN*

COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

NET_AMT_REALISED

Attribute	**Description**	
Name	NET_AMT_REALISED	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

COLBANK_REFNO

Attribute	**Description**	
Name	COLBANK_REFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VALUE_DATE

Attribute	**Description**	
Name	VALUE_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	**Description**	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	**Description**	
Name	CLEARNW	
Datatype	String	
Description	Indicates Network Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	**Description**	
Name	COVERBY	
Datatype	String	
Description	Indicates Cover By Clearing : C Message : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	**Description**
Name	RTGSPMNT
Datatype	String

Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	Description	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP

Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2

Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	Description	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATEVNSEQNO

Attribute	Description	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Txnmisdetails

Attribute	**Description**	
Name	Txnmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Compmisdetails

Attribute	**Description**	
Name	Compmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.84.3.RB-CreateOvsrealizecontract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *INSTRNO*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *CPTY_AC_NO*
    - *NET_AMT_REALISED*
    - *OTHER_BANK_CHARGES*
    - *COLL_BNK_CIF*
    - *COLBANK_REFNO*

VALUE_DATE
REMARKS
DB_ACC_REAL
COLL_BNK_NAME
ACCBRN
ACC_BRANCH
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*

CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3

ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*

FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL

- *ACCRREQD*
- *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*
  - *COSTCD4*
  - *COSTCD5*
  - *TXNMIS1*
  - *TXNMIS10*
  - *TXNMIS2*
  - *TXNMIS3*
  - *TXNMIS4*
  - *TXNMIS5*
  - *TXNMIS6*

TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8

COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CTR_PRTY_NAME

Attribute	Description
Name	CTR_PRTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,A,H,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

COLBANK_REFNO

Attribute	Description
Name	COLBANK_REFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC_BRANCH

Attribute	Description
Name	ACC_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SUPRESS

Attribute	**Description**	
Name	SUPRESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number

Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String

Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description

Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1

Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5

Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	**Description**	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	**Description**	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	**Description**
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	**Description**
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	**Description**
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	**Description**
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description

Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	Description	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	Description	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.84.4.RB-CreateOvsrealizecontract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONREFNUM*
    - *Main-IO*
      - *CONREFNUM*
      - *CPTY_AC_NO*
      - *NET_AMT_REALISED*
      - *COLBANK_REFNO*
      - *VALUE_DATE*
      - *REMARKS*
      - *DB_ACC_REAL*
      - *Con*
        - *CONTREFNO*
        - *EVENTSEQ*
        - *Adv*
          - *SUPRESS*
          - *PRIOR*
          - *MEDM*
          - *CHGREQ*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*
  - *RECVCVR*
  - *RECEIVER*
  - *REIMINST1*
  - *REIMINST4*
  - *RCVRCORRS1*
  - *RCVRCORRS2*
  - *RCVRCORRS3*
  - *RCVRCORRS4*
  - *INTERMEDIARY1*

INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail

INSTRCD1
INSTRCD2
INSTRCD3
INSTRCD4
ITIMEIND1
ITIMEIND2
ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges

- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*

TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

COLBANK_REFNO

Attribute	**Description**	
Name	COLBANK_REFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VALUE_DATE

Attribute	**Description**	
Name	VALUE_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DB_ACC_REAL

Attribute	**Description**	
Name	DB_ACC_REAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String

Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	Description	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	Description	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	Description	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO5

Attribute	Description	
Name	SNDTRRCVINFO5	
Datatype	String	
Description	Indicates Sender To Receiver Information 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description

Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1

Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	Description	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5

Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD

Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3

Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	Indicates Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	**Description**
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	**Description**
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	**Description**
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	**Description**
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description

Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.85.CreatePDCContract

CreatePDCContract

2.85.1.RB-CreatePDCContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNUM*
    - *BOOKDT*
    - *USERREFNUM*
    - *XREF*
    - *PRDCD*
    - *MODCOD*
    - *UDSTAT*
    - *STOPDT*
    - *EVENTCD*
    - *INSTRUCODE*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *INSTRNO*
    - *INSTRDATE*
    - *CONTCCY*

AMOUNT
LCYAMT
OTHRPTYIDEN
BOOKINGDT
ACTDATE
VALUEDT
TRACKLIMIT
CRDLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
DISCOUNTAMT
COLLATERAL
COLLATVAL
COLLPOOL
ISRBNK
ISSUERBRN
CLGBANK
CLGBRN
SECTORCD
ENDPNT
INTREMARKS
ACCBRN
ROUTNO
DRACCBRN
INSTR_DESC
PRDDESC
CPTYNAME
OTHERPARTYNAME
ISSBANKNAME
ISSBRNCNAME
CLEARBANKNAME
AUTOLIQD
CLEARBRNCNAME
MAKER
MAKDTTIME
CHKR
CHKDTTIME
CONST
AUTHSTAT
BATCHREFENUM
BATCHSEQNO
DRACCREAL
CLGPRD

- *Party-Details*
  - *PRTYTYP*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *PARTYREFNO*
  - *COUNTRYCD*
  - *ADDLN1*
  - *ADDLN2*
  - *ADDLN3*
  - *ADDLN4*
  - *PARTLANG*
- *Settlements*
  - *CONREFNO*
  - *Contract-Settlement*
    - *IBANACNO*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *COMPNT*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *ACCCCY*
    - *EXRATE*
    - *NETIND*
    - *ERICCY*
    - *ERIAMT*
    - *GENMSG*
    - *RATECD*
    - *CLEARNW*
    - *COVERBY*
    - *RTGSPMNT*
    - *BANKPRIOR*
    - *RTGSNW*
    - *PAYBY*
    - *TRANSTYP*
    - *INSTYP*
    - *INSNO*
    - *CHGDET*
    - *PAYMNTDET1*
    - *PAYMNTDET2*
    - *PAYMNTDET3*
    - *PAYMNTDET4*
    - *SNDTRRCVINFO1*
    - *SNDTRRCVINFO2*

SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC

COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*

SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT

CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10

COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5

- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Con

- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Clpref

- *CONTREFNNO*
- *CONTRACT_CCY*
- *LATEVNSEQNO*
- *PRD*
- *PRDDESC*
- *COUNTERPARTY*
- *CURRENCY*
- *TENOR*
- *UNITS*
- *LOAN_CONREFNO*
- *RATECODE*
- *EXCHANGERATE*
- *RATE_TYPE*
- *MAXIMUM*
- *MINIMUM*
- *PAYMENT_MODE*
- *LOANVALDATE*
- *MATURITY_DATE*
- *Ude*
  - *USERDEID*

UDEDESC
RATEASOF
USAGE
USERDEVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description

Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USERREFNUM

Attribute	Description
Name	USERREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MODCOD

Attribute	Description
Name	MODCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BOOKINGDT

Attribute	Description
Name	BOOKINGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACTDATE

Attribute	Description
Name	ACTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRDLINE

Attribute	Description
Name	CRDLINE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,F,N

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLATVAL

Attribute	Description
Name	COLLATVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ISRBNK

Attribute	Description
Name	ISRBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ISSUERBRN

Attribute	Description
Name	ISSUERBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBANK

Attribute	Description
Name	CLGBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBRN

Attribute	Description
Name	CLGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ENDPNT

Attribute	Description
Name	ENDPNT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTREMARKS

Attribute	**Description**	
Name	INTREMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ROUTNO

Attribute	**Description**	
Name	ROUTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	27

TOP

DRACCBRN

Attribute	**Description**	
Name	DRACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ISSBANKNAME

Attribute	Description
Name	ISSBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ISSBRNCNAME

Attribute	Description
Name	ISSBRNCNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CLEARBANKNAME

Attribute	Description
Name	CLEARBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLEARBRNCNAME

Attribute	Description
Name	CLEARBRNCNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,H,R,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DRACCREAL

Attribute	**Description**	
Name	DRACCREAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CLGPRD

Attribute	**Description**	
Name	CLGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Party-Details

Attribute	**Description**	
Name	Party-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRTYTYP

Attribute	**Description**	
Name	PRTYTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	DRAWER,PAYEE

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTYREFNO

Attribute	Description
Name	PARTYREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ADDLN1

Attribute	Description

Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTLANG

Attribute	Description
Name	PARTLANG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Settlements

Attribute	**Description**	
Name	Settlements	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Settlement

Attribute	**Description**	
Name	Contract-Settlement	
Datatype		
Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	**Description**	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	**Description**	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,S</td></tr></table>

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.85.2.RB-CreatePDCContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNUM*
    - *BOOKDT*
    - *USERREFNUM*
    - *XREF*
    - *PRDCD*
    - *MODCOD*
    - *UDSTAT*
    - *STOPDT*
    - *EVENTCD*
    - *INSTRUCODE*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *INSTRNO*
    - *INSTRDATE*
    - *CONTCCY*
    - *AMOUNT*
    - *OTHRPTYIDEN*
    - *TRACKLIMIT*

CRDLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
COLLATERAL
COLLPOOL
ISRBNK
ISSUERBRN
ENDPNT
INTREMARKS
ROUTNO
AUTOLIQD
BATCHREFENUM
CLGPRD
Party-Details
  PARTYNAME
  PARTYREFNO
  COUNTRYCD
  ADDLN1
  ADDLN2
  ADDLN3
  ADDLN4
  PARTLANG
Settlements
  CONREFNO
  LATEVNSEQNO
  Contract-Settlement
    CUSTSPREAD
    SPREADDEFN
    TAGCCY
    ACCBRN
    ACC
    EXRATE
    NETIND
    ERICCY
    ERIAMT
    GENMSG
    RATECD
    CLEARNW
    COVERBY
    RTGSPMNT
    BANKPRIOR
    RTGSNW
    PAYBY

TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2

ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*

FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Charges
- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails
- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*

RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7

FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
SUPRESS
PRIOR
MEDM
CHGREQ
Clpref
CONTREFNNO
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BOOKDT

Attribute	Description
Name	BOOKDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USERREFNUM

Attribute	Description
Name	USERREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MODCOD

Attribute	Description
Name	MODCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMOUNT

Attribute	**Description**	
Name	AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

OTHRPTYIDEN

Attribute	**Description**	
Name	OTHRPTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TRACKLIMIT

Attribute	**Description**	
Name	TRACKLIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CRDLINE

Attribute	**Description**	
Name	CRDLINE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,F,N

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ISRBNK

Attribute	Description
Name	ISRBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ISSUERBRN

Attribute	Description
Name	ISSUERBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ENDPNT

Attribute	Description
Name	ENDPNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ROUTNO

Attribute	**Description**	
Name	ROUTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	27

TOP

AUTOLIQD

Attribute	**Description**	
Name	AUTOLIQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BATCHREFENUM

Attribute	**Description**	
Name	BATCHREFENUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CLGPRD

Attribute	**Description**	
Name	CLGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYREFNO

Attribute	Description
Name	PARTYREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTLANG

Attribute	Description

Name	PARTLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC

Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	Description	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	Description	
Name	CLEARNW	
Datatype	String	
Description	Indicates Network Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	Description	
Name	COVERBY	
Datatype	String	
Description	Indicates Cover By Clearing : C Message : M	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4

Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String

Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing

Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ULTBANDCD

Attribute	Description	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SUPPID

Attribute	Description	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	Description	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PMNTTYP

Attribute	Description	
Name	PMNTTYP	
Datatype	String	
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	Description	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	Description	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String

Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**
Name	LATESN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.85.3.RB-CreatePDCContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNUM*
    - *BOOKDT*
    - *USERREFNUM*
    - *XREF*
    - *PRDCD*
    - *MODCOD*
    - *UDSTAT*
    - *STOPDT*
    - *EVENTCD*
    - *INSTRUCODE*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *INSTRNO*
    - *INSTRDATE*
    - *CONTCCY*
    - *AMOUNT*
    - *LCYAMT*
    - *OTHRPTYIDEN*

BOOKINGDT
ACTDATE
VALUEDT
TRACKLIMIT
CRDLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
DISCOUNTAMT
COLLATERAL
COLLATVAL
COLLPOOL
ISRBNK
ISSUERBRN
CLGBANK
CLGBRN
SECTORCD
ENDPNT
INTREMARKS
ACCBRN
ROUTNO
DRACCBRN
INSTR_DESC
PRDDESC
CPTYNAME
OTHERPARTYNAME
ISSBANKNAME
ISSBRNCNAME
CLEARBANKNAME
AUTOLIQD
CLEARBRNCNAME
MAKER
MAKDTTIME
CHKR
CHKDTTIME
CONST
AUTHSTAT
BATCHREFENUM
BATCHSEQNO
DRACCREAL
CLGPRD
Party-Details
  PRTYTYP
  PARTYIDEN

- *PARTYNAME*
- *PARTYREFNO*
- *COUNTRYCD*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ADDLN4*
- *PARTLANG*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*

COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID

POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*

RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL

- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*
  - *COSTCD4*
  - *COSTCD5*
  - *TXNMIS1*
  - *TXNMIS10*
  - *TXNMIS2*
  - *TXNMIS3*
  - *TXNMIS4*
  - *TXNMIS5*
  - *TXNMIS6*
  - *TXNMIS7*
  - *TXNMIS8*
  - *TXNMIS9*
  - *MISGRPCOMP*
  - *MISGRPTXN*
  - *COMPMIS1*
  - *COMPMIS10*
  - *COMPMIS2*
  - *COMPMIS3*
  - *COMPMIS4*

COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8

- FUNMIS9
- FUNMIS10
- Txnmisdetails
- Compmisdetails
- Fundmisdetails

TXNUDFDETAILS

- FLDNAME
- FLDVAL

Con

- CONTREFNO
- EVENTSEQ
- Adv
  - ADVNAME
  - SUPRESS
  - PRIOR
  - MEDM
  - PARTYIDEN
  - PARTYNAME
  - CHGREQ
  - PARTTYP

Clpref

- CONTREFNNO
- CONTRACT_CCY
- LATEVNSEQNO
- PRD
- PRDDESC
- COUNTERPARTY
- CURRENCY
- TENOR
- UNITS
- LOAN_CONREFNO
- RATECODE
- EXCHANGERATE
- RATE_TYPE
- MAXIMUM
- MINIMUM
- PAYMENT_MODE
- LOANVALDATE
- MATURITY_DATE
- Ude
  - USERDEID
  - UDEDESC
  - RATEASOF
  - USAGE

USERDEVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

USERREFNUM

Attribute	Description
Name	USERREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MODCOD

Attribute	Description
Name	MODCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BOOKINGDT

Attribute	Description
Name	BOOKINGDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACTDATE

Attribute	Description
Name	ACTDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,F,N

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLATVAL

Attribute	Description
Name	COLLATVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ISRBNK

Attribute	Description
Name	ISRBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ISSUERBRN

Attribute	Description
Name	ISSUERBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBANK

Attribute	Description
Name	CLGBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBRN

Attribute	Description
Name	CLGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ENDPNT

Attribute	Description
Name	ENDPNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>27</td></tr></table>

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ISSBANKNAME

Attribute	**Description**	
Name	ISSBANKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ISSBRNCNAME

Attribute	**Description**	
Name	ISSBRNCNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CLEARBANKNAME

Attribute	**Description**	
Name	CLEARBANKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

AUTOLIQD

Attribute	**Description**	
Name	AUTOLIQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CLEARBRNCNAME

Attribute	Description
Name	CLEARBRNCNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,H,R,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CLGPRD

Attribute	Description
Name	CLGPRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / DRAWER,PAYEE

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYREFNO

Attribute	Description
Name	PARTYREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTLANG

Attribute	Description
Name	PARTLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String

Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	**Description**
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	**Description**
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	**Description**
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	**Description**
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,S</td></tr></table>

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.85.4.RB-CreatePDCContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNUM*
    - *Contract-Details-IO*
      - *CONREFNUM*
      - *BOOKDT*
      - *USERREFNUM*
      - *XREF*
      - *PRDCD*
      - *MODCOD*
      - *UDSTAT*
      - *STOPDT*
      - *EVENTCD*
      - *INSTRUCODE*
      - *CPTYIDEN*
      - *CPTYACCNUM*
      - *INSTRNO*
      - *INSTRDATE*
      - *CONTCCY*

AMOUNT
OTHRPTYIDEN
TRACKLIMIT
CRDLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
COLLATERAL
COLLPOOL
ISRBNK
ISSUERBRN
ENDPNT
INTREMARKS
ROUTNO
AUTOLIQD
BATCHREFENUM
CLGPRD
Party-Details
  PARTYNAME
  PARTYREFNO
  COUNTRYCD
  ADDLN1
  ADDLN2
  ADDLN3
  ADDLN4
  PARTLANG
Settlements
  CONREFNO
  LATEVNSEQNO
  Contract-Settlement
    CUSTSPREAD
    SPREADDEFN
    TAGCCY
    ACCBRN
    ACC
    EXRATE
    NETIND
    ERICCY
    ERIAMT
    GENMSG
    RATECD
    CLEARNW
    COVERBY
    RTGSPMNT

BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3

BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*

ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
LATEVNSEQNO
CONREFNO
Charge-Association
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO

LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4

FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
SUPRESS
PRIOR
MEDM
CHGREQ
Clpref
CONTREFNNO
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

USERREFNUM

Attribute	Description
Name	USERREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MODCOD

Attribute	Description
Name	MODCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,F,N</td></tr></table>

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,C,T,N</td></tr></table>

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ISRBNK

Attribute	Description
Name	ISRBNK
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ISSUERBRN

Attribute	**Description**	
Name	ISSUERBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ENDPNT

Attribute	**Description**	
Name	ENDPNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTREMARKS

Attribute	**Description**	
Name	INTREMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ROUTNO

Attribute	**Description**	
Name	ROUTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CLGPRD

Attribute	Description
Name	CLGPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTYREFNO

Attribute	Description
Name	PARTYREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN2

Attribute	Description

Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTLANG

Attribute	Description
Name	PARTLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String

Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String

Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description

Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	**Description**	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	**Description**	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	**Description**	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4

Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5

Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1

Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	**Description**	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String

Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3

Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	**Description**	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	**Description**	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	**Description**	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number

Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,S</td></tr></table>

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.86.CloseBulkPDRContract

CloseBulkPDRContract

2.86.1.RB-CloseBulkPDRContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulkpdr-Full*
    - *BANK_CODE*
    - *BRNCODE*
    - *BANKNAME*
    - *BRNNAME*
    - *ACTION*
    - *DISPATCHLOTREFNO*
    - *BULKPDRREFNO*
    - *PROCESSTAT*
    - *AUTHSTAT*
    - *CHKR*
    - *CHKDTTIME*
    - *EVSEQNO*
    - *MAKER*
    - *MAKDTTIME*
    - *RECORDSTAT*

ESNUI

Bulkpdrdetail

CONREFNUM

ACC_CCY

AMNT

DISHONOUR_DATE

NOTARYCODE

PROTESTDATE

INTREMRKS

DISHONOUR_REASON

RETURN_DATE

CPTYIDEN

OTHRPTYIDEN

CPTYNAME

OTHERPARTYNAME

INSTRNO

PROCESSSTAT

PRDTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Bulkpdr-Full

Attribute	Description
Name	Bulkpdr-Full
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description	Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BRNCODE

Attribute	Description	
Name	BRNCODE	
Datatype	String	
Description	Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BANKNAME

Attribute	Description	
Name	BANKNAME	
Datatype	String	
Description	Bank Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

DISPATCHLOTREFNO

Attribute	**Description**	
Name	DISPATCHLOTREFNO	
Datatype	String	
Description	Dispatch Lot Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BULKPDRREFNO

Attribute	**Description**	
Name	BULKPDRREFNO	
Datatype	String	
Description	Bulk Dishonor / Protest / Return Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,U

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	Checker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	Date Time
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EVSEQNO

Attribute	Description
Name	EVSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	Date Time
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	Record Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,O,C</td></tr></table>

TOP

ESNUI

Attribute	Description
Name	ESNUI
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bulkpdrdetail

Attribute	Description
Name	Bulkpdrdetail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISHONOUR_DATE

Attribute	Description

Name	DISHONOUR_DATE
Datatype	Date
Description	Dishonour Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	Notary Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	Protest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Internal Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DISHONOUR_REASON

Attribute	Description
Name	DISHONOUR_REASON
Datatype	String
Description	Dishonor Reason
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	Return Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	CounterParty Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	Other Party Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	CounterParty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME

Datatype	String
Description	Other Party Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	Instrument Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,H,S,F

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Product Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

2.86.2.RB-CloseBulkPDRContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulkpdr-IO*
    - *BULKPDRREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Bulkpdr-IO

Attribute	Description
Name	Bulkpdr-IO
Datatype	
Description	

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	Bulk Dishonor / Protest / Return Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.86.3.RB-CloseBulkPDRContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulkpdr-Full*
    - *BANK_CODE*
    - *BRNCODE*
    - *BANKNAME*
    - *BRNNAME*
    - *ACTION*
    - *DISPATCHLOTREFNO*
    - *BULKPDRREFNO*
    - *PROCESSTAT*
    - *AUTHSTAT*
    - *CHKR*
    - *CHKDTTIME*
    - *EVSEQNO*
    - *MAKER*
    - *MAKDTTIME*
    - *RECORDSTAT*
    - *ESNUI*
    - *Bulkpdrdetail*
      - *CONREFNUM*

ACC_CCY
AMNT
DISHONOUR_DATE
NOTARYCODE
PROTESTDATE
INTREMRKS
DISHONOUR_REASON
RETURN_DATE
CPTYIDEN
OTHRPTYIDEN
CPTYNAME
OTHERPARTYNAME
INSTRNO
PROCESSSTAT
PRDTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Bulkpdr-Full

Attribute	Description
Name	Bulkpdr-Full
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description	Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BRNCODE

Attribute	Description	
Name	BRNCODE	
Datatype	String	
Description	Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BANKNAME

Attribute	Description	
Name	BANKNAME	
Datatype	String	
Description	Bank Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description	Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

DISPATCHLOTREFNO

Attribute	Description	
Name	DISPATCHLOTREFNO	
Datatype	String	
Description	Dispatch Lot Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BULKPDRREFNO

Attribute	Description

Name	BULKPDRREFNO
Datatype	String
Description	Bulk Dishonor / Protest / Return Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,U

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	Checker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	Date Time

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

EVSEQNO

Attribute	**Description**	
Name	EVSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description	Maker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	**Description**	
Name	MAKDTTIME	
Datatype	String	
Description	Date Time	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RECORDSTAT

Attribute	**Description**	
Name	RECORDSTAT	
Datatype	String	
Description	Record Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,O,C

TOP

ESNUI

Attribute	Description
Name	ESNUI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bulkpdrdetail

Attribute	Description
Name	Bulkpdrdetail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number

Description	Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISHONOUR_DATE

Attribute	Description
Name	DISHONOUR_DATE
Datatype	Date
Description	Dishonour Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	Notary Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	Protest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Internal Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DISHONOUR_REASON

Attribute	Description

Name	DISHONOUR_REASON
Datatype	String
Description	Dishonor Reason
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	Return Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	CounterParty Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	Other Party Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	CounterParty Name
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYNAME

Attribute	**Description**	
Name	OTHERPARTYNAME	
Datatype	String	
Description	Other Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INSTRNO

Attribute	**Description**	
Name	INSTRNO	
Datatype	String	
Description	Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

PROCESSSTAT

Attribute	**Description**	
Name	PROCESSSTAT	
Datatype	String	
Description	Process Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,H,S,F

TOP

PRDTYP

Attribute	**Description**	
Name	PRDTYP	
Datatype	String	
Description	Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.86.4.RB-CloseBulkPDRContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulkpdr-PK*
      - *BULKPDRREFNO*
    - *Bulkpdr-IO*
      - *BULKPDRREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulkpdr-PK

Attribute	Description
Name	Bulkpdr-PK
Datatype	
Description	

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	Bulk Dishonor / Protest / Return Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Bulkpdr-IO

Attribute	Description
Name	Bulkpdr-IO
Datatype	
Description	

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	Bulk Dishonor / Protest / Return Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.87.CloseBulkRealization

CloseBulkRealization

2.87.1.RB-CloseBulkRealization-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-Full*
    - *BULKREALNUM*
    - *DISLOTREF*
    - *DRACFORREALISATION*
    - *COLBANKREFNUM*
    - *VDATE*
    - *CURRENCY*
    - *TOTNETREAL*
    - *DRACCBRN*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *CHKR*
    - *CHKDTTIME*
    - *EVENSEQNO*
    - *MAKER*
    - *MAKDTTIME*

PROCESSTAT

MAXESN

Detail

CONREFNUM

AMUNT

INTREMRKS

NETREALAMT

CUSTNUMBER1

OTHRBNKCHARGS

INSTRNO

PROCESSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	Bulk Realization Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DISLOTREF

Attribute	Description
Name	DISLOTREF
Datatype	String
Description	Dispatch Lot Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DRACFORREALISATION

Attribute	Description
Name	DRACFORREALISATION
Datatype	String
Description	Debit Account for Realization
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	Collecting Bank Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VDATE

Attribute	Description
Name	VDATE
Datatype	Date
Description	Value date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TOTNETREAL

Attribute	Description
Name	TOTNETREAL
Datatype	Number
Description	Total Net Realized
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Debit Account Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,O,C,H

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description	Checker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description	Date Time	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVENSEQNO

Attribute	Description
Name	EVENSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	Date Time
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U,F

TOP

MAXESN

Attribute	Description
Name	MAXESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Detail

Attribute	Description
Name	Detail
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

AMUNT

Attribute	Description
Name	AMUNT
Datatype	Number
Description	Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Internal Remarks
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

NETREALAMT

Attribute	Description
Name	NETREALAMT
Datatype	Number
Description	Net Realized Amount
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CUSTNUMBER1

Attribute	Description
Name	CUSTNUMBER1
Datatype	String
Description	Customer Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	Other Bank Charges
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT

Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U,F

TOP

2.87.2.RB-CloseBulkRealization-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Master-IO*
  - *BULKREALNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	Bulk Realization Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.87.3.RB-CloseBulkRealization-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-Full*
    - *BULKREALNUM*
    - *DISLOTREF*
    - *DRACFORREALISATION*
    - *COLBANKREFNUM*
    - *VDATE*
    - *CURRENCY*
    - *TOTNETREAL*
    - *DRACCBRN*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *CHKR*
    - *CHKDTTIME*
    - *EVENSEQNO*
    - *MAKER*
    - *MAKDTTIME*
    - *PROCESSTAT*
    - *MAXESN*
    - *Detail*

CONREFNUM
AMUNT
INTREMRKS
NETREALAMT
CUSTNUMBER1
OTHRBNKCHARGS
INSTRNO
PROCESSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	Bulk Realization Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DISLOTREF

Attribute	Description
Name	DISLOTREF
Datatype	String
Description	Dispatch Lot Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRACFORREALISATION

Attribute	Description
Name	DRACFORREALISATION
Datatype	String
Description	Debit Account for Realization
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	Collecting Bank Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VDATE

Attribute	Description
Name	VDATE
Datatype	Date
Description	Value date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TOTNETREAL

Attribute	Description
Name	TOTNETREAL
Datatype	Number
Description	Total Net Realized
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Debit Account Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,O,C,H

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description	Checker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description	Date Time	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVENSEQNO

Attribute	Description
Name	EVENSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	Date Time
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U,F

TOP

MAXESN

Attribute	Description
Name	MAXESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Detail

Attribute	Description
Name	Detail
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

AMUNT

Attribute	Description
Name	AMUNT
Datatype	Number
Description	Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Internal Remarks
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

NETREALAMT

Attribute	Description
Name	NETREALAMT
Datatype	Number
Description	Net Realized Amount
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CUSTNUMBER1

Attribute	Description
Name	CUSTNUMBER1
Datatype	String
Description	Customer Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	Other Bank Charges
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT

Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U,F

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Master-PK*
      - *BULKREALNUM*
    - *Master-IO*
      - *BULKREALNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Master-PK

Attribute	Description
Name	Master-PK
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	Bulk Realization Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	Bulk Realization Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.88.CloseCreatebulkfcycheck

CloseCreatebulkfcycheck

2.88.1.RB-CloseCreatebulkfcycheck-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Cashletter-Full*
    - *INSTRUCODE*
    - *INSTR_DESC*
    - *PRCD*
    - *PRODDESC*
    - *BATCHREFENUM*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *CPTY_AC_NO*
    - *ACCBRNRE*
    - *AC_CCYY*
    - *ACCBRN*
    - *COLL_BNK_NAME*
    - *BDTE*
    - *VAL_DATE_BANK*
    - *VALUE_DATE_CUST*

LIQDMODE
FINANCING
MARGINPERCENT
TRACK_LIMIT
CREDITLINE
NOOFINSTRUMENTS
PROCESS_STATUS
NOSTROACC
ESN
EVENT_SEQ_NO
RECORD_STAT
AUTHORIZATION_STATUS
CHECKER
CHKDTTIME
MAKER
MAKDTTIME
Bulk-Cashletter-Dtl
- *CONREFNUM*
- *INSTRNO*
- *INSTRU_DATE*
- *ADJSTAMT*
- *LCY_AMT*
- *DISCAMT*
- *OTHR_PARTYNAME*
- *DRAWEE_BNK_NAME*
- *REMRKS*
- *PROCESS_STATUS*

Summary
- *AUTHSTAT*
- *RECORD_STAT*
- *INSTRUCODE*
- *PRCD*
- *CPTY_ID*
- *BATCHREFENUM*
- *NOSTROACC*
- *COLL_BNK_NAME*
- *INSTRNO*
- *INSTRU_DATE*
- *AC_CCYY*
- *AMNT*
- *BDTE*
- *VAL_DATE_BANK*
- *VALUE_DATE_CUST*
- *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Cashletter-Full

Attribute	Description
Name	Bulk-Cashletter-Full
Datatype	
Description	

TOP

INSTRUCODE

Attribute	Description	
Name	INSTRUCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTR_DESC

Attribute	Description	
Name	INSTR_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRCD

Attribute	Description	
Name	PRCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRODDESC

Attribute	Description	
Name	PRODDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCBRNRE

Attribute	Description
Name	ACCBRNRE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BDTE

Attribute	Description
Name	BDTE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDMODE

Attribute	Description
Name	LIQDMODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,U,

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C,

TOP

AUTHORIZATION_STATUS

Attribute	Description
Name	AUTHORIZATION_STATUS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Bulk-Cashletter-Dtl

Attribute	Description
Name	Bulk-Cashletter-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

ADJSTAMT

Attribute	Description

Name	ADJSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,U,</td></tr></table>

TOP

Summary

Attribute	Description
Name	Summary
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,U</td></tr></table>

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C,

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BDTE

Attribute	Description
Name	BDTE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.88.2.RB-CloseCreatebulkfcycheck-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Bulk-Cashletter-IO
BATCHREFENUM

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Cashletter-IO

Attribute	Description
Name	Bulk-Cashletter-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.88.3.RB-CloseCreatebulkfcycheck-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Cashletter-Full*
    - *INSTRUCODE*
    - *INSTR_DESC*
    - *PRCD*
    - *PRODDESC*
    - *BATCHREFENUM*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *CPTY_AC_NO*
    - *ACCBRNRE*
    - *AC_CCYY*
    - *ACCBRN*
    - *COLL_BNK_NAME*
    - *BDTE*
    - *VAL_DATE_BANK*
    - *VALUE_DATE_CUST*
    - *LIQDMODE*
    - *FINANCING*
    - *MARGINPERCENT*

- *TRACK_LIMIT*
- *CREDITLINE*
- *NOOFINSTRUMENTS*
- *PROCESS_STATUS*
- *NOSTROACC*
- *ESN*
- *EVENT_SEQ_NO*
- *RECORD_STAT*
- *AUTHORIZATION_STATUS*
- *CHECKER*
- *CHKDTTIME*
- *MAKER*
- *MAKDTTIME*
- *Bulk-Cashletter-Dtl*
  - *CONREFNUM*
  - *INSTRNO*
  - *INSTRU_DATE*
  - *ADJSTAMT*
  - *LCY_AMT*
  - *DISCAMT*
  - *OTHR_PARTYNAME*
  - *DRAWEE_BNK_NAME*
  - *REMRKS*
  - *PROCESS_STATUS*
- *Summary*
  - *AUTHSTAT*
  - *RECORD_STAT*
  - *INSTRUCODE*
  - *PRCD*
  - *CPTY_ID*
  - *BATCHREFENUM*
  - *NOSTROACC*
  - *COLL_BNK_NAME*
  - *INSTRNO*
  - *INSTRU_DATE*
  - *AC_CCYY*
  - *AMNT*
  - *BDTE*
  - *VAL_DATE_BANK*
  - *VALUE_DATE_CUST*
  - *CONREFNUM*

FCUBS_ERROR_RESP

- *ERROR*
  - *ECODE*

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Cashletter-Full

Attribute	Description

Name	Bulk-Cashletter-Full
Datatype	
Description	

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRNRE

Attribute	Description
Name	ACCBRNRE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BDTE

Attribute	Description
Name	BDTE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDMODE

Attribute	Description
Name	LIQDMODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / P,U,

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,C,

TOP

AUTHORIZATION_STATUS

Attribute	Description
Name	AUTHORIZATION_STATUS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Bulk-Cashletter-Dtl

Attribute	**Description**	
Name	Bulk-Cashletter-Dtl	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CONREFNUM

Attribute	**Description**	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INSTRNO

Attribute	**Description**	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRU_DATE

Attribute	**Description**	
Name	INSTRU_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,U,

TOP

Summary

Attribute	Description
Name	Summary
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>O,C,</td></tr></table>

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BDTE

Attribute	Description
Name	BDTE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.88.4.RB-CloseCreatebulkfcycheck-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Cashletter-PK*
      - *BATCHREFENUM*
    - *Bulk-Cashletter-IO*
      - *BATCHREFENUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Cashletter-PK

Attribute	Description
Name	Bulk-Cashletter-PK
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Cashletter-IO

Attribute	Description
Name	Bulk-Cashletter-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.89.CloseCreatebulkfcyreal

CloseCreatebulkfcyreal

2.89.1.RB-CloseCreatebulkfcyreal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liqd-Cashletter-Full*
    - *CASHREFNO*
    - *AC_CCYY*
    - *ACCBRN*
    - *VALUE_DATE_CUST*
    - *CASHLTRCONREFNO*
    - *NOSTROACC*
    - *PROCESS_STATUS*
    - *ESN*
    - *EVENT_SEQ_NO*
    - *RECORD_STAT*
    - *AUTHORIZATION_STATUS*
    - *CHECKER*
    - *CHKDTTIME*
    - *MAKER*
    - *MAKDTTIME*

Liqd-Cashletter-Dtl

CONREFNUM

CPTY_ID

INSTRNO

INSTRU_DATE

AMNT

INTREMRKS

PROCESS_STATUS

Summary

AUTHSTAT

RECORD_STAT

CASHREFNO

AC_CCYY

NOSTROACC

CONREFNUM

INSTRNO

INSTRU_DATE

AMNT

CPTY_ID

COUNTRPRYNAM

CASHLTRCONREFNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liqd-Cashletter-Full

Attribute	Description
Name	Liqd-Cashletter-Full
Datatype	
Description	

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACCBRN

Attribute	Description

Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,U,

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,C,

TOP

AUTHORIZATION_STATUS

Attribute	Description
Name	AUTHORIZATION_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Liqd-Cashletter-Dtl

Attribute	Description
Name	Liqd-Cashletter-Dtl
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,U,</td></tr></table>

TOP

Summary

Attribute	Description
Name	Summary
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U,

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,C,

TOP

CASHREFNO

Attribute	**Description**	
Name	CASHREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AC_CCYY

Attribute	**Description**	
Name	AC_CCYY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

NOSTROACC

Attribute	**Description**	
Name	NOSTROACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

2.89.2.RB-CloseCreatebulkfcyreal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liqd-Cashletter-IO*
    - *CASHLTRCONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liqd-Cashletter-IO

Attribute	Description
Name	Liqd-Cashletter-IO
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.89.3.RB-CloseCreatebulkfcyreal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liqd-Cashletter-Full*
    - *CASHREFNO*
    - *AC_CCYY*
    - *ACCBRN*
    - *VALUE_DATE_CUST*
    - *CASHLTRCONREFNO*
    - *NOSTROACC*
    - *PROCESS_STATUS*
    - *ESN*
    - *EVENT_SEQ_NO*
    - *RECORD_STAT*
    - *AUTHORIZATION_STATUS*
    - *CHECKER*
    - *CHKDTTIME*
    - *MAKER*
    - *MAKDTTIME*
    - *Liqd-Cashletter-Dtl*
      - *CONREFNUM*
      - *CPTY_ID*

INSTRNO
INSTRU_DATE
AMNT
INTREMRKS
PROCESS_STATUS
Summary
AUTHSTAT
RECORD_STAT
CASHREFNO
AC_CCYY
NOSTROACC
CONREFNUM
INSTRNO
INSTRU_DATE
AMNT
CPTY_ID
COUNTRPRYNAM
CASHLTRCONREFNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liqd-Cashletter-Full

Attribute	Description
Name	Liqd-Cashletter-Full
Datatype	
Description	

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,U,

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,C,

TOP

AUTHORIZATION_STATUS

Attribute	Description
Name	AUTHORIZATION_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Liqd-Cashletter-Dtl

Attribute	Description
Name	Liqd-Cashletter-Dtl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,U,

TOP

Summary

Attribute	Description
Name	Summary
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description

Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C,

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CONREFNUM

Attribute	**Description**	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INSTRNO

Attribute	**Description**	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRU_DATE

Attribute	**Description**	
Name	INSTRU_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMNT

Attribute	**Description**	
Name	AMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.89.4.RB-CloseCreatebulkfcyreal-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Liqd-Cashletter-PK*
      - *CASHLTRCONREFNO*
    - *Liqd-Cashletter-IO*
      - *CASHLTRCONREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Liqd-Cashletter-PK

Attribute	Description
Name	Liqd-Cashletter-PK
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Liqd-Cashletter-IO

Attribute	Description
Name	Liqd-Cashletter-IO
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.90.CloseOutBulkCol

CloseOutBulkCol

2.90.1.RB-CloseOutBulkCol-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Full*
    - *CREDITLINE*
    - *OTHRPARTYLMTCHK*
    - *MARGINPERC*
    - *FINANCING*
    - *COLLATERAL*
    - *COLLPOOL*
    - *INSTRCODE*
    - *PRODCODE*
    - *CPTYIDEN*
    - *CPACCNO*
    - *CONTCCY*
    - *OTHRPTYIDEN*
    - *DRACCREAL*
    - *BANKCD*
    - *BOOKINGDATE*

PROTEST
TRACKLIMIT
INSTRUMENTDESC
PRODDESC
COUNTERPRTYNAME
OTHERPARTYNAME
BNKNAME
BRNNAME
NOOFINSTRUMENTS
BRNCODE
BATCHREFENUM
ACCBRN
DRACCBRN
PROCESSTAT
VERNUM
CVERNO
CONST
AUTHSTAT
CHKR
CHKDTTIME
MAKER
MAKDTTIME
Bulk-Input-Detail
- *CONTREFNO*
- *INSTRNO*
- *INSTRDATE*
- *AMNT*
- *CONTAMTLCY*
- *MATURITYDATE*
- *DISCAMT*
- *COLLTVAL*
- *INTREMARKS*
- *PROCESSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Full

Attribute	Description
Name	Bulk-Input-Full
Datatype	
Description	

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

OTHRPARTYLMTCHK

Attribute	Description
Name	OTHRPARTYLMTCHK

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,F,N

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRCODE

Attribute	Description
Name	INSTRCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRODCODE

Attribute	Description
Name	PRODCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPACCNO

Attribute	Description
Name	CPACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BANKCD

Attribute	Description
Name	BANKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

INSTRUMENTDESC

Attribute	Description
Name	INSTRUMENTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COUNTERPRTYNAME

Attribute	**Description**	
Name	COUNTERPRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYNAME

Attribute	**Description**	
Name	OTHERPARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BNKNAME

Attribute	**Description**	
Name	BNKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,U</td></tr></table>

TOP

VERNUM

Attribute	Description
Name	VERNUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CVERNO

Attribute	Description
Name	CVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	enumeration	,O,C

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

CHKR

Attribute	Description	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	Description	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

Bulk-Input-Detail

Attribute	Description
Name	Bulk-Input-Detail
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 20

TOP

INSTRDATE

Attribute	Description

Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CONTAMTLCY

Attribute	Description
Name	CONTAMTLCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTVAL

Attribute	Description
Name	COLLTVAL
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U

TOP

2.90.2.RB-CloseOutBulkCol-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Bulk-Input-IO*
  - *BATCHREFENUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.90.3.RB-CloseOutBulkCol-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Full*
    - *CREDITLINE*
    - *OTHRPARTYLMTCHK*
    - *MARGINPERC*
    - *FINANCING*
    - *COLLATERAL*
    - *COLLPOOL*
    - *INSTRCODE*
    - *PRODCODE*
    - *CPTYIDEN*
    - *CPACCNO*
    - *CONTCCY*
    - *OTHRPTYIDEN*
    - *DRACCREAL*
    - *BANKCD*
    - *BOOKINGDATE*
    - *PROTEST*
    - *TRACKLIMIT*
    - *INSTRUMENTDESC*

PRODDESC
COUNTERPRTYNAME
OTHERPARTYNAME
BNKNAME
BRNNAME
NOOFINSTRUMENTS
BRNCODE
BATCHREFENUM
ACCBRN
DRACCBRN
PROCESSTAT
VERNUM
CVERNO
CONST
AUTHSTAT
CHKR
CHKDTTIME
MAKER
MAKDTTIME
Bulk-Input-Detail
CONTREFNO
INSTRNO
INSTRDATE
AMNT
CONTAMTLCY
MATURITYDATE
DISCAMT
COLLTVAL
INTREMARKS
PROCESSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Full

Attribute	Description
Name	Bulk-Input-Full
Datatype	
Description	

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

OTHRPARTYLMTCHK

Attribute	**Description**	
Name	OTHRPARTYLMTCHK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MARGINPERC

Attribute	**Description**	
Name	MARGINPERC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,F,N

TOP

COLLATERAL

Attribute	**Description**	
Name	COLLATERAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,C,T,N

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRCODE

Attribute	Description
Name	INSTRCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRODCODE

Attribute	Description
Name	PRODCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPACCNO

Attribute	Description
Name	CPACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BANKCD

Attribute	Description
Name	BANKCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INSTRUMENTDESC

Attribute	Description
Name	INSTRUMENTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRODDESC

Attribute	**Description**	
Name	PRODDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COUNTERPRTYNAME

Attribute	**Description**	
Name	COUNTERPRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYNAME

Attribute	**Description**	
Name	OTHERPARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BNKNAME

Attribute	**Description**	
Name	BNKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,U

TOP

VERNUM

Attribute	Description
Name	VERNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CVERNO

Attribute	Description
Name	CVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

Bulk-Input-Detail

Attribute	Description
Name	Bulk-Input-Detail
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CONTAMTLCY

Attribute	Description
Name	CONTAMTLCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTVAL

Attribute	Description
Name	COLLTVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.90.4.RB-CloseOutBulkCol-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Input-PK*
      - *BATCHREFENUM*
    - *Bulk-Input-IO*
      - *BATCHREFENUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Input-PK

Attribute	Description
Name	Bulk-Input-PK
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.91.CloseOvsbulkcontract

CloseOvsbulkcontract

2.91.1.RB-CloseOvsbulkcontract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Overseas-Full*
    - *INSTRUMENT_CODE*
    - *INSTR_DESC*
    - *PRODCD*
    - *PRDDESC*
    - *CURRENCY*
    - *COLLECTINGBANKCIF*
    - *CBN_S*
    - *DB_ACC_REAL*
    - *ACCBRN*
    - *BOKNGDT*
    - *PAYDUEDATE*
    - *TRANSITDAYS*
    - *BATCHREFENUM*
    - *COLLBANKCODE*
    - *NOOFINSTRUMENTS*

STAT
ESN_NO
RECORD_STAT
AUTHSTAT
CHKR
CHKDTTIME
MAKER
MAKDTTIME
EVENTSEQNO
Bulk-Input-Overseas-Dtl
- *CONTRACTREFNO*
- *CPTY_ID*
- *CPTY_AC_NO*
- *ACCBRNRE*
- *INSTRNO*
- *INSTRU_DATE*
- *AMNT*
- *LCY_AMT*
- *OTHR_PARTYNAME*
- *DRAWEE_BNK_NAME*
- *AUTOLIQD*
- *FINANCING*
- *MARGIN_PERCENTAGE*
- *TRACK_LIMIT*
- *CREDIT_LINE*
- *DISCAMT*
- *CPTY_NAME*
- *INTREMRKS*
- *BATCHREFNO*
- *BATCHSEQNO*
- *CONTRACTCCY*
- *PROCESS_STATUS*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Overseas-Full

Attribute	Description
Name	Bulk-Input-Overseas-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRODCD

Attribute	Description
Name	PRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLECTINGBANKCIF

Attribute	Description
Name	COLLECTINGBANKCIF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CBN_S

Attribute	**Description**	
Name	CBN_S	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

DB_ACC_REAL

Attribute	**Description**	
Name	DB_ACC_REAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BOKNGDT

Attribute	**Description**	
Name	BOKNGDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

COLLBANKCODE

Attribute	Description
Name	COLLBANKCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STAT

Attribute	**Description**	
Name	STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,U,

TOP

ESN_NO

Attribute	**Description**	
Name	ESN_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,C,

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U,

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bulk-Input-Overseas-Dtl

Attribute	Description
Name	Bulk-Input-Overseas-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCBRNRE

Attribute	Description
Name	ACCBRNRE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHR_PARTYNAME

Attribute	**Description**	
Name	OTHR_PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRAWEE_BNK_NAME

Attribute	**Description**	
Name	DRAWEE_BNK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AUTOLIQD

Attribute	**Description**	
Name	AUTOLIQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,N,F,

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INTREMRKS

Attribute	**Description**	
Name	INTREMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BATCHREFNO

Attribute	**Description**	
Name	BATCHREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BATCHSEQNO

Attribute	**Description**	
Name	BATCHSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTRACTCCY

Attribute	**Description**	
Name	CONTRACTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,H,F,</td></tr></table>

TOP

2.91.2.RB-CloseOvsbulkcontract-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Bulk-Input-Overseas-IO
BATCHREFENUM

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Overseas-IO

Attribute	Description
Name	Bulk-Input-Overseas-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.91.3.RB-CloseOvsbulkcontract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Overseas-Full*
    - *INSTRUMENT_CODE*
    - *INSTR_DESC*
    - *PRODCD*
    - *PRDDESC*
    - *CURRENCY*
    - *COLLECTINGBANKCIF*
    - *CBN_S*
    - *DB_ACC_REAL*
    - *ACCBRN*
    - *BOKNGDT*
    - *PAYDUEDATE*
    - *TRANSITDAYS*
    - *BATCHREFENUM*
    - *COLLBANKCODE*
    - *NOOFINSTRUMENTS*
    - *STAT*
    - *ESN_NO*
    - *RECORD_STAT*

AUTHSTAT
CHKR
CHKDTTIME
MAKER
MAKDTTIME
EVENTSEQNO
Bulk-Input-Overseas-Dtl
CONTRACTREFNO
CPTY_ID
CPTY_AC_NO
ACCBRNRE
INSTRNO
INSTRU_DATE
AMNT
LCY_AMT
OTHR_PARTYNAME
DRAWEE_BNK_NAME
AUTOLIQD
FINANCING
MARGIN_PERCENTAGE
TRACK_LIMIT
CREDIT_LINE
DISCAMT
CPTY_NAME
INTREMRKS
BATCHREFNO
BATCHSEQNO
CONTRACTCCY
PROCESS_STATUS
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Overseas-Full

Attribute	Description
Name	Bulk-Input-Overseas-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTR_DESC

Attribute	**Description**	
Name	INSTR_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

PRODCD

Attribute	**Description**	
Name	PRODCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CURRENCY

Attribute	**Description**	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLECTINGBANKCIF

Attribute	Description
Name	COLLECTINGBANKCIF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CBN_S

Attribute	Description
Name	CBN_S
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COLLBANKCODE

Attribute	Description
Name	COLLBANKCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,U,

TOP

ESN_NO

Attribute	Description
Name	ESN_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,C,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

EVENTSEQNO

Attribute	**Description**	
Name	EVENTSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Bulk-Input-Overseas-Dtl

Attribute	**Description**	
Name	Bulk-Input-Overseas-Dtl	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

CONTRACTREFNO

Attribute	**Description**	
Name	CONTRACTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	**Description**	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRNRE

Attribute	Description
Name	ACCBRNRE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F,

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BATCHREFNO

Attribute	Description
Name	BATCHREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,H,F,

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.91.4.RB-CloseOvsbulkcontract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Input-Overseas-PK*
      - *BATCHREFENUM*
    - *Bulk-Input-Overseas-IO*
      - *BATCHREFENUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Input-Overseas-PK

Attribute	Description
Name	Bulk-Input-Overseas-PK
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Input-Overseas-IO

Attribute	Description
Name	Bulk-Input-Overseas-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.92.CloseOvsbulkrealize

CloseOvsbulkrealize

2.92.1.RB-CloseOvsbulkrealize-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Liqd-Overseas-Full*
    - *BATCHREFENUM*
    - *BULK_REAL_NUM*
    - *CURRENCY*
    - *DB_ACC_REAL*
    - *ACCBRN*
    - *COLBANK_REFNO*
    - *COLL_BNK_CIF*
    - *COLLBNKNAME*
    - *VALUEDATE*
    - *PROCSTAT*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *CHKR*
    - *CHKDTTIME*
    - *ESN_NO*

MAKER
MAKDTTIME
EVENTSEQNO
Bulk-Liqd-Overseas-Dtl
CONTRACTREFNO
CPTY_ID
CPTY_NAME
CPTY_AC_NO
ACCBRNRE
INSTRNO
INSTRU_DATE
AMNT
NET_AMT_REALISED
OTHER_BANK_CHARGES
INTREMRKS
PROCESSSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Liqd-Overseas-Full

Attribute	Description
Name	Bulk-Liqd-Overseas-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BULK_REAL_NUM

Attribute	Description
Name	BULK_REAL_NUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLBANK_REFNO

Attribute	Description
Name	COLBANK_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

PROCSTAT

Attribute	Description
Name	PROCSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,U,</td></tr></table>

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>O,C,</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U,

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ESN_NO

Attribute	**Description**	
Name	ESN_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

Bulk-Liqd-Overseas-Dtl

Attribute	Description
Name	Bulk-Liqd-Overseas-Dtl
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRNRE

Attribute	Description
Name	ACCBRNRE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,H,F,</td></tr></table>

TOP

2.92.2.RB-CloseOvsbulkrealize-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Liqd-Overseas-IO*
    - *BULK_REAL_NUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Liqd-Overseas-IO

Attribute	Description
Name	Bulk-Liqd-Overseas-IO
Datatype	
Description	

TOP

BULK_REAL_NUM

Attribute	Description
Name	BULK_REAL_NUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.92.3.RB-CloseOvsbulkrealize-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Liqd-Overseas-Full*
    - *BATCHREFENUM*
    - *BULK_REAL_NUM*
    - *CURRENCY*
    - *DB_ACC_REAL*
    - *ACCBRN*
    - *COLBANK_REFNO*
    - *COLL_BNK_CIF*
    - *COLLBNKNAME*
    - *VALUEDATE*
    - *PROCSTAT*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *CHKR*
    - *CHKDTTIME*
    - *ESN_NO*
    - *MAKER*
    - *MAKDTTIME*
    - *EVENTSEQNO*

Bulk-Liqd-Overseas-Dtl

CONTRACTREFNO

CPTY_ID

CPTY_NAME

CPTY_AC_NO

ACCBRNRE

INSTRNO

INSTRU_DATE

AMNT

NET_AMT_REALISED

OTHER_BANK_CHARGES

INTREMRKS

PROCESSSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Liqd-Overseas-Full

Attribute	Description
Name	Bulk-Liqd-Overseas-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BULK_REAL_NUM

Attribute	Description
Name	BULK_REAL_NUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CURRENCY

Attribute	Description

Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLBANK_REFNO

Attribute	Description
Name	COLBANK_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

COLLBNKNAME

Attribute	**Description**	
Name	COLLBNKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

VALUEDATE

Attribute	**Description**	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

PROCSTAT

Attribute	**Description**	
Name	PROCSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,U,

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,C,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ESN_NO

Attribute	Description
Name	ESN_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bulk-Liqd-Overseas-Dtl

Attribute	Description
Name	Bulk-Liqd-Overseas-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY_ID

Attribute	Description	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_NAME

Attribute	Description	
Name	CPTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTY_AC_NO

Attribute	Description	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCBRNRE

Attribute	Description	
Name	ACCBRNRE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,H,F,</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.92.4.RB-CloseOvsbulkrealize-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Liqd-Overseas-PK*
      - *BULK_REAL_NUM*
    - *Bulk-Liqd-Overseas-IO*
      - *BULK_REAL_NUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Liqd-Overseas-PK

Attribute	Description
Name	Bulk-Liqd-Overseas-PK
Datatype	
Description	

TOP

BULK_REAL_NUM

Attribute	Description
Name	BULK_REAL_NUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Liqd-Overseas-IO

Attribute	Description
Name	Bulk-Liqd-Overseas-IO
Datatype	
Description	

TOP

BULK_REAL_NUM

Attribute	Description
Name	BULK_REAL_NUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.93.CreateBulkInwardInput

CreateBulkInwardInput

2.93.1.RB-CreateBulkInwardInput-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Full*
    - *INSTRUMENT_CODE*
    - *BATCHREFENUM*
    - *PRDCD*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *ACCBRN*
    - *CPTY_AC_NO*
    - *OTHRPTY_ID*
    - *OTHRPTY_NM*
    - *BNKCD*
    - *BRNCODE*
    - *CORRESPBNK*
    - *CORRESPACNO*
    - *BOKNGDT*
    - *PROTEST*

AUTOLIQD
NOOFINSTRUMENTS
ACFORREALISATION
CRACCBRN
CCY
PROCESSSTAT
EVENTSEQNO
ESNLOG
RECORDSTAT
AUTHSTAT
CHKR
CHKDTTIME
BULKREF
MAKER
MAKDTTIME
Bulkinput-Detail
- *CONREFNUM*
- *INSTRNO*
- *INSTRU_DATE*
- *CURRENCY*
- *AMNT*
- *REMITBANK_REF*
- *REM_BNK_DT*
- *LCY_AMOUNTT*
- *MATURITYDATE*
- *GRACEDAYS*
- *REMARKS*
- *PROCESSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Full

Attribute	Description
Name	Bulk-Input-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRDCD

Attribute	**Description**	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CPTY_ID

Attribute	**Description**	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_NAME

Attribute	**Description**	
Name	CPTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CPTY_AC_NO

Attribute	**Description**	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

OTHRPTY_ID

Attribute	**Description**	
Name	OTHRPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OTHRPTY_NM

Attribute	**Description**	
Name	OTHRPTY_NM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BNKCD

Attribute	**Description**	
Name	BNKCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CORRESPBNK

Attribute	Description
Name	CORRESPBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CORRESPACNO

Attribute	Description
Name	CORRESPACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRACCBRN

Attribute	Description
Name	CRACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESNLOG

Attribute	Description
Name	ESNLOG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BULKREF

Attribute	Description
Name	BULKREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	**Description**	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Bulkinput-Detail

Attribute	**Description**	
Name	Bulkinput-Detail	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CONREFNUM

Attribute	**Description**	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

REM_BNK_DT

Attribute	Description
Name	REM_BNK_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCY_AMOUNTT

Attribute	Description
Name	LCY_AMOUNTT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,S,U,F,H</td></tr></table>

TOP

2.93.2.RB-CreateBulkInwardInput-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-IO*
    - *INSTRUMENT_CODE*
    - *BATCHREFENUM*
    - *PRDCD*
    - *CPTY_ID*
    - *CPTY_AC_NO*
    - *OTHRPTY_ID*
    - *BNKCD*
    - *CORRESPBNK*
    - *CORRESPACNO*
    - *PROTEST*
    - *AUTOLIQD*
    - *NOOFINSTRUMENTS*
    - *ACFORREALISATION*
    - *CCY*
    - *BULKREF*
    - *Bulkinput-Detail*
      - *INSTRNO*
      - *INSTRU_DATE*

CURRENCY
AMNT
REMITBANK_REF
REM_BNK_DT
MATURITYDATE
GRACEDAYS
REMARKS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_AC_NO

Attribute	**Description**	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

OTHRPTY_ID

Attribute	**Description**	
Name	OTHRPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BNKCD

Attribute	**Description**	
Name	BNKCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CORRESPBNK

Attribute	**Description**	
Name	CORRESPBNK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CORRESPACNO

Attribute	Description
Name	CORRESPACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

BULKREF

Attribute	Description
Name	BULKREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulkinput-Detail

Attribute	Description
Name	Bulkinput-Detail
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REM_BNK_DT

Attribute	Description
Name	REM_BNK_DT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

2.93.3.RB-CreateBulkInwardInput-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Full*
    - *INSTRUMENT_CODE*
    - *BATCHREFENUM*
    - *PRDCD*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *ACCBRN*
    - *CPTY_AC_NO*
    - *OTHRPTY_ID*
    - *OTHRPTY_NM*
    - *BNKCD*
    - *BRNCODE*
    - *CORRESPBNK*
    - *CORRESPACNO*
    - *BOKNGDT*
    - *PROTEST*
    - *AUTOLIQD*
    - *NOOFINSTRUMENTS*
    - *ACFORREALISATION*

CRACCBRN
CCY
PROCESSSTAT
EVENTSEQNO
ESNLOG
RECORDSTAT
AUTHSTAT
CHKR
CHKDTTIME
BULKREF
MAKER
MAKDTTIME
Bulkinput-Detail
CONREFNUM
INSTRNO
INSTRU_DATE
CURRENCY
AMNT
REMITBANK_REF
REM_BNK_DT
LCY_AMOUNTT
MATURITYDATE
GRACEDAYS
REMARKS
PROCESSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Full

Attribute	Description
Name	Bulk-Input-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CPTY_AC_NO

Attribute	**Description**	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

OTHRPTY_ID

Attribute	**Description**	
Name	OTHRPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OTHRPTY_NM

Attribute	**Description**	
Name	OTHRPTY_NM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BNKCD

Attribute	**Description**	
Name	BNKCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CORRESPBNK

Attribute	Description
Name	CORRESPBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CORRESPACNO

Attribute	Description
Name	CORRESPACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CRACCBRN

Attribute	Description
Name	CRACCBRN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PROCESSSTAT

Attribute	**Description**	
Name	PROCESSSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,U

TOP

EVENTSEQNO

Attribute	**Description**	
Name	EVENTSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ESNLOG

Attribute	**Description**	
Name	ESNLOG	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,O,C</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BULKREF

Attribute	Description
Name	BULKREF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Bulkinput-Detail

Attribute	Description
Name	Bulkinput-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REM_BNK_DT

Attribute	Description
Name	REM_BNK_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCY_AMOUNTT

Attribute	Description
Name	LCY_AMOUNTT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,U,F,H

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description

Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.93.4.RB-CreateBulkInwardInput-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Input-PK*
      - *BATCHREFENUM*
    - *Bulk-Input-IO*
      - *INSTRUMENT_CODE*
      - *BATCHREFENUM*
      - *PRDCD*
      - *CPTY_ID*
      - *CPTY_AC_NO*
      - *OTHRPTY_ID*
      - *BNKCD*
      - *CORRESPBNK*
      - *CORRESPACNO*
      - *PROTEST*
      - *AUTOLIQD*
      - *NOOFINSTRUMENTS*
      - *ACFORREALISATION*
      - *CCY*
      - *BULKREF*

Bulkinput-Detail

INSTRNO

INSTRU_DATE

CURRENCY

AMNT

REMITBANK_REF

REM_BNK_DT

MATURITYDATE

GRACEDAYS

REMARKS

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Input-PK

Attribute	Description
Name	Bulk-Input-PK
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BATCHREFENUM

Attribute	**Description**	
Name	BATCHREFENUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRDCD

Attribute	**Description**	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CPTY_ID

Attribute	**Description**	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_AC_NO

Attribute	**Description**	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

OTHRPTY_ID

Attribute	Description
Name	OTHRPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CORRESPBNK

Attribute	Description
Name	CORRESPBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CORRESPACNO

Attribute	Description
Name	CORRESPACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CCY

Attribute	Description
Name	CCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BULKREF

Attribute	Description
Name	BULKREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Bulkinput-Detail

Attribute	Description
Name	Bulkinput-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REM_BNK_DT

Attribute	Description
Name	REM_BNK_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String

Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.94.CreateBulkInwardPDR

CreateBulkInwardPDR

2.94.1.RB-CreateBulkInwardPDR-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Pdr-Full*
    - *BATCHREFENUM*
    - *BULKPDRREFNO*
    - *ACTION*
    - *PRDTY*
    - *CPTY_ID*
    - *COUNTRPRYNAM*
    - *OTHRPTY_ID*
    - *OTHRPTY_NM*
    - *BANK_CODE*
    - *BANK_NAME*
    - *BRNCODE*
    - *BRANCH_NAME*
    - *VALUEDT*
    - *RETURN_DATE*
    - *PROCESSSTAT*

SEQNO
ESN
TXNSTAT
AUTHSTAT
CHKR
CHKDTTIME
MKRID
MKRDT
Bulk-Pdr-Detail
- *CONREFNUM*
- *INSTRNO*
- *INSTRUMENT_DATE*
- *REMITBANK_REF*
- *CCY*
- *AMT*
- *REASON_CODE*
- *DISHONOUR_DATE*
- *NOTARYCODE*
- *PROTESTDATE*
- *REMARKS*
- *PROCESSSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Pdr-Full

Attribute	Description
Name	Bulk-Pdr-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

PRDTY

Attribute	Description
Name	PRDTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHRPTY_ID

Attribute	Description
Name	OTHRPTY_ID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OTHRPTY_NM

Attribute	**Description**	
Name	OTHRPTY_NM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BANK_CODE

Attribute	**Description**	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANK_NAME

Attribute	**Description**	
Name	BANK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNCODE

Attribute	**Description**	
Name	BRNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRANCH_NAME

Attribute	Description
Name	BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,P

TOP

SEQNO

Attribute	Description
Name	SEQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MKRID

Attribute	Description
Name	MKRID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MKRDT

Attribute	Description
Name	MKRDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Bulk-Pdr-Detail

Attribute	Description
Name	Bulk-Pdr-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description

Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DISHONOUR_DATE

Attribute	Description
Name	DISHONOUR_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,P

TOP

2.94.2.RB-CreateBulkInwardPDR-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Pdr-IO*
    - *BATCHREFENUM*
    - *BULKPDRREFNO*
    - *ACTION*
    - *PRDTY*
    - *VALUEDT*
    - *RETURN_DATE*
    - *Bulk-Pdr-Detail*
      - *REASON_CODE*
      - *DISHONOUR_DATE*
      - *NOTARYCODE*
      - *PROTESTDATE*
      - *REMARKS*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Pdr-IO

Attribute	Description
Name	Bulk-Pdr-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

PRDTY

Attribute	Description
Name	PRDTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bulk-Pdr-Detail

Attribute	Description
Name	Bulk-Pdr-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DISHONOUR_DATE

Attribute	Description
Name	DISHONOUR_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

2.94.3.RB-CreateBulkInwardPDR-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Pdr-Full*
    - *BATCHREFENUM*
    - *BULKPDRREFNO*
    - *ACTION*
    - *PRDTY*
    - *CPTY_ID*
    - *COUNTRPRYNAM*
    - *OTHRPTY_ID*
    - *OTHRPTY_NM*
    - *BANK_CODE*
    - *BANK_NAME*
    - *BRNCODE*
    - *BRANCH_NAME*
    - *VALUEDT*
    - *RETURN_DATE*
    - *PROCESSSTAT*
    - *SEQNO*
    - *ESN*
    - *TXNSTAT*

AUTHSTAT
CHKR
CHKDTTIME
MKRID
MKRDT
Bulk-Pdr-Detail
CONREFNUM
INSTRNO
INSTRUMENT_DATE
REMITBANK_REF
CCY
AMT
REASON_CODE
DISHONOUR_DATE
NOTARYCODE
PROTESTDATE
REMARKS
PROCESSSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Pdr-Full

Attribute	Description
Name	Bulk-Pdr-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

PRDTY

Attribute	Description
Name	PRDTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHRPTY_ID

Attribute	Description
Name	OTHRPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

OTHRPTY_NM

Attribute	Description
Name	OTHRPTY_NM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BANK_CODE

Attribute	Description
Name	BANK_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BANK_NAME

Attribute	Description
Name	BANK_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BRNCODE

Attribute	Description
Name	BRNCODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRANCH_NAME

Attribute	Description
Name	BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,P

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MKRID

Attribute	Description
Name	MKRID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MKRDT

Attribute	Description
Name	MKRDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Bulk-Pdr-Detail

Attribute	Description
Name	Bulk-Pdr-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CCY

Attribute	Description
Name	CCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DISHONOUR_DATE

Attribute	Description
Name	DISHONOUR_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: U,P

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.94.4.RB-CreateBulkInwardPDR-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Pdr-PK*
      - *BULKPDRREFNO*
    - *Bulk-Pdr-IO*
      - *BATCHREFENUM*
      - *BULKPDRREFNO*
      - *ACTION*
      - *PRDTY*
      - *VALUEDT*
      - *RETURN_DATE*
      - *Bulk-Pdr-Detail*
        - *REASON_CODE*
        - *DISHONOUR_DATE*
        - *NOTARYCODE*
        - *PROTESTDATE*
        - *REMARKS*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Bulk-Pdr-PK

Attribute	Description
Name	Bulk-Pdr-PK
Datatype	
Description	

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

Bulk-Pdr-IO

Attribute	Description
Name	Bulk-Pdr-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

PRDTY

Attribute	Description
Name	PRDTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bulk-Pdr-Detail

Attribute	Description
Name	Bulk-Pdr-Detail

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DISHONOUR_DATE

Attribute	Description
Name	DISHONOUR_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description

Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.95.CreateBulkInwardReal

CreateBulkInwardReal

2.95.1.RB-CreateBulkInwardReal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liq-Master-Full*
    - *BATCHREFENUM*
    - *BULKREALNUM*
    - *CPTY_ID*
    - *DUP_CPTY_NAME*
    - *CCY*
    - *OTHRPTY_ID*
    - *OTHRPTY_NM*
    - *BNKCD*
    - *BANK_NAME*
    - *BRNCODE*
    - *BRNNAME*
    - *CPTY_AC_NO*
    - *ACFORREALISATION*
    - *CRACCBRN*
    - *VALUEDATE*

ACCBRN
CORRESPBNK
CORRESPACNO
NETAMT_REAL
PROCESSSTAT
EVENTSEQNO
RECORDSTAT
AUTHSTAT
CKRID
CHKDTTIME
BULKREF
ESN
MAKER
MAKDTTIME
Liq-Detail
- *CONREFNUM*
- *INSTRNO*
- *INSTRUMENT_DATE*
- *REMITBANK_REF*
- *REM_BNK_DT*
- *AMNT*
- *REMRKS*
- *PROCESSSTAT*
- *OTHRBNKCHARGS*
- *NETAMT_REAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liq-Master-Full

Attribute	Description
Name	Liq-Master-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

DUP_CPTY_NAME

Attribute	Description	
Name	DUP_CPTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

OTHRPTY_ID

Attribute	Description	
Name	OTHRPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OTHRPTY_NM

Attribute	Description
Name	OTHRPTY_NM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BANK_NAME

Attribute	Description
Name	BANK_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BRNNAME

Attribute	Description
Name	BRNNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRACCBRN

Attribute	Description
Name	CRACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CORRESPBNK

Attribute	**Description**	
Name	CORRESPBNK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CORRESPACNO

Attribute	**Description**	
Name	CORRESPACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

NETAMT_REAL

Attribute	**Description**	
Name	NETAMT_REAL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,P</td></tr></table>

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,O,C</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

CKRID

Attribute	Description
Name	CKRID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BULKREF

Attribute	**Description**	
Name	BULKREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	Description	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Liq-Detail

Attribute	Description	
Name	Liq-Detail	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CONREFNUM

Attribute	Description	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INSTRNO

Attribute	Description	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRUMENT_DATE

Attribute	Description

Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REM_BNK_DT

Attribute	Description
Name	REM_BNK_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,P</td></tr></table>

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NETAMT_REAL

Attribute	Description
Name	NETAMT_REAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liq-Master-IO*
    - *BATCHREFENUM*
    - *BULKREALNUM*
    - *CPTY_AC_NO*
    - *ACFORREALISATION*
    - *VALUEDATE*
    - *CORRESPBNK*
    - *CORRESPACNO*
    - *BULKREF*
    - *Liq-Detail*
      - *REMRKS*
      - *OTHRBNKCHARGS*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liq-Master-IO

Attribute	Description
Name	Liq-Master-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BULKREALNUM

Attribute	**Description**	
Name	BULKREALNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_AC_NO

Attribute	**Description**	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACFORREALISATION

Attribute	**Description**	
Name	ACFORREALISATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

VALUEDATE

Attribute	**Description**	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

CORRESPBNK

Attribute	Description	
Name	CORRESPBNK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CORRESPACNO

Attribute	Description	
Name	CORRESPACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BULKREF

Attribute	Description	
Name	BULKREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Liq-Detail

Attribute	Description	
Name	Liq-Detail	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

REMRKS

Attribute	Description

Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.95.3.RB-CreateBulkInwardReal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liq-Master-Full*
    - *BATCHREFENUM*
    - *BULKREALNUM*
    - *CPTY_ID*
    - *DUP_CPTY_NAME*
    - *CCY*
    - *OTHRPTY_ID*
    - *OTHRPTY_NM*
    - *BNKCD*
    - *BANK_NAME*
    - *BRNCODE*
    - *BRNNAME*
    - *CPTY_AC_NO*
    - *ACFORREALISATION*
    - *CRACCBRN*
    - *VALUEDATE*
    - *ACCBRN*
    - *CORRESPBNK*
    - *CORRESPACNO*

NETAMT_REAL
PROCESSSTAT
EVENTSEQNO
RECORDSTAT
AUTHSTAT
CKRID
CHKDTTIME
BULKREF
ESN
MAKER
MAKDTTIME
Liq-Detail
CONREFNUM
INSTRNO
INSTRUMENT_DATE
REMITBANK_REF
REM_BNK_DT
AMNT
REMRKS
PROCESSSTAT
OTHRBNKCHARGS
NETAMT_REAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liq-Master-Full

Attribute	Description
Name	Liq-Master-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DUP_CPTY_NAME

Attribute	Description
Name	DUP_CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OTHRPTY_ID

Attribute	Description
Name	OTHRPTY_ID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OTHRPTY_NM

Attribute	Description
Name	OTHRPTY_NM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANK_NAME

Attribute	Description
Name	BANK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTY_AC_NO

Attribute	**Description**	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACFORREALISATION

Attribute	**Description**	
Name	ACFORREALISATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CRACCBRN

Attribute	**Description**	
Name	CRACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CORRESPBNK

Attribute	Description
Name	CORRESPBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CORRESPACNO

Attribute	Description
Name	CORRESPACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

NETAMT_REAL

Attribute	Description
Name	NETAMT_REAL

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,P

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CKRID

Attribute	Description
Name	CKRID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BULKREF

Attribute	Description
Name	BULKREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Liq-Detail

Attribute	Description
Name	Liq-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

REM_BNK_DT

Attribute	Description
Name	REM_BNK_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,P

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETAMT_REAL

Attribute	Description
Name	NETAMT_REAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description

Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.95.4.RB-CreateBulkInwardReal-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Liq-Master-PK*
      - *BULKREALNUM*
    - *Liq-Master-IO*
      - *BATCHREFENUM*
      - *BULKREALNUM*
      - *CPTY_AC_NO*
      - *ACFORREALISATION*
      - *VALUEDATE*
      - *CORRESPBNK*
      - *CORRESPACNO*
      - *BULKREF*
      - *Liq-Detail*
        - *REMRKS*
        - *OTHRBNKCHARGS*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Liq-Master-PK

Attribute	Description
Name	Liq-Master-PK
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Liq-Master-IO

Attribute	Description
Name	Liq-Master-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CORRESPBNK

Attribute	Description
Name	CORRESPBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CORRESPACNO

Attribute	Description
Name	CORRESPACNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BULKREF

Attribute	Description
Name	BULKREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Liq-Detail

Attribute	Description
Name	Liq-Detail
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.96.CreateBulkOutClearing

CreateBulkOutClearing

2.96.1.RB-CreateBulkOutClearing-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Full*
    - *CRDLINE*
    - *OTHPARTYLIMIT*
    - *MARGINPERC*
    - *FINANCING*
    - *COLLATERAL*
    - *COLLPOOL*
    - *INSTRUCODE*
    - *PRDCODE*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *CURRENCY*
    - *OTHRPTYIDEN*
    - *DRACCREAL*
    - *NOOFINSTRUMENTS*
    - *CLGPRD*

ISRBNK
ISSUERBRN
CLRBNK
CLGBRN
SECTORCR
ENDPOINT
ROUTNO
CHECKINSERIES
FIRSTINSTRNO
BOOKINGDATE
TRACKLIMIT
INSTRUMENT_DESCRIPTION
INSTRDESC
COUNTRPRYNAM
OTHERPARTYNAME
ISSBANKNAME
ISSBRNCNAME
CLEARBANKNAME
CLEARBRNCNAME
BATCHREFENUM
ACCBRN
PROCESSTAT
CONTSTATUS
AUTSTAT
CHECKER
CHECKERDT
VERSIONNUM
MKER
MAKERDT
DRACCBRN
VERNUMBER
Input-Detail
- *CONREFNUM*
- *INSTRNO*
- *INSTRDATE*
- *LCYAMT*
- *AMNT*
- *VALUEDATE*
- *DISCAMT*
- *COLLTVAL*
- *INTREMRKS*
- *PROCESSSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Full

Attribute	Description
Name	Bulk-Input-Full
Datatype	
Description	

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,F,N</td></tr></table>

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CLGPRD

Attribute	Description
Name	CLGPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ISRBNK

Attribute	Description
Name	ISRBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ISSUERBRN

Attribute	Description
Name	ISSUERBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CLRBNK

Attribute	Description
Name	CLRBNK

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBRN

Attribute	Description
Name	CLGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SECTORCR

Attribute	Description
Name	SECTORCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

CHECKINSERIES

Attribute	Description
Name	CHECKINSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FIRSTINSTRNO

Attribute	Description
Name	FIRSTINSTRNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description
Name	INSTRUMENT_DESCRIPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

INSTRDESC

Attribute	Description
Name	INSTRDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ISSBANKNAME

Attribute	Description
Name	ISSBANKNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSBRNCNAME

Attribute	Description
Name	ISSBRNCNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CLEARBANKNAME

Attribute	Description
Name	CLEARBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CLEARBRNCNAME

Attribute	Description
Name	CLEARBRNCNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PROCESSTAT

Attribute	**Description**	
Name	PROCESSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,E

TOP

CONTSTATUS

Attribute	**Description**	
Name	CONTSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,O,C

TOP

AUTSTAT

Attribute	**Description**	
Name	AUTSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDT

Attribute	Description	
Name	CHECKERDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

VERSIONNUM

Attribute	Description	
Name	VERSIONNUM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MKER

Attribute	Description	
Name	MKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VERNUMBER

Attribute	Description
Name	VERNUMBER
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Input-Detail

Attribute	Description
Name	Input-Detail
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTVAL

Attribute	Description
Name	COLLTVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,F,H

TOP

2.96.2.RB-CreateBulkOutClearing-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-IO*
    - *CRDLINE*
    - *OTHPARTYLIMIT*
    - *MARGINPERC*
    - *FINANCING*
    - *COLLATERAL*
    - *COLLPOOL*
    - *INSTRUCODE*
    - *PRDCODE*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *CURRENCY*
    - *OTHRPTYIDEN*
    - *NOOFINSTRUMENTS*
    - *CLGPRD*
    - *ISRBNK*
    - *ISSUERBRN*
    - *ENDPOINT*
    - *ROUTNO*

CHECKINSERIES

FIRSTINSTRNO

TRACKLIMIT

BATCHREFENUM

Input-Detail

INSTRNO

INSTRDATE

AMNT

INTREMRKS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / E,F,N

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,C,T,N

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 20

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 3

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 9

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

CLGPRD

Attribute	Description
Name	CLGPRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ISRBNK

Attribute	Description
Name	ISRBNK
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ISSUERBRN

Attribute	Description
Name	ISSUERBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

CHECKINSERIES

Attribute	Description
Name	CHECKINSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FIRSTINSTRNO

Attribute	Description
Name	FIRSTINSTRNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Input-Detail

Attribute	Description
Name	Input-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

2.96.3.RB-CreateBulkOutClearing-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Full*
    - *CRDLINE*
    - *OTHPARTYLIMIT*
    - *MARGINPERC*
    - *FINANCING*
    - *COLLATERAL*
    - *COLLPOOL*
    - *INSTRUCODE*
    - *PRDCODE*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *CURRENCY*
    - *OTHRPTYIDEN*
    - *DRACCREAL*
    - *NOOFINSTRUMENTS*
    - *CLGPRD*
    - *ISRBNK*
    - *ISSUERBRN*
    - *CLRBNK*

- CLGBRN
- SECTORCR
- ENDPOINT
- ROUTNO
- CHECKINSERIES
- FIRSTINSTRNO
- BOOKINGDATE
- TRACKLIMIT
- INSTRUMENT_DESCRIPTION
- INSTRDESC
- COUNTRPRYNAM
- OTHERPARTYNAME
- ISSBANKNAME
- ISSBRNCNAME
- CLEARBANKNAME
- CLEARBRNCNAME
- BATCHREFENUM
- ACCBRN
- PROCESSTAT
- CONTSTATUS
- AUTSTAT
- CHECKER
- CHECKERDT
- VERSIONNUM
- MKER
- MAKERDT
- DRACCBRN
- VERNUMBER
- Input-Detail
  - CONREFNUM
  - INSTRNO
  - INSTRDATE
  - LCYAMT
  - AMNT
  - VALUEDATE
  - DISCAMT
  - COLLTVAL
  - INTREMRKS
  - PROCESSSTAT
- FCUBS_ERROR_RESP
  - ERROR
    - ECODE
    - EDESC
- FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Full

Attribute	Description

Name	Bulk-Input-Full
Datatype	
Description	

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,F,N

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTYIDEN

Attribute	Description

Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

NOOFINSTRUMENTS

Attribute	**Description**	
Name	NOOFINSTRUMENTS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

CLGPRD

Attribute	**Description**	
Name	CLGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ISRBNK

Attribute	**Description**	
Name	ISRBNK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ISSUERBRN

Attribute	**Description**	
Name	ISSUERBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CLRBNK

Attribute	Description
Name	CLRBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBRN

Attribute	Description
Name	CLGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SECTORCR

Attribute	Description
Name	SECTORCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>27</td></tr></table>

TOP

CHECKINSERIES

Attribute	Description
Name	CHECKINSERIES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

FIRSTINSTRNO

Attribute	Description
Name	FIRSTINSTRNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description	
Name	INSTRUMENT_DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INSTRDESC

Attribute	Description	
Name	INSTRDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

OTHERPARTYNAME

Attribute	Description	
Name	OTHERPARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ISSBANKNAME

Attribute	Description
Name	ISSBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSBRNCNAME

Attribute	Description
Name	ISSBRNCNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CLEARBANKNAME

Attribute	Description
Name	CLEARBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CLEARBRNCNAME

Attribute	Description
Name	CLEARBRNCNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,E</td></tr></table>

TOP

CONTSTATUS

Attribute	Description
Name	CONTSTATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,O,C</td></tr></table>

TOP

AUTSTAT

Attribute	Description
Name	AUTSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDT

Attribute	Description
Name	CHECKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VERSIONNUM

Attribute	Description
Name	VERSIONNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MKER

Attribute	Description
Name	MKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

VERNUMBER

Attribute	Description
Name	VERNUMBER
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Input-Detail

Attribute	Description
Name	Input-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description

Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTVAL

Attribute	Description
Name	COLLTVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,S,F,H

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.96.4.RB-CreateBulkOutClearing-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Input-PK*
      - *BATCHREFENUM*
    - *Bulk-Input-IO*
      - *CRDLINE*
      - *OTHPARTYLIMIT*
      - *MARGINPERC*
      - *FINANCING*
      - *COLLATERAL*
      - *COLLPOOL*
      - *INSTRUCODE*
      - *PRDCODE*
      - *CPTYIDEN*
      - *CPTYACCNUM*
      - *CURRENCY*
      - *OTHRPTYIDEN*
      - *NOOFINSTRUMENTS*
      - *CLGPRD*
      - *ISRBNK*

ISSUERBRN
ENDPOINT
ROUTNO
CHECKINSERIES
FIRSTINSTRNO
TRACKLIMIT
BATCHREFENUM
Input-Detail
INSTRNO
INSTRDATE
AMNT
INTREMRKS
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Input-PK

Attribute	Description
Name	Bulk-Input-PK
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,F,N

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CLGPRD

Attribute	Description
Name	CLGPRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ISRBNK

Attribute	Description
Name	ISRBNK
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ISSUERBRN

Attribute	Description
Name	ISSUERBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

ROUTNO

Attribute	Description
Name	ROUTNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 27

TOP

CHECKINSERIES

Attribute	Description
Name	CHECKINSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FIRSTINSTRNO

Attribute	Description
Name	FIRSTINSTRNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Input-Detail

Attribute	Description
Name	Input-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.97.CreateBulkPDRContract

CreateBulkPDRContract

2.97.1.RB-CreateBulkPDRContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulkpdr-Full*
    - *BANK_CODE*
    - *BRNCODE*
    - *BANKNAME*
    - *BRNNAME*
    - *ACTION*
    - *DISPATCHLOTREFNO*
    - *BULKPDRREFNO*
    - *PROCESSTAT*
    - *AUTHSTAT*
    - *CHKR*
    - *CHKDTTIME*
    - *EVSEQNO*
    - *MAKER*
    - *MAKDTTIME*
    - *RECORDSTAT*

ESNUI

Bulkpdrdetail

CONREFNUM

ACC_CCY

AMNT

DISHONOUR_DATE

NOTARYCODE

PROTESTDATE

INTREMRKS

DISHONOUR_REASON

RETURN_DATE

CPTYIDEN

OTHRPTYIDEN

CPTYNAME

OTHERPARTYNAME

INSTRNO

PROCESSSTAT

PRDTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulkpdr-Full

Attribute	Description
Name	Bulkpdr-Full
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description	Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BRNCODE

Attribute	Description	
Name	BRNCODE	
Datatype	String	
Description	Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BANKNAME

Attribute	Description	
Name	BANKNAME	
Datatype	String	
Description	Bank Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

DISPATCHLOTREFNO

Attribute	**Description**	
Name	DISPATCHLOTREFNO	
Datatype	String	
Description	Dispatch Lot Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BULKPDRREFNO

Attribute	**Description**	
Name	BULKPDRREFNO	
Datatype	String	
Description	Bulk Dishonor / Protest / Return Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,U

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	Checker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	Date Time
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EVSEQNO

Attribute	Description
Name	EVSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	Date Time
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	Record Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,O,C</td></tr></table>

TOP

ESNUI

Attribute	Description
Name	ESNUI
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Bulkpdrdetail

Attribute	**Description**	
Name	Bulkpdrdetail	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CONREFNUM

Attribute	**Description**	
Name	CONREFNUM	
Datatype	String	
Description	Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ACC_CCY

Attribute	**Description**	
Name	ACC_CCY	
Datatype	String	
Description	Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNT

Attribute	**Description**	
Name	AMNT	
Datatype	Number	
Description	Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISHONOUR_DATE

Attribute	**Description**

Name	DISHONOUR_DATE
Datatype	Date
Description	Dishonour Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	Notary Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	Protest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Internal Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DISHONOUR_REASON

Attribute	Description
Name	DISHONOUR_REASON
Datatype	String
Description	Dishonor Reason
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	Return Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	CounterParty Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	Other Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	CounterParty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME

Datatype	String
Description	Other Party Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	Instrument Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,H,S,F

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Product Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

2.97.2.RB-CreateBulkPDRContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulkpdr-IO*
    - *ACTION*
    - *DISPATCHLOTREFNO*
    - *BULKPDRREFNO*
    - *AUTHSTAT*
    - *CHKR*
    - *CHKDTTIME*
    - *MAKER*
    - *MAKDTTIME*
    - *RECORDSTAT*
    - *Bulkpdrdetail*
      - *DISHONOUR_DATE*
      - *NOTARYCODE*
      - *PROTESTDATE*
      - *INTREMRKS*
      - *DISHONOUR_REASON*
      - *RETURN_DATE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulkpdr-IO

Attribute	Description
Name	Bulkpdr-IO
Datatype	
Description	

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

DISPATCHLOTREFNO

Attribute	Description
Name	DISPATCHLOTREFNO
Datatype	String
Description	Dispatch Lot Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	Bulk Dishonor / Protest / Return Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHKR

Attribute	Description

Name	CHKR
Datatype	String
Description	Checker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	Date Time
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	Date Time
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	Record Status

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,O,C

TOP

Bulkpdrdetail

Attribute	**Description**	
Name	Bulkpdrdetail	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

DISHONOUR_DATE

Attribute	**Description**	
Name	DISHONOUR_DATE	
Datatype	Date	
Description	Dishonour Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NOTARYCODE

Attribute	**Description**	
Name	NOTARYCODE	
Datatype	String	
Description	Notary Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

PROTESTDATE

Attribute	**Description**	
Name	PROTESTDATE	
Datatype	Date	
Description	Protest Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTREMRKS

Attribute	**Description**

Name	INTREMRKS
Datatype	String
Description	Internal Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DISHONOUR_REASON

Attribute	Description
Name	DISHONOUR_REASON
Datatype	String
Description	Dishonor Reason
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	Return Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.97.3.RB-CreateBulkPDRContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulkpdr-Full*
    - *BANK_CODE*
    - *BRNCODE*
    - *BANKNAME*
    - *BRNNAME*
    - *ACTION*
    - *DISPATCHLOTREFNO*
    - *BULKPDRREFNO*
    - *PROCESSTAT*
    - *AUTHSTAT*
    - *CHKR*
    - *CHKDTTIME*
    - *EVSEQNO*
    - *MAKER*
    - *MAKDTTIME*
    - *RECORDSTAT*
    - *ESNUI*
    - *Bulkpdrdetail*
      - *CONREFNUM*

ACC_CCY
AMNT
DISHONOUR_DATE
NOTARYCODE
PROTESTDATE
INTREMRKS
DISHONOUR_REASON
RETURN_DATE
CPTYIDEN
OTHRPTYIDEN
CPTYNAME
OTHERPARTYNAME
INSTRNO
PROCESSSTAT
PRDTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulkpdr-Full

Attribute	Description
Name	Bulkpdr-Full
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description	Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BRNCODE

Attribute	Description	
Name	BRNCODE	
Datatype	String	
Description	Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BANKNAME

Attribute	Description	
Name	BANKNAME	
Datatype	String	
Description	Bank Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description	Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

DISPATCHLOTREFNO

Attribute	Description	
Name	DISPATCHLOTREFNO	
Datatype	String	
Description	Dispatch Lot Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BULKPDRREFNO

Attribute	Description

Name	BULKPDRREFNO
Datatype	String
Description	Bulk Dishonor / Protest / Return Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,U

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	Checker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	Date Time

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

EVSEQNO

Attribute	**Description**	
Name	EVSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description	Maker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	**Description**	
Name	MAKDTTIME	
Datatype	String	
Description	Date Time	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RECORDSTAT

Attribute	**Description**	
Name	RECORDSTAT	
Datatype	String	
Description	Record Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,O,C

TOP

ESNUI

Attribute	Description
Name	ESNUI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bulkpdrdetail

Attribute	Description
Name	Bulkpdrdetail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number

Description	Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISHONOUR_DATE

Attribute	Description
Name	DISHONOUR_DATE
Datatype	Date
Description	Dishonour Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	Notary Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	Protest Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Internal Remarks
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DISHONOUR_REASON

Attribute	Description

Name	DISHONOUR_REASON
Datatype	String
Description	Dishonor Reason
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	Return Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	CounterParty Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	Other Party Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	CounterParty Name
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYNAME

Attribute	Description	
Name	OTHERPARTYNAME	
Datatype	String	
Description	Other Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INSTRNO

Attribute	Description	
Name	INSTRNO	
Datatype	String	
Description	Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

PROCESSSTAT

Attribute	Description	
Name	PROCESSSTAT	
Datatype	String	
Description	Process Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,H,S,F

TOP

PRDTYP

Attribute	Description	
Name	PRDTYP	
Datatype	String	
Description	Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.97.4.RB-CreateBulkPDRContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulkpdr-PK*
      - *BULKPDRREFNO*
    - *Bulkpdr-IO*
      - *ACTION*
      - *DISPATCHLOTREFNO*
      - *BULKPDRREFNO*
      - *AUTHSTAT*
      - *CHKR*
      - *CHKDTTIME*
      - *MAKER*
      - *MAKDTTIME*
      - *RECORDSTAT*
      - *Bulkpdrdetail*
        - *DISHONOUR_DATE*
        - *NOTARYCODE*
        - *PROTESTDATE*
        - *INTREMRKS*
        - *DISHONOUR_REASON*

RETURN_DATE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulkpdr-PK

Attribute	Description
Name	Bulkpdr-PK
Datatype	
Description	

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	Bulk Dishonor / Protest / Return Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulkpdr-IO

Attribute	Description
Name	Bulkpdr-IO
Datatype	
Description	

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

DISPATCHLOTREFNO

Attribute	Description

Name	DISPATCHLOTREFNO
Datatype	String
Description	Dispatch Lot Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	Bulk Dishonor / Protest / Return Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	Checker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	Date Time

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description	Maker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	**Description**	
Name	MAKDTTIME	
Datatype	String	
Description	Date Time	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RECORDSTAT

Attribute	**Description**	
Name	RECORDSTAT	
Datatype	String	
Description	Record Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,O,C

TOP

Bulkpdrdetail

Attribute	**Description**	
Name	Bulkpdrdetail	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

DISHONOUR_DATE

Attribute	Description
Name	DISHONOUR_DATE
Datatype	Date
Description	Dishonour Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	Notary Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	Protest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Internal Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DISHONOUR_REASON

Attribute	Description
Name	DISHONOUR_REASON
Datatype	String
Description	Dishonor Reason

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	Return Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.98.CreateBulkRealization

CreateBulkRealization

2.98.1.RB-CreateBulkRealization-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-Full*
    - *BULKREALNUM*
    - *DISLOTREF*
    - *DRACFORREALISATION*
    - *COLBANKREFNUM*
    - *VDATE*
    - *CURRENCY*
    - *TOTNETREAL*
    - *DRACCBRN*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *CHKR*
    - *CHKDTTIME*
    - *EVENSEQNO*
    - *MAKER*
    - *MAKDTTIME*

PROCESSTAT

MAXESN

Detail

CONREFNUM

AMUNT

INTREMRKS

NETREALAMT

CUSTNUMBER1

OTHRBNKCHARGS

INSTRNO

PROCESSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	Bulk Realization Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

DISLOTREF

Attribute	Description
Name	DISLOTREF
Datatype	String
Description	Dispatch Lot Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

DRACFORREALISATION

Attribute	Description
Name	DRACFORREALISATION
Datatype	String
Description	Debit Account for Realization
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	Collecting Bank Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VDATE

Attribute	Description
Name	VDATE
Datatype	Date
Description	Value date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TOTNETREAL

Attribute	Description
Name	TOTNETREAL
Datatype	Number
Description	Total Net Realized
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Debit Account Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,O,C,H

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description	Checker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description	Date Time	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVENSEQNO

Attribute	Description
Name	EVENSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	Date Time
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U,F

TOP

MAXESN

Attribute	Description
Name	MAXESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Detail

Attribute	Description
Name	Detail
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

AMUNT

Attribute	Description
Name	AMUNT
Datatype	Number
Description	Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Internal Remarks
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

NETREALAMT

Attribute	Description
Name	NETREALAMT
Datatype	Number
Description	Net Realized Amount
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CUSTNUMBER1

Attribute	Description
Name	CUSTNUMBER1
Datatype	String
Description	Customer Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	Other Bank Charges
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	Instrument Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT

Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U,F

TOP

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Master-IO*
  - *BULKREALNUM*
  - *DISLOTREF*
  - *DRACFORREALISATION*
  - *COLBANKREFNUM*
  - *VDATE*
  - *CURRENCY*
  - *TOTNETREAL*
  - *CHKR*
  - *CHKDTTIME*
  - *MAKER*
  - *MAKDTTIME*
  - *Detail*
    - *INTREMRKS*
    - *NETREALAMT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	Bulk Realization Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DISLOTREF

Attribute	**Description**	
Name	DISLOTREF	
Datatype	String	
Description	Dispatch Lot Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DRACFORREALISATION

Attribute	**Description**	
Name	DRACFORREALISATION	
Datatype	String	
Description	Debit Account for Realization	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COLBANKREFNUM

Attribute	**Description**	
Name	COLBANKREFNUM	
Datatype	String	
Description	Collecting Bank Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VDATE

Attribute	**Description**	
Name	VDATE	
Datatype	Date	
Description	Value date	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	Currency
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TOTNETREAL

Attribute	Description
Name	TOTNETREAL
Datatype	Number
Description	Total Net Realized
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	Checker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	Date Time
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	Maker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	Date Time
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Detail

Attribute	Description
Name	Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Internal Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

NETREALAMT

Attribute	Description
Name	NETREALAMT
Datatype	Number
Description	Net Realized Amount
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

2.98.3.RB-CreateBulkRealization-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-Full*
    - *BULKREALNUM*
    - *DISLOTREF*
    - *DRACFORREALISATION*
    - *COLBANKREFNUM*
    - *VDATE*
    - *CURRENCY*
    - *TOTNETREAL*
    - *DRACCBRN*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *CHKR*
    - *CHKDTTIME*
    - *EVENSEQNO*
    - *MAKER*
    - *MAKDTTIME*
    - *PROCESSTAT*
    - *MAXESN*
    - *Detail*

CONREFNUM
AMUNT
INTREMRKS
NETREALAMT
CUSTNUMBER1
OTHRBNKCHARGS
INSTRNO
PROCESSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	Bulk Realization Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DISLOTREF

Attribute	Description
Name	DISLOTREF
Datatype	String
Description	Dispatch Lot Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRACFORREALISATION

Attribute	Description
Name	DRACFORREALISATION
Datatype	String
Description	Debit Account for Realization
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	Collecting Bank Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VDATE

Attribute	Description
Name	VDATE
Datatype	Date
Description	Value date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TOTNETREAL

Attribute	Description
Name	TOTNETREAL
Datatype	Number
Description	Total Net Realized
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Debit Account Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,O,C,H

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description	Checker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description	Date Time	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVENSEQNO

Attribute	Description
Name	EVENSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	Date Time
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U,F

TOP

MAXESN

Attribute	Description
Name	MAXESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Detail

Attribute	Description
Name	Detail
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

AMUNT

Attribute	Description
Name	AMUNT
Datatype	Number
Description	Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Internal Remarks
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

NETREALAMT

Attribute	Description
Name	NETREALAMT
Datatype	Number
Description	Net Realized Amount
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CUSTNUMBER1

Attribute	Description
Name	CUSTNUMBER1
Datatype	String
Description	Customer Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	Other Bank Charges
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT

Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U,F

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.98.4.RB-CreateBulkRealization-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Master-PK*
      - *BULKREALNUM*
    - *Master-IO*
      - *BULKREALNUM*
      - *DISLOTREF*
      - *DRACFORREALISATION*
      - *COLBANKREFNUM*
      - *VDATE*
      - *CURRENCY*
      - *TOTNETREAL*
      - *CHKR*
      - *CHKDTTIME*
      - *MAKER*
      - *MAKDTTIME*
      - *Detail*
        - *INTREMRKS*
        - *NETREALAMT*
  - *FCUBS_ERROR_RESP*

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Master-PK

Attribute	Description
Name	Master-PK
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	Bulk Realization Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	Bulk Realization Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

DISLOTREF

Attribute	Description
Name	DISLOTREF

Datatype	String
Description	Dispatch Lot Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DRACFORREALISATION

Attribute	Description
Name	DRACFORREALISATION
Datatype	String
Description	Debit Account for Realization
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	Collecting Bank Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VDATE

Attribute	Description
Name	VDATE
Datatype	Date
Description	Value date
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	Currency
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TOTNETREAL

Attribute	Description
Name	TOTNETREAL
Datatype	Number
Description	Total Net Realized
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	Checker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	Date Time
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	Date Time
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

Detail

Attribute	Description
Name	Detail
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Internal Remarks
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

NETREALAMT

Attribute	Description
Name	NETREALAMT
Datatype	Number
Description	Net Realized Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	**Description**	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.99.CreateCashletterdishonour

CreateCashletterdishonour

2.99.1.RB-CreateCashletterdishonour-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CASHREFNO*
    - *CPTY_ID*
    - *COUNTRPRYNAM*
    - *INSTRNO*
    - *INSTRU_DATE*
    - *CURRENCY*
    - *AMNT*
    - *COLLBNKNAME*
    - *BOKNGDT*
    - *OTHR_PARTYNAME*
    - *DRAWEE_BNK_NAME*
    - *REASON_CODE*
    - *REASON*
    - *DT_OF_DISHONOR*

OTHRBNKCHARGS
REMRKS
MAKER
MAKDTTIME
CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Charges
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*

CHRGAMT

LIQDSTAT

Misdetails

CONREFNO

LATESN

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*
  - *RECVCVR*
  - *RECEIVER*
  - *REIMINST1*
  - *REIMINST2*
  - *REIMINST3*

REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5

REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*

ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REASON

Attribute	Description
Name	REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DT_OF_DISHONOR

Attribute	Description
Name	DT_OF_DISHONOR
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,L,A</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr></table>

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description

Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description

Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS6

Attribute	**Description**	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

2.99.2.RB-CreateCashletterdishonour-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONREFNUM*
    - *REASON_CODE*
    - *DT_OF_DISHONOR*
    - *OTHRBNKCHARGS*
    - *REMRKS*
    - *MAKER*
    - *MAKDTTIME*
    - *CHKR*
    - *CHKDTTIME*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *Con*
      - *CONTREFNO*
      - *EVENTSEQ*
      - *Adv*
        - *SUPRESS*
        - *PRIOR*
        - *MEDM*

- CHGREQ
- Charges
  - LATEVNSEQNO
  - CONREFNO
  - Charge-Association
    - WAIVER
    - DISACCRAPPL
    - ACCRREQD
    - DESC
  - Charge-Application
    - CHRGAMT
    - DISACCRAPPL
    - WAIVER
    - LIQDIND
  - Charge-Liquidation
    - ESN
    - CHRGAMT
    - LIQDSTAT
- Misdetails
  - CONREFNO
  - LATESN
  - MISGRP
  - RELACC
  - RELETED_REFERENCE
  - MISHEAD
  - RATEFLG
  - POOLCD
  - REFINANCE_RATE
  - REFRATETYP
  - PROCALCMTH
  - REFSPREAD
  - REFRATECD
  - COSTCD1
  - COSTCD2
  - COSTCD3
  - COSTCD4
  - COSTCD5
  - TXNMIS1
  - TXNMIS10
  - TXNMIS2
  - TXNMIS3
  - TXNMIS4
  - TXNMIS5
  - TXNMIS6

- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*
- *MISGRPTXN*
- *COMPMIS1*
- *COMPMIS10*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *FUNDMIS1*
- *FUNDMIS10*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *MISGRPFUN*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*

ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1

ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*

REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DT_OF_DISHONOR

Attribute	Description
Name	DT_OF_DISHONOR
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKR

Attribute	Description	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	Description	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RECORD_STAT

Attribute	Description	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,L,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**
Name	Charge-Application
Datatype	
Description	Includes Charge Application details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description

Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String

Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO

Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String

Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	Description	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO5

Attribute	Description	
Name	SNDTRRCVINFO5	
Datatype	String	
Description	Indicates Sender To Receiver Information 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	Description	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2

Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3

Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	**Description**	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	Description	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5

Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID

Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1

Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

2.99.3.RB-CreateCashletterdishonour-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CASHREFNO*
    - *CPTY_ID*
    - *COUNTRPRYNAM*
    - *INSTRNO*
    - *INSTRU_DATE*
    - *CURRENCY*
    - *AMNT*
    - *COLLBNKNAME*
    - *BOKNGDT*
    - *OTHR_PARTYNAME*
    - *DRAWEE_BNK_NAME*
    - *REASON_CODE*
    - *REASON*
    - *DT_OF_DISHONOR*
    - *OTHRBNKCHARGS*
    - *REMRKS*
    - *MAKER*

MAKDTTIME
CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Charges
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3

FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Settlements

CONREFNO

Contract-Settlement

- *IBANACNO*
- *CUSTSPREAD*
- *SPREADDEFN*
- *COMPNT*
- *TAGCCY*
- *ACCBRN*
- *ACC*
- *ACCCCY*
- *EXRATE*
- *NETIND*
- *ERICCY*
- *ERIAMT*
- *GENMSG*
- *RATECD*
- *CLEARNW*
- *COVERBY*
- *RTGSPMNT*
- *BANKPRIOR*
- *RTGSNW*
- *PAYBY*
- *TRANSTYP*
- *INSTYP*
- *INSNO*
- *CHGDET*
- *PAYMNTDET1*
- *PAYMNTDET2*
- *PAYMNTDET3*
- *PAYMNTDET4*
- *SNDTRRCVINFO1*
- *SNDTRRCVINFO2*
- *SNDTRRCVINFO3*
- *SNDTRRCVINFO4*
- *SNDTRRCVINFO5*
- *COVREQRD*
- *RECVCVR*
- *RECEIVER*
- *REIMINST1*
- *REIMINST2*
- *REIMINST3*
- *REIMINST4*
- *RCVRCORRS1*
- *RCVRCORRS2*

RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5

ORDINST5

ULTBEN5

DRCRIND

Settlement-Detail

- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*

SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REASON

Attribute	Description
Name	REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DT_OF_DISHONOR

Attribute	Description
Name	DT_OF_DISHONOR
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association

Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	**Description**	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	**Description**	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS5

Attribute	**Description**	
Name	TRANMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	**Description**	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs: 1
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	Description	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	Description	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP

Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String

Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.99.4.RB-CreateCashletterdishonour-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONREFNUM*
    - *Main-IO*
      - *CONREFNUM*
      - *REASON_CODE*
      - *DT_OF_DISHONOR*
      - *OTHRBNKCHARGS*
      - *REMRKS*
      - *MAKER*
      - *MAKDTTIME*
      - *CHKR*
      - *CHKDTTIME*
      - *RECORD_STAT*
      - *AUTHSTAT*
      - *Con*
        - *CONTREFNO*
        - *EVENTSEQ*
        - *Adv*

- *SUPRESS*
- *PRIOR*
- *MEDM*
- *CHGREQ*

Charges

- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*

- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*
- *MISGRPTXN*
- *COMPMIS1*
- *COMPMIS10*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *FUNDMIS1*
- *FUNDMIS10*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *MISGRPFUN*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*

EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2

ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*

INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC
FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DT_OF_DISHONOR

Attribute	Description
Name	DT_OF_DISHONOR
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,L,A

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String

Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Compmisdetails

Attribute	**Description**	
Name	Compmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Fundmisdetails

Attribute	**Description**	
Name	Fundmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

TXNUDFDETAILS

Attribute	**Description**	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL

Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC

Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	Description	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	Description	
Name	CLEARNW	
Datatype	String	
Description	Indicates Network Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	Description	
Name	COVERBY	
Datatype	String	
Description	Indicates Cover By Clearing : C Message : M	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4

Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String

Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing

Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ULTBANDCD

Attribute	Description	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SUPPID

Attribute	Description	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	Description	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PMNTTYP

Attribute	Description	
Name	PMNTTYP	
Datatype	String	
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	Description	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	Description	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.100.CreateCashletterrealize

CreateCashletterrealize

2.100.1.RB-CreateCashletterrealize-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CASHLTRCONREFNO*
    - *EVENTCODE*
    - *CL_REF*
    - *CURRENCY*
    - *AMNT*
    - *NOSTROACC*
    - *ACCBRN*
    - *INTREMRKS*
    - *COLBANKREFNUM*
    - *Footer*
      - *MAKER*
      - *MAKDTTIME*
      - *CHKR*
      - *CHKDTTIME*
      - *RECORD_STAT*

AUTHSTATS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CL_REF

Attribute	Description
Name	CL_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Footer

Attribute	Description	
Name	Footer	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	Description	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKR

Attribute	Description	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	Description	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RECORD_STAT

Attribute	Description	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,L

TOP

AUTHSTATS

Attribute	Description	
Name	AUTHSTATS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

2.100.2.RB-CreateCashletterrealize-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CASHLTRCONREFNO*
    - *EVENTCODE*
    - *INTREMRKS*
    - *COLBANKREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

2.100.3.RB-CreateCashletterrealize-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CASHLTRCONREFNO*
    - *EVENTCODE*
    - *CL_REF*
    - *CURRENCY*
    - *AMNT*
    - *NOSTROACC*
    - *ACCBRN*
    - *INTREMRKS*
    - *COLBANKREFNUM*
    - *Footer*
      - *MAKER*
      - *MAKDTTIME*
      - *CHKR*
      - *CHKDTTIME*
      - *RECORD_STAT*
      - *AUTHSTATS*
  - *FCUBS_ERROR_RESP*
    - *ERROR*

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CL_REF

Attribute	Description
Name	CL_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNT

Attribute	**Description**	
Name	AMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NOSTROACC

Attribute	**Description**	
Name	NOSTROACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INTREMRKS

Attribute	**Description**	
Name	INTREMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Footer

Attribute	Description
Name	Footer
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,L

TOP

AUTHSTATS

Attribute	Description
Name	AUTHSTATS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CASHLTRCONREFNO*
    - *Main-IO*
      - *CASHLTRCONREFNO*
      - *EVENTCODE*
      - *INTREMRKS*
      - *COLBANKREFNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.101.CreateCreatebulkfcycheck

CreateCreatebulkfcycheck

2.101.1.RB-CreateCreatebulkfcycheck-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Cashletter-Full*
    - *INSTRUCODE*
    - *INSTR_DESC*
    - *PRCD*
    - *PRODDESC*
    - *BATCHREFENUM*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *CPTY_AC_NO*
    - *ACCBRNRE*
    - *AC_CCYY*
    - *ACCBRN*
    - *COLL_BNK_NAME*
    - *BDTE*
    - *VAL_DATE_BANK*
    - *VALUE_DATE_CUST*

LIQDMODE
FINANCING
MARGINPERCENT
TRACK_LIMIT
CREDITLINE
NOOFINSTRUMENTS
PROCESS_STATUS
NOSTROACC
ESN
EVENT_SEQ_NO
RECORD_STAT
AUTHORIZATION_STATUS
CHECKER
CHKDTTIME
MAKER
MAKDTTIME
Bulk-Cashletter-Dtl
  CONREFNUM
  INSTRNO
  INSTRU_DATE
  ADJSTAMT
  LCY_AMT
  DISCAMT
  OTHR_PARTYNAME
  DRAWEE_BNK_NAME
  REMRKS
  PROCESS_STATUS
Summary
  AUTHSTAT
  RECORD_STAT
  INSTRUCODE
  PRCD
  CPTY_ID
  BATCHREFENUM
  NOSTROACC
  COLL_BNK_NAME
  INSTRNO
  INSTRU_DATE
  AC_CCYY
  AMNT
  BDTE
  VAL_DATE_BANK
  VALUE_DATE_CUST
  CONREFNUM

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Cashletter-Full

Attribute	Description
Name	Bulk-Cashletter-Full
Datatype	
Description	

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCBRNRE

Attribute	Description
Name	ACCBRNRE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BDTE

Attribute	Description
Name	BDTE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDMODE

Attribute	Description
Name	LIQDMODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,U,

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C,

TOP

AUTHORIZATION_STATUS

Attribute	Description
Name	AUTHORIZATION_STATUS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Bulk-Cashletter-Dtl

Attribute	Description
Name	Bulk-Cashletter-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

ADJSTAMT

Attribute	Description

Name	ADJSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,U,</td></tr></table>

TOP

Summary

Attribute	Description
Name	Summary
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,U</td></tr></table>

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C,

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BDTE

Attribute	Description
Name	BDTE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.101.2.RB-CreateCreatebulkfcycheck-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Cashletter-IO*
    - *INSTRUCODE*
    - *PRCD*
    - *BATCHREFENUM*
    - *CPTY_ID*
    - *CPTY_AC_NO*
    - *AC_CCYY*
    - *VALUE_DATE_CUST*
    - *LIQDMODE*
    - *FINANCING*
    - *MARGINPERCENT*
    - *TRACK_LIMIT*
    - *CREDITLINE*
    - *NOOFINSTRUMENTS*
    - *Bulk-Cashletter-Dtl*
      - *INSTRNO*
      - *INSTRU_DATE*
      - *ADJSTAMT*
      - *OTHR_PARTYNAME*

DRAWEE_BNK_NAME
REMRKS
Summary
AUTHSTAT
RECORD_STAT
INSTRUCODE
PRCD
CPTY_ID
BATCHREFENUM
NOSTROACC
COLL_BNK_NAME
INSTRNO
INSTRU_DATE
AC_CCYY
AMNT
BDTE
VAL_DATE_BANK
VALUE_DATE_CUST
CONREFNUM

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Cashletter-IO

Attribute	Description
Name	Bulk-Cashletter-IO
Datatype	
Description	

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDMODE

Attribute	**Description**	
Name	LIQDMODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,N,F

TOP

MARGINPERCENT

Attribute	**Description**	
Name	MARGINPERCENT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRACK_LIMIT

Attribute	**Description**	
Name	TRACK_LIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Bulk-Cashletter-Dtl

Attribute	Description
Name	Bulk-Cashletter-Dtl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Summary

Attribute	Description
Name	Summary
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,U</td></tr></table>

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>O,C,</td></tr></table>

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CPTY_ID

Attribute	**Description**	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BATCHREFENUM

Attribute	**Description**	
Name	BATCHREFENUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

NOSTROACC

Attribute	**Description**	
Name	NOSTROACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COLL_BNK_NAME

Attribute	**Description**	
Name	COLL_BNK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BDTE

Attribute	Description
Name	BDTE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

2.101.3.RB-CreateCreatebulkfcycheck-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Cashletter-Full*
    - *INSTRUCODE*
    - *INSTR_DESC*
    - *PRCD*
    - *PRODDESC*
    - *BATCHREFENUM*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *CPTY_AC_NO*
    - *ACCBRNRE*
    - *AC_CCYY*
    - *ACCBRN*
    - *COLL_BNK_NAME*
    - *BDTE*
    - *VAL_DATE_BANK*
    - *VALUE_DATE_CUST*
    - *LIQDMODE*
    - *FINANCING*
    - *MARGINPERCENT*

- *TRACK_LIMIT*
- *CREDITLINE*
- *NOOFINSTRUMENTS*
- *PROCESS_STATUS*
- *NOSTROACC*
- *ESN*
- *EVENT_SEQ_NO*
- *RECORD_STAT*
- *AUTHORIZATION_STATUS*
- *CHECKER*
- *CHKDTTIME*
- *MAKER*
- *MAKDTTIME*
- *Bulk-Cashletter-Dtl*
  - *CONREFNUM*
  - *INSTRNO*
  - *INSTRU_DATE*
  - *ADJSTAMT*
  - *LCY_AMT*
  - *DISCAMT*
  - *OTHR_PARTYNAME*
  - *DRAWEE_BNK_NAME*
  - *REMRKS*
  - *PROCESS_STATUS*
- *Summary*
  - *AUTHSTAT*
  - *RECORD_STAT*
  - *INSTRUCODE*
  - *PRCD*
  - *CPTY_ID*
  - *BATCHREFENUM*
  - *NOSTROACC*
  - *COLL_BNK_NAME*
  - *INSTRNO*
  - *INSTRU_DATE*
  - *AC_CCYY*
  - *AMNT*
  - *BDTE*
  - *VAL_DATE_BANK*
  - *VALUE_DATE_CUST*
  - *CONREFNUM*

FCUBS_ERROR_RESP

- *ERROR*
  - *ECODE*

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Cashletter-Full

Attribute	Description

Name	Bulk-Cashletter-Full
Datatype	
Description	

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BATCHREFENUM

Attribute	Description	
Name	BATCHREFENUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	Description	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_NAME

Attribute	Description	
Name	CPTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTY_AC_NO

Attribute	Description	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCBRNRE

Attribute	Description
Name	ACCBRNRE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BDTE

Attribute	Description
Name	BDTE

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDMODE

Attribute	Description
Name	LIQDMODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / P,U,

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,C,

TOP

AUTHORIZATION_STATUS

Attribute	Description
Name	AUTHORIZATION_STATUS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Bulk-Cashletter-Dtl

Attribute	**Description**	
Name	Bulk-Cashletter-Dtl	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CONREFNUM

Attribute	**Description**	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INSTRNO

Attribute	**Description**	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRU_DATE

Attribute	**Description**	
Name	INSTRU_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,U,

TOP

Summary

Attribute	Description
Name	Summary
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>O,C,</td></tr></table>

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BDTE

Attribute	Description
Name	BDTE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.101.4.RB-CreateCreatebulkfcycheck-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Cashletter-PK*
      - *BATCHREFENUM*
    - *Bulk-Cashletter-IO*
      - *INSTRUCODE*
      - *PRCD*
      - *BATCHREFENUM*
      - *CPTY_ID*
      - *CPTY_AC_NO*
      - *AC_CCYY*
      - *VALUE_DATE_CUST*
      - *LIQDMODE*
      - *FINANCING*
      - *MARGINPERCENT*
      - *TRACK_LIMIT*
      - *CREDITLINE*
      - *NOOFINSTRUMENTS*
      - *Bulk-Cashletter-Dtl*
        - *INSTRNO*

INSTRU_DATE
ADJSTAMT
OTHR_PARTYNAME
DRAWEE_BNK_NAME
REMRKS
Summary
AUTHSTAT
RECORD_STAT
INSTRUCODE
PRCD
CPTY_ID
BATCHREFENUM
NOSTROACC
COLL_BNK_NAME
INSTRNO
INSTRU_DATE
AC_CCYY
AMNT
BDTE
VAL_DATE_BANK
VALUE_DATE_CUST
CONREFNUM
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Cashletter-PK

Attribute	Description
Name	Bulk-Cashletter-PK
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Bulk-Cashletter-IO

Attribute	Description
Name	Bulk-Cashletter-IO
Datatype	
Description	

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDMODE

Attribute	Description
Name	LIQDMODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Bulk-Cashletter-Dtl

Attribute	Description
Name	Bulk-Cashletter-Dtl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Summary

Attribute	Description
Name	Summary
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C,

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BATCHREFENUM

Attribute	**Description**	
Name	BATCHREFENUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

NOSTROACC

Attribute	**Description**	
Name	NOSTROACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COLL_BNK_NAME

Attribute	**Description**	
Name	COLL_BNK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRNO

Attribute	**Description**	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BDTE

Attribute	Description
Name	BDTE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String

Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.102.AuthorizeOutRealization

AuthorizeOutRealization

2.102.1.RB-AuthorizeOutRealization-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contractdet-Full*
    - *CONREFNUM*
    - *MAKER*
    - *MAKERDT*
    - *CHKR*
    - *CHECKERDT*
    - *CONTSTAT*
    - *AUTSTAT*
    - *CPTYIDEN*
    - *CURR*
    - *AMNT*
    - *OTHRPTYIDEN*
    - *DISCOUNTAMT*
    - *DRACCREAL*
    - *CPTYACCNUM*
    - *NETREALIZED*

OTHRBNKCHARGS
COLBANKREFNUM
VALUEDT
DUEDATE
COUNTRPRYNAM
OTHERPARTYNAME
BNKCD
BRNCODE
DRACCBRN
ACCBRN
BNKNAME
BRNNAME
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*

BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1

BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*

ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO

- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*

TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2

COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contractdet-Full

Attribute	Description
Name	Contractdet-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERDT

Attribute	Description
Name	CHECKERDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,L</td></tr></table>

TOP

AUTSTAT

Attribute	Description

Name	AUTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

NETREALIZED

Attribute	Description
Name	NETREALIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description

Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description

Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String

Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description

Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	**Description**	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	**Description**	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	**Description**	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	**Description**	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2

Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3

Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	**Description**	
Name	COUNTRPRYNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

AGID

Attribute	**Description**	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	**Description**	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2

Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	**Description**	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**	
Name	REGREP2	
Datatype	String	
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**
Name	REGREP3
Datatype	String

Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2

Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	**Description**	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	**Description**	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO2

Attribute	**Description**	
Name	SNDRRCVRINFO2	
Datatype	String	
Description	Indicates Sender Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	**Description**	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	Description	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	Description	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	Description	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	Description	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.102.2.RB-AuthorizeOutRealization-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contractdet-IO*
    - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contractdet-IO

Attribute	Description
Name	Contractdet-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.102.3.RB-AuthorizeOutRealization-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contractdet-Full*
    - *CONREFNUM*
    - *MAKER*
    - *MAKERDT*
    - *CHKR*
    - *CHECKERDT*
    - *CONTSTAT*
    - *AUTSTAT*
    - *CPTYIDEN*
    - *CURR*
    - *AMNT*
    - *OTHRPTYIDEN*
    - *DISCOUNTAMT*
    - *DRACCREAL*
    - *CPTYACCNUM*
    - *NETREALIZED*
    - *OTHRBNKCHARGS*
    - *COLBANKREFNUM*
    - *VALUEDT*

DUEDATE
COUNTRPRYNAM
OTHERPARTYNAME
BNKCD
BRNCODE
DRACCBRN
ACCBRN
BNKNAME
BRNNAME
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*

TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4

ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*

ENVCONT5

Lcl_Clearing

FREETXT1

FREETXT2

FREETXT3

PMNTCD

ADDINFOSORBNET

SNDRCUSTNAME1

SNDRCUSTNAME2

SNDRCUSTNAME3

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

Charges

CONREFNO

Charge-Association

COMPNT

CREATESN

RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3

TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5

COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contractdet-Full

Attribute	Description
Name	Contractdet-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDT

Attribute	Description
Name	CHECKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L

TOP

AUTSTAT

Attribute	Description
Name	AUTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

NETREALIZED

Attribute	Description
Name	NETREALIZED

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	**Description**
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BNKNAME

Attribute	**Description**
Name	BNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BRNNAME

Attribute	**Description**
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Con

Attribute	**Description**
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement

Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	**Description**	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	**Description**	
Name	CLEARNW	
Datatype	String	
Description	Indicates Network Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	**Description**	
Name	COVERBY	
Datatype	String	
Description	Indicates Cover By Clearing : C Message : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	**Description**
Name	RTGSPMNT
Datatype	String

Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	Description	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1

Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	**Description**	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2

Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5

Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	**Description**	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description	
Name	REGREP3	
Datatype	String	
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1

Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRPART

Attribute	**Description**	
Name	SNDRRCVRPART	
Datatype	Number	
Description	Indicates Sender Receiver Participant	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	Description	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	Description	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	Description	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description

Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description

Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	Description	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association

Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	**Description**	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	**Description**	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS5

Attribute	**Description**	
Name	TRANMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	**Description**	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS4

Attribute	**Description**	
Name	FUNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS5

Attribute	**Description**	
Name	FUNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS6

Attribute	**Description**	
Name	FUNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS7

Attribute	**Description**	
Name	FUNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.102.4.RB-AuthorizeOutRealization-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contractdet-PK*
      - *CONREFNUM*
    - *Contractdet-IO*
      - *CONREFNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contractdet-PK

Attribute	Description
Name	Contractdet-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contractdet-IO

Attribute	Description
Name	Contractdet-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.103.AuthorizeOutwardcollection

AuthorizeOutwardcollection

2.103.1.RB-AuthorizeOutwardcollection-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNUM*
    - *BOOKDT*
    - *USERREFNUM*
    - *BRN*
    - *PRDCD*
    - *MODULE*
    - *UDS*
    - *STOPDT*
    - *VERSIONNO*
    - *EVENTSEQ*
    - *EVENTCODE*
    - *INSTRUCODE*
    - *PRODTYP*
    - *CPTYIDEN*
    - *CPTYACCNUM*

INSTRNO
INSTRU_DATE
INITCCY
OSAMT
LCYAMT
OTHRPTYIDEN
BNKCD
BRN_D
REFERENCENO
BOOKINGDT
MATDAYS
LEADDAYS
DISPATCHDT
GRACEDAYS
PROTEST
TRACKLIMIT
CREDITLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
DISCAMT
COLLATERAL
COLLVL
COLLPOOL
ACCBRN
PAYDUEDATE
DRACCBRN
INTREMARKS
INSTRUMENT_DESCRIPTION
TXTPDTDESC
CPTYNAME
OTHERPARTYNAME
BNKNAME
BRNNAME
XREF
BATCHREFENUM
BATCHSEQNO
DRACCREAL
AUTOLIQD
CONTREFLOG
MAKER
MAKDTTIME
CHKR
CHKDTTIME

EVENTLOG
CONST
AUTHSTAT
LATVERNO
DATE
Party-Details
  PARTTYP
  PARTYIDEN
  PARTYNAME
  ADDLN1
  ADDLN2
  ADDLN3
  ADDLN4
  CNTY
  PRTYLANG
Settlements
  CONREFNO
  Contract-Settlement
    IBANACNO
    CUSTSPREAD
    SPREADDEFN
    COMPNT
    TAGCCY
    ACCBRN
    ACC
    ACCCCY
    EXRATE
    NETIND
    ERICCY
    ERIAMT
    GENMSG
    RATECD
    CLEARNW
    COVERBY
    RTGSPMNT
    BANKPRIOR
    RTGSNW
    PAYBY
    TRANSTYP
    INSTYP
    INSNO
    CHGDET
    PAYMNTDET1
    PAYMNTDET2

PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2

BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*

ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP

PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3

- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*

- *CREATESN*
- *COMPNT*
- *TGCCY*
- *TGAMT*
- *CHRGCCY*
- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Con*
  - *CONTREFNO*
  - *EVENTSEQ*
  - *Adv*
    - *ADVNAME*
    - *SUPRESS*
    - *PRIOR*
    - *MEDM*
    - *PARTYIDEN*
    - *PARTYNAME*
    - *CHGREQ*
    - *PARTTYP*
- *Clpref*
  - *CONTREFNNO*
  - *CONTRACT_CCY*
  - *LATEVNSEQNO*
  - *PRD*
  - *PRDDESC*
  - *COUNTERPARTY*
  - *CURRENCY*
  - *TENOR*
  - *UNITS*
  - *LOAN_CONREFNO*
  - *RATECODE*
  - *EXCHANGERATE*
  - *RATE_TYPE*
  - *MAXIMUM*
  - *MINIMUM*
  - *PAYMENT_MODE*

LOANVALDATE

MATURITY_DATE

Ude

USERDEID

UDEDESC

RATEASOF

USAGE

USERDEVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

USERREFNUM

Attribute	Description
Name	USERREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDS

Attribute	Description
Name	UDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSIONNO

Attribute	Description
Name	VERSIONNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

PRODTYP

Attribute	Description
Name	PRODTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INITCCY

Attribute	Description
Name	INITCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

OSAMT

Attribute	Description
Name	OSAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BRN_D

Attribute	Description
Name	BRN_D
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKINGDT

Attribute	Description
Name	BOOKINGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LEADDAYS

Attribute	Description
Name	LEADDAYS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISPATCHDT

Attribute	Description
Name	DISPATCHDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,N,F</td></tr></table>

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COLLATERAL

Attribute	**Description**	
Name	COLLATERAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,C,T,N

TOP

COLLVL

Attribute	**Description**	
Name	COLLVL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COLLPOOL

Attribute	**Description**	
Name	COLLPOOL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description
Name	INSTRUMENT_DESCRIPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

TXTPDTDESC

Attribute	Description
Name	TXTPDTDESC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CONTREFLOG

Attribute	Description
Name	CONTREFLOG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EVENTLOG

Attribute	Description
Name	EVENTLOG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,H,R,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / DRAWEE,DRAWER,PAYEE,COLLECTING_BANK,

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRTYLANG

Attribute	Description
Name	PRTYLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	**Description**	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO

Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String

Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	Description	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO5

Attribute	Description	
Name	SNDTRRCVINFO5	
Datatype	String	
Description	Indicates Sender To Receiver Information 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	Description	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4

Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1

Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5

Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	

Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	**Description**	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS7

Attribute	**Description**	
Name	TRANMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS8

Attribute	**Description**	
Name	TRANMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String

Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description

Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / DRAWEE,DRAWER,PAYEE,COLLECTING_BANK,

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description

Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNITS

Attribute	**Description**	
Name	UNITS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LOAN_CONREFNO

Attribute	**Description**	
Name	LOAN_CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RATECODE

Attribute	**Description**	
Name	RATECODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,S

TOP

EXCHANGERATE

Attribute	**Description**	
Name	EXCHANGERATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.103.2.RB-AuthorizeOutwardcollection-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.103.3.RB-AuthorizeOutwardcollection-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNUM*
    - *BOOKDT*
    - *USERREFNUM*
    - *BRN*
    - *PRDCD*
    - *MODULE*
    - *UDS*
    - *STOPDT*
    - *VERSIONNO*
    - *EVENTSEQ*
    - *EVENTCODE*
    - *INSTRUCODE*
    - *PRODTYP*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *INSTRNO*
    - *INSTRU_DATE*
    - *INITCCY*

OSAMT
LCYAMT
OTHRPTYIDEN
BNKCD
BRN_D
REFERENCENO
BOOKINGDT
MATDAYS
LEADDAYS
DISPATCHDT
GRACEDAYS
PROTEST
TRACKLIMIT
CREDITLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
DISCAMT
COLLATERAL
COLLVL
COLLPOOL
ACCBRN
PAYDUEDATE
DRACCBRN
INTREMARKS
INSTRUMENT_DESCRIPTION
TXTPDTDESC
CPTYNAME
OTHERPARTYNAME
BNKNAME
BRNNAME
XREF
BATCHREFENUM
BATCHSEQNO
DRACCREAL
AUTOLIQD
CONTREFLOG
MAKER
MAKDTTIME
CHKR
CHKDTTIME
EVENTLOG
CONST
AUTHSTAT

LATVERNO

DATE

Party-Details

- *PARTTYP*
- *PARTYIDEN*
- *PARTYNAME*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ADDLN4*
- *CNTY*
- *PRTYLANG*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*

SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5

COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*

SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD

COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6

- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*

TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
Clpref
CONTREFNNO
CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM
PAYMENT_MODE
LOANVALDATE
MATURITY_DATE
Ude

USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USERREFNUM

Attribute	Description
Name	USERREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

UDS

Attribute	Description
Name	UDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

STOPDT

Attribute	Description
Name	STOPDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSIONNO

Attribute	Description
Name	VERSIONNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRODTYP

Attribute	Description
Name	PRODTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INITCCY

Attribute	Description
Name	INITCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OSAMT

Attribute	Description
Name	OSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BRN_D

Attribute	Description
Name	BRN_D
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BOOKINGDT

Attribute	Description
Name	BOOKINGDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LEADDAYS

Attribute	Description
Name	LEADDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISPATCHDT

Attribute	Description
Name	DISPATCHDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CREDITLINE

Attribute	**Description**	
Name	CREDITLINE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

OTHPARTYLIMIT

Attribute	**Description**	
Name	OTHPARTYLIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MARGINPERC

Attribute	**Description**	
Name	MARGINPERC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,N,F

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLVL

Attribute	Description
Name	COLLVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PAYDUEDATE

Attribute	**Description**	
Name	PAYDUEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DRACCBRN

Attribute	**Description**	
Name	DRACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INTREMARKS

Attribute	**Description**	
Name	INTREMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INSTRUMENT_DESCRIPTION

Attribute	**Description**	
Name	INSTRUMENT_DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

TXTPDTDESC

Attribute	Description
Name	TXTPDTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONTREFLOG

Attribute	Description
Name	CONTREFLOG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVENTLOG

Attribute	Description
Name	EVENTLOG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,H,R,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / DRAWEE,DRAWER,PAYEE,COLLECTING_BANK,

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN3

Attribute	Description	
Name	ADDLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDLN4

Attribute	Description	
Name	ADDLN4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CNTY

Attribute	Description	
Name	CNTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRTYLANG

Attribute	Description	
Name	PRTYLANG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	**Description**
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	**Description**
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	**Description**
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	**Description**
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	**Description**	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	**Description**	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	Description	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	Description	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	Description	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	**Description**
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	**Description**
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	**Description**
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	**Description**
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number

Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY

Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / DRAWEE,DRAWER,PAYEE,COLLECTING_BANK,

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description

Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.103.4.RB-AuthorizeOutwardcollection-Res-PK-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *CHOICE*
  - *Contract-Details-PK*
    - *CONREFNUM*
  - *Contract-Details-IO*
    - *CONREFNUM*
- *FCUBS_ERROR_RESP*
  - *ERROR*
    - *ECODE*
    - *EDESC*
- *FCUBS_WARNING_RESP*
  - *WARNING*
    - *WCODE*
    - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.104.AuthorizeOverseasfinance

AuthorizeOverseasfinance

2.104.1.RB-AuthorizeOverseasfinance-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *INSTRNO*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *BOOKINGDATE*
    - *OTHR_PARTY_NAME*
    - *DRAWEE_BNK_NAME*
    - *FINANCING*
    - *MARGINPERCENT*
    - *TRACK_LIMIT*
    - *CREDIT_LINE*
    - *DISCOUNT_AMOUNT*

MAKER
MAKERDTSTAMP
CHECKER
CHECKERSTAMP
RECORD_STAT
AUTHSTAT
PAYDUEDATE
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*

INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2

ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER

- *DISACCRAPPL*
- *ACCRREQD*
- *DESC*

Charge-Application

- *CREATESN*
- *COMPNT*
- *TGCCY*
- *TGAMT*
- *CHRGCCY*
- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*

Charge-Liquidation

- *ESN*
- *COMPNT*
- *CHRGCCY*
- *CHRGAMT*
- *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*

TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7

- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Clpref

- *CONTREFNNO*
- *CONTRACT_CCY*
- *LATEVNSEQNO*
- *PRD*
- *PRDDESC*
- *COUNTERPARTY*
- *CURRENCY*
- *TENOR*
- *UNITS*
- *LOAN_CONREFNO*
- *RATECODE*
- *EXCHANGERATE*
- *RATE_TYPE*
- *MAXIMUM*
- *MINIMUM*
- *PAYMENT_MODE*
- *LOANVALDATE*
- *MATURITY_DATE*
- *Ude*
  - *USERDEID*
  - *UDEDESC*
  - *RATEASOF*
  - *USAGE*
  - *USERDEVAL*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,A,H,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr></table>

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Settlement

Attribute	**Description**	
Name	Contract-Settlement	
Datatype		
Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	**Description**	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description

Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	**Description**	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	**Description**	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	**Description**	
Name	CLEARNW	
Datatype	String	
Description	Indicates Network Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	**Description**
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates RTGS Payment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	**Description**	
Name	BANKPRIOR	
Datatype	String	
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1

Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC

Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	**Description**	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1

Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String

Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description

Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PMNTTYP

Attribute	Description	
Name	PMNTTYP	
Datatype	String	
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	Description	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	Description	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description

Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY

Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	**Description**	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS6

Attribute	**Description**	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	**Description**	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	**Description**	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	**Description**	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	**Description**	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS2

Attribute	**Description**	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.104.2.RB-AuthorizeOverseasfinance-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.104.3.RB-AuthorizeOverseasfinance-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *INSTRNO*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *BOOKINGDATE*
    - *OTHR_PARTY_NAME*
    - *DRAWEE_BNK_NAME*
    - *FINANCING*
    - *MARGINPERCENT*
    - *TRACK_LIMIT*
    - *CREDIT_LINE*
    - *DISCOUNT_AMOUNT*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHECKER*

CHECKERSTAMP
RECORD_STAT
AUTHSTAT
PAYDUEDATE
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*

PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1

BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*

PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC

- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*

TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10

FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
Clpref
CONTREFNNO
CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM
PAYMENT_MODE
LOANVALDATE
MATURITY_DATE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description

Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,A,H,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SUPRESS

Attribute	**Description**	
Name	SUPRESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number

Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String

Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	Description	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	Description	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description

Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	**Description**	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	**Description**	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1

Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5

Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	**Description**	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	**Description**	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description

Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	**Description**	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS2

Attribute	**Description**	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS3

Attribute	**Description**	
Name	FUNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS4

Attribute	**Description**	
Name	FUNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS5

Attribute	**Description**	
Name	FUNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS6

Attribute	**Description**	
Name	FUNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description

Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.104.4.RB-AuthorizeOverseasfinance-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONREFNUM*
    - *Main-IO*
      - *CONREFNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.105.AuthorizeOverseaspdr

AuthorizeOverseaspdr

2.105.1.RB-AuthorizeOverseaspdr-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *INSTRUMENTNORE*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *OTHER_BANK_CHARGES*
    - *BNK_CODE*

REMRKS
BANK_NAME
DISHONORDATE
NOTARY_DESCRIPTION
BOOKING_DATE
DISCOUNT_AMOUNT
REASON_CODE
REASON
PROTESTDATE
RETURN_DATE
OTHR_PARTY_NAME
DRAWEE_BNK_NAME
Charges
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*

COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3

INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
  INSTRCD1

INSTRCD2
INSTRCD3
INSTRCD4
ITIMEIND1
ITIMEIND2
ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID

SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1

COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4

FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	Description	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CTR_PRTY_NAME

Attribute	Description
Name	CTR_PRTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRUMENTNORE

Attribute	Description
Name	INSTRUMENTNORE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,A,H,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BNK_CODE

Attribute	Description
Name	BNK_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REMRKS

Attribute	Description
Name	REMRKS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BANK_NAME

Attribute	Description
Name	BANK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DISHONORDATE

Attribute	Description
Name	DISHONORDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTARY_DESCRIPTION

Attribute	Description
Name	NOTARY_DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BOOKING_DATE

Attribute	Description
Name	BOOKING_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REASON

Attribute	Description
Name	REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHR_PARTY_NAME

Attribute	**Description**	
Name	OTHR_PARTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRAWEE_BNK_NAME

Attribute	**Description**	
Name	DRAWEE_BNK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**
Name	Charge-Application
Datatype	
Description	Includes Charge Application details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	**Description**	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**

Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String

Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	**Description**	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	**Description**	
Name	BANKPRIOR	
Datatype	String	
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	Description	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	**Description**	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	**Description**	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	**Description**	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	**Description**	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	**Description**	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	**Description**	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	**Description**	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	Description	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	**Description**	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS5

Attribute	**Description**	
Name	TRANMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	**Description**	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS4

Attribute	**Description**	
Name	FUNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS5

Attribute	**Description**	
Name	FUNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS6

Attribute	**Description**	
Name	FUNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS7

Attribute	**Description**	
Name	FUNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

2.105.2.RB-AuthorizeOverseaspdr-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.105.3.RB-AuthorizeOverseaspdr-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *INSTRUMENTNORE*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *OTHER_BANK_CHARGES*
    - *BNK_CODE*
    - *REMRKS*
    - *BANK_NAME*
    - *DISHONORDATE*

NOTARY_DESCRIPTION
BOOKING_DATE
DISCOUNT_AMOUNT
REASON_CODE
REASON
PROTESTDATE
RETURN_DATE
OTHR_PARTY_NAME
DRAWEE_BNK_NAME
Charges
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*

ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2

ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*

ITIMEIND1
ITIMEIND2
ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3

SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3

COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7

FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CTR_PRTY_NAME

Attribute	Description
Name	CTR_PRTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRUMENTNORE

Attribute	Description
Name	INSTRUMENTNORE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>L,A,H,</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,U,</td></tr></table>

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BNK_CODE

Attribute	Description
Name	BNK_CODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REMRKS

Attribute	**Description**	
Name	REMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BANK_NAME

Attribute	**Description**	
Name	BANK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DISHONORDATE

Attribute	**Description**	
Name	DISHONORDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NOTARY_DESCRIPTION

Attribute	**Description**	
Name	NOTARY_DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BOOKING_DATE

Attribute	Description
Name	BOOKING_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REASON

Attribute	Description
Name	REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RETURN_DATE

Attribute	**Description**	
Name	RETURN_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHR_PARTY_NAME

Attribute	**Description**	
Name	OTHR_PARTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRAWEE_BNK_NAME

Attribute	**Description**	
Name	DRAWEE_BNK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description

Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	**Description**	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1

Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC

Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	**Description**	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1

Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String

Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description

Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PMNTTYP

Attribute	Description	
Name	PMNTTYP	
Datatype	String	
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	Description	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	Description	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	**Description**	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS2

Attribute	**Description**	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	
Restrictions	

Restrictions	Description
maxLength	15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	
Restrictions	

Restrictions	Description
enumeration	Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	
Restrictions	

Restrictions	Description
maxLength	15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.105.4.RB-AuthorizeOverseaspdr-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONREFNUM*
    - *Main-IO*
      - *CONREFNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.106.AuthorizeOvsbulkcontract

AuthorizeOvsbulkcontract

2.106.1.RB-AuthorizeOvsbulkcontract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Overseas-Full*
    - *INSTRUMENT_CODE*
    - *INSTR_DESC*
    - *PRODCD*
    - *PRDDESC*
    - *CURRENCY*
    - *COLLECTINGBANKCIF*
    - *CBN_S*
    - *DB_ACC_REAL*
    - *ACCBRN*
    - *BOKNGDT*
    - *PAYDUEDATE*
    - *TRANSITDAYS*
    - *BATCHREFENUM*
    - *COLLBANKCODE*
    - *NOOFINSTRUMENTS*

STAT
ESN_NO
RECORD_STAT
AUTHSTAT
CHKR
CHKDTTIME
MAKER
MAKDTTIME
EVENTSEQNO
Bulk-Input-Overseas-Dtl
- *CONTRACTREFNO*
- *CPTY_ID*
- *CPTY_AC_NO*
- *ACCBRNRE*
- *INSTRNO*
- *INSTRU_DATE*
- *AMNT*
- *LCY_AMT*
- *OTHR_PARTYNAME*
- *DRAWEE_BNK_NAME*
- *AUTOLIQD*
- *FINANCING*
- *MARGIN_PERCENTAGE*
- *TRACK_LIMIT*
- *CREDIT_LINE*
- *DISCAMT*
- *CPTY_NAME*
- *INTREMRKS*
- *BATCHREFNO*
- *BATCHSEQNO*
- *CONTRACTCCY*
- *PROCESS_STATUS*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Overseas-Full

Attribute	Description
Name	Bulk-Input-Overseas-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRODCD

Attribute	Description
Name	PRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLECTINGBANKCIF

Attribute	Description
Name	COLLECTINGBANKCIF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CBN_S

Attribute	**Description**	
Name	CBN_S	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

DB_ACC_REAL

Attribute	**Description**	
Name	DB_ACC_REAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BOKNGDT

Attribute	**Description**	
Name	BOKNGDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

COLLBANKCODE

Attribute	Description
Name	COLLBANKCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STAT

Attribute	**Description**	
Name	STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,U,

TOP

ESN_NO

Attribute	**Description**	
Name	ESN_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,C,

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U,

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bulk-Input-Overseas-Dtl

Attribute	Description
Name	Bulk-Input-Overseas-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCBRNRE

Attribute	Description
Name	ACCBRNRE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHR_PARTYNAME

Attribute	**Description**	
Name	OTHR_PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRAWEE_BNK_NAME

Attribute	**Description**	
Name	DRAWEE_BNK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AUTOLIQD

Attribute	**Description**	
Name	AUTOLIQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,N,F,

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BATCHREFNO

Attribute	Description
Name	BATCHREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,H,F,</td></tr></table>

TOP

2.106.2.RB-AuthorizeOvsbulkcontract-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Bulk-Input-Overseas-IO
BATCHREFENUM

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Overseas-IO

Attribute	Description
Name	Bulk-Input-Overseas-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.106.3.RB-AuthorizeOvsbulkcontract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Overseas-Full*
    - *INSTRUMENT_CODE*
    - *INSTR_DESC*
    - *PRODCD*
    - *PRDDESC*
    - *CURRENCY*
    - *COLLECTINGBANKCIF*
    - *CBN_S*
    - *DB_ACC_REAL*
    - *ACCBRN*
    - *BOKNGDT*
    - *PAYDUEDATE*
    - *TRANSITDAYS*
    - *BATCHREFENUM*
    - *COLLBANKCODE*
    - *NOOFINSTRUMENTS*
    - *STAT*
    - *ESN_NO*
    - *RECORD_STAT*

AUTHSTAT
CHKR
CHKDTTIME
MAKER
MAKDTTIME
EVENTSEQNO
Bulk-Input-Overseas-Dtl
CONTRACTREFNO
CPTY_ID
CPTY_AC_NO
ACCBRNRE
INSTRNO
INSTRU_DATE
AMNT
LCY_AMT
OTHR_PARTYNAME
DRAWEE_BNK_NAME
AUTOLIQD
FINANCING
MARGIN_PERCENTAGE
TRACK_LIMIT
CREDIT_LINE
DISCAMT
CPTY_NAME
INTREMRKS
BATCHREFNO
BATCHSEQNO
CONTRACTCCY
PROCESS_STATUS
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Overseas-Full

Attribute	Description
Name	Bulk-Input-Overseas-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTR_DESC

Attribute	**Description**	
Name	INSTR_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

PRODCD

Attribute	**Description**	
Name	PRODCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CURRENCY

Attribute	**Description**	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLECTINGBANKCIF

Attribute	Description
Name	COLLECTINGBANKCIF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CBN_S

Attribute	Description
Name	CBN_S
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COLLBANKCODE

Attribute	Description
Name	COLLBANKCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,U,

TOP

ESN_NO

Attribute	Description
Name	ESN_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,C,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

EVENTSEQNO

Attribute	**Description**	
Name	EVENTSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Bulk-Input-Overseas-Dtl

Attribute	**Description**	
Name	Bulk-Input-Overseas-Dtl	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

CONTRACTREFNO

Attribute	**Description**	
Name	CONTRACTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	**Description**	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRNRE

Attribute	Description
Name	ACCBRNRE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F,

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BATCHREFNO

Attribute	Description
Name	BATCHREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,H,F,

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.106.4.RB-AuthorizeOvsbulkcontract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Input-Overseas-PK*
      - *BATCHREFENUM*
    - *Bulk-Input-Overseas-IO*
      - *BATCHREFENUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Input-Overseas-PK

Attribute	Description
Name	Bulk-Input-Overseas-PK
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Input-Overseas-IO

Attribute	Description
Name	Bulk-Input-Overseas-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.107.AuthorizeOvsbulkrealize

AuthorizeOvsbulkrealize

2.107.1.RB-AuthorizeOvsbulkrealize-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Liqd-Overseas-Full*
    - *BATCHREFENUM*
    - *BULK_REAL_NUM*
    - *CURRENCY*
    - *DB_ACC_REAL*
    - *ACCBRN*
    - *COLBANK_REFNO*
    - *COLL_BNK_CIF*
    - *COLLBNKNAME*
    - *VALUEDATE*
    - *PROCSTAT*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *CHKR*
    - *CHKDTTIME*
    - *ESN_NO*

MAKER
MAKDTTIME
EVENTSEQNO
Bulk-Liqd-Overseas-Dtl
CONTRACTREFNO
CPTY_ID
CPTY_NAME
CPTY_AC_NO
ACCBRNRE
INSTRNO
INSTRU_DATE
AMNT
NET_AMT_REALISED
OTHER_BANK_CHARGES
INTREMRKS
PROCESSSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Liqd-Overseas-Full

Attribute	Description
Name	Bulk-Liqd-Overseas-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BULK_REAL_NUM

Attribute	Description
Name	BULK_REAL_NUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLBANK_REFNO

Attribute	Description
Name	COLBANK_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

PROCSTAT

Attribute	Description
Name	PROCSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,U,</td></tr></table>

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>O,C,</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U,

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ESN_NO

Attribute	**Description**	
Name	ESN_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bulk-Liqd-Overseas-Dtl

Attribute	Description
Name	Bulk-Liqd-Overseas-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRNRE

Attribute	Description
Name	ACCBRNRE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,H,F,</td></tr></table>

TOP

2.107.2.RB-AuthorizeOvsbulkrealize-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Liqd-Overseas-IO*
    - *BULK_REAL_NUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Liqd-Overseas-IO

Attribute	Description
Name	Bulk-Liqd-Overseas-IO
Datatype	
Description	

TOP

BULK_REAL_NUM

Attribute	Description
Name	BULK_REAL_NUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.107.3.RB-AuthorizeOvsbulkrealize-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Liqd-Overseas-Full*
    - *BATCHREFENUM*
    - *BULK_REAL_NUM*
    - *CURRENCY*
    - *DB_ACC_REAL*
    - *ACCBRN*
    - *COLBANK_REFNO*
    - *COLL_BNK_CIF*
    - *COLLBNKNAME*
    - *VALUEDATE*
    - *PROCSTAT*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *CHKR*
    - *CHKDTTIME*
    - *ESN_NO*
    - *MAKER*
    - *MAKDTTIME*
    - *EVENTSEQNO*

Bulk-Liqd-Overseas-Dtl

CONTRACTREFNO

CPTY_ID

CPTY_NAME

CPTY_AC_NO

ACCBRNRE

INSTRNO

INSTRU_DATE

AMNT

NET_AMT_REALISED

OTHER_BANK_CHARGES

INTREMRKS

PROCESSSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Liqd-Overseas-Full

Attribute	Description
Name	Bulk-Liqd-Overseas-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BULK_REAL_NUM

Attribute	Description
Name	BULK_REAL_NUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CURRENCY

Attribute	Description

Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLBANK_REFNO

Attribute	Description
Name	COLBANK_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

COLLBNKNAME

Attribute	**Description**	
Name	COLLBNKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

VALUEDATE

Attribute	**Description**	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

PROCSTAT

Attribute	**Description**	
Name	PROCSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,U,

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,C,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ESN_NO

Attribute	Description
Name	ESN_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bulk-Liqd-Overseas-Dtl

Attribute	Description
Name	Bulk-Liqd-Overseas-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRNRE

Attribute	Description
Name	ACCBRNRE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,H,F,

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.107.4.RB-AuthorizeOvsbulkrealize-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Liqd-Overseas-PK*
      - *BULK_REAL_NUM*
    - *Bulk-Liqd-Overseas-IO*
      - *BULK_REAL_NUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Liqd-Overseas-PK

Attribute	Description
Name	Bulk-Liqd-Overseas-PK
Datatype	
Description	

TOP

BULK_REAL_NUM

Attribute	Description
Name	BULK_REAL_NUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Liqd-Overseas-IO

Attribute	Description
Name	Bulk-Liqd-Overseas-IO
Datatype	
Description	

TOP

BULK_REAL_NUM

Attribute	Description
Name	BULK_REAL_NUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.108.AuthorizeOvscheckspay

AuthorizeOvscheckspay

2.108.1.RB-AuthorizeOvscheckspay-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONTREFNO*
    - *LATESTVERSIONNO*
    - *RECORD_STAT*
    - *AUTHSTATUS*
    - *CURR_EVENT_CODE*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHKR*
    - *CHKDTTIME*
    - *EVENT_SEQ_NO*
    - *CONT_STAT*
    - *AUTH_STAT*
    - *CPTY_ID*
    - *CPTY_AC_NO*
    - *INSTRNO*

INSTRUMENT_DATE
CURRENCY
AMNT
NET_AMT_REALISED
OTHER_BANK_CHARGES
COLL_BNK_CIF
BOOKINGDATE
MATURITY_DATE
VALUE_DATE
TRACK_LIMIT
CREDIT_LINE
FINANCING
INT_REM
INSTRUMENT_CODE
INSTR_DESC
PRCD
PRODDESC
USERREF_NO
XREF
COUNTRPRYNAM
LCY_AMT
COLLBANKNAME
PAYDUEDATE
CONREF
EVENTSEQ
PARTYTYP
ADDRESS
PARTYADDR2
PARTYADDR3
PARTYADDR4
WALKINCUSTFLG
COLLEC_BANK_CIF
COLLBNKNAME
DISCOUNT_AMOUNT
DB_ACC_REAL
BULK_INPUT_REF_NO
DRAWEE_BNK_NAME
AUTOLIQD
OTHER_PARTY_ID
VERSION_NO
TRANSITDAYS
MARGIN_PERCENTAGE
ACC_BRANCH
OTHR_PARTY_NAME

- *ACCBRN*
- *TXNUDFDETAILS*
  - *FLDNAME*
  - *FLDVAL*
- *Charges*
  - *CONREFNO*
  - *Charge-Association*
    - *COMPNT*
    - *CREATESN*
    - *RULE*
    - *WAIVER*
    - *DISACCRAPPL*
    - *ACCRREQD*
    - *DESC*
  - *Charge-Application*
    - *CREATESN*
    - *COMPNT*
    - *TGCCY*
    - *TGAMT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *DISACCRAPPL*
    - *WAIVER*
    - *LIQDIND*
  - *Charge-Liquidation*
    - *ESN*
    - *COMPNT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *LIQDSTAT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*
  - *REFRATECD*

COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6

- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*

CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2

ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*

REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4

RCVRACC

Clpref

CONTREFNNO

CONTRACT_CCY

LATEVNSEQNO

PRD

PRDDESC

COUNTERPARTY

CURRENCY

TENOR

UNITS

LOAN_CONREFNO

RATECODE

EXCHANGERATE

RATE_TYPE

MAXIMUM

MINIMUM

PAYMENT_MODE

LOANVALDATE

MATURITY_DATE

Ude

USERDEID

UDEDESC

RATEASOF

USAGE

USERDEVAL

Con

CONTREFNO

EVENTSEQ

Adv

ADVNAME

SUPRESS

PRIOR

MEDM

PARTYIDEN

PARTYNAME

CHGREQ

PARTTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESTVERSIONNO

Attribute	**Description**	
Name	LATESTVERSIONNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTATUS

Attribute	**Description**	
Name	AUTHSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CURR_EVENT_CODE

Attribute	**Description**	
Name	CURR_EVENT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONT_STAT

Attribute	Description
Name	CONT_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,L,R,H,</td></tr></table>

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,U,</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRNO

Attribute	**Description**	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRUMENT_DATE

Attribute	**Description**	
Name	INSTRUMENT_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

CURRENCY

Attribute	**Description**	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNT

Attribute	**Description**	
Name	AMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

INT_REM

Attribute	Description
Name	INT_REM
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLBANKNAME

Attribute	Description
Name	COLLBANKNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREF

Attribute	Description
Name	CONREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ADDRESS

Attribute	Description
Name	ADDRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYADDR2

Attribute	Description
Name	PARTYADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYADDR3

Attribute	Description
Name	PARTYADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYADDR4

Attribute	Description
Name	PARTYADDR4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINCUSTFLG

Attribute	Description
Name	WALKINCUSTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COLLEC_BANK_CIF

Attribute	Description
Name	COLLEC_BANK_CIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BULK_INPUT_REF_NO

Attribute	Description
Name	BULK_INPUT_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OTHER_PARTY_ID

Attribute	Description
Name	OTHER_PARTY_ID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

VERSION_NO

Attribute	**Description**	
Name	VERSION_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRANSITDAYS

Attribute	**Description**	
Name	TRANSITDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MARGIN_PERCENTAGE

Attribute	**Description**	
Name	MARGIN_PERCENTAGE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACC_BRANCH

Attribute	**Description**	
Name	ACC_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

OTHR_PARTY_NAME

Attribute	**Description**
Name	OTHR_PARTY_NAME

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD

Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	**Description**	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	**Description**
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	**Description**
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	**Description**
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	**Description**
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	Description	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	Description	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COUNTERPARTY

Attribute	**Description**	
Name	COUNTERPARTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CURRENCY

Attribute	**Description**	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TENOR

Attribute	**Description**	
Name	TENOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	**Description**
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	**Description**
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Con

Attribute	**Description**
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	**Description**
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CHGREQ

Attribute	**Description**	
Name	CHGREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.108.2.RB-AuthorizeOvscheckspay-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONTREFNO*
    - *CPTY_AC_NO*
    - *NET_AMT_REALISED*
    - *COLL_BNK_CIF*
    - *BOOKINGDATE*
    - *TRACK_LIMIT*
    - *CREDIT_LINE*
    - *FINANCING*
    - *INT_REM*
    - *COUNTRPRYNAM*
    - *LCY_AMT*
    - *COLLBANKNAME*
    - *PAYDUEDATE*
    - *ADDRESS*
    - *PARTYADDR2*
    - *PARTYADDR3*
    - *PARTYADDR4*
    - *COLLEC_BANK_CIF*

COLLBNKNAME
DISCOUNT_AMOUNT
DRAWEE_BNK_NAME
AUTOLIQD
OTHER_PARTY_ID

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description

Name	Main-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 20

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,N,F

TOP

INT_REM

Attribute	Description
Name	INT_REM
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLBANKNAME

Attribute	Description
Name	COLLBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDRESS

Attribute	Description
Name	ADDRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTYADDR2

Attribute	Description
Name	PARTYADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTYADDR3

Attribute	Description
Name	PARTYADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTYADDR4

Attribute	Description
Name	PARTYADDR4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COLLEC_BANK_CIF

Attribute	Description

Name	COLLEC_BANK_CIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

OTHER_PARTY_ID

Attribute	Description
Name	OTHER_PARTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

2.108.3.RB-AuthorizeOvscheckspay-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONTREFNO*
    - *LATESTVERSIONNO*
    - *RECORD_STAT*
    - *AUTHSTATUS*
    - *CURR_EVENT_CODE*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHKR*
    - *CHKDTTIME*
    - *EVENT_SEQ_NO*
    - *CONT_STAT*
    - *AUTH_STAT*
    - *CPTY_ID*
    - *CPTY_AC_NO*
    - *INSTRNO*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*

NET_AMT_REALISED
OTHER_BANK_CHARGES
COLL_BNK_CIF
BOOKINGDATE
MATURITY_DATE
VALUE_DATE
TRACK_LIMIT
CREDIT_LINE
FINANCING
INT_REM
INSTRUMENT_CODE
INSTR_DESC
PRCD
PRODDESC
USERREF_NO
XREF
COUNTRPRYNAM
LCY_AMT
COLLBANKNAME
PAYDUEDATE
CONREF
EVENTSEQ
PARTYTYP
ADDRESS
PARTYADDR2
PARTYADDR3
PARTYADDR4
WALKINCUSTFLG
COLLEC_BANK_CIF
COLLBNKNAME
DISCOUNT_AMOUNT
DB_ACC_REAL
BULK_INPUT_REF_NO
DRAWEE_BNK_NAME
AUTOLIQD
OTHER_PARTY_ID
VERSION_NO
TRANSITDAYS
MARGIN_PERCENTAGE
ACC_BRANCH
OTHR_PARTY_NAME
ACCBRN
TXNUDFDETAILS
  FLDNAME

- *FLDVAL*
- *Charges*
  - *CONREFNO*
  - *Charge-Association*
    - *COMPNT*
    - *CREATESN*
    - *RULE*
    - *WAIVER*
    - *DISACCRAPPL*
    - *ACCRREQD*
    - *DESC*
  - *Charge-Application*
    - *CREATESN*
    - *COMPNT*
    - *TGCCY*
    - *TGAMT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *DISACCRAPPL*
    - *WAIVER*
    - *LIQDIND*
  - *Charge-Liquidation*
    - *ESN*
    - *COMPNT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *LIQDSTAT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*

COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9

- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*

BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1

BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*

ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Clpref
CONTREFNNO

CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM
PAYMENT_MODE
LOANVALDATE
MATURITY_DATE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESTVERSIONNO

Attribute	Description
Name	LATESTVERSIONNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTATUS

Attribute	Description
Name	AUTHSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CURR_EVENT_CODE

Attribute	Description
Name	CURR_EVENT_CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONT_STAT

Attribute	**Description**	
Name	CONT_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,L,R,H,

TOP

AUTH_STAT

Attribute	**Description**	
Name	AUTH_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U,

TOP

CPTY_ID

Attribute	**Description**	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

INT_REM

Attribute	Description	
Name	INT_REM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INSTRUMENT_CODE

Attribute	Description	
Name	INSTRUMENT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTR_DESC

Attribute	Description	
Name	INSTR_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRCD

Attribute	Description	
Name	PRCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLBANKNAME

Attribute	Description
Name	COLLBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREF

Attribute	Description
Name	CONREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

ADDRESS

Attribute	Description
Name	ADDRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTYADDR2

Attribute	Description
Name	PARTYADDR2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTYADDR3

Attribute	Description
Name	PARTYADDR3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTYADDR4

Attribute	Description
Name	PARTYADDR4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINCUSTFLG

Attribute	Description
Name	WALKINCUSTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COLLEC_BANK_CIF

Attribute	Description
Name	COLLEC_BANK_CIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BULK_INPUT_REF_NO

Attribute	Description
Name	BULK_INPUT_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

OTHER_PARTY_ID

Attribute	Description
Name	OTHER_PARTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACC_BRANCH

Attribute	Description
Name	ACC_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	**Description**	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	**Description**	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	**Description**	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	**Description**	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Clpref

Attribute	**Description**	
Name	Clpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNNO

Attribute	**Description**	
Name	CONTREFNNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CONTRACT_CCY

Attribute	**Description**	
Name	CONTRACT_CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TENOR

Attribute	Description
Name	TENOR

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description

Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.108.4.RB-AuthorizeOvscheckspay-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONTREFNO*
    - *Main-IO*
      - *CONTREFNO*
      - *CPTY_AC_NO*
      - *NET_AMT_REALISED*
      - *COLL_BNK_CIF*
      - *BOOKINGDATE*
      - *TRACK_LIMIT*
      - *CREDIT_LINE*
      - *FINANCING*
      - *INT_REM*
      - *COUNTRPRYNAM*
      - *LCY_AMT*
      - *COLLBANKNAME*
      - *PAYDUEDATE*
      - *ADDRESS*
      - *PARTYADDR2*

PARTYADDR3
PARTYADDR4
COLLEC_BANK_CIF
COLLBNKNAME
DISCOUNT_AMOUNT
DRAWEE_BNK_NAME
AUTOLIQD
OTHER_PARTY_ID
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_AC_NO

Attribute	**Description**	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

NET_AMT_REALISED

Attribute	**Description**	
Name	NET_AMT_REALISED	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COLL_BNK_CIF

Attribute	**Description**	
Name	COLL_BNK_CIF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BOOKINGDATE

Attribute	**Description**	
Name	BOOKINGDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CREDIT_LINE

Attribute	Description
Name	CREDIT_LINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,N,F</td></tr></table>

TOP

INT_REM

Attribute	Description
Name	INT_REM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLBANKNAME

Attribute	Description
Name	COLLBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDRESS

Attribute	Description
Name	ADDRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTYADDR2

Attribute	Description
Name	PARTYADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYADDR3

Attribute	Description
Name	PARTYADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYADDR4

Attribute	Description
Name	PARTYADDR4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COLLEC_BANK_CIF

Attribute	Description
Name	COLLEC_BANK_CIF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

OTHER_PARTY_ID

Attribute	Description
Name	OTHER_PARTY_ID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.109.AuthorizeOvsrealizecontract

AuthorizeOvsrealizecontract

2.109.1.RB-AuthorizeOvsrealizecontract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *INSTRNO*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *CPTY_AC_NO*
    - *NET_AMT_REALISED*

OTHER_BANK_CHARGES
COLL_BNK_CIF
COLBANK_REFNO
VALUE_DATE
REMARKS
DB_ACC_REAL
COLL_BNK_NAME
ACCBRN
ACC_BRANCH
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*

TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4

ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*

ENVCONT5

Lcl_Clearing

FREETXT1

FREETXT2

FREETXT3

PMNTCD

ADDINFOSORBNET

SNDRCUSTNAME1

SNDRCUSTNAME2

SNDRCUSTNAME3

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

Charges

CONREFNO

Charge-Association

COMPNT

CREATESN

RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3

TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5

COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	Description	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CTR_PRTY_NAME

Attribute	Description

Name	CTR_PRTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>L,A,H,</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,U,</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COLL_BNK_CIF

Attribute	**Description**	
Name	COLL_BNK_CIF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

COLBANK_REFNO

Attribute	**Description**	
Name	COLBANK_REFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VALUE_DATE

Attribute	**Description**	
Name	VALUE_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACC_BRANCH

Attribute	Description
Name	ACC_BRANCH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Con

Attribute	Description
Name	Con

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	**Description**	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	**Description**	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1

Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2

Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5

Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1

Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	**Description**	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	**Description**	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application

Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	**Description**	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	Description	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	Description	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	Description	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	Description	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Compmisdetails

Attribute	**Description**	
Name	Compmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Fundmisdetails

Attribute	**Description**	
Name	Fundmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

TXNUDFDETAILS

Attribute	**Description**	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL

Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.109.2.RB-AuthorizeOvsrealizecontract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.109.3.RB-AuthorizeOvsrealizecontract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *INSTRNO*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *MAKER*
    - *MAKERDTSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *CPTY_AC_NO*
    - *NET_AMT_REALISED*
    - *OTHER_BANK_CHARGES*
    - *COLL_BNK_CIF*
    - *COLBANK_REFNO*

VALUE_DATE
REMARKS
DB_ACC_REAL
COLL_BNK_NAME
ACCBRN
ACC_BRANCH
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*

CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3

ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*

FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL

- *ACCRREQD*
- *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*
  - *COSTCD4*
  - *COSTCD5*
  - *TXNMIS1*
  - *TXNMIS10*
  - *TXNMIS2*
  - *TXNMIS3*
  - *TXNMIS4*
  - *TXNMIS5*
  - *TXNMIS6*

TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8

COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CTR_PRTY_NAME

Attribute	Description
Name	CTR_PRTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,A,H,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

NET_AMT_REALISED

Attribute	Description
Name	NET_AMT_REALISED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

OTHER_BANK_CHARGES

Attribute	Description
Name	OTHER_BANK_CHARGES
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLL_BNK_CIF

Attribute	Description
Name	COLL_BNK_CIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

COLBANK_REFNO

Attribute	Description
Name	COLBANK_REFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DB_ACC_REAL

Attribute	Description
Name	DB_ACC_REAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC_BRANCH

Attribute	Description
Name	ACC_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SUPRESS

Attribute	**Description**	
Name	SUPRESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number

Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String

Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description

Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	**Description**	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	**Description**	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1

Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5

Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description

Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	**Description**	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS2

Attribute	**Description**	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.109.4.RB-AuthorizeOvsrealizecontract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONREFNUM*
    - *Main-IO*
      - *CONREFNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.110.AuthorizePDCContract

AuthorizePDCContract

2.110.1.RB-AuthorizePDCContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNUM*
    - *BOOKDT*
    - *USERREFNUM*
    - *XREF*
    - *PRDCD*
    - *MODCOD*
    - *UDSTAT*
    - *STOPDT*
    - *EVENTCD*
    - *INSTRUCODE*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *INSTRNO*
    - *INSTRDATE*
    - *CONTCCY*

AMOUNT
LCYAMT
OTHRPTYIDEN
BOOKINGDT
ACTDATE
VALUEDT
TRACKLIMIT
CRDLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
DISCOUNTAMT
COLLATERAL
COLLATVAL
COLLPOOL
ISRBNK
ISSUERBRN
CLGBANK
CLGBRN
SECTORCD
ENDPNT
INTREMARKS
ACCBRN
ROUTNO
DRACCBRN
INSTR_DESC
PRDDESC
CPTYNAME
OTHERPARTYNAME
ISSBANKNAME
ISSBRNCNAME
CLEARBANKNAME
AUTOLIQD
CLEARBRNCNAME
MAKER
MAKDTTIME
CHKR
CHKDTTIME
CONST
AUTHSTAT
BATCHREFENUM
BATCHSEQNO
DRACCREAL
CLGPRD

- *Party-Details*
  - *PRTYTYP*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *PARTYREFNO*
  - *COUNTRYCD*
  - *ADDLN1*
  - *ADDLN2*
  - *ADDLN3*
  - *ADDLN4*
  - *PARTLANG*
- *Settlements*
  - *CONREFNO*
  - *Contract-Settlement*
    - *IBANACNO*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *COMPNT*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *ACCCCY*
    - *EXRATE*
    - *NETIND*
    - *ERICCY*
    - *ERIAMT*
    - *GENMSG*
    - *RATECD*
    - *CLEARNW*
    - *COVERBY*
    - *RTGSPMNT*
    - *BANKPRIOR*
    - *RTGSNW*
    - *PAYBY*
    - *TRANSTYP*
    - *INSTYP*
    - *INSNO*
    - *CHGDET*
    - *PAYMNTDET1*
    - *PAYMNTDET2*
    - *PAYMNTDET3*
    - *PAYMNTDET4*
    - *SNDTRRCVINFO1*
    - *SNDTRRCVINFO2*

SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC

COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*

SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Charges

CONREFNO

Charge-Association

COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC

Charge-Application

CREATESN
COMPNT
TGCCY
TGAMT

CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10

COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5

- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Con

- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Clpref

- *CONTREFNNO*
- *CONTRACT_CCY*
- *LATEVNSEQNO*
- *PRD*
- *PRDDESC*
- *COUNTERPARTY*
- *CURRENCY*
- *TENOR*
- *UNITS*
- *LOAN_CONREFNO*
- *RATECODE*
- *EXCHANGERATE*
- *RATE_TYPE*
- *MAXIMUM*
- *MINIMUM*
- *PAYMENT_MODE*
- *LOANVALDATE*
- *MATURITY_DATE*
- *Ude*
  - *USERDEID*

UDEDESC
RATEASOF
USAGE
USERDEVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description

Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USERREFNUM

Attribute	Description
Name	USERREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MODCOD

Attribute	Description
Name	MODCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BOOKINGDT

Attribute	Description
Name	BOOKINGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACTDATE

Attribute	Description
Name	ACTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRDLINE

Attribute	Description
Name	CRDLINE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,F,N

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLATVAL

Attribute	Description
Name	COLLATVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ISRBNK

Attribute	Description
Name	ISRBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ISSUERBRN

Attribute	Description
Name	ISSUERBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBANK

Attribute	Description
Name	CLGBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBRN

Attribute	Description
Name	CLGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ENDPNT

Attribute	Description
Name	ENDPNT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTREMARKS

Attribute	**Description**	
Name	INTREMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ROUTNO

Attribute	**Description**	
Name	ROUTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	27

TOP

DRACCBRN

Attribute	**Description**	
Name	DRACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INSTR_DESC

Attribute	**Description**	
Name	INSTR_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTYNAME

Attribute	**Description**	
Name	CPTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYNAME

Attribute	**Description**	
Name	OTHERPARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ISSBANKNAME

Attribute	Description
Name	ISSBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ISSBRNCNAME

Attribute	Description
Name	ISSBRNCNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CLEARBANKNAME

Attribute	Description
Name	CLEARBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLEARBRNCNAME

Attribute	Description
Name	CLEARBRNCNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,H,R,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DRACCREAL

Attribute	**Description**	
Name	DRACCREAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CLGPRD

Attribute	**Description**	
Name	CLGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Party-Details

Attribute	**Description**	
Name	Party-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRTYTYP

Attribute	**Description**	
Name	PRTYTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	DRAWER,PAYEE

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTYREFNO

Attribute	Description
Name	PARTYREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ADDLN1

Attribute	Description

Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTLANG

Attribute	Description
Name	PARTLANG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Settlements

Attribute	**Description**	
Name	Settlements	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Settlement

Attribute	**Description**	
Name	Contract-Settlement	
Datatype		
Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	**Description**	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description	
Name	SNDRCUSTNAME2	
Datatype	String	
Description	Indicates Sender Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	**Description**
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	**Description**
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	**Description**
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	**Description**
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,S</td></tr></table>

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.110.2.RB-AuthorizePDCContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.110.3.RB-AuthorizePDCContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNUM*
    - *BOOKDT*
    - *USERREFNUM*
    - *XREF*
    - *PRDCD*
    - *MODCOD*
    - *UDSTAT*
    - *STOPDT*
    - *EVENTCD*
    - *INSTRUCODE*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *INSTRNO*
    - *INSTRDATE*
    - *CONTCCY*
    - *AMOUNT*
    - *LCYAMT*
    - *OTHRPTYIDEN*

BOOKINGDT
ACTDATE
VALUEDT
TRACKLIMIT
CRDLINE
OTHPARTYLIMIT
MARGINPERC
FINANCING
DISCOUNTAMT
COLLATERAL
COLLATVAL
COLLPOOL
ISRBNK
ISSUERBRN
CLGBANK
CLGBRN
SECTORCD
ENDPNT
INTREMARKS
ACCBRN
ROUTNO
DRACCBRN
INSTR_DESC
PRDDESC
CPTYNAME
OTHERPARTYNAME
ISSBANKNAME
ISSBRNCNAME
CLEARBANKNAME
AUTOLIQD
CLEARBRNCNAME
MAKER
MAKDTTIME
CHKR
CHKDTTIME
CONST
AUTHSTAT
BATCHREFENUM
BATCHSEQNO
DRACCREAL
CLGPRD
Party-Details
  PRTYTYP
  PARTYIDEN

- *PARTYNAME*
- *PARTYREFNO*
- *COUNTRYCD*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ADDLN4*
- *PARTLANG*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*

COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID

POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*

RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL

- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*
  - *COSTCD4*
  - *COSTCD5*
  - *TXNMIS1*
  - *TXNMIS10*
  - *TXNMIS2*
  - *TXNMIS3*
  - *TXNMIS4*
  - *TXNMIS5*
  - *TXNMIS6*
  - *TXNMIS7*
  - *TXNMIS8*
  - *TXNMIS9*
  - *MISGRPCOMP*
  - *MISGRPTXN*
  - *COMPMIS1*
  - *COMPMIS10*
  - *COMPMIS2*
  - *COMPMIS3*
  - *COMPMIS4*

COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8

- FUNMIS9
- FUNMIS10
- Txnmisdetails
- Compmisdetails
- Fundmisdetails

TXNUDFDETAILS

- FLDNAME
- FLDVAL

Con

- CONTREFNO
- EVENTSEQ
- Adv
  - ADVNAME
  - SUPRESS
  - PRIOR
  - MEDM
  - PARTYIDEN
  - PARTYNAME
  - CHGREQ
  - PARTTYP

Clpref

- CONTREFNNO
- CONTRACT_CCY
- LATEVNSEQNO
- PRD
- PRDDESC
- COUNTERPARTY
- CURRENCY
- TENOR
- UNITS
- LOAN_CONREFNO
- RATECODE
- EXCHANGERATE
- RATE_TYPE
- MAXIMUM
- MINIMUM
- PAYMENT_MODE
- LOANVALDATE
- MATURITY_DATE
- Ude
  - USERDEID
  - UDEDESC
  - RATEASOF
  - USAGE

USERDEVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USERREFNUM

Attribute	Description
Name	USERREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MODCOD

Attribute	Description
Name	MODCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BOOKINGDT

Attribute	Description
Name	BOOKINGDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACTDATE

Attribute	Description
Name	ACTDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,F,N

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLATVAL

Attribute	Description
Name	COLLATVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ISRBNK

Attribute	Description
Name	ISRBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ISSUERBRN

Attribute	Description	
Name	ISSUERBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CLGBANK

Attribute	Description	
Name	CLGBANK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CLGBRN

Attribute	Description	
Name	CLGBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SECTORCD

Attribute	Description	
Name	SECTORCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

ENDPNT

Attribute	Description
Name	ENDPNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>27</td></tr></table>

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ISSBANKNAME

Attribute	**Description**	
Name	ISSBANKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ISSBRNCNAME

Attribute	**Description**	
Name	ISSBRNCNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CLEARBANKNAME

Attribute	**Description**	
Name	CLEARBANKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

AUTOLIQD

Attribute	**Description**	
Name	AUTOLIQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CLEARBRNCNAME

Attribute	Description
Name	CLEARBRNCNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,H,R,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CLGPRD

Attribute	Description
Name	CLGPRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / DRAWER,PAYEE

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYREFNO

Attribute	Description
Name	PARTYREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTLANG

Attribute	Description
Name	PARTLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String

Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,S</td></tr></table>

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.110.4.RB-AuthorizePDCContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNUM*
    - *Contract-Details-IO*
      - *CONREFNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.111.AuthorizePDR

AuthorizePDR

2.111.1.RB-AuthorizePDR-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-Full*
    - *CONREFNUM*
    - *CPTYIDEN*
    - *INSTRNO*
    - *INSTRDATE*
    - *CCY*
    - *AMNT*
    - *OTHRBNKCHARGS*
    - *OTHRPTYIDEN*
    - *BANKCODE*
    - *BOOKINGDATE*
    - *DISCOUNTAMT*
    - *CHARGESCLAIMED*
    - *COLLATVAL*
    - *REASONCODE*
    - *REASON*

DISHONORDATE
PROTESTDATE
RETURNDATE
REMARK
MAKER
MAKDTTIME
CHKR
CHKDTTIME
CONTSTAT
AUTHSTAT
CPTYNAME
OTHERPARTYNAME
BANKNAME
NOTARYDESCRIPTION
NOTARYCODE
Charges
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements
- *CONREFNO*
- *Contract-Settlement*

IBANACNO
CUSTSPREAD
SPREADDEFN
COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4

INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5

DRCRIND

Settlement-Detail

- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*
- *SUPPID*
- *PAYERID*

PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9

MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1

FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INSTRNO

Attribute	**Description**	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRDATE

Attribute	**Description**	
Name	INSTRDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNT

Attribute	**Description**	
Name	AMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BANKCODE

Attribute	Description
Name	BANKCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHARGESCLAIMED

Attribute	Description
Name	CHARGESCLAIMED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLATVAL

Attribute	Description
Name	COLLATVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REASONCODE

Attribute	Description
Name	REASONCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REASON

Attribute	Description
Name	REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DISHONORDATE

Attribute	Description
Name	DISHONORDATE
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PROTESTDATE

Attribute	**Description**	
Name	PROTESTDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RETURNDATE

Attribute	**Description**	
Name	RETURNDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REMARK

Attribute	**Description**	
Name	REMARK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	**Description**
Name	MAKDTTIME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

CPTYNAME

Attribute	**Description**	
Name	CPTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYNAME

Attribute	**Description**	
Name	OTHERPARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BANKNAME

Attribute	**Description**	
Name	BANKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

NOTARYDESCRIPTION

Attribute	**Description**	
Name	NOTARYDESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT

Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.111.2.RB-AuthorizePDR-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-IO*
    - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.111.3.RB-AuthorizePDR-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-Full*
    - *CONREFNUM*
    - *CPTYIDEN*
    - *INSTRNO*
    - *INSTRDATE*
    - *CCY*
    - *AMNT*
    - *OTHRBNKCHARGS*
    - *OTHRPTYIDEN*
    - *BANKCODE*
    - *BOOKINGDATE*
    - *DISCOUNTAMT*
    - *CHARGESCLAIMED*
    - *COLLATVAL*
    - *REASONCODE*
    - *REASON*
    - *DISHONORDATE*
    - *PROTESTDATE*
    - *RETURNDATE*

REMARK
MAKER
MAKDTTIME
CHKR
CHKDTTIME
CONTSTAT
AUTHSTAT
CPTYNAME
OTHERPARTYNAME
BANKNAME
NOTARYDESCRIPTION
NOTARYCODE
Charges
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*

COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3

INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
  INSTRCD1

INSTRCD2
INSTRCD3
INSTRCD4
ITIMEIND1
ITIMEIND2
ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID

SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1

COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4

FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BANKCODE

Attribute	Description
Name	BANKCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHARGESCLAIMED

Attribute	**Description**	
Name	CHARGESCLAIMED	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COLLATVAL

Attribute	**Description**	
Name	COLLATVAL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REASONCODE

Attribute	**Description**	
Name	REASONCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

REASON

Attribute	**Description**	
Name	REASON	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DISHONORDATE

Attribute	**Description**
Name	DISHONORDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RETURNDATE

Attribute	Description
Name	RETURNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARK

Attribute	Description
Name	REMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,H</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BANKNAME

Attribute	Description
Name	BANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

NOTARYDESCRIPTION

Attribute	Description
Name	NOTARYDESCRIPTION
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	**Description**	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Settlements

Attribute	**Description**	
Name	Settlements	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Settlement

Attribute	**Description**	
Name	Contract-Settlement	
Datatype		
Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	**Description**

Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String

Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description

Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	**Description**	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	**Description**	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	**Description**	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2

Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3

Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	**Description**	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	**Description**	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	**Description**	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2

Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	**Description**	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**	
Name	REGREP2	
Datatype	String	
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**
Name	REGREP3
Datatype	String

Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2

Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	**Description**	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	**Description**	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO2

Attribute	**Description**	
Name	SNDRRCVRINFO2	
Datatype	String	
Description	Indicates Sender Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS6

Attribute	**Description**	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	**Description**	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr></table>

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.111.4.RB-AuthorizePDR-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Master-PK*
      - *CONREFNUM*
    - *Master-IO*
      - *CONREFNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Master-PK

Attribute	Description
Name	Master-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.112.AuthorizeStatusChg

AuthorizeStatusChg

2.112.1.RB-AuthorizeStatusChg-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-Full*
    - *CONTREFNO*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *INSTRUMENTNO*
    - *INSTRULOC*
    - *INSTRSTAT*
    - *INSTRDATE*
    - *CCY*
    - *CONTRACTAMT*
    - *OTHRPTYIDEN*
    - *BANKCD*
    - *BRNCODE*
    - *BOOKINGDATE*
    - *MATURITYDATE*
    - *MAKER*

MAKDTTIME
CHKR
CHKDTTIME
CONTSTAT
AUTHSTAT
INTREMRKS
DRACFORREALISATION
COUNTRPRYNAM
OTHERPARTYNAME
BNKNAME
BRNNAME

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 20

TOP

INSTRUMENTNO

Attribute	Description
Name	INSTRUMENTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRULOC

Attribute	Description
Name	INSTRULOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRSTAT

Attribute	Description
Name	INSTRSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONTRACTAMT

Attribute	Description
Name	CONTRACTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BANKCD

Attribute	Description
Name	BANKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DRACFORREALISATION

Attribute	Description
Name	DRACFORREALISATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

2.112.2.RB-AuthorizeStatusChg-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-IO*
    - *CONTREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.112.3.RB-AuthorizeStatusChg-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-Full*
    - *CONTREFNO*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *INSTRUMENTNO*
    - *INSTRULOC*
    - *INSTRSTAT*
    - *INSTRDATE*
    - *CCY*
    - *CONTRACTAMT*
    - *OTHRPTYIDEN*
    - *BANKCD*
    - *BRNCODE*
    - *BOOKINGDATE*
    - *MATURITYDATE*
    - *MAKER*
    - *MAKDTTIME*
    - *CHKR*
    - *CHKDTTIME*

CONTSTAT
AUTHSTAT
INTREMRKS
DRACFORREALISATION
COUNTRPRYNAM
OTHERPARTYNAME
BNKNAME
BRNNAME
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENTNO

Attribute	Description
Name	INSTRUMENTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRULOC

Attribute	Description
Name	INSTRULOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRSTAT

Attribute	Description
Name	INSTRSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONTRACTAMT

Attribute	Description
Name	CONTRACTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BANKCD

Attribute	Description
Name	BANKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DRACFORREALISATION

Attribute	**Description**	
Name	DRACFORREALISATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	**Description**	
Name	COUNTRPRYNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYNAME

Attribute	**Description**	
Name	OTHERPARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BNKNAME

Attribute	**Description**	
Name	BNKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.112.4.RB-AuthorizeStatusChg-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Master-PK*
      - *CONTREFNO*
    - *Master-IO*
      - *CONTREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Master-PK

Attribute	Description
Name	Master-PK
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.113.Authorizefcychecksinput

Authorizefcychecksinput

2.113.1.RB-Authorizefcychecksinput-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *INSTRUMENT_CODE*
    - *INSTR_DESC*
    - *PRODUCT_CODE*
    - *PRDDESC*
    - *CONREFNUM*
    - *USERREF_NO1*
    - *XREF*
    - *BATCHREFENUM*
    - *BATCH_SEQ_NO*
    - *CASHLETTER_REFNUM*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *CPTY_AC_NO*
    - *ACC_BRANCH*
    - *INSTRUMENTNORE*

INSTRUMENT_DATE
CURRENCY
AMNT
LCY_AMOUNT
NOSTROACC
ACCBRN
COLLECTINGBANKCIF
COLL_BNK_NAME
BOOKINGDATE
VAL_DATE_BANK
VALUE_DATE_CUST
OTHR_PARTY_NAME
DRAWEE_BNK_NAME
AUTOLIQD
INTREMRKS
FINANCING
MARGIN_PERCENTAGE
TRACK_LIMIT
CRLINE
DISCOUNTAMT
MAKER
MAKDTTIME
CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
VERSION_NO
LATVERNO
Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*

RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1

ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*

REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3

- REPRES4
- RCVRACC

Charges

- CONREFNO
- Charge-Association
  - COMPNT
  - CREATESN
  - RULE
  - WAIVER
  - DISACCRAPPL
  - ACCRREQD
  - DESC
- Charge-Application
  - CREATESN
  - COMPNT
  - TGCCY
  - TGAMT
  - CHRGCCY
  - CHRGAMT
  - DISACCRAPPL
  - WAIVER
  - LIQDIND
- Charge-Liquidation
  - ESN
  - COMPNT
  - CHRGCCY
  - CHRGAMT
  - LIQDSTAT

Misdetails

- CONREFNO
- LATESN
- MISGRP
- RELACC
- RELETED_REFERENCE
- MISHEAD
- RATEFLG
- POOLCD
- REFINANCE_RATE
- REFRATETYP
- PROCALCMTH
- REFSPREAD
- REFRATECD
- COSTCD1
- COSTCD2

COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8

TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Clpref
CONTREFNNO
CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM

PAYMENT_MODE
LOANVALDATE
MATURITY_DATE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PRODUCT_CODE

Attribute	Description

Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BATCHREFENUM

Attribute	**Description**	
Name	BATCHREFENUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BATCH_SEQ_NO

Attribute	**Description**	
Name	BATCH_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CASHLETTER_REFNUM

Attribute	**Description**	
Name	CASHLETTER_REFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	**Description**	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CTR_PRTY_NAME

Attribute	Description	
Name	CTR_PRTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTY_AC_NO

Attribute	Description	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACC_BRANCH

Attribute	Description	
Name	ACC_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INSTRUMENTNORE

Attribute	Description	
Name	INSTRUMENTNORE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLECTINGBANKCIF

Attribute	Description
Name	COLLECTINGBANKCIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

MARGIN_PERCENTAGE

Attribute	Description
Name	MARGIN_PERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRLINE

Attribute	Description
Name	CRLINE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,L,R,H,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String

Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

2.113.2.RB-Authorizefcychecksinput-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONREFNUM*
    - *USERREF_NO1*
    - *XREF*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1
Datatype	String
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.113.3.RB-Authorizefcychecksinput-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *INSTRUMENT_CODE*
    - *INSTR_DESC*
    - *PRODUCT_CODE*
    - *PRDDESC*
    - *CONREFNUM*
    - *USERREF_NO1*
    - *XREF*
    - *BATCHREFENUM*
    - *BATCH_SEQ_NO*
    - *CASHLETTER_REFNUM*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *CPTY_AC_NO*
    - *ACC_BRANCH*
    - *INSTRUMENTNORE*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*

LCY_AMOUNT
NOSTROACC
ACCBRN
COLLECTINGBANKCIF
COLL_BNK_NAME
BOOKINGDATE
VAL_DATE_BANK
VALUE_DATE_CUST
OTHR_PARTY_NAME
DRAWEE_BNK_NAME
AUTOLIQD
INTREMRKS
FINANCING
MARGIN_PERCENTAGE
TRACK_LIMIT
CRLINE
DISCOUNTAMT
MAKER
MAKDTTIME
CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
VERSION_NO
LATVERNO
Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*

RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4

BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*

ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*

TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1

- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Clpref

- *CONTREFNNO*
- *CONTRACT_CCY*
- *LATEVNSEQNO*
- *PRD*
- *PRDDESC*
- *COUNTERPARTY*
- *CURRENCY*
- *TENOR*
- *UNITS*
- *LOAN_CONREFNO*
- *RATECODE*
- *EXCHANGERATE*
- *RATE_TYPE*
- *MAXIMUM*
- *MINIMUM*
- *PAYMENT_MODE*
- *LOANVALDATE*
- *MATURITY_DATE*

Ude

USERDEID

UDEDESC

RATEASOF

USAGE

USERDEVAL

Con

CONTREFNO

EVENTSEQ

Adv

ADVNAME

SUPRESS

PRIOR

MEDM

PARTYIDEN

PARTYNAME

CHGREQ

PARTTYP

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PRODUCT_CODE

Attribute	Description
Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BATCH_SEQ_NO

Attribute	Description
Name	BATCH_SEQ_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CASHLETTER_REFNUM

Attribute	Description
Name	CASHLETTER_REFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CTR_PRTY_NAME

Attribute	**Description**	
Name	CTR_PRTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTY_AC_NO

Attribute	**Description**	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACC_BRANCH

Attribute	**Description**	
Name	ACC_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INSTRUMENTNORE

Attribute	**Description**	
Name	INSTRUMENTNORE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

COLLECTINGBANKCIF

Attribute	**Description**	
Name	COLLECTINGBANKCIF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

COLL_BNK_NAME

Attribute	**Description**	
Name	COLL_BNK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BOOKINGDATE

Attribute	**Description**	
Name	BOOKINGDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTREMRKS

Attribute	**Description**	
Name	INTREMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,N,F

TOP

MARGIN_PERCENTAGE

Attribute	**Description**	
Name	MARGIN_PERCENTAGE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRACK_LIMIT

Attribute	**Description**	
Name	TRACK_LIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CRLINE

Attribute	Description
Name	CRLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,L,R,H,

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATVERNO

Attribute	**Description**	
Name	LATVERNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Settlements

Attribute	**Description**	
Name	Settlements	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Settlement

Attribute	**Description**	
Name	Contract-Settlement	
Datatype		
Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	**Description**
Name	IBANACNO
Datatype	String

Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description	
Name	TRANMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	Description	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	Description	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	Description	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.113.4.RB-Authorizefcychecksinput-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONREFNUM*
      - *USERREF_NO1*
      - *XREF*
    - *Main-IO*
      - *CONREFNUM*
      - *USERREF_NO1*
      - *XREF*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF_NO1

Attribute	Description
Name	USERREF_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description

Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.114.CloseBulkInwardInput

CloseBulkInwardInput

2.114.1.RB-CloseBulkInwardInput-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Full*
    - *INSTRUMENT_CODE*
    - *BATCHREFENUM*
    - *PRDCD*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *ACCBRN*
    - *CPTY_AC_NO*
    - *OTHRPTY_ID*
    - *OTHRPTY_NM*
    - *BNKCD*
    - *BRNCODE*
    - *CORRESPBNK*
    - *CORRESPACNO*
    - *BOKNGDT*
    - *PROTEST*

AUTOLIQD
NOOFINSTRUMENTS
ACFORREALISATION
CRACCBRN
CCY
PROCESSSTAT
EVENTSEQNO
ESNLOG
RECORDSTAT
AUTHSTAT
CHKR
CHKDTTIME
BULKREF
MAKER
MAKDTTIME
Bulkinput-Detail
- *CONREFNUM*
- *INSTRNO*
- *INSTRU_DATE*
- *CURRENCY*
- *AMNT*
- *REMITBANK_REF*
- *REM_BNK_DT*
- *LCY_AMOUNTT*
- *MATURITYDATE*
- *GRACEDAYS*
- *REMARKS*
- *PROCESSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Full

Attribute	Description
Name	Bulk-Input-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRDCD

Attribute	**Description**	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CPTY_ID

Attribute	**Description**	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_NAME

Attribute	**Description**	
Name	CPTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CPTY_AC_NO

Attribute	**Description**	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

OTHRPTY_ID

Attribute	**Description**	
Name	OTHRPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OTHRPTY_NM

Attribute	**Description**	
Name	OTHRPTY_NM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BNKCD

Attribute	**Description**	
Name	BNKCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CORRESPBNK

Attribute	Description
Name	CORRESPBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CORRESPACNO

Attribute	Description
Name	CORRESPACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRACCBRN

Attribute	Description
Name	CRACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESNLOG

Attribute	Description
Name	ESNLOG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BULKREF

Attribute	Description
Name	BULKREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	**Description**	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Bulkinput-Detail

Attribute	**Description**	
Name	Bulkinput-Detail	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CONREFNUM

Attribute	**Description**	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

REM_BNK_DT

Attribute	**Description**	
Name	REM_BNK_DT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCY_AMOUNTT

Attribute	**Description**	
Name	LCY_AMOUNTT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MATURITYDATE

Attribute	**Description**	
Name	MATURITYDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GRACEDAYS

Attribute	**Description**	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PROCESSTAT

Attribute	**Description**
Name	PROCESSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,U,F,H

TOP

2.114.2.RB-CloseBulkInwardInput-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-IO*
    - *BATCHREFENUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.114.3.RB-CloseBulkInwardInput-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Full*
    - *INSTRUMENT_CODE*
    - *BATCHREFENUM*
    - *PRDCD*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *ACCBRN*
    - *CPTY_AC_NO*
    - *OTHRPTY_ID*
    - *OTHRPTY_NM*
    - *BNKCD*
    - *BRNCODE*
    - *CORRESPBNK*
    - *CORRESPACNO*
    - *BOKNGDT*
    - *PROTEST*
    - *AUTOLIQD*
    - *NOOFINSTRUMENTS*
    - *ACFORREALISATION*

CRACCBRN
CCY
PROCESSSTAT
EVENTSEQNO
ESNLOG
RECORDSTAT
AUTHSTAT
CHKR
CHKDTTIME
BULKREF
MAKER
MAKDTTIME
Bulkinput-Detail
CONREFNUM
INSTRNO
INSTRU_DATE
CURRENCY
AMNT
REMITBANK_REF
REM_BNK_DT
LCY_AMOUNTT
MATURITYDATE
GRACEDAYS
REMARKS
PROCESSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Full

Attribute	Description
Name	Bulk-Input-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CPTY_AC_NO

Attribute	**Description**	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

OTHRPTY_ID

Attribute	**Description**	
Name	OTHRPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OTHRPTY_NM

Attribute	**Description**	
Name	OTHRPTY_NM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BNKCD

Attribute	**Description**	
Name	BNKCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CORRESPBNK

Attribute	Description
Name	CORRESPBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CORRESPACNO

Attribute	Description
Name	CORRESPACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CRACCBRN

Attribute	Description
Name	CRACCBRN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PROCESSSTAT

Attribute	**Description**	
Name	PROCESSSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,U

TOP

EVENTSEQNO

Attribute	**Description**	
Name	EVENTSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ESNLOG

Attribute	**Description**	
Name	ESNLOG	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,O,C</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BULKREF

Attribute	Description
Name	BULKREF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Bulkinput-Detail

Attribute	Description
Name	Bulkinput-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REM_BNK_DT

Attribute	Description
Name	REM_BNK_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCY_AMOUNTT

Attribute	Description
Name	LCY_AMOUNTT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,U,F,H

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description

Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.114.4.RB-CloseBulkInwardInput-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Input-PK*
      - *BATCHREFENUM*
    - *Bulk-Input-IO*
      - *BATCHREFENUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Input-PK

Attribute	Description
Name	Bulk-Input-PK
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.115.CloseBulkInwardPDR

CloseBulkInwardPDR

2.115.1.RB-CloseBulkInwardPDR-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Pdr-Full*
    - *BATCHREFENUM*
    - *BULKPDRREFNO*
    - *ACTION*
    - *PRDTY*
    - *CPTY_ID*
    - *COUNTRPRYNAM*
    - *OTHRPTY_ID*
    - *OTHRPTY_NM*
    - *BANK_CODE*
    - *BANK_NAME*
    - *BRNCODE*
    - *BRANCH_NAME*
    - *VALUEDT*
    - *RETURN_DATE*
    - *PROCESSSTAT*

SEQNO
ESN
TXNSTAT
AUTHSTAT
CHKR
CHKDTTIME
MKRID
MKRDT
Bulk-Pdr-Detail
- *CONREFNUM*
- *INSTRNO*
- *INSTRUMENT_DATE*
- *REMITBANK_REF*
- *CCY*
- *AMT*
- *REASON_CODE*
- *DISHONOUR_DATE*
- *NOTARYCODE*
- *PROTESTDATE*
- *REMARKS*
- *PROCESSSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Pdr-Full

Attribute	Description
Name	Bulk-Pdr-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

PRDTY

Attribute	Description
Name	PRDTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHRPTY_ID

Attribute	Description
Name	OTHRPTY_ID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OTHRPTY_NM

Attribute	**Description**	
Name	OTHRPTY_NM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BANK_CODE

Attribute	**Description**	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANK_NAME

Attribute	**Description**	
Name	BANK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNCODE

Attribute	**Description**	
Name	BRNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRANCH_NAME

Attribute	Description
Name	BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,P

TOP

SEQNO

Attribute	Description
Name	SEQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MKRID

Attribute	Description
Name	MKRID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKRDT

Attribute	Description
Name	MKRDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Bulk-Pdr-Detail

Attribute	Description
Name	Bulk-Pdr-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFNUM

Attribute	Description

Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DISHONOUR_DATE

Attribute	Description
Name	DISHONOUR_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,P

TOP

2.115.2.RB-CloseBulkInwardPDR-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Pdr-IO*
    - *BULKPDRREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Pdr-IO

Attribute	Description
Name	Bulk-Pdr-IO
Datatype	
Description	

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.115.3.RB-CloseBulkInwardPDR-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Pdr-Full*
    - *BATCHREFENUM*
    - *BULKPDRREFNO*
    - *ACTION*
    - *PRDTY*
    - *CPTY_ID*
    - *COUNTRPRYNAM*
    - *OTHRPTY_ID*
    - *OTHRPTY_NM*
    - *BANK_CODE*
    - *BANK_NAME*
    - *BRNCODE*
    - *BRANCH_NAME*
    - *VALUEDT*
    - *RETURN_DATE*
    - *PROCESSSTAT*
    - *SEQNO*
    - *ESN*
    - *TXNSTAT*

AUTHSTAT
CHKR
CHKDTTIME
MKRID
MKRDT
Bulk-Pdr-Detail
CONREFNUM
INSTRNO
INSTRUMENT_DATE
REMITBANK_REF
CCY
AMT
REASON_CODE
DISHONOUR_DATE
NOTARYCODE
PROTESTDATE
REMARKS
PROCESSSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Pdr-Full

Attribute	Description
Name	Bulk-Pdr-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

PRDTY

Attribute	Description	
Name	PRDTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CPTY_ID

Attribute	Description	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHRPTY_ID

Attribute	Description
Name	OTHRPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

OTHRPTY_NM

Attribute	Description
Name	OTHRPTY_NM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BANK_CODE

Attribute	Description
Name	BANK_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BANK_NAME

Attribute	Description
Name	BANK_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BRNCODE

Attribute	Description
Name	BRNCODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRANCH_NAME

Attribute	Description
Name	BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,P

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	**Description**
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MKRID

Attribute	**Description**
Name	MKRID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MKRDT

Attribute	**Description**
Name	MKRDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Bulk-Pdr-Detail

Attribute	**Description**
Name	Bulk-Pdr-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CCY

Attribute	Description
Name	CCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DISHONOUR_DATE

Attribute	Description
Name	DISHONOUR_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,P

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.115.4.RB-CloseBulkInwardPDR-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Pdr-PK*
      - *BULKPDRREFNO*
    - *Bulk-Pdr-IO*
      - *BULKPDRREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Pdr-PK

Attribute	Description
Name	Bulk-Pdr-PK
Datatype	
Description	

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Pdr-IO

Attribute	Description
Name	Bulk-Pdr-IO
Datatype	
Description	

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.116.CloseBulkInwardReal

CloseBulkInwardReal

2.116.1.RB-CloseBulkInwardReal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liq-Master-Full*
    - *BATCHREFENUM*
    - *BULKREALNUM*
    - *CPTY_ID*
    - *DUP_CPTY_NAME*
    - *CCY*
    - *OTHRPTY_ID*
    - *OTHRPTY_NM*
    - *BNKCD*
    - *BANK_NAME*
    - *BRNCODE*
    - *BRNNAME*
    - *CPTY_AC_NO*
    - *ACFORREALISATION*
    - *CRACCBRN*
    - *VALUEDATE*

ACCBRN
CORRESPBNK
CORRESPACNO
NETAMT_REAL
PROCESSSTAT
EVENTSEQNO
RECORDSTAT
AUTHSTAT
CKRID
CHKDTTIME
BULKREF
ESN
MAKER
MAKDTTIME
Liq-Detail
- *CONREFNUM*
- *INSTRNO*
- *INSTRUMENT_DATE*
- *REMITBANK_REF*
- *REM_BNK_DT*
- *AMNT*
- *REMRKS*
- *PROCESSSTAT*
- *OTHRBNKCHARGS*
- *NETAMT_REAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liq-Master-Full

Attribute	Description
Name	Liq-Master-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

DUP_CPTY_NAME

Attribute	Description	
Name	DUP_CPTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

OTHRPTY_ID

Attribute	Description	
Name	OTHRPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OTHRPTY_NM

Attribute	Description
Name	OTHRPTY_NM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BANK_NAME

Attribute	Description
Name	BANK_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BRNNAME

Attribute	Description
Name	BRNNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRACCBRN

Attribute	Description
Name	CRACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CORRESPBNK

Attribute	**Description**	
Name	CORRESPBNK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CORRESPACNO

Attribute	**Description**	
Name	CORRESPACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

NETAMT_REAL

Attribute	**Description**	
Name	NETAMT_REAL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,P</td></tr></table>

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,O,C</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

CKRID

Attribute	Description
Name	CKRID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BULKREF

Attribute	**Description**	
Name	BULKREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	Description	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Liq-Detail

Attribute	Description	
Name	Liq-Detail	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CONREFNUM

Attribute	Description	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INSTRNO

Attribute	Description	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRUMENT_DATE

Attribute	Description

Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REM_BNK_DT

Attribute	Description
Name	REM_BNK_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,P</td></tr></table>

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NETAMT_REAL

Attribute	Description
Name	NETAMT_REAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.116.2.RB-CloseBulkInwardReal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liq-Master-IO*
    - *BULKREALNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liq-Master-IO

Attribute	Description
Name	Liq-Master-IO
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.116.3.RB-CloseBulkInwardReal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liq-Master-Full*
    - *BATCHREFENUM*
    - *BULKREALNUM*
    - *CPTY_ID*
    - *DUP_CPTY_NAME*
    - *CCY*
    - *OTHRPTY_ID*
    - *OTHRPTY_NM*
    - *BNKCD*
    - *BANK_NAME*
    - *BRNCODE*
    - *BRNNAME*
    - *CPTY_AC_NO*
    - *ACFORREALISATION*
    - *CRACCBRN*
    - *VALUEDATE*
    - *ACCBRN*
    - *CORRESPBNK*
    - *CORRESPACNO*

NETAMT_REAL
PROCESSSTAT
EVENTSEQNO
RECORDSTAT
AUTHSTAT
CKRID
CHKDTTIME
BULKREF
ESN
MAKER
MAKDTTIME
Liq-Detail
CONREFNUM
INSTRNO
INSTRUMENT_DATE
REMITBANK_REF
REM_BNK_DT
AMNT
REMRKS
PROCESSSTAT
OTHRBNKCHARGS
NETAMT_REAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liq-Master-Full

Attribute	Description
Name	Liq-Master-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DUP_CPTY_NAME

Attribute	Description
Name	DUP_CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OTHRPTY_ID

Attribute	Description
Name	OTHRPTY_ID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OTHRPTY_NM

Attribute	**Description**	
Name	OTHRPTY_NM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BNKCD

Attribute	**Description**	
Name	BNKCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANK_NAME

Attribute	**Description**	
Name	BANK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNCODE

Attribute	**Description**	
Name	BRNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTY_AC_NO

Attribute	**Description**	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACFORREALISATION

Attribute	**Description**	
Name	ACFORREALISATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CRACCBRN

Attribute	**Description**	
Name	CRACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CORRESPBNK

Attribute	Description
Name	CORRESPBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CORRESPACNO

Attribute	Description
Name	CORRESPACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

NETAMT_REAL

Attribute	Description
Name	NETAMT_REAL

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,P

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CKRID

Attribute	Description
Name	CKRID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BULKREF

Attribute	Description
Name	BULKREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Liq-Detail

Attribute	Description
Name	Liq-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

REM_BNK_DT

Attribute	Description
Name	REM_BNK_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,P

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETAMT_REAL

Attribute	Description
Name	NETAMT_REAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description

Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.116.4.RB-CloseBulkInwardReal-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Liq-Master-PK*
      - *BULKREALNUM*
    - *Liq-Master-IO*
      - *BULKREALNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Liq-Master-PK

Attribute	Description
Name	Liq-Master-PK
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Liq-Master-IO

Attribute	Description
Name	Liq-Master-IO
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.117.CloseBulkOutClearing

CloseBulkOutClearing

2.117.1.RB-CloseBulkOutClearing-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Full*
    - *CRDLINE*
    - *OTHPARTYLIMIT*
    - *MARGINPERC*
    - *FINANCING*
    - *COLLATERAL*
    - *COLLPOOL*
    - *INSTRUCODE*
    - *PRDCODE*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *CURRENCY*
    - *OTHRPTYIDEN*
    - *DRACCREAL*
    - *NOOFINSTRUMENTS*
    - *CLGPRD*

ISRBNK
ISSUERBRN
CLRBNK
CLGBRN
SECTORCR
ENDPOINT
ROUTNO
CHECKINSERIES
FIRSTINSTRNO
BOOKINGDATE
TRACKLIMIT
INSTRUMENT_DESCRIPTION
INSTRDESC
COUNTRPRYNAM
OTHERPARTYNAME
ISSBANKNAME
ISSBRNCNAME
CLEARBANKNAME
CLEARBRNCNAME
BATCHREFENUM
ACCBRN
PROCESSTAT
CONTSTATUS
AUTSTAT
CHECKER
CHECKERDT
VERSIONNUM
MKER
MAKERDT
DRACCBRN
VERNUMBER
Input-Detail
- *CONREFNUM*
- *INSTRNO*
- *INSTRDATE*
- *LCYAMT*
- *AMNT*
- *VALUEDATE*
- *DISCAMT*
- *COLLTVAL*
- *INTREMRKS*
- *PROCESSSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Full

Attribute	Description
Name	Bulk-Input-Full
Datatype	
Description	

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,F,N

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTYACCNUM

Attribute	Description	
Name	CPTYACCNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

OTHRPTYIDEN

Attribute	Description	
Name	OTHRPTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

DRACCREAL

Attribute	Description	
Name	DRACCREAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CLGPRD

Attribute	Description
Name	CLGPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ISRBNK

Attribute	Description
Name	ISRBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ISSUERBRN

Attribute	Description
Name	ISSUERBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CLRBNK

Attribute	Description
Name	CLRBNK

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBRN

Attribute	Description
Name	CLGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SECTORCR

Attribute	Description
Name	SECTORCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

CHECKINSERIES

Attribute	Description
Name	CHECKINSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FIRSTINSTRNO

Attribute	Description
Name	FIRSTINSTRNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description
Name	INSTRUMENT_DESCRIPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

INSTRDESC

Attribute	Description
Name	INSTRDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ISSBANKNAME

Attribute	Description
Name	ISSBANKNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSBRNCNAME

Attribute	Description
Name	ISSBRNCNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CLEARBANKNAME

Attribute	Description
Name	CLEARBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CLEARBRNCNAME

Attribute	Description
Name	CLEARBRNCNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PROCESSTAT

Attribute	**Description**	
Name	PROCESSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,E

TOP

CONTSTATUS

Attribute	**Description**	
Name	CONTSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,O,C

TOP

AUTSTAT

Attribute	**Description**	
Name	AUTSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDT

Attribute	Description
Name	CHECKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

VERSIONNUM

Attribute	Description
Name	VERSIONNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MKER

Attribute	Description
Name	MKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VERNUMBER

Attribute	Description
Name	VERNUMBER
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Input-Detail

Attribute	Description
Name	Input-Detail
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTVAL

Attribute	Description
Name	COLLTVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,F,H

TOP

2.117.2.RB-CloseBulkOutClearing-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-IO*
    - *BATCHREFENUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.117.3.RB-CloseBulkOutClearing-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Full*
    - *CRDLINE*
    - *OTHPARTYLIMIT*
    - *MARGINPERC*
    - *FINANCING*
    - *COLLATERAL*
    - *COLLPOOL*
    - *INSTRUCODE*
    - *PRDCODE*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *CURRENCY*
    - *OTHRPTYIDEN*
    - *DRACCREAL*
    - *NOOFINSTRUMENTS*
    - *CLGPRD*
    - *ISRBNK*
    - *ISSUERBRN*
    - *CLRBNK*

- CLGBRN
- SECTORCR
- ENDPOINT
- ROUTNO
- CHECKINSERIES
- FIRSTINSTRNO
- BOOKINGDATE
- TRACKLIMIT
- INSTRUMENT_DESCRIPTION
- INSTRDESC
- COUNTRPRYNAM
- OTHERPARTYNAME
- ISSBANKNAME
- ISSBRNCNAME
- CLEARBANKNAME
- CLEARBRNCNAME
- BATCHREFENUM
- ACCBRN
- PROCESSTAT
- CONTSTATUS
- AUTSTAT
- CHECKER
- CHECKERDT
- VERSIONNUM
- MKER
- MAKERDT
- DRACCBRN
- VERNUMBER
- Input-Detail
  - CONREFNUM
  - INSTRNO
  - INSTRDATE
  - LCYAMT
  - AMNT
  - VALUEDATE
  - DISCAMT
  - COLLTVAL
  - INTREMRKS
  - PROCESSSTAT
- FCUBS_ERROR_RESP
  - ERROR
    - ECODE
    - EDESC
- FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Full

Attribute	Description

Name	Bulk-Input-Full
Datatype	
Description	

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,F,N

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTYIDEN

Attribute	Description

Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

NOOFINSTRUMENTS

Attribute	**Description**	
Name	NOOFINSTRUMENTS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

CLGPRD

Attribute	**Description**	
Name	CLGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ISRBNK

Attribute	**Description**	
Name	ISRBNK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ISSUERBRN

Attribute	**Description**	
Name	ISSUERBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CLRBNK

Attribute	Description
Name	CLRBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBRN

Attribute	Description
Name	CLGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SECTORCR

Attribute	Description
Name	SECTORCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>27</td></tr></table>

TOP

CHECKINSERIES

Attribute	Description
Name	CHECKINSERIES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

FIRSTINSTRNO

Attribute	Description
Name	FIRSTINSTRNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description	
Name	INSTRUMENT_DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INSTRDESC

Attribute	Description	
Name	INSTRDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

OTHERPARTYNAME

Attribute	Description	
Name	OTHERPARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ISSBANKNAME

Attribute	Description	
Name	ISSBANKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ISSBRNCNAME

Attribute	Description	
Name	ISSBRNCNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CLEARBANKNAME

Attribute	Description	
Name	CLEARBANKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CLEARBRNCNAME

Attribute	Description	
Name	CLEARBRNCNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,E</td></tr></table>

TOP

CONTSTATUS

Attribute	Description
Name	CONTSTATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,O,C</td></tr></table>

TOP

AUTSTAT

Attribute	Description
Name	AUTSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDT

Attribute	Description
Name	CHECKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VERSIONNUM

Attribute	Description
Name	VERSIONNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MKER

Attribute	Description
Name	MKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

VERNUMBER

Attribute	Description
Name	VERNUMBER
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Input-Detail

Attribute	Description
Name	Input-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description

Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTVAL

Attribute	Description
Name	COLLTVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,S,F,H

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.117.4.RB-CloseBulkOutClearing-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Input-PK*
      - *BATCHREFENUM*
    - *Bulk-Input-IO*
      - *BATCHREFENUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Input-PK

Attribute	Description
Name	Bulk-Input-PK
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.118.AuthorizeBulkInwardInput

AuthorizeBulkInwardInput

2.118.1.RB-AuthorizeBulkInwardInput-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Full*
    - *INSTRUMENT_CODE*
    - *BATCHREFENUM*
    - *PRDCD*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *ACCBRN*
    - *CPTY_AC_NO*
    - *OTHRPTY_ID*
    - *OTHRPTY_NM*
    - *BNKCD*
    - *BRNCODE*
    - *CORRESPBNK*
    - *CORRESPACNO*
    - *BOKNGDT*
    - *PROTEST*

AUTOLIQD
NOOFINSTRUMENTS
ACFORREALISATION
CRACCBRN
CCY
PROCESSSTAT
EVENTSEQNO
ESNLOG
RECORDSTAT
AUTHSTAT
CHKR
CHKDTTIME
BULKREF
MAKER
MAKDTTIME
Bulkinput-Detail
- *CONREFNUM*
- *INSTRNO*
- *INSTRU_DATE*
- *CURRENCY*
- *AMNT*
- *REMITBANK_REF*
- *REM_BNK_DT*
- *LCY_AMOUNTT*
- *MATURITYDATE*
- *GRACEDAYS*
- *REMARKS*
- *PROCESSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Full

Attribute	Description
Name	Bulk-Input-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRDCD

Attribute	**Description**	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CPTY_ID

Attribute	**Description**	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_NAME

Attribute	**Description**	
Name	CPTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

OTHRPTY_ID

Attribute	Description
Name	OTHRPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OTHRPTY_NM

Attribute	Description
Name	OTHRPTY_NM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CORRESPBNK

Attribute	Description
Name	CORRESPBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CORRESPACNO

Attribute	Description
Name	CORRESPACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRACCBRN

Attribute	Description
Name	CRACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESNLOG

Attribute	Description
Name	ESNLOG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BULKREF

Attribute	Description
Name	BULKREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	**Description**	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Bulkinput-Detail

Attribute	**Description**	
Name	Bulkinput-Detail	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CONREFNUM

Attribute	**Description**	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

REM_BNK_DT

Attribute	**Description**	
Name	REM_BNK_DT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCY_AMOUNTT

Attribute	**Description**	
Name	LCY_AMOUNTT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MATURITYDATE

Attribute	**Description**	
Name	MATURITYDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GRACEDAYS

Attribute	**Description**	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,U,F,H

TOP

2.118.2.RB-AuthorizeBulkInwardInput-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-IO*
    - *BATCHREFENUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.118.3.RB-AuthorizeBulkInwardInput-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Full*
    - *INSTRUMENT_CODE*
    - *BATCHREFENUM*
    - *PRDCD*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *ACCBRN*
    - *CPTY_AC_NO*
    - *OTHRPTY_ID*
    - *OTHRPTY_NM*
    - *BNKCD*
    - *BRNCODE*
    - *CORRESPBNK*
    - *CORRESPACNO*
    - *BOKNGDT*
    - *PROTEST*
    - *AUTOLIQD*
    - *NOOFINSTRUMENTS*
    - *ACFORREALISATION*

CRACCBRN
CCY
PROCESSSTAT
EVENTSEQNO
ESNLOG
RECORDSTAT
AUTHSTAT
CHKR
CHKDTTIME
BULKREF
MAKER
MAKDTTIME
Bulkinput-Detail
CONREFNUM
INSTRNO
INSTRU_DATE
CURRENCY
AMNT
REMITBANK_REF
REM_BNK_DT
LCY_AMOUNTT
MATURITYDATE
GRACEDAYS
REMARKS
PROCESSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Full

Attribute	Description
Name	Bulk-Input-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CPTY_AC_NO

Attribute	**Description**
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

OTHRPTY_ID

Attribute	**Description**
Name	OTHRPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OTHRPTY_NM

Attribute	**Description**
Name	OTHRPTY_NM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BNKCD

Attribute	**Description**
Name	BNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CORRESPBNK

Attribute	Description
Name	CORRESPBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CORRESPACNO

Attribute	Description
Name	CORRESPACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CRACCBRN

Attribute	Description
Name	CRACCBRN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PROCESSSTAT

Attribute	**Description**	
Name	PROCESSSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,U

TOP

EVENTSEQNO

Attribute	**Description**	
Name	EVENTSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ESNLOG

Attribute	**Description**	
Name	ESNLOG	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,O,C</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BULKREF

Attribute	Description
Name	BULKREF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Bulkinput-Detail

Attribute	Description
Name	Bulkinput-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REM_BNK_DT

Attribute	Description
Name	REM_BNK_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCY_AMOUNTT

Attribute	Description
Name	LCY_AMOUNTT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,U,F,H

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description

Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.118.4.RB-AuthorizeBulkInwardInput-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Input-PK*
      - *BATCHREFENUM*
    - *Bulk-Input-IO*
      - *BATCHREFENUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Input-PK

Attribute	Description
Name	Bulk-Input-PK
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.119.AuthorizeBulkInwardPDR

AuthorizeBulkInwardPDR

2.119.1.RB-AuthorizeBulkInwardPDR-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Pdr-Full*
    - *BATCHREFENUM*
    - *BULKPDRREFNO*
    - *ACTION*
    - *PRDTY*
    - *CPTY_ID*
    - *COUNTRPRYNAM*
    - *OTHRPTY_ID*
    - *OTHRPTY_NM*
    - *BANK_CODE*
    - *BANK_NAME*
    - *BRNCODE*
    - *BRANCH_NAME*
    - *VALUEDT*
    - *RETURN_DATE*
    - *PROCESSSTAT*

SEQNO
ESN
TXNSTAT
AUTHSTAT
CHKR
CHKDTTIME
MKRID
MKRDT
Bulk-Pdr-Detail
- *CONREFNUM*
- *INSTRNO*
- *INSTRUMENT_DATE*
- *REMITBANK_REF*
- *CCY*
- *AMT*
- *REASON_CODE*
- *DISHONOUR_DATE*
- *NOTARYCODE*
- *PROTESTDATE*
- *REMARKS*
- *PROCESSSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Pdr-Full

Attribute	Description
Name	Bulk-Pdr-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

PRDTY

Attribute	Description
Name	PRDTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHRPTY_ID

Attribute	Description
Name	OTHRPTY_ID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OTHRPTY_NM

Attribute	**Description**	
Name	OTHRPTY_NM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BANK_CODE

Attribute	**Description**	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANK_NAME

Attribute	**Description**	
Name	BANK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNCODE

Attribute	**Description**	
Name	BRNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRANCH_NAME

Attribute	Description
Name	BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,P

TOP

SEQNO

Attribute	Description
Name	SEQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MKRID

Attribute	Description
Name	MKRID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKRDT

Attribute	Description
Name	MKRDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Bulk-Pdr-Detail

Attribute	Description
Name	Bulk-Pdr-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFNUM

Attribute	Description

Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DISHONOUR_DATE

Attribute	Description
Name	DISHONOUR_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,P

TOP

2.119.2.RB-AuthorizeBulkInwardPDR-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Pdr-IO*
    - *BULKPDRREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Pdr-IO

Attribute	Description
Name	Bulk-Pdr-IO
Datatype	
Description	

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.119.3.RB-AuthorizeBulkInwardPDR-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Pdr-Full*
    - *BATCHREFENUM*
    - *BULKPDRREFNO*
    - *ACTION*
    - *PRDTY*
    - *CPTY_ID*
    - *COUNTRPRYNAM*
    - *OTHRPTY_ID*
    - *OTHRPTY_NM*
    - *BANK_CODE*
    - *BANK_NAME*
    - *BRNCODE*
    - *BRANCH_NAME*
    - *VALUEDT*
    - *RETURN_DATE*
    - *PROCESSSTAT*
    - *SEQNO*
    - *ESN*
    - *TXNSTAT*

AUTHSTAT
CHKR
CHKDTTIME
MKRID
MKRDT
Bulk-Pdr-Detail
CONREFNUM
INSTRNO
INSTRUMENT_DATE
REMITBANK_REF
CCY
AMT
REASON_CODE
DISHONOUR_DATE
NOTARYCODE
PROTESTDATE
REMARKS
PROCESSSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Pdr-Full

Attribute	Description
Name	Bulk-Pdr-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

PRDTY

Attribute	Description	
Name	PRDTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CPTY_ID

Attribute	Description	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHRPTY_ID

Attribute	Description
Name	OTHRPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

OTHRPTY_NM

Attribute	Description
Name	OTHRPTY_NM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BANK_CODE

Attribute	Description
Name	BANK_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BANK_NAME

Attribute	Description
Name	BANK_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BRNCODE

Attribute	Description
Name	BRNCODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRANCH_NAME

Attribute	Description
Name	BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,P

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MKRID

Attribute	**Description**	
Name	MKRID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MKRDT

Attribute	**Description**	
Name	MKRDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Bulk-Pdr-Detail

Attribute	**Description**	
Name	Bulk-Pdr-Detail	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CONREFNUM

Attribute	Description	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INSTRNO

Attribute	Description	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRUMENT_DATE

Attribute	Description	
Name	INSTRUMENT_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REMITBANK_REF

Attribute	Description	
Name	REMITBANK_REF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CCY

Attribute	Description
Name	CCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DISHONOUR_DATE

Attribute	Description
Name	DISHONOUR_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: U,P

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.119.4.RB-AuthorizeBulkInwardPDR-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Pdr-PK*
      - *BULKPDRREFNO*
    - *Bulk-Pdr-IO*
      - *BULKPDRREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Pdr-PK

Attribute	Description
Name	Bulk-Pdr-PK
Datatype	
Description	

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Pdr-IO

Attribute	Description
Name	Bulk-Pdr-IO
Datatype	
Description	

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.120.AuthorizeBulkInwardReal

AuthorizeBulkInwardReal

2.120.1.RB-AuthorizeBulkInwardReal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liq-Master-Full*
    - *BATCHREFENUM*
    - *BULKREALNUM*
    - *CPTY_ID*
    - *DUP_CPTY_NAME*
    - *CCY*
    - *OTHRPTY_ID*
    - *OTHRPTY_NM*
    - *BNKCD*
    - *BANK_NAME*
    - *BRNCODE*
    - *BRNNAME*
    - *CPTY_AC_NO*
    - *ACFORREALISATION*
    - *CRACCBRN*
    - *VALUEDATE*

ACCBRN
CORRESPBNK
CORRESPACNO
NETAMT_REAL
PROCESSSTAT
EVENTSEQNO
RECORDSTAT
AUTHSTAT
CKRID
CHKDTTIME
BULKREF
ESN
MAKER
MAKDTTIME
Liq-Detail
- *CONREFNUM*
- *INSTRNO*
- *INSTRUMENT_DATE*
- *REMITBANK_REF*
- *REM_BNK_DT*
- *AMNT*
- *REMRKS*
- *PROCESSSTAT*
- *OTHRBNKCHARGS*
- *NETAMT_REAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liq-Master-Full

Attribute	Description
Name	Liq-Master-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

DUP_CPTY_NAME

Attribute	Description	
Name	DUP_CPTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

OTHRPTY_ID

Attribute	Description	
Name	OTHRPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OTHRPTY_NM

Attribute	Description
Name	OTHRPTY_NM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BANK_NAME

Attribute	Description
Name	BANK_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BRNNAME

Attribute	Description
Name	BRNNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRACCBRN

Attribute	Description
Name	CRACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CORRESPBNK

Attribute	**Description**	
Name	CORRESPBNK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CORRESPACNO

Attribute	**Description**	
Name	CORRESPACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

NETAMT_REAL

Attribute	**Description**	
Name	NETAMT_REAL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,P</td></tr></table>

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,O,C</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

CKRID

Attribute	Description
Name	CKRID
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BULKREF

Attribute	Description
Name	BULKREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Liq-Detail

Attribute	Description	
Name	Liq-Detail	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CONREFNUM

Attribute	Description	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INSTRNO

Attribute	Description	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRUMENT_DATE

Attribute	Description

Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REM_BNK_DT

Attribute	Description
Name	REM_BNK_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,P</td></tr></table>

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NETAMT_REAL

Attribute	Description
Name	NETAMT_REAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.120.2.RB-AuthorizeBulkInwardReal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liq-Master-IO*
    - *BULKREALNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liq-Master-IO

Attribute	Description
Name	Liq-Master-IO
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.120.3.RB-AuthorizeBulkInwardReal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liq-Master-Full*
    - *BATCHREFENUM*
    - *BULKREALNUM*
    - *CPTY_ID*
    - *DUP_CPTY_NAME*
    - *CCY*
    - *OTHRPTY_ID*
    - *OTHRPTY_NM*
    - *BNKCD*
    - *BANK_NAME*
    - *BRNCODE*
    - *BRNNAME*
    - *CPTY_AC_NO*
    - *ACFORREALISATION*
    - *CRACCBRN*
    - *VALUEDATE*
    - *ACCBRN*
    - *CORRESPBNK*
    - *CORRESPACNO*

NETAMT_REAL
PROCESSSTAT
EVENTSEQNO
RECORDSTAT
AUTHSTAT
CKRID
CHKDTTIME
BULKREF
ESN
MAKER
MAKDTTIME
Liq-Detail
CONREFNUM
INSTRNO
INSTRUMENT_DATE
REMITBANK_REF
REM_BNK_DT
AMNT
REMRKS
PROCESSSTAT
OTHRBNKCHARGS
NETAMT_REAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liq-Master-Full

Attribute	Description
Name	Liq-Master-Full
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DUP_CPTY_NAME

Attribute	Description
Name	DUP_CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OTHRPTY_ID

Attribute	Description
Name	OTHRPTY_ID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OTHRPTY_NM

Attribute	**Description**	
Name	OTHRPTY_NM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BNKCD

Attribute	**Description**	
Name	BNKCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANK_NAME

Attribute	**Description**	
Name	BANK_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNCODE

Attribute	**Description**	
Name	BRNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTY_AC_NO

Attribute	**Description**	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACFORREALISATION

Attribute	**Description**	
Name	ACFORREALISATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CRACCBRN

Attribute	**Description**	
Name	CRACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CORRESPBNK

Attribute	Description
Name	CORRESPBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CORRESPACNO

Attribute	Description
Name	CORRESPACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

NETAMT_REAL

Attribute	Description
Name	NETAMT_REAL

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,P

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CKRID

Attribute	Description
Name	CKRID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BULKREF

Attribute	Description
Name	BULKREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Liq-Detail

Attribute	Description
Name	Liq-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMITBANK_REF

Attribute	Description
Name	REMITBANK_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

REM_BNK_DT

Attribute	Description
Name	REM_BNK_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PROCESSSTAT

Attribute	**Description**	
Name	PROCESSSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,P

TOP

OTHRBNKCHARGS

Attribute	**Description**	
Name	OTHRBNKCHARGS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETAMT_REAL

Attribute	**Description**	
Name	NETAMT_REAL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**

Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.120.4.RB-AuthorizeBulkInwardReal-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Liq-Master-PK*
      - *BULKREALNUM*
    - *Liq-Master-IO*
      - *BULKREALNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Liq-Master-PK

Attribute	Description
Name	Liq-Master-PK
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Liq-Master-IO

Attribute	Description
Name	Liq-Master-IO
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.121.AuthorizeBulkOutClearing

AuthorizeBulkOutClearing

2.121.1.RB-AuthorizeBulkOutClearing-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Full*
    - *CRDLINE*
    - *OTHPARTYLIMIT*
    - *MARGINPERC*
    - *FINANCING*
    - *COLLATERAL*
    - *COLLPOOL*
    - *INSTRUCODE*
    - *PRDCODE*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *CURRENCY*
    - *OTHRPTYIDEN*
    - *DRACCREAL*
    - *NOOFINSTRUMENTS*
    - *CLGPRD*

ISRBNK
ISSUERBRN
CLRBNK
CLGBRN
SECTORCR
ENDPOINT
ROUTNO
CHECKINSERIES
FIRSTINSTRNO
BOOKINGDATE
TRACKLIMIT
INSTRUMENT_DESCRIPTION
INSTRDESC
COUNTRPRYNAM
OTHERPARTYNAME
ISSBANKNAME
ISSBRNCNAME
CLEARBANKNAME
CLEARBRNCNAME
BATCHREFENUM
ACCBRN
PROCESSTAT
CONTSTATUS
AUTSTAT
CHECKER
CHECKERDT
VERSIONNUM
MKER
MAKERDT
DRACCBRN
VERNUMBER
Input-Detail
- *CONREFNUM*
- *INSTRNO*
- *INSTRDATE*
- *LCYAMT*
- *AMNT*
- *VALUEDATE*
- *DISCAMT*
- *COLLTVAL*
- *INTREMRKS*
- *PROCESSSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Full

Attribute	Description
Name	Bulk-Input-Full
Datatype	
Description	

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,F,N

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTYACCNUM

Attribute	Description	
Name	CPTYACCNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

OTHRPTYIDEN

Attribute	Description	
Name	OTHRPTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

DRACCREAL

Attribute	Description	
Name	DRACCREAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CLGPRD

Attribute	Description
Name	CLGPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ISRBNK

Attribute	Description
Name	ISRBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ISSUERBRN

Attribute	Description
Name	ISSUERBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLRBNK

Attribute	Description
Name	CLRBNK

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBRN

Attribute	Description
Name	CLGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SECTORCR

Attribute	Description
Name	SECTORCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	27

TOP

CHECKINSERIES

Attribute	**Description**	
Name	CHECKINSERIES	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FIRSTINSTRNO

Attribute	**Description**	
Name	FIRSTINSTRNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKINGDATE

Attribute	**Description**	
Name	BOOKINGDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRACKLIMIT

Attribute	**Description**	
Name	TRACKLIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description
Name	INSTRUMENT_DESCRIPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

INSTRDESC

Attribute	Description
Name	INSTRDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ISSBANKNAME

Attribute	Description
Name	ISSBANKNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSBRNCNAME

Attribute	Description
Name	ISSBRNCNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CLEARBANKNAME

Attribute	Description
Name	CLEARBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CLEARBRNCNAME

Attribute	Description
Name	CLEARBRNCNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,E

TOP

CONTSTATUS

Attribute	Description
Name	CONTSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,O,C

TOP

AUTSTAT

Attribute	Description
Name	AUTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDT

Attribute	Description
Name	CHECKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

VERSIONNUM

Attribute	Description
Name	VERSIONNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MKER

Attribute	Description
Name	MKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VERNUMBER

Attribute	Description
Name	VERNUMBER
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Input-Detail

Attribute	Description
Name	Input-Detail
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTVAL

Attribute	Description
Name	COLLTVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,F,H

TOP

2.121.2.RB-AuthorizeBulkOutClearing-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Bulk-Input-IO*
  - *BATCHREFENUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.121.3.RB-AuthorizeBulkOutClearing-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Full*
    - *CRDLINE*
    - *OTHPARTYLIMIT*
    - *MARGINPERC*
    - *FINANCING*
    - *COLLATERAL*
    - *COLLPOOL*
    - *INSTRUCODE*
    - *PRDCODE*
    - *CPTYIDEN*
    - *CPTYACCNUM*
    - *CURRENCY*
    - *OTHRPTYIDEN*
    - *DRACCREAL*
    - *NOOFINSTRUMENTS*
    - *CLGPRD*
    - *ISRBNK*
    - *ISSUERBRN*
    - *CLRBNK*

- *CLGBRN*
- *SECTORCR*
- *ENDPOINT*
- *ROUTNO*
- *CHECKINSERIES*
- *FIRSTINSTRNO*
- *BOOKINGDATE*
- *TRACKLIMIT*
- *INSTRUMENT_DESCRIPTION*
- *INSTRDESC*
- *COUNTRPRYNAM*
- *OTHERPARTYNAME*
- *ISSBANKNAME*
- *ISSBRNCNAME*
- *CLEARBANKNAME*
- *CLEARBRNCNAME*
- *BATCHREFENUM*
- *ACCBRN*
- *PROCESSTAT*
- *CONTSTATUS*
- *AUTSTAT*
- *CHECKER*
- *CHECKERDT*
- *VERSIONNUM*
- *MKER*
- *MAKERDT*
- *DRACCBRN*
- *VERNUMBER*
- *Input-Detail*
  - *CONREFNUM*
  - *INSTRNO*
  - *INSTRDATE*
  - *LCYAMT*
  - *AMNT*
  - *VALUEDATE*
  - *DISCAMT*
  - *COLLTVAL*
  - *INTREMRKS*
  - *PROCESSSTAT*

FCUBS_ERROR_RESP

- *ERROR*
  - *ECODE*
  - *EDESC*

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Full

Attribute	Description

Name	Bulk-Input-Full
Datatype	
Description	

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTHPARTYLIMIT

Attribute	Description
Name	OTHPARTYLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,F,N

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTYIDEN

Attribute	Description

Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTYACCNUM

Attribute	Description
Name	CPTYACCNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

NOOFINSTRUMENTS

Attribute	**Description**	
Name	NOOFINSTRUMENTS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

CLGPRD

Attribute	**Description**	
Name	CLGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ISRBNK

Attribute	**Description**	
Name	ISRBNK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ISSUERBRN

Attribute	**Description**	
Name	ISSUERBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CLRBNK

Attribute	Description
Name	CLRBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLGBRN

Attribute	Description
Name	CLGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SECTORCR

Attribute	Description
Name	SECTORCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>27</td></tr></table>

TOP

CHECKINSERIES

Attribute	Description
Name	CHECKINSERIES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

FIRSTINSTRNO

Attribute	Description
Name	FIRSTINSTRNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description
Name	INSTRUMENT_DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSTRDESC

Attribute	Description
Name	INSTRDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ISSBANKNAME

Attribute	Description
Name	ISSBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSBRNCNAME

Attribute	Description
Name	ISSBRNCNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CLEARBANKNAME

Attribute	Description
Name	CLEARBANKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CLEARBRNCNAME

Attribute	Description
Name	CLEARBRNCNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,E</td></tr></table>

TOP

CONTSTATUS

Attribute	Description
Name	CONTSTATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,O,C</td></tr></table>

TOP

AUTSTAT

Attribute	Description
Name	AUTSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDT

Attribute	Description
Name	CHECKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VERSIONNUM

Attribute	Description
Name	VERSIONNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MKER

Attribute	Description
Name	MKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

VERNUMBER

Attribute	Description
Name	VERNUMBER
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Input-Detail

Attribute	Description
Name	Input-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description

Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTVAL

Attribute	Description
Name	COLLTVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,S,F,H

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.121.4.RB-AuthorizeBulkOutClearing-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Input-PK*
      - *BATCHREFENUM*
    - *Bulk-Input-IO*
      - *BATCHREFENUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Input-PK

Attribute	Description
Name	Bulk-Input-PK
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.122.AuthorizeBulkPDRContract

AuthorizeBulkPDRContract

2.122.1.RB-AuthorizeBulkPDRContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulkpdr-Full*
    - *BANK_CODE*
    - *BRNCODE*
    - *BANKNAME*
    - *BRNNAME*
    - *ACTION*
    - *DISPATCHLOTREFNO*
    - *BULKPDRREFNO*
    - *PROCESSTAT*
    - *AUTHSTAT*
    - *CHKR*
    - *CHKDTTIME*
    - *EVSEQNO*
    - *MAKER*
    - *MAKDTTIME*
    - *RECORDSTAT*

ESNUI

Bulkpdrdetail

CONREFNUM

ACC_CCY

AMNT

DISHONOUR_DATE

NOTARYCODE

PROTESTDATE

INTREMRKS

DISHONOUR_REASON

RETURN_DATE

CPTYIDEN

OTHRPTYIDEN

CPTYNAME

OTHERPARTYNAME

INSTRNO

PROCESSSTAT

PRDTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulkpdr-Full

Attribute	Description
Name	Bulkpdr-Full
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description	Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BRNCODE

Attribute	Description	
Name	BRNCODE	
Datatype	String	
Description	Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BANKNAME

Attribute	Description	
Name	BANKNAME	
Datatype	String	
Description	Bank Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

DISPATCHLOTREFNO

Attribute	**Description**	
Name	DISPATCHLOTREFNO	
Datatype	String	
Description	Dispatch Lot Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BULKPDRREFNO

Attribute	**Description**	
Name	BULKPDRREFNO	
Datatype	String	
Description	Bulk Dishonor / Protest / Return Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PROCESSTAT

Attribute	Description	
Name	PROCESSTAT	
Datatype	String	
Description	Process Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,U

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

CHKR

Attribute	Description	
Name	CHKR	
Datatype	String	
Description	Checker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	Description	
Name	CHKDTTIME	
Datatype	String	
Description	Date Time	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

EVSEQNO

Attribute	Description
Name	EVSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	Date Time
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	Record Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,O,C</td></tr></table>

TOP

ESNUI

Attribute	Description
Name	ESNUI
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bulkpdrdetail

Attribute	Description
Name	Bulkpdrdetail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISHONOUR_DATE

Attribute	Description

Name	DISHONOUR_DATE
Datatype	Date
Description	Dishonour Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	Notary Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	Protest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Internal Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DISHONOUR_REASON

Attribute	Description
Name	DISHONOUR_REASON
Datatype	String
Description	Dishonor Reason
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	Return Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	CounterParty Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	Other Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	CounterParty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME

Datatype	String
Description	Other Party Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	Instrument Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,H,S,F

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Product Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

2.122.2.RB-AuthorizeBulkPDRContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulkpdr-IO*
    - *BULKPDRREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulkpdr-IO

Attribute	Description
Name	Bulkpdr-IO
Datatype	
Description	

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	Bulk Dishonor / Protest / Return Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.122.3.RB-AuthorizeBulkPDRContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulkpdr-Full*
    - *BANK_CODE*
    - *BRNCODE*
    - *BANKNAME*
    - *BRNNAME*
    - *ACTION*
    - *DISPATCHLOTREFNO*
    - *BULKPDRREFNO*
    - *PROCESSTAT*
    - *AUTHSTAT*
    - *CHKR*
    - *CHKDTTIME*
    - *EVSEQNO*
    - *MAKER*
    - *MAKDTTIME*
    - *RECORDSTAT*
    - *ESNUI*
    - *Bulkpdrdetail*
      - *CONREFNUM*

ACC_CCY
AMNT
DISHONOUR_DATE
NOTARYCODE
PROTESTDATE
INTREMRKS
DISHONOUR_REASON
RETURN_DATE
CPTYIDEN
OTHRPTYIDEN
CPTYNAME
OTHERPARTYNAME
INSTRNO
PROCESSSTAT
PRDTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulkpdr-Full

Attribute	Description
Name	Bulkpdr-Full
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description	Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BRNCODE

Attribute	Description	
Name	BRNCODE	
Datatype	String	
Description	Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BANKNAME

Attribute	Description	
Name	BANKNAME	
Datatype	String	
Description	Bank Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description	Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

DISPATCHLOTREFNO

Attribute	Description	
Name	DISPATCHLOTREFNO	
Datatype	String	
Description	Dispatch Lot Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BULKPDRREFNO

Attribute	Description

Name	BULKPDRREFNO
Datatype	String
Description	Bulk Dishonor / Protest / Return Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,U

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	Checker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	Date Time

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

EVSEQNO

Attribute	**Description**	
Name	EVSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description	Maker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	**Description**	
Name	MAKDTTIME	
Datatype	String	
Description	Date Time	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RECORDSTAT

Attribute	**Description**	
Name	RECORDSTAT	
Datatype	String	
Description	Record Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,O,C

TOP

ESNUI

Attribute	Description
Name	ESNUI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bulkpdrdetail

Attribute	Description
Name	Bulkpdrdetail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number

Description	Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISHONOUR_DATE

Attribute	Description
Name	DISHONOUR_DATE
Datatype	Date
Description	Dishonour Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTARYCODE

Attribute	Description
Name	NOTARYCODE
Datatype	String
Description	Notary Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	Protest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Internal Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DISHONOUR_REASON

Attribute	Description

Name	DISHONOUR_REASON
Datatype	String
Description	Dishonor Reason
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RETURN_DATE

Attribute	Description
Name	RETURN_DATE
Datatype	Date
Description	Return Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	CounterParty Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	Other Party Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	CounterParty Name
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	Other Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,H,S,F

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Product Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.122.4.RB-AuthorizeBulkPDRContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulkpdr-PK*
      - *BULKPDRREFNO*
    - *Bulkpdr-IO*
      - *BULKPDRREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulkpdr-PK

Attribute	Description
Name	Bulkpdr-PK
Datatype	
Description	

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	Bulk Dishonor / Protest / Return Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Bulkpdr-IO

Attribute	Description
Name	Bulkpdr-IO
Datatype	
Description	

TOP

BULKPDRREFNO

Attribute	Description
Name	BULKPDRREFNO
Datatype	String
Description	Bulk Dishonor / Protest / Return Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.123.AuthorizeBulkRealization

AuthorizeBulkRealization

2.123.1.RB-AuthorizeBulkRealization-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-Full*
    - *BULKREALNUM*
    - *DISLOTREF*
    - *DRACFORREALISATION*
    - *COLBANKREFNUM*
    - *VDATE*
    - *CURRENCY*
    - *TOTNETREAL*
    - *DRACCBRN*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *CHKR*
    - *CHKDTTIME*
    - *EVENSEQNO*
    - *MAKER*
    - *MAKDTTIME*

PROCESSTAT

MAXESN

Detail

CONREFNUM

AMUNT

INTREMRKS

NETREALAMT

CUSTNUMBER1

OTHRBNKCHARGS

INSTRNO

PROCESSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	Bulk Realization Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

DISLOTREF

Attribute	Description
Name	DISLOTREF
Datatype	String
Description	Dispatch Lot Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

DRACFORREALISATION

Attribute	Description
Name	DRACFORREALISATION
Datatype	String
Description	Debit Account for Realization
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	Collecting Bank Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VDATE

Attribute	Description
Name	VDATE
Datatype	Date
Description	Value date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TOTNETREAL

Attribute	Description
Name	TOTNETREAL
Datatype	Number
Description	Total Net Realized
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Debit Account Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,O,C,H

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description	Checker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description	Date Time	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVENSEQNO

Attribute	Description
Name	EVENSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	Date Time
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U,F

TOP

MAXESN

Attribute	Description
Name	MAXESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Detail

Attribute	Description
Name	Detail
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

AMUNT

Attribute	Description
Name	AMUNT
Datatype	Number
Description	Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Internal Remarks
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

NETREALAMT

Attribute	Description
Name	NETREALAMT
Datatype	Number
Description	Net Realized Amount
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CUSTNUMBER1

Attribute	Description
Name	CUSTNUMBER1
Datatype	String
Description	Customer Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	Other Bank Charges
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	Instrument Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT

Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U,F

TOP

2.123.2.RB-AuthorizeBulkRealization-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-IO*
    - *BULKREALNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	Bulk Realization Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.123.3.RB-AuthorizeBulkRealization-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Master-Full*
    - *BULKREALNUM*
    - *DISLOTREF*
    - *DRACFORREALISATION*
    - *COLBANKREFNUM*
    - *VDATE*
    - *CURRENCY*
    - *TOTNETREAL*
    - *DRACCBRN*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *CHKR*
    - *CHKDTTIME*
    - *EVENSEQNO*
    - *MAKER*
    - *MAKDTTIME*
    - *PROCESSTAT*
    - *MAXESN*
    - *Detail*

CONREFNUM
AMUNT
INTREMRKS
NETREALAMT
CUSTNUMBER1
OTHRBNKCHARGS
INSTRNO
PROCESSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	Bulk Realization Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DISLOTREF

Attribute	Description
Name	DISLOTREF
Datatype	String
Description	Dispatch Lot Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRACFORREALISATION

Attribute	Description
Name	DRACFORREALISATION
Datatype	String
Description	Debit Account for Realization
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	Collecting Bank Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VDATE

Attribute	Description
Name	VDATE
Datatype	Date
Description	Value date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TOTNETREAL

Attribute	Description
Name	TOTNETREAL
Datatype	Number
Description	Total Net Realized
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Debit Account Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,O,C,H

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description	Checker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description	Date Time	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVENSEQNO

Attribute	Description
Name	EVENSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	Date Time
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U,F

TOP

MAXESN

Attribute	Description
Name	MAXESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Detail

Attribute	Description
Name	Detail
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

AMUNT

Attribute	Description
Name	AMUNT
Datatype	Number
Description	Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Internal Remarks
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

NETREALAMT

Attribute	Description
Name	NETREALAMT
Datatype	Number
Description	Net Realized Amount
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CUSTNUMBER1

Attribute	Description
Name	CUSTNUMBER1
Datatype	String
Description	Customer Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	Other Bank Charges
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT

Datatype	String
Description	Process Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U,F

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.123.4.RB-AuthorizeBulkRealization-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Master-PK*
      - *BULKREALNUM*
    - *Master-IO*
      - *BULKREALNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Master-PK

Attribute	Description
Name	Master-PK
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	Bulk Realization Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TOP

BULKREALNUM

Attribute	Description
Name	BULKREALNUM
Datatype	String
Description	Bulk Realization Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.124.AuthorizeCashletterdishonour

AuthorizeCashletterdishonour

2.124.1.RB-AuthorizeCashletterdishonour-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CASHREFNO*
    - *CPTY_ID*
    - *COUNTRPRYNAM*
    - *INSTRNO*
    - *INSTRU_DATE*
    - *CURRENCY*
    - *AMNT*
    - *COLLBNKNAME*
    - *BOKNGDT*
    - *OTHR_PARTYNAME*
    - *DRAWEE_BNK_NAME*
    - *REASON_CODE*
    - *REASON*
    - *DT_OF_DISHONOR*

OTHRBNKCHARGS
REMRKS
MAKER
MAKDTTIME
CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
Con
- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Charges
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*

CHRGAMT

LIQDSTAT

Misdetails

CONREFNO

LATESN

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*
  - *RECVCVR*
  - *RECEIVER*
  - *REIMINST1*
  - *REIMINST2*
  - *REIMINST3*

REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5

REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*

ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REASON

Attribute	Description
Name	REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DT_OF_DISHONOR

Attribute	Description
Name	DT_OF_DISHONOR
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,L,A</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr></table>

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description

Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description

Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS6

Attribute	**Description**	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	**Description**	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	**Description**	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	Description	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	Description	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

2.124.2.RB-AuthorizeCashletterdishonour-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.124.3.RB-AuthorizeCashletterdishonour-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CASHREFNO*
    - *CPTY_ID*
    - *COUNTRPRYNAM*
    - *INSTRNO*
    - *INSTRU_DATE*
    - *CURRENCY*
    - *AMNT*
    - *COLLBNKNAME*
    - *BOKNGDT*
    - *OTHR_PARTYNAME*
    - *DRAWEE_BNK_NAME*
    - *REASON_CODE*
    - *REASON*
    - *DT_OF_DISHONOR*
    - *OTHRBNKCHARGS*
    - *REMRKS*
    - *MAKER*

MAKDTTIME
CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
Con
  CONTREFNO
  EVENTSEQ
  Adv
    ADVNAME
    SUPRESS
    PRIOR
    MEDM
    PARTYIDEN
    PARTYNAME
    CHGREQ
    PARTTYP
Charges
  CONREFNO
  Charge-Association
    COMPNT
    CREATESN
    RULE
    WAIVER
    DISACCRAPPL
    ACCRREQD
    DESC
  Charge-Application
    CREATESN
    COMPNT
    TGCCY
    TGAMT
    CHRGCCY
    CHRGAMT
    DISACCRAPPL
    WAIVER
    LIQDIND
  Charge-Liquidation
    ESN
    COMPNT
    CHRGCCY
    CHRGAMT
    LIQDSTAT
Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3

FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Settlements

CONREFNO

Contract-Settlement

- *IBANACNO*
- *CUSTSPREAD*
- *SPREADDEFN*
- *COMPNT*
- *TAGCCY*
- *ACCBRN*
- *ACC*
- *ACCCCY*
- *EXRATE*
- *NETIND*
- *ERICCY*
- *ERIAMT*
- *GENMSG*
- *RATECD*
- *CLEARNW*
- *COVERBY*
- *RTGSPMNT*
- *BANKPRIOR*
- *RTGSNW*
- *PAYBY*
- *TRANSTYP*
- *INSTYP*
- *INSNO*
- *CHGDET*
- *PAYMNTDET1*
- *PAYMNTDET2*
- *PAYMNTDET3*
- *PAYMNTDET4*
- *SNDTRRCVINFO1*
- *SNDTRRCVINFO2*
- *SNDTRRCVINFO3*
- *SNDTRRCVINFO4*
- *SNDTRRCVINFO5*
- *COVREQRD*
- *RECVCVR*
- *RECEIVER*
- *REIMINST1*
- *REIMINST2*
- *REIMINST3*
- *REIMINST4*
- *RCVRCORRS1*
- *RCVRCORRS2*

RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5

ORDINST5

ULTBEN5

DRCRIND

Settlement-Detail

- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*

SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLBNKNAME

Attribute	Description
Name	COLLBNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REASON

Attribute	Description
Name	REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DT_OF_DISHONOR

Attribute	Description
Name	DT_OF_DISHONOR
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

OTHRBNKCHARGS

Attribute	Description
Name	OTHRBNKCHARGS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association

Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	**Description**	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	Description	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	Description	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	**Description**	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS5

Attribute	**Description**	
Name	TRANMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	**Description**	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs: 1
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	Description	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	Description	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP

Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String

Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	**Description**
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	**Description**
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	**Description**
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	**Description**
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.124.4.RB-AuthorizeCashletterdishonour-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONREFNUM*
    - *Main-IO*
      - *CONREFNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.125.AuthorizeCashletterrealize

AuthorizeCashletterrealize

2.125.1.RB-AuthorizeCashletterrealize-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CASHLTRCONREFNO*
    - *EVENTCODE*
    - *CL_REF*
    - *CURRENCY*
    - *AMNT*
    - *NOSTROACC*
    - *ACCBRN*
    - *INTREMRKS*
    - *COLBANKREFNUM*
    - *Footer*
      - *MAKER*
      - *MAKDTTIME*
      - *CHKR*
      - *CHKDTTIME*
      - *RECORD_STAT*

AUTHSTATS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description	
Name	CASHLTRCONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EVENTCODE

Attribute	Description	
Name	EVENTCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CL_REF

Attribute	Description	
Name	CL_REF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Footer

Attribute	Description	
Name	Footer	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	Description	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKR

Attribute	Description	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,L

TOP

AUTHSTATS

Attribute	Description
Name	AUTHSTATS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

2.125.2.RB-AuthorizeCashletterrealize-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CASHLTRCONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.125.3.RB-AuthorizeCashletterrealize-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CASHLTRCONREFNO*
    - *EVENTCODE*
    - *CL_REF*
    - *CURRENCY*
    - *AMNT*
    - *NOSTROACC*
    - *ACCBRN*
    - *INTREMRKS*
    - *COLBANKREFNUM*
    - *Footer*
      - *MAKER*
      - *MAKDTTIME*
      - *CHKR*
      - *CHKDTTIME*
      - *RECORD_STAT*
      - *AUTHSTATS*
  - *FCUBS_ERROR_RESP*
    - *ERROR*

ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CL_REF

Attribute	Description
Name	CL_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNT

Attribute	Description	
Name	AMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NOSTROACC

Attribute	Description	
Name	NOSTROACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INTREMRKS

Attribute	Description	
Name	INTREMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COLBANKREFNUM

Attribute	Description
Name	COLBANKREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Footer

Attribute	Description
Name	Footer
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,L

TOP

AUTHSTATS

Attribute	Description
Name	AUTHSTATS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	**Description**	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.125.4.RB-AuthorizeCashletterrealize-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CASHLTRCONREFNO*
    - *Main-IO*
      - *CASHLTRCONREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.126.AuthorizeCreatebulkfcycheck

AuthorizeCreatebulkfcycheck

2.126.1.RB-AuthorizeCreatebulkfcycheck-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Cashletter-Full*
    - *INSTRUCODE*
    - *INSTR_DESC*
    - *PRCD*
    - *PRODDESC*
    - *BATCHREFENUM*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *CPTY_AC_NO*
    - *ACCBRNRE*
    - *AC_CCYY*
    - *ACCBRN*
    - *COLL_BNK_NAME*
    - *BDTE*
    - *VAL_DATE_BANK*
    - *VALUE_DATE_CUST*

LIQDMODE
FINANCING
MARGINPERCENT
TRACK_LIMIT
CREDITLINE
NOOFINSTRUMENTS
PROCESS_STATUS
NOSTROACC
ESN
EVENT_SEQ_NO
RECORD_STAT
AUTHORIZATION_STATUS
CHECKER
CHKDTTIME
MAKER
MAKDTTIME
Bulk-Cashletter-Dtl
- *CONREFNUM*
- *INSTRNO*
- *INSTRU_DATE*
- *ADJSTAMT*
- *LCY_AMT*
- *DISCAMT*
- *OTHR_PARTYNAME*
- *DRAWEE_BNK_NAME*
- *REMRKS*
- *PROCESS_STATUS*

Summary
- *AUTHSTAT*
- *RECORD_STAT*
- *INSTRUCODE*
- *PRCD*
- *CPTY_ID*
- *BATCHREFENUM*
- *NOSTROACC*
- *COLL_BNK_NAME*
- *INSTRNO*
- *INSTRU_DATE*
- *AC_CCYY*
- *AMNT*
- *BDTE*
- *VAL_DATE_BANK*
- *VALUE_DATE_CUST*
- *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Cashletter-Full

Attribute	Description
Name	Bulk-Cashletter-Full
Datatype	
Description	

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCBRNRE

Attribute	Description
Name	ACCBRNRE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BDTE

Attribute	Description
Name	BDTE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDMODE

Attribute	Description
Name	LIQDMODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,U,

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C,

TOP

AUTHORIZATION_STATUS

Attribute	Description
Name	AUTHORIZATION_STATUS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	**Description**
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	**Description**
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Bulk-Cashletter-Dtl

Attribute	Description
Name	Bulk-Cashletter-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

ADJSTAMT

Attribute	Description

Name	ADJSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,U,

TOP

Summary

Attribute	Description
Name	Summary
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C,

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BDTE

Attribute	Description
Name	BDTE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.126.2.RB-AuthorizeCreatebulkfcycheck-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Bulk-Cashletter-IO
BATCHREFENUM

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Cashletter-IO

Attribute	Description
Name	Bulk-Cashletter-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.126.3.RB-AuthorizeCreatebulkfcycheck-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Cashletter-Full*
    - *INSTRUCODE*
    - *INSTR_DESC*
    - *PRCD*
    - *PRODDESC*
    - *BATCHREFENUM*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *CPTY_AC_NO*
    - *ACCBRNRE*
    - *AC_CCYY*
    - *ACCBRN*
    - *COLL_BNK_NAME*
    - *BDTE*
    - *VAL_DATE_BANK*
    - *VALUE_DATE_CUST*
    - *LIQDMODE*
    - *FINANCING*
    - *MARGINPERCENT*

- *TRACK_LIMIT*
- *CREDITLINE*
- *NOOFINSTRUMENTS*
- *PROCESS_STATUS*
- *NOSTROACC*
- *ESN*
- *EVENT_SEQ_NO*
- *RECORD_STAT*
- *AUTHORIZATION_STATUS*
- *CHECKER*
- *CHKDTTIME*
- *MAKER*
- *MAKDTTIME*
- *Bulk-Cashletter-Dtl*
  - *CONREFNUM*
  - *INSTRNO*
  - *INSTRU_DATE*
  - *ADJSTAMT*
  - *LCY_AMT*
  - *DISCAMT*
  - *OTHR_PARTYNAME*
  - *DRAWEE_BNK_NAME*
  - *REMRKS*
  - *PROCESS_STATUS*
- *Summary*
  - *AUTHSTAT*
  - *RECORD_STAT*
  - *INSTRUCODE*
  - *PRCD*
  - *CPTY_ID*
  - *BATCHREFENUM*
  - *NOSTROACC*
  - *COLL_BNK_NAME*
  - *INSTRNO*
  - *INSTRU_DATE*
  - *AC_CCYY*
  - *AMNT*
  - *BDTE*
  - *VAL_DATE_BANK*
  - *VALUE_DATE_CUST*
  - *CONREFNUM*

FCUBS_ERROR_RESP

- *ERROR*
  - *ECODE*

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Cashletter-Full

Attribute	Description

Name	Bulk-Cashletter-Full
Datatype	
Description	

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTR_DESC

Attribute	Description
Name	INSTR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BATCHREFENUM

Attribute	Description	
Name	BATCHREFENUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	Description	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_NAME

Attribute	Description	
Name	CPTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CPTY_AC_NO

Attribute	Description	
Name	CPTY_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCBRNRE

Attribute	Description
Name	ACCBRNRE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BDTE

Attribute	Description
Name	BDTE

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDMODE

Attribute	Description
Name	LIQDMODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / P,U,

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,C,

TOP

AUTHORIZATION_STATUS

Attribute	Description
Name	AUTHORIZATION_STATUS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Bulk-Cashletter-Dtl

Attribute	**Description**	
Name	Bulk-Cashletter-Dtl	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CONREFNUM

Attribute	**Description**	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INSTRNO

Attribute	**Description**	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRU_DATE

Attribute	**Description**	
Name	INSTRU_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LCY_AMT

Attribute	Description
Name	LCY_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,U,

TOP

Summary

Attribute	Description
Name	Summary
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>O,C,</td></tr></table>

TOP

INSTRUCODE

Attribute	Description
Name	INSTRUCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COLL_BNK_NAME

Attribute	Description
Name	COLL_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BDTE

Attribute	Description
Name	BDTE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.126.4.RB-AuthorizeCreatebulkfcycheck-Res-PK-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *CHOICE*
  - *Bulk-Cashletter-PK*
    - *BATCHREFENUM*
  - *Bulk-Cashletter-IO*
    - *BATCHREFENUM*
- *FCUBS_ERROR_RESP*
  - *ERROR*
    - *ECODE*
    - *EDESC*
- *FCUBS_WARNING_RESP*
  - *WARNING*
    - *WCODE*
    - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Cashletter-PK

Attribute	Description
Name	Bulk-Cashletter-PK
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Cashletter-IO

Attribute	Description
Name	Bulk-Cashletter-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.127.AuthorizeCreatebulkfcyreal

AuthorizeCreatebulkfcyreal

2.127.1.RB-AuthorizeCreatebulkfcyreal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liqd-Cashletter-Full*
    - *CASHREFNO*
    - *AC_CCYY*
    - *ACCBRN*
    - *VALUE_DATE_CUST*
    - *CASHLTRCONREFNO*
    - *NOSTROACC*
    - *PROCESS_STATUS*
    - *ESN*
    - *EVENT_SEQ_NO*
    - *RECORD_STAT*
    - *AUTHORIZATION_STATUS*
    - *CHECKER*
    - *CHKDTTIME*
    - *MAKER*
    - *MAKDTTIME*

Liqd-Cashletter-Dtl

CONREFNUM

CPTY_ID

INSTRNO

INSTRU_DATE

AMNT

INTREMRKS

PROCESS_STATUS

Summary

AUTHSTAT

RECORD_STAT

CASHREFNO

AC_CCYY

NOSTROACC

CONREFNUM

INSTRNO

INSTRU_DATE

AMNT

CPTY_ID

COUNTRPRYNAM

CASHLTRCONREFNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liqd-Cashletter-Full

Attribute	Description
Name	Liqd-Cashletter-Full
Datatype	
Description	

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACCBRN

Attribute	Description

Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,U,

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,C,

TOP

AUTHORIZATION_STATUS

Attribute	Description
Name	AUTHORIZATION_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U,

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Liqd-Cashletter-Dtl

Attribute	Description
Name	Liqd-Cashletter-Dtl
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,U,</td></tr></table>

TOP

Summary

Attribute	Description
Name	Summary
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U,

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,C,

TOP

CASHREFNO

Attribute	**Description**	
Name	CASHREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AC_CCYY

Attribute	**Description**	
Name	AC_CCYY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

NOSTROACC

Attribute	**Description**	
Name	NOSTROACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

2.127.2.RB-AuthorizeCreatebulkfcyreal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liqd-Cashletter-IO*
    - *CASHLTRCONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liqd-Cashletter-IO

Attribute	Description
Name	Liqd-Cashletter-IO
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.127.3.RB-AuthorizeCreatebulkfcyreal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liqd-Cashletter-Full*
    - *CASHREFNO*
    - *AC_CCYY*
    - *ACCBRN*
    - *VALUE_DATE_CUST*
    - *CASHLTRCONREFNO*
    - *NOSTROACC*
    - *PROCESS_STATUS*
    - *ESN*
    - *EVENT_SEQ_NO*
    - *RECORD_STAT*
    - *AUTHORIZATION_STATUS*
    - *CHECKER*
    - *CHKDTTIME*
    - *MAKER*
    - *MAKDTTIME*
    - *Liqd-Cashletter-Dtl*
      - *CONREFNUM*
      - *CPTY_ID*

INSTRNO
INSTRU_DATE
AMNT
INTREMRKS
PROCESS_STATUS
Summary
AUTHSTAT
RECORD_STAT
CASHREFNO
AC_CCYY
NOSTROACC
CONREFNUM
INSTRNO
INSTRU_DATE
AMNT
CPTY_ID
COUNTRPRYNAM
CASHLTRCONREFNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Liqd-Cashletter-Full

Attribute	Description
Name	Liqd-Cashletter-Full
Datatype	
Description	

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,U,

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C,

TOP

AUTHORIZATION_STATUS

Attribute	Description
Name	AUTHORIZATION_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Liqd-Cashletter-Dtl

Attribute	Description
Name	Liqd-Cashletter-Dtl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PROCESS_STATUS

Attribute	Description
Name	PROCESS_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,U,

TOP

Summary

Attribute	Description
Name	Summary
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description

Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U,

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C,

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

AC_CCYY

Attribute	Description
Name	AC_CCYY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NOSTROACC

Attribute	Description
Name	NOSTROACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CONREFNUM

Attribute	**Description**	
Name	CONREFNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INSTRNO

Attribute	**Description**	
Name	INSTRNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INSTRU_DATE

Attribute	**Description**	
Name	INSTRU_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMNT

Attribute	**Description**	
Name	AMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.127.4.RB-AuthorizeCreatebulkfcyreal-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Liqd-Cashletter-PK*
      - *CASHLTRCONREFNO*
    - *Liqd-Cashletter-IO*
      - *CASHLTRCONREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Liqd-Cashletter-PK

Attribute	Description
Name	Liqd-Cashletter-PK
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Liqd-Cashletter-IO

Attribute	Description
Name	Liqd-Cashletter-IO
Datatype	
Description	

TOP

CASHLTRCONREFNO

Attribute	Description
Name	CASHLTRCONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.128.AuthorizeFcychecksfinance

AuthorizeFcychecksfinance

2.128.1.RB-AuthorizeFcychecksfinance-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONTRACT_REF*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *INSTRNO*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *BOOKINGDATE*
    - *VAL_DATE_BANK*
    - *VALUE_DATE_CUST*
    - *OTHR_PARTY_NAME*
    - *DRAWEE_BNK_NAME*
    - *FINANCING*
    - *MARGINPERCENT*
    - *TRACK_LIMIT*

CRLINE
DISCOUNT_AMOUNT
MAKER
MAKDTTIME
CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
Con
  CONTREFNO
  EVENTSEQ
  Adv
    ADVNAME
    SUPRESS
    PRIOR
    MEDM
    PARTYIDEN
    PARTYNAME
    CHGREQ
    PARTTYP
Settlements
  CONREFNO
  Contract-Settlement
    IBANACNO
    CUSTSPREAD
    SPREADDEFN
    COMPNT
    TAGCCY
    ACCBRN
    ACC
    ACCCCY
    EXRATE
    NETIND
    ERICCY
    ERIAMT
    GENMSG
    RATECD
    CLEARNW
    COVERBY
    RTGSPMNT
    BANKPRIOR
    RTGSNW
    PAYBY
    TRANSTYP

INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1

ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

FREETXT1

FREETXT2

FREETXT3

PMNTCD

ADDINFOSORBNET

SNDRCUSTNAME1

SNDRCUSTNAME2

SNDRCUSTNAME3

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

Charges

CONREFNO

Charge-Association

COMPNT

CREATESN

RULE

- *WAIVER*
- *DISACCRAPPL*
- *ACCRREQD*
- *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*
  - *COSTCD4*
  - *COSTCD5*
  - *TXNMIS1*
  - *TXNMIS10*
  - *TXNMIS2*
  - *TXNMIS3*
  - *TXNMIS4*

TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6

- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Clpref

- *CONTREFNNO*
- *CONTRACT_CCY*
- *LATEVNSEQNO*
- *PRD*
- *PRDDESC*
- *COUNTERPARTY*
- *CURRENCY*
- *TENOR*
- *UNITS*
- *LOAN_CONREFNO*
- *RATECODE*
- *EXCHANGERATE*
- *RATE_TYPE*
- *MAXIMUM*
- *MINIMUM*
- *PAYMENT_MODE*
- *LOANVALDATE*
- *MATURITY_DATE*
- *Ude*
  - *USERDEID*
  - *UDEDESC*
  - *RATEASOF*
  - *USAGE*
  - *USERDEVAL*

TXNUDFDETAILS

- *FLDNAME*

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONTRACT_REF

Attribute	Description
Name	CONTRACT_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CTR_PRTY_NAME

Attribute	Description
Name	CTR_PRTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRLINE

Attribute	Description
Name	CRLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L,A

TOP

AUTHSTAT

Attribute	Description

Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Settlement

Attribute	**Description**	
Name	Contract-Settlement	
Datatype		
Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	**Description**	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**

Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	**Description**	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	Description	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	Description	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	Description	
Name	CLEARNW	
Datatype	String	
Description	Indicates Network Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO

Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String

Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4

Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1

Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5

Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	

Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description

Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	**Description**	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS2

Attribute	**Description**	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description

Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.128.2.RB-AuthorizeFcychecksfinance-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONTRACT_REF*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONTRACT_REF

Attribute	Description
Name	CONTRACT_REF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.128.3.RB-AuthorizeFcychecksfinance-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONTRACT_REF*
    - *CPTY_ID*
    - *CTR_PRTY_NAME*
    - *INSTRNO*
    - *INSTRUMENT_DATE*
    - *CURRENCY*
    - *AMNT*
    - *BOOKINGDATE*
    - *VAL_DATE_BANK*
    - *VALUE_DATE_CUST*
    - *OTHR_PARTY_NAME*
    - *DRAWEE_BNK_NAME*
    - *FINANCING*
    - *MARGINPERCENT*
    - *TRACK_LIMIT*
    - *CRLINE*
    - *DISCOUNT_AMOUNT*
    - *MAKER*

MAKDTTIME
CHKR
CHKDTTIME
RECORD_STAT
AUTHSTAT
Con
  CONTREFNO
  EVENTSEQ
  Adv
    ADVNAME
    SUPRESS
    PRIOR
    MEDM
    PARTYIDEN
    PARTYNAME
    CHGREQ
    PARTTYP
Settlements
  CONREFNO
  Contract-Settlement
    IBANACNO
    CUSTSPREAD
    SPREADDEFN
    COMPNT
    TAGCCY
    ACCBRN
    ACC
    ACCCCY
    EXRATE
    NETIND
    ERICCY
    ERIAMT
    GENMSG
    RATECD
    CLEARNW
    COVERBY
    RTGSPMNT
    BANKPRIOR
    RTGSNW
    PAYBY
    TRANSTYP
    INSTYP
    INSNO
    CHGDET

PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4

BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*

FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD

- *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*

TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9

- COMMIS10
- FUNMIS1
- FUNMIS2
- FUNMIS3
- FUNMIS4
- FUNMIS5
- FUNMIS6
- FUNMIS7
- FUNMIS8
- FUNMIS9
- FUNMIS10
- Txnmisdetails
- Compmisdetails
- Fundmisdetails

Clpref

- CONTREFNNO
- CONTRACT_CCY
- LATEVNSEQNO
- PRD
- PRDDESC
- COUNTERPARTY
- CURRENCY
- TENOR
- UNITS
- LOAN_CONREFNO
- RATECODE
- EXCHANGERATE
- RATE_TYPE
- MAXIMUM
- MINIMUM
- PAYMENT_MODE
- LOANVALDATE
- MATURITY_DATE
- Ude
  - USERDEID
  - UDEDESC
  - RATEASOF
  - USAGE
  - USERDEVAL

TXNUDFDETAILS

- FLDNAME
- FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONTRACT_REF

Attribute	Description
Name	CONTRACT_REF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CTR_PRTY_NAME

Attribute	Description
Name	CTR_PRTY_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VAL_DATE_BANK

Attribute	Description
Name	VAL_DATE_BANK

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALUE_DATE_CUST

Attribute	Description
Name	VALUE_DATE_CUST
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHR_PARTY_NAME

Attribute	Description
Name	OTHR_PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRAWEE_BNK_NAME

Attribute	Description
Name	DRAWEE_BNK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,N,F

TOP

MARGINPERCENT

Attribute	Description
Name	MARGINPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACK_LIMIT

Attribute	Description
Name	TRACK_LIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRLINE

Attribute	Description
Name	CRLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

DISCOUNT_AMOUNT

Attribute	Description
Name	DISCOUNT_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	**Description**	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / ,L,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	Description	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	Description	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number

Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	Description	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	**Description**	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNNO

Attribute	**Description**	
Name	CONTREFNNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CONTRACT_CCY

Attribute	**Description**	
Name	CONTRACT_CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRD

Attribute	**Description**	
Name	PRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LOAN_CONREFNO

Attribute	**Description**	
Name	LOAN_CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RATECODE

Attribute	**Description**	
Name	RATECODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,S

TOP

EXCHANGERATE

Attribute	**Description**	
Name	EXCHANGERATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATE_TYPE

Attribute	**Description**	
Name	RATE_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

USAGE

Attribute	Description

Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.128.4.RB-AuthorizeFcychecksfinance-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONTRACT_REF*
    - *Main-IO*
      - *CONTRACT_REF*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONTRACT_REF

Attribute	Description
Name	CONTRACT_REF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONTRACT_REF

Attribute	Description
Name	CONTRACT_REF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.129.AuthorizeFcychecksrealize

AuthorizeFcychecksrealize

2.129.1.RB-AuthorizeFcychecksrealize-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CASHREFNO*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *INSTRNO*
    - *INSTRU_DATE*
    - *CURRENCY*
    - *AMNT*
    - *VALUEDATE*
    - *REMRKS*
    - *MAKER*
    - *MAKDTTIME*
    - *CHKR*
    - *CHKDTTIME*
    - *RECORD_STAT*

AUTHSTAT

Con

- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*

SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4

BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*

SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT

TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN

COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3

FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

AMNT

Attribute	Description
Name	AMNT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr></table>

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Settlement

Attribute	**Description**	
Name	Contract-Settlement	
Datatype		
Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	**Description**	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description

Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	**Description**	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	**Description**	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	**Description**	
Name	CLEARNW	
Datatype	String	
Description	Indicates Network Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	**Description**
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates RTGS Payment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	**Description**	
Name	BANKPRIOR	
Datatype	String	
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1

Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC

Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	**Description**	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1

Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String

Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description

Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	**Description**	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	**Description**	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	**Description**	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description

Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY

Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	**Description**	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS6

Attribute	**Description**	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	**Description**	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	**Description**	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS2

Attribute	**Description**	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.129.2.RB-AuthorizeFcychecksrealize-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-IO*
    - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.129.3.RB-AuthorizeFcychecksrealize-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Main-Full*
    - *CONREFNUM*
    - *CASHREFNO*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *INSTRNO*
    - *INSTRU_DATE*
    - *CURRENCY*
    - *AMNT*
    - *VALUEDATE*
    - *REMRKS*
    - *MAKER*
    - *MAKDTTIME*
    - *CHKR*
    - *CHKDTTIME*
    - *RECORD_STAT*
    - *AUTHSTAT*
    - *Con*
      - *CONTREFNO*

- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*
  - *PARTTYP*
- *Settlements*
  - *CONREFNO*
  - *Contract-Settlement*
    - *IBANACNO*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *COMPNT*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *ACCCCY*
    - *EXRATE*
    - *NETIND*
    - *ERICCY*
    - *ERIAMT*
    - *GENMSG*
    - *RATECD*
    - *CLEARNW*
    - *COVERBY*
    - *RTGSPMNT*
    - *BANKPRIOR*
    - *RTGSNW*
    - *PAYBY*
    - *TRANSTYP*
    - *INSTYP*
    - *INSNO*
    - *CHGDET*
    - *PAYMNTDET1*
    - *PAYMNTDET2*
    - *PAYMNTDET3*
    - *PAYMNTDET4*
    - *SNDTRRCVINFO1*
    - *SNDTRRCVINFO2*
    - *SNDTRRCVINFO3*

SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC

COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*

RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Charges

CONREFNO

Charge-Association

COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC

Charge-Application

CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY

- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*

Charge-Liquidation

- *ESN*
- *COMPNT*
- *CHRGCCY*
- *CHRGAMT*
- *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*
- *MISGRPTXN*
- *COMPMIS1*
- *COMPMIS10*
- *COMPMIS2*

COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6

FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

CASHREFNO

Attribute	Description
Name	CASHREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRU_DATE

Attribute	Description
Name	INSTRU_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SUPRESS

Attribute	**Description**	
Name	SUPRESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number

Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String

Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description

Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	**Description**	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	**Description**	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1

Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5

Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description

Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	**Description**
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	**Description**
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	**Description**
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	**Description**
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.129.4.RB-AuthorizeFcychecksrealize-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Main-PK*
      - *CONREFNUM*
    - *Main-IO*
      - *CONREFNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.130.AuthorizeInwardContract

AuthorizeInwardContract

2.130.1.RB-AuthorizeInwardContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *INSTRUMENT_CODE*
    - *INSTRUMENT_DESCRIPTION*
    - *PRCD*
    - *CONREFNUM*
    - *USERREF_NO*
    - *XREF*
    - *BATCHREFENUM*
    - *BATCHSEQNO*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *ACCBRN*
    - *CPTY_AC_NO*
    - *INSTNO*
    - *INSTRDATE*
    - *CCY*

AMT
LCYAMT
BNKCD
BNKNAME
BRNCDE
BRNNAME
REFNO
DATE
CORRESPBNK
CORRESPACNO
OTHERPARTYIDE
OTHR_PARTYNAME
BOKNGDT
MATDT
GRACEDAYS
PAYDUEDATE
ACBRN1
ACFORREALISATION
PROTEST
AUTOLIQD
LIQWITHBUKNG
INTREMARKS
REASON_CODE
REASON
CONREFNOLOG
MAKER
MAKDTTIME
CHKR
CHKDTTIME
SE_TXNSTAT
AUTHSTAT
VERSIONNORB
LATVERNO
Contract-Parties
- *PARTYTYPE*
- *PARTYIDEN*
- *PARTYNAME*
- *COUNTRYCD*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ADDLN4*
- *LANG*

Settlements

CONREFNO

Contract-Settlement

- *IBANACNO*
- *CUSTSPREAD*
- *SPREADDEFN*
- *COMPNT*
- *TAGCCY*
- *ACCBRN*
- *ACC*
- *ACCCCY*
- *EXRATE*
- *NETIND*
- *ERICCY*
- *ERIAMT*
- *GENMSG*
- *RATECD*
- *CLEARNW*
- *COVERBY*
- *RTGSPMNT*
- *BANKPRIOR*
- *RTGSNW*
- *PAYBY*
- *TRANSTYP*
- *INSTYP*
- *INSNO*
- *CHGDET*
- *PAYMNTDET1*
- *PAYMNTDET2*
- *PAYMNTDET3*
- *PAYMNTDET4*
- *SNDTRRCVINFO1*
- *SNDTRRCVINFO2*
- *SNDTRRCVINFO3*
- *SNDTRRCVINFO4*
- *SNDTRRCVINFO5*
- *COVREQRD*
- *RECVCVR*
- *RECEIVER*
- *REIMINST1*
- *REIMINST2*
- *REIMINST3*
- *REIMINST4*
- *RCVRCORRS1*
- *RCVRCORRS2*

RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5

ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*

SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Charges

CONREFNO

Charge-Association

COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC

Charge-Application

CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND

Charge-Liquidation

ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3

FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con

CONTREFNO

EVENTSEQ

Adv

- *ADVNAME*
- *SUPRESS*
- *PRIOR*
- *MEDM*
- *PARTYIDEN*
- *PARTYNAME*
- *CHGREQ*
- *PARTTYP*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description
Name	INSTRUMENT_DESCRIPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHSEQNO

Attribute	Description

Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTNO

Attribute	Description
Name	INSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRNCDE

Attribute	Description
Name	BRNCDE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORRESPBNK

Attribute	Description
Name	CORRESPBNK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CORRESPACNO

Attribute	Description
Name	CORRESPACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

OTHERPARTYIDE

Attribute	Description	
Name	OTHERPARTYIDE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OTHR_PARTYNAME

Attribute	Description	
Name	OTHR_PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BOKNGDT

Attribute	Description	
Name	BOKNGDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MATDT

Attribute	Description	
Name	MATDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PAYDUEDATE

Attribute	Description
Name	PAYDUEDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

ACBRN1

Attribute	Description
Name	ACBRN1
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

ACFORREALISATION

Attribute	Description
Name	ACFORREALISATION
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 20

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: Y,N

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQWITHBUKNG

Attribute	Description
Name	LIQWITHBUKNG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REASON

Attribute	Description
Name	REASON
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CONREFNOLOG

Attribute	**Description**	
Name	CONREFNOLOG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	**Description**	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	Description	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SE_TXNSTAT

Attribute	Description	
Name	SE_TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,L,R,H

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

VERSIONNORB

Attribute	Description	
Name	VERSIONNORB	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>DRAWER,PAYEE,REMITTING_BANK,DRAWEE</td></tr></table>

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRYCD

Attribute	**Description**	
Name	COUNTRYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ADDLN1

Attribute	**Description**	
Name	ADDLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDLN2

Attribute	**Description**	
Name	ADDLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDLN3

Attribute	**Description**	
Name	ADDLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	**Description**	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	**Description**	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1

Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2

Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5

Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1

Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	**Description**	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	**Description**	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application

Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	**Description**	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	Description	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	Description	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	Description	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	Description	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL

Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

2.130.2.RB-AuthorizeInwardContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.130.3.RB-AuthorizeInwardContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *INSTRUMENT_CODE*
    - *INSTRUMENT_DESCRIPTION*
    - *PRCD*
    - *CONREFNUM*
    - *USERREF_NO*
    - *XREF*
    - *BATCHREFENUM*
    - *BATCHSEQNO*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *ACCBRN*
    - *CPTY_AC_NO*
    - *INSTNO*
    - *INSTRDATE*
    - *CCY*
    - *AMT*
    - *LCYAMT*
    - *BNKCD*

BNKNAME
BRNCDE
BRNNAME
REFNO
DATE
CORRESPBNK
CORRESPACNO
OTHERPARTYIDE
OTHR_PARTYNAME
BOKNGDT
MATDT
GRACEDAYS
PAYDUEDATE
ACBRN1
ACFORREALISATION
PROTEST
AUTOLIQD
LIQWITHBUKNG
INTREMARKS
REASON_CODE
REASON
CONREFNOLOG
MAKER
MAKDTTIME
CHKR
CHKDTTIME
SE_TXNSTAT
AUTHSTAT
VERSIONNORB
LATVERNO
Contract-Parties
- *PARTYTYPE*
- *PARTYIDEN*
- *PARTYNAME*
- *COUNTRYCD*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ADDLN4*
- *LANG*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*

CUSTSPREAD
SPREADDEFN
COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1

INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND

Settlement-Detail

- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*

- NOOFDEC
- ADDID
- SNDRRCVRINFO1
- SNDRRCVRINFO2
- SNDRRCVRINFO3
- SNDRRCVRINFO4
- SNDRRCVRINFO5
- SNDRRCVRINFO6
- DECLARTION
- REPRES1
- REPRES2
- REPRES3
- REPRES4
- RCVRACC

Charges

- CONREFNO
- Charge-Association
  - COMPNT
  - CREATESN
  - RULE
  - WAIVER
  - DISACCRAPPL
  - ACCRREQD
  - DESC
- Charge-Application
  - CREATESN
  - COMPNT
  - TGCCY
  - TGAMT
  - CHRGCCY
  - CHRGAMT
  - DISACCRAPPL
  - WAIVER
  - LIQDIND
- Charge-Liquidation
  - ESN
  - COMPNT
  - CHRGCCY
  - CHRGAMT
  - LIQDSTAT

Misdetails

- CONREFNO
- LATESN
- MISGRP

RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6

FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv

ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

INSTRUMENT_CODE

Attribute	Description
Name	INSTRUMENT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENT_DESCRIPTION

Attribute	Description
Name	INSTRUMENT_DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF_NO

Attribute	Description
Name	USERREF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BATCHSEQNO

Attribute	Description
Name	BATCHSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTNO

Attribute	Description
Name	INSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BNKCD

Attribute	Description
Name	BNKCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

BRNCDE

Attribute	Description
Name	BRNCDE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

REFNO

Attribute	**Description**	
Name	REFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DATE

Attribute	**Description**	
Name	DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CORRESPBNK

Attribute	**Description**	
Name	CORRESPBNK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CORRESPACNO

Attribute	**Description**	
Name	CORRESPACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

OTHERPARTYIDE

Attribute	Description
Name	OTHERPARTYIDE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BOKNGDT

Attribute	Description
Name	BOKNGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GRACEDAYS

Attribute	Description
Name	GRACEDAYS
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PAYDUEDATE

Attribute	**Description**	
Name	PAYDUEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACBRN1

Attribute	**Description**	
Name	ACBRN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACFORREALISATION

Attribute	**Description**	
Name	ACFORREALISATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

PROTEST

Attribute	**Description**	
Name	PROTEST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOLIQD

Attribute	Description
Name	AUTOLIQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

LIQWITHBUKNG

Attribute	Description
Name	LIQWITHBUKNG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

REASON

Attribute	Description
Name	REASON

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CONREFNOLOG

Attribute	Description
Name	CONREFNOLOG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SE_TXNSTAT

Attribute	Description
Name	SE_TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,L,R,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

VERSIONNORB

Attribute	Description
Name	VERSIONNORB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / DRAWER,PAYEE,REMITTING_BANK,DRAWEE

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDLN4

Attribute	Description
Name	ADDLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1

Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2

Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5

Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1

Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	**Description**	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	**Description**	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application

Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	**Description**	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	

Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL

Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.130.4.RB-AuthorizeInwardContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNUM*
    - *Contract-Details-IO*
      - *CONREFNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.131.AuthorizeInwardRealize

AuthorizeInwardRealize

2.131.1.RB-AuthorizeInwardRealize-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-Full*
    - *CONTREFNO*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *OTHERPARTYIDE*
    - *OTHR_PARTYNAME*
    - *INSTRUMENTNO*
    - *INSTRUMENTDATE*
    - *CONTRACTCCY*
    - *CONTRACTAMT*
    - *DUEDATE*
    - *REMBANKCODE*
    - *BANK_NAME*
    - *REMBRANCHCODE*
    - *BRANCH_NAME*
    - *REMREFNO*

REMBNKREFDT
CORRESBANK
CORRESACNO
ACCBRN
CPTY_AC_NO
CR_ACC_BR
REALISATIONAC
VALUEDATE
CHARGES_DEDUCTED
REALISEDNETAMT
DISHNRCODE
DISHONORREASON
LATVERNO
MAKER
MAKDTTIME
TXNSTAT
CHKR
CHKDTTIME
AUTHSTAT
EVENT_SEQ_NO
CURR_EVENT_CODE
CONTRCTREF_NO
Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*

PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3

BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*

ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT

CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2

TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4

COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master-Full

Attribute	Description
Name	Contract-Master-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY_ID

Attribute	Description
Name	CPTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OTHERPARTYIDE

Attribute	Description
Name	OTHERPARTYIDE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OTHR_PARTYNAME

Attribute	Description
Name	OTHR_PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INSTRUMENTNO

Attribute	Description

Name	INSTRUMENTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRUMENTDATE

Attribute	Description
Name	INSTRUMENTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONTRACTAMT

Attribute	Description
Name	CONTRACTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMBANKCODE

Attribute	Description
Name	REMBANKCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANK_NAME

Attribute	Description
Name	BANK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REMBRANCHCODE

Attribute	Description
Name	REMBRANCHCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRANCH_NAME

Attribute	Description
Name	BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REMREFNO

Attribute	Description

Name	REMREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REMBNKREFDT

Attribute	Description
Name	REMBNKREFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CORRESBANK

Attribute	Description
Name	CORRESBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CORRESACNO

Attribute	Description
Name	CORRESACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CR_ACC_BR

Attribute	Description
Name	CR_ACC_BR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REALISATIONAC

Attribute	Description
Name	REALISATIONAC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHARGES_DEDUCTED

Attribute	Description
Name	CHARGES_DEDUCTED
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REALISEDNETAMT

Attribute	Description
Name	REALISEDNETAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISHNRCODE

Attribute	Description
Name	DISHNRCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DISHONORREASON

Attribute	Description
Name	DISHONORREASON
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,L,R,H

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,A</td></tr></table>

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CURR_EVENT_CODE

Attribute	Description
Name	CURR_EVENT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CONTRCTREF_NO

Attribute	Description
Name	CONTRCTREF_NO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	**Description**	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	Description	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

2.131.2.RB-AuthorizeInwardRealize-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-IO*
    - *CONTREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.131.3.RB-AuthorizeInwardRealize-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-Full*
    - *CONTREFNO*
    - *CPTY_ID*
    - *CPTY_NAME*
    - *OTHERPARTYIDE*
    - *OTHR_PARTYNAME*
    - *INSTRUMENTNO*
    - *INSTRUMENTDATE*
    - *CONTRACTCCY*
    - *CONTRACTAMT*
    - *DUEDATE*
    - *REMBANKCODE*
    - *BANK_NAME*
    - *REMBRANCHCODE*
    - *BRANCH_NAME*
    - *REMREFNO*
    - *REMBNKREFDT*
    - *CORRESBANK*
    - *CORRESACNO*

ACCBRN
CPTY_AC_NO
CR_ACC_BR
REALISATIONAC
VALUEDATE
CHARGES_DEDUCTED
REALISEDNETAMT
DISHNRCODE
DISHONORREASON
LATVERNO
MAKER
MAKDTTIME
TXNSTAT
CHKR
CHKDTTIME
AUTHSTAT
EVENT_SEQ_NO
CURR_EVENT_CODE
CONTRCTREF_NO
Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*

INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2

ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER

- *DISACCRAPPL*
- *ACCRREQD*
- *DESC*

Charge-Application

- *CREATESN*
- *COMPNT*
- *TGCCY*
- *TGAMT*
- *CHRGCCY*
- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*

Charge-Liquidation

- *ESN*
- *COMPNT*
- *CHRGCCY*
- *CHRGAMT*
- *LIQDSTAT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*

TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7

COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master-Full

Attribute	Description
Name	Contract-Master-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY_ID

Attribute	**Description**	
Name	CPTY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTY_NAME

Attribute	**Description**	
Name	CPTY_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYIDE

Attribute	**Description**	
Name	OTHERPARTYIDE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OTHR_PARTYNAME

Attribute	**Description**	
Name	OTHR_PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INSTRUMENTNO

Attribute	Description
Name	INSTRUMENTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRUMENTDATE

Attribute	Description
Name	INSTRUMENTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CONTRACTAMT

Attribute	Description
Name	CONTRACTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DUEDATE

Attribute	Description
Name	DUEDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMBANKCODE

Attribute	Description
Name	REMBANKCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANK_NAME

Attribute	Description
Name	BANK_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REMBRANCHCODE

Attribute	Description
Name	REMBRANCHCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRANCH_NAME

Attribute	Description
Name	BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

REMREFNO

Attribute	Description
Name	REMREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

REMBNKREFDT

Attribute	Description
Name	REMBNKREFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CORRESBANK

Attribute	Description
Name	CORRESBANK
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CORRESACNO

Attribute	Description
Name	CORRESACNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CPTY_AC_NO

Attribute	Description
Name	CPTY_AC_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CR_ACC_BR

Attribute	Description
Name	CR_ACC_BR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

REALISATIONAC

Attribute	Description
Name	REALISATIONAC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

VALUEDATE

Attribute	Description
Name	VALUEDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHARGES_DEDUCTED

Attribute	Description
Name	CHARGES_DEDUCTED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REALISEDNETAMT

Attribute	Description
Name	REALISEDNETAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISHNRCODE

Attribute	Description
Name	DISHNRCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DISHONORREASON

Attribute	Description
Name	DISHONORREASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,L,R,H</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CURR_EVENT_CODE

Attribute	**Description**	
Name	CURR_EVENT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CONTRCTREF_NO

Attribute	Description	
Name	CONTRCTREF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Settlements

Attribute	Description	
Name	Settlements	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Settlement

Attribute	Description	
Name	Contract-Settlement	
Datatype		
Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String

Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	Description	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	Description	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	**Description**	
Name	PRIOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDM

Attribute	**Description**	
Name	MEDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PARTYIDEN

Attribute	**Description**	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String

Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.131.4.RB-AuthorizeInwardRealize-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Master-PK*
      - *CONTREFNO*
    - *Contract-Master-IO*
      - *CONTREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Master-PK

Attribute	Description
Name	Contract-Master-PK
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.132.AuthorizeOutBulkCol

AuthorizeOutBulkCol

2.132.1.RB-AuthorizeOutBulkCol-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Full*
    - *CREDITLINE*
    - *OTHRPARTYLMTCHK*
    - *MARGINPERC*
    - *FINANCING*
    - *COLLATERAL*
    - *COLLPOOL*
    - *INSTRCODE*
    - *PRODCODE*
    - *CPTYIDEN*
    - *CPACCNO*
    - *CONTCCY*
    - *OTHRPTYIDEN*
    - *DRACCREAL*
    - *BANKCD*
    - *BOOKINGDATE*

PROTEST
TRACKLIMIT
INSTRUMENTDESC
PRODDESC
COUNTERPRTYNAME
OTHERPARTYNAME
BNKNAME
BRNNAME
NOOFINSTRUMENTS
BRNCODE
BATCHREFENUM
ACCBRN
DRACCBRN
PROCESSTAT
VERNUM
CVERNO
CONST
AUTHSTAT
CHKR
CHKDTTIME
MAKER
MAKDTTIME
Bulk-Input-Detail
- *CONTREFNO*
- *INSTRNO*
- *INSTRDATE*
- *AMNT*
- *CONTAMTLCY*
- *MATURITYDATE*
- *DISCAMT*
- *COLLTVAL*
- *INTREMARKS*
- *PROCESSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Full

Attribute	Description
Name	Bulk-Input-Full
Datatype	
Description	

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

OTHRPARTYLMTCHK

Attribute	Description
Name	OTHRPARTYLMTCHK

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,F,N

TOP

COLLATERAL

Attribute	Description
Name	COLLATERAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,C,T,N

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRCODE

Attribute	Description
Name	INSTRCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRODCODE

Attribute	Description
Name	PRODCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPACCNO

Attribute	Description
Name	CPACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CONTCCY

Attribute	Description	
Name	CONTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

OTHRPTYIDEN

Attribute	Description	
Name	OTHRPTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

DRACCREAL

Attribute	Description	
Name	DRACCREAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BANKCD

Attribute	Description	
Name	BANKCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

INSTRUMENTDESC

Attribute	Description
Name	INSTRUMENTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COUNTERPRTYNAME

Attribute	**Description**	
Name	COUNTERPRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OTHERPARTYNAME

Attribute	**Description**	
Name	OTHERPARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BNKNAME

Attribute	**Description**	
Name	BNKNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,U</td></tr></table>

TOP

VERNUM

Attribute	Description
Name	VERNUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CVERNO

Attribute	Description
Name	CVERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / ,O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Bulk-Input-Detail

Attribute	Description
Name	Bulk-Input-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRDATE

Attribute	Description

Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CONTAMTLCY

Attribute	Description
Name	CONTAMTLCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTVAL

Attribute	Description
Name	COLLTVAL
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U

TOP

2.132.2.RB-AuthorizeOutBulkCol-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Bulk-Input-IO*
  - *BATCHREFENUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.132.3.RB-AuthorizeOutBulkCol-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bulk-Input-Full*
    - *CREDITLINE*
    - *OTHRPARTYLMTCHK*
    - *MARGINPERC*
    - *FINANCING*
    - *COLLATERAL*
    - *COLLPOOL*
    - *INSTRCODE*
    - *PRODCODE*
    - *CPTYIDEN*
    - *CPACCNO*
    - *CONTCCY*
    - *OTHRPTYIDEN*
    - *DRACCREAL*
    - *BANKCD*
    - *BOOKINGDATE*
    - *PROTEST*
    - *TRACKLIMIT*
    - *INSTRUMENTDESC*

PRODDESC
COUNTERPRTYNAME
OTHERPARTYNAME
BNKNAME
BRNNAME
NOOFINSTRUMENTS
BRNCODE
BATCHREFENUM
ACCBRN
DRACCBRN
PROCESSTAT
VERNUM
CVERNO
CONST
AUTHSTAT
CHKR
CHKDTTIME
MAKER
MAKDTTIME
Bulk-Input-Detail
CONTREFNO
INSTRNO
INSTRDATE
AMNT
CONTAMTLCY
MATURITYDATE
DISCAMT
COLLTVAL
INTREMARKS
PROCESSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Bulk-Input-Full

Attribute	Description
Name	Bulk-Input-Full
Datatype	
Description	

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

OTHRPARTYLMTCHK

Attribute	**Description**	
Name	OTHRPARTYLMTCHK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MARGINPERC

Attribute	**Description**	
Name	MARGINPERC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FINANCING

Attribute	**Description**	
Name	FINANCING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,F,N

TOP

COLLATERAL

Attribute	**Description**	
Name	COLLATERAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,C,T,N

TOP

COLLPOOL

Attribute	Description
Name	COLLPOOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRCODE

Attribute	Description
Name	INSTRCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRODCODE

Attribute	Description
Name	PRODCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPACCNO

Attribute	Description
Name	CPACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

DRACCREAL

Attribute	Description
Name	DRACCREAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BANKCD

Attribute	Description
Name	BANKCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROTEST

Attribute	Description
Name	PROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INSTRUMENTDESC

Attribute	Description
Name	INSTRUMENTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

COUNTERPRTYNAME

Attribute	Description
Name	COUNTERPRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BNKNAME

Attribute	Description
Name	BNKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

NOOFINSTRUMENTS

Attribute	Description
Name	NOOFINSTRUMENTS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,U

TOP

VERNUM

Attribute	Description
Name	VERNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CVERNO

Attribute	Description
Name	CVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONST

Attribute	Description
Name	CONST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

Bulk-Input-Detail

Attribute	Description
Name	Bulk-Input-Detail
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CONTAMTLCY

Attribute	Description
Name	CONTAMTLCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DISCAMT

Attribute	Description
Name	DISCAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTVAL

Attribute	Description
Name	COLLTVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMARKS

Attribute	Description
Name	INTREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PROCESSTAT

Attribute	Description
Name	PROCESSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,U

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.132.4.RB-AuthorizeOutBulkCol-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bulk-Input-PK*
      - *BATCHREFENUM*
    - *Bulk-Input-IO*
      - *BATCHREFENUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bulk-Input-PK

Attribute	Description
Name	Bulk-Input-PK
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Bulk-Input-IO

Attribute	Description
Name	Bulk-Input-IO
Datatype	
Description	

TOP

BATCHREFENUM

Attribute	Description
Name	BATCHREFENUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.133.AuthorizeOutFinDet

AuthorizeOutFinDet

2.133.1.RB-AuthorizeOutFinDet-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Rbtbs-Contract-Master-Full*
    - *CPTYIDEN*
    - *INSTRNO*
    - *INSTRDATE*
    - *CONTCCY*
    - *AMNT*
    - *OTHRPTYIDEN*
    - *BOOKINGDATE*
    - *TRACKLIMIT*
    - *CREDITLINE*
    - *MARGINPERC*
    - *FINANCING*
    - *DISCOUNTAMT*
    - *DUEDATE*
    - *OTHERPARTYNAME*
    - *CPTYNAME*

CONREFNUM
MAKER
MAKERDT
CHKR
CHECKERDT
CONTSTAT
AUTHSTAT
OTHRPARTYLMTCHK
Settlements
  CONREFNO
  Contract-Settlement
    IBANACNO
    CUSTSPREAD
    SPREADDEFN
    COMPNT
    TAGCCY
    ACCBRN
    ACC
    ACCCCY
    EXRATE
    NETIND
    ERICCY
    ERIAMT
    GENMSG
    RATECD
    CLEARNW
    COVERBY
    RTGSPMNT
    BANKPRIOR
    RTGSNW
    PAYBY
    TRANSTYP
    INSTYP
    INSNO
    CHGDET
    PAYMNTDET1
    PAYMNTDET2
    PAYMNTDET3
    PAYMNTDET4
    SNDTRRCVINFO1
    SNDTRRCVINFO2
    SNDTRRCVINFO3
    SNDTRRCVINFO4
    SNDTRRCVINFO5

COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID

POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*

RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL

- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*
  - *COSTCD4*
  - *COSTCD5*
  - *TXNMIS1*
  - *TXNMIS10*
  - *TXNMIS2*
  - *TXNMIS3*
  - *TXNMIS4*
  - *TXNMIS5*
  - *TXNMIS6*
  - *TXNMIS7*
  - *TXNMIS8*
  - *TXNMIS9*
  - *MISGRPCOMP*
  - *MISGRPTXN*
  - *COMPMIS1*
  - *COMPMIS10*
  - *COMPMIS2*
  - *COMPMIS3*
  - *COMPMIS4*

COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8

- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Clpref

- *CONTREFNNO*
- *CONTRACT_CCY*
- *LATEVNSEQNO*
- *PRD*
- *PRDDESC*
- *COUNTERPARTY*
- *CURRENCY*
- *TENOR*
- *UNITS*
- *LOAN_CONREFNO*
- *RATECODE*
- *EXCHANGERATE*
- *RATE_TYPE*
- *MAXIMUM*
- *MINIMUM*
- *PAYMENT_MODE*
- *LOANVALDATE*
- *MATURITY_DATE*
- *Ude*
  - *USERDEID*
  - *UDEDESC*
  - *RATEASOF*
  - *USAGE*
  - *USERDEVAL*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Con

- *CONTREFNO*
- *EVENTSEQ*
- *Adv*
  - *ADVNAME*
  - *SUPRESS*
  - *PRIOR*
  - *MEDM*
  - *PARTYIDEN*
  - *PARTYNAME*
  - *CHGREQ*

PARTTYP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Rbtbs-Contract-Master-Full

Attribute	Description
Name	Rbtbs-Contract-Master-Full
Datatype	
Description	

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDT

Attribute	Description
Name	CHECKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

OTHRPARTYLMTCHK

Attribute	Description
Name	OTHRPARTYLMTCHK
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TENOR

Attribute	Description

Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description

Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

TOP

PARTYIDEN

Attribute	Description	
Name	PARTYIDEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PARTYNAME

Attribute	Description	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CHGREQ

Attribute	Description	
Name	CHGREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTTYP

Attribute	Description	
Name	PARTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.133.2.RB-AuthorizeOutFinDet-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Rbtbs-Contract-Master-IO
CONREFNUM

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Rbtbs-Contract-Master-IO

Attribute	Description
Name	Rbtbs-Contract-Master-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.133.3.RB-AuthorizeOutFinDet-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Rbtbs-Contract-Master-Full*
    - *CPTYIDEN*
    - *INSTRNO*
    - *INSTRDATE*
    - *CONTCCY*
    - *AMNT*
    - *OTHRPTYIDEN*
    - *BOOKINGDATE*
    - *TRACKLIMIT*
    - *CREDITLINE*
    - *MARGINPERC*
    - *FINANCING*
    - *DISCOUNTAMT*
    - *DUEDATE*
    - *OTHERPARTYNAME*
    - *CPTYNAME*
    - *CONREFNUM*
    - *MAKER*
    - *MAKERDT*

CHKR
CHECKERDT
CONTSTAT
AUTHSTAT
OTHRPARTYLMTCHK
Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*
  - *RECVCVR*
  - *RECEIVER*

REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6

ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*

ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation

ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7

COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails

Compmisdetails
Fundmisdetails
Clpref
CONTREFNNO
CONTRACT_CCY
LATEVNSEQNO
PRD
PRDDESC
COUNTERPARTY
CURRENCY
TENOR
UNITS
LOAN_CONREFNO
RATECODE
EXCHANGERATE
RATE_TYPE
MAXIMUM
MINIMUM
PAYMENT_MODE
LOANVALDATE
MATURITY_DATE
Ude
USERDEID
UDEDESC
RATEASOF
USAGE
USERDEVAL
TXNUDFDETAILS
FLDNAME
FLDVAL
Con
CONTREFNO
EVENTSEQ
Adv
ADVNAME
SUPRESS
PRIOR
MEDM
PARTYIDEN
PARTYNAME
CHGREQ
PARTTYP
FCUBS_ERROR_RESP
ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Rbtbs-Contract-Master-Full

Attribute	Description
Name	Rbtbs-Contract-Master-Full
Datatype	
Description	

TOP

CPTYIDEN

Attribute	Description
Name	CPTYIDEN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHRPTYIDEN

Attribute	Description
Name	OTHRPTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BOOKINGDATE

Attribute	Description
Name	BOOKINGDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACKLIMIT

Attribute	Description
Name	TRACKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CREDITLINE

Attribute	Description
Name	CREDITLINE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

MARGINPERC

Attribute	Description
Name	MARGINPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINANCING

Attribute	Description
Name	FINANCING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHERPARTYNAME

Attribute	Description
Name	OTHERPARTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

CPTYNAME

Attribute	Description
Name	CPTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERDT

Attribute	Description
Name	MAKERDT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDT

Attribute	Description
Name	CHECKERDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

OTHRPARTYLMTCHK

Attribute	Description
Name	OTHRPARTYLMTCHK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String

Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String

Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description

Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	**Description**	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	**Description**	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	**Description**	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2

Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3

Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	**Description**	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	**Description**	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	**Description**	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2

Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	**Description**	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	**Description**	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	**Description**	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**	
Name	REGREP2	
Datatype	String	
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**
Name	REGREP3
Datatype	String

Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2

Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	Description	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	Description	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO2

Attribute	Description	
Name	SNDRRCVRINFO2	
Datatype	String	
Description	Indicates Sender Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	**Description**	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Clpref

Attribute	Description
Name	Clpref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CONTRACT_CCY

Attribute	Description
Name	CONTRACT_CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNTERPARTY

Attribute	Description
Name	COUNTERPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LOAN_CONREFNO

Attribute	Description
Name	LOAN_CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_MODE

Attribute	Description
Name	PAYMENT_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATURITY_DATE

Attribute	Description
Name	MATURITY_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Ude

Attribute	Description
Name	Ude
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USERDEID

Attribute	Description
Name	USERDEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

RATEASOF

Attribute	Description
Name	RATEASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USERDEVAL

Attribute	Description
Name	USERDEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description

Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Con

Attribute	Description
Name	Con
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

TOP

EVENTSEQ

Attribute	Description
Name	EVENTSEQ
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

Adv

Attribute	Description
Name	Adv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVNAME

Attribute	Description
Name	ADVNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MEDM

Attribute	Description
Name	MEDM
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTYIDEN

Attribute	Description
Name	PARTYIDEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.133.4.RB-AuthorizeOutFinDet-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Rbtbs-Contract-Master-PK*
      - *CONREFNUM*
    - *Rbtbs-Contract-Master-IO*
      - *CONREFNUM*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Rbtbs-Contract-Master-PK

Attribute	Description
Name	Rbtbs-Contract-Master-PK
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Rbtbs-Contract-Master-IO

Attribute	Description
Name	Rbtbs-Contract-Master-IO
Datatype	
Description	

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

Retail Bills Service
[April] [2014]

Oracle Financial Services software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax:+91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2007], [2013], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of
this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any

kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.